

LEARN OPENCV BY EXAMPLES

OpenCV simplified for beginners by the use of examples. Learn OpenCV with basic implementation of different algorithms.

Home	For Beginners	Table of Contents	Keywords	
----------------------	-------------------------------	-----------------------------------	--------------------------	--

Load, Display and Save an image

Mat **imread**(const string& filename, int flags=1)

- Parameters:**
- **filename** – Name of file to be loaded.
 - **flags** –Flags specifying the color type of a loaded image:
 - CV_LOAD_IMAGE_ANYDEPTH - return 16-bit/32-bit image when the input has the corresponding depth, otherwise convert it to 8-bit.
 - CV_LOAD_IMAGE_COLOR(>0) - If set, always convert image to the color one
 - CV_LOAD_IMAGE_GRAYSCALE (0)- If set, always convert image to the grayscale one
 - CV_LOAD_IMAGE_UNCHANGED (<0) loads the image as is (including the alpha channel if present)

bool **imwrite**(const string& filename, InputArray img, const vector<int>¶ms=vector<int>())

- Parameters:**
- **filename** – Name of the file.
 - **image** – Image to be saved.
 - **params** – Format-specific save parameters encoded as pairs paramId_1, paramValue_1, paramId_2,

SEARCH CONTENTS OF THIS BLOG

POPULAR POSTS

- 1 Find Contour
 - 2 Basic drawing examples
 - 3 Line Detection by Hough Line Transform
 - 4 Face Detection using Haar-Cascade Classifier
- Perspective Transform
- Sobel Edge Detection

paramValue_2, The following parameters are currently supported:

- For JPEG, it can be a quality (CV_IMWRITE_JPEG_QUALITY) from 0 to 100 (the higher is the better). Default value is 95.
- For PNG, it can be the compression level (CV_IMWRITE_PNG_COMPRESSION) from 0 to 9. A higher value means a smaller size and longer compression time. Default value is 3.
- For PPM, PGM, or PBM, it can be a binary format flag (CV_IMWRITE_PXM_BINARY), 0 or 1. Default value is 1.

Kalman Filter Implementation (Tracking mouse position)

Histogram Calculation

OpenCV example to convert RGB to gray / other color spaces

void imshow(const string& winname, InputArray mat)

Parameters:

- **winname** – Name of the window.
- **image** – Image to be shown.

Steps:

1. Load image using **imread()**.
2. Display image using **namedWindow()** and **imshow()**.
3. Save the image using **imwrite()**.
4. Wait for keyboard button press using **waitKey()**.

Example:

```

1  #include <opencv2/core/core.hpp>
2  #include <opencv2/highgui/highgui.hpp>
3  #include <iostream>
4
5  using namespace cv;
6  using namespace std;
7
8  int main( )
9  {
10
11      Mat image;
12
13      // LOAD image
14      image = imread("image1.jpg", CV_LOAD_IMAGE_COLOR); // Read
15                  //This file "image.jpg" should be in the project fold
16                  //Else provide full address : "D:/images/image.jpg"
17
18      if(! image.data ) // Check for invalid input
19      {
20          cout << "Could not open or find the image" << std::e
21          return -1;

```

10 Hough Circle Detection

CATEGORIES

- [Accessory](#)
- [Applications](#)
- [Basics](#)
- [Edge Detection](#)
- [Feature Extraction](#)
- [Filter](#)
- [Miscellaneous](#)
- [Morphological Operation](#)

```
22     }
23
24     //DISPLAY image
25     namedWindow( "window", CV_WINDOW_AUTOSIZE ); // Create a win
26     imshow( "window", image ); // Show our image inside it.
27
28     //SAVE image
29     imwrite("result.jpg",image);// it will store the image in na
30
31     waitKey(0);           // Wait for a keystroke in
32     return 0;
33 }
```

Sources:

http://docs.opencv.org/doc/tutorials/introduction/display_image/display_image.html

 Recommend this on Google

Labels: [Basics](#)

No comments:

Post a Comment