

# LEARN OPENCV BY EXAMPLES

OpenCV simplified for beginners by the use of examples. Learn OpenCV with basic implementation of different algorithms.

<a href="#">Home</a>	<a href="#">For Beginners</a>	<a href="#">Table of Contents</a>	<a href="#">Keywords</a>	
----------------------	-------------------------------	-----------------------------------	--------------------------	--

## Sobel Edge Detection

void **Sobel**(InputArray src, OutputArray dst, int ddepth, int dx, int dy, int ksize=3, double scale=1, double delta=0, int borderType=BORDER\_DEFAULT)

Parameters:

- **src** – input image.
- **dst** – output image of the same size and the same number of channels as **src**.
- **ddepth** –

**output image depth; the following combinations of `src.depth()` and `ddepth` are supported:**

- `src.depth() = CV_8U, ddepth = -1/CV_16S/CV_32F/CV_64F`
- `src.depth() = CV_16U/CV_16S, ddepth = -1/CV_32F/CV_64F`
- `src.depth() = CV_32F, ddepth = -1/CV_32F/CV_64F`
- `src.depth() = CV_64F, ddepth = -1/CV_64F`

when `ddepth=-1`, the destination image will have the same depth as the source; in the case of 8-bit input images it will result in truncated derivatives.

- **xorder** – order of the derivative x.
- **yorder** – order of the derivative y.

### SEARCH CONTENTS OF THIS BLOG

### POPULAR POSTS

Find Contour

Basic drawing examples

Line Detection by Hough Line Transform

Face Detection using Haar-Cascade Classifier

Perspective Transform

Sobel Edge Detection

- **ksize** – size of the extended Sobel kernel; it must be 1, 3, 5, or 7.
- **scale** – optional scale factor for the computed derivative values; by default, no scaling is applied (see [getDerivKernels\(\)](#) for details).
- **delta** – optional delta value that is added to the results prior to storing them in dst.
- **borderType** – pixel extrapolation method (see [borderInterpolate\(\)](#) for details).

**Functions:**

[Sobel](#), [Vec3b](#), [convertTo](#), [imshow](#), [imread](#), [namedWindow](#), [waitKey](#).

This is a code from [OpenCV documentation](#). I have made some changes to it.

**Example:**

-----

```

1  #include "opencv2/core/core.hpp"
2  #include "opencv2/highgui/highgui.hpp"
3  #include "opencv2/imgproc/imgproc.hpp"
4  #include "iostream"
5
6  using namespace cv;
7  using namespace std;
8
9  int main( )
10 {
11     Mat src1;
12     src1 = imread("lena.jpg", CV_LOAD_IMAGE_COLOR);
13     namedWindow( "Original image", CV_WINDOW_AUTOSIZE );
14     imshow( "Original image", src1 );
15
16     Mat grey;
17     cvtColor(src1, grey, CV_BGR2GRAY);
18
19     Mat sobelx;
20     Sobel(grey, sobelx, CV_32F, 1, 0);
21
22     double minVal, maxVal;
23     minMaxLoc(sobelx, &minVal, &maxVal); //find minimum and maximum
24     cout << "minVal : " << minVal << endl << "maxVal : " << maxVal
25
26     Mat draw;
27     sobelx.convertTo(draw, CV_8U, 255.0/(maxVal - minVal), -minVal
28
29     namedWindow("image", CV_WINDOW_AUTOSIZE);
30     imshow("image", draw);
31
32     waitKey(0);
33     return 0;
34 }
```


- 7 Kalman Filter Implementation (Tracking mouse position)
- 8 Histogram Calculation
- 9 OpenCV example to convert RGB to gray / other color spaces
- 10 Hough Circle Detection

## CATEGORIES

-----

- [Accessory](#)
- [Applications](#)
- [Basics](#)
- [Edge Detection](#)
- [Feature Extraction](#)
- [Filter](#)
- [Miscellaneous](#)
- [Morphological Operation](#)

-----  
Result:



 Recommend this on Google

Labels: [Edge Detection](#)

**No comments:**

**Post a Comment**