

4

ESM-Tools Terminology

Overview

YAML Hierarchy

Configuration files

Runscripts

YAML Sections

Feature Variables

Compilation Scripts

.run files



4 Terminology

- ▶ Through out this workshop we will be using ESM-Tools-specific terms that you'll need to be familiar with. Those terms are defined in this power point.
- ▶ You'll see those terms in the other slides coloured in orange

4 YAML Hierarchy



▶ YAML files are always inherited from more general to more specific. Last one wins (eg. user runscript).



4 Terminology – configuration files



The yaml files that contain the **default configurations** for HPCs, models, coupled systems, job schedulers (SLURM, PBS), default ESM-Tools recipes, ...

esm_tools/configs/

— components	Stand-alone model, couplers, I/O libraries configurations
— setups	Coupled system default configurations
— machines	HPC default configurations
— coupling	Source code branch information for coupled system stored here, only for use in ESM-Master (to be removed in the future)
— default	ESM-Tools default configurations
— esm_software	Recipes and defaults for ESM-Runscripts and ESM-Master
— other_software	Job schedulers and other external software configurations

4 Terminology – runscripts

- ▶ User interface for running experiments
- ▶ Should include all the deviations from the defaults defined in the **configuration files**
- ▶ Can be shared to reproduce the same experiment
- ▶ A yaml file with **sections**

<your_fesom_runscript>.yaml

```
general:  
  account: <your_account>  
  setup_name: fesom  
  compute_time: "00:20:00"  
  initial_date: '2001-01-01'  
  final_date: '2001-03-01'  
  base_dir: <your_basedir>  
  nyear: 0  
  nmonth: 1  
  nday: 0  
  use_venv: False  
  
fesom:  
  version: 2.1  
  model_dir: <your_model_dir>  
  lresume: 0  
  restart_rate: 1  
  restart_unit: 'm'  
  post_processing: 0
```

4 Terminology – YAML sections

- ▶ 1st level keys on a yaml file
 - general
 - <model_name>/<component_name>
 - computer
- ▶ Only the **runscripts** and the **setups** files have **sections**

runscripts

configs

components

setups

machines

coupling

default

esm_software

other_software

<your_fesom_runscript>.yaml

general:

```
account: <your_account>
setup_name: fesom
compute_time: "00:20:00"
initial_date: '2001-01-01'
final_date: '2001-03-01'
base_dir: <your_basedir>
nyear: 0
nmonth: 1
nday: 0
use_venv: False
```

fesom:

```
version: 2.1
model_dir: <your_model_dir>
lresume: 0
restart_rate: 1
restart_unit: 'm'
post_processing: 0
```

4 Terminology – feature variables



Some variables in the yaml files trigger functionalities in ESM-Tools. Through this variables the **yaml syntax is extended**.

We refer to this variables as **feature variables**

```
# time variables
```

```
general:
  nday: 0
  nmonth: 1
  initial_date: "1850-01-01T00:00:00"
  final_date: "1860-01-01T00:00:00"
```

```
# creating and accessing variables from different sections
```

```
ini_restart_dir: "${general.ini_restart_dir}/fesom/"
```

```
# Changing Fortran namelists
```

```
namelist_changes:
  namelist.echam:
    runctl:
      out_expname: ${general.expid}
      dt_start:
        - ${pseudo_start_date!year}
        - ${pseudo_start_date!month}
```

```
# adding and removing elements from lists and dicts
```

```
list1:
  - element1
  - element2

add_list1:
  - element3
  - element4
```

```
# choose_blocks allow select-case (aka switch) statements
resolution: CORE2
```

```
choose_resolution:
  CORE2:
    nx: 126858
    mesh_dir: "${pool_dir}/meshes/mesh_CORE2_final/"
    nproc: 288
    time_step: 450
  GLOB:
    nx: 830305
```

4 Terminology – compilation scripts

- ▶ For each component that **esm_master** builds, it produces a compilation script **comp-*.sh** that includes the environment specified in the configuration files (**machine** + **components** + **setups**) files involved
- ▶ Written in the same directory where you execute **esm_master**
- ▶ Copied to the compilation folder after the building finishes

```
#!/bin/bash -L
# Dummy script generated by esm-tools, to be removed later:
set -e
module purge
module unload netcdf_c
module unload intel intelmpi
module load python3/2021.01-gcc-9.1.0
module load cmake/3.13.3
module load autoconf/2.69
module load nco
module load cdo
module load gcc/4.8.2
module unload intel intelmpi
module load intel/18.0.4 intelmpi/2018.5.288
module load libtool/2.4.6
module load automake/1.14.1
module unload gcc
module load gcc/4.8.2
export LC_ALL=en_US.UTF-8
export FC=mpiifort
export F77=mpiifort
export MPIFC=mpiifort
export CC=mpiicc
export CXX=mpiicpc
export MPIROOT="$(mpiifort -show | perl -lne 'm{ -I(.*)/include } and print $1')"
```

```
...
cd fesom-2.1
mkdir -p build; cd build; cmake -DFESOM_COUPLED=ON ..; make install -j `nproc` --all`
cd ..
```


4 Terminology – *.run files

▶ **esm_runscripts** produces a ***.run** script with SBATCH headers that is then submitted to SBATCH. This script contains the combined environments specified in the configuration files (**machine** + **components** + **setups**) files involved

▶ This script can be found in **<experiment_dir>/run_DATE/scripts** for runs that have not being submitted or are still running, or in the **<experiment_dir/scripts>** directory for runs that have already run

```
#SBATCH --partition=compute
#SBATCH --time=01:45:00
#SBATCH --ntasks=896
...
module purge
module unload netcdf_c
module unload intel intelmpi
...
export LC_ALL=en_US.UTF-8
export FC=mpif90
export F77=mpif90
...

# Set stack size to unlimited
ulimit -s unlimited

# 3...2...1...Liftoff!
echo $(date +"%a %b %e %T %Y") : compute 1 1850-01-01T00:00:00 1233 - start
>> /work/ab0995/a270152//workshop_test/log//workshop_test_awiesm.log


cd /work/ab0995/a270152//workshop_test/run_18500101-18501231/work/

time srun -l --kill-on-bad-exit=1 --cpu_bind=cores --multi-prog hostfile_srun
2>&1 &

...
```

4 Terminology – finished_config file

- ▶ Internally, **esm_parser** puts together all the information from the different yaml files for the given experiment into a Python object called **config**
- ▶ This object, containing all the information about the experiment, is passed to the different ESM-Tools functions
- ▶ **esm_runscripts** dumps this object into a yaml file in **<experiment_dir>/run_DATE/configs/*finished_config.yaml** for runs that have not being submitted or are still running, or in **<experiment_dir>/configs/*finished_config.yaml** for runs that have already run
- ▶ The **finished_config file** is used for checking that the final configuration works as expected



Terminology – check mode

- ▶ **esm_master** and **esm_runscripts** can run in check mode by adding the **--check** or **-c** flags to the command
- ▶ **esm_master** in check mode
 - Outputs the git commands and building commands but does not produce the **comp-*.sh** files
- ▶ **esm_runscripts** in check mode
 - Bakes the yaml information and produces the **finished_config.yaml**
 - Prepares the experiment folder (copies in input, forcing, binaries, ...)
 - Produces the ***.run** file
 - **Does not** submit the ***.run** script to **sbatch**

To be changed in the future to
it produces **comp-*.sh** files

Terminology – models and components



FESOM-2

- AWI's ocean model
- Finite Volume
- Unstructure mesh



AWI-ESM-2.1

- ECHAM6 + FESOM-2.1 with OASIS3MCT
- Dynamic vegetation
- + REcoM (biogeochemistry) + PISM (WIP, offline coupled)



VILMA-PISM

- Offline coupling through ESM-Tools workflow manager