Security risk assessment report

Part 1: Select up to three hardening tools and methods to implement
By implementing: 1. Strong password policies 2. Enabling MFA 3. Properly configuring firewalls With these three hardening tools and methods to implement, organization can significantly reduce the risk of future data breaches. These measures collectively address the primary vulnerabilities that was identified in the social media organization and strengthen the overall network security posture.

Part 2: Explain your recommendations
Implementing Strong Password Policies – It mitigates the risk of default or shared passwords being exploited. It also reduces the likelihood of brute-force attacks and unauthorized access via shared credentials. Password policies should be enforced continuously for all users and should be updated or rotated regularly typically every 60-90 days. - Require complex passwords such as minimum of 8 characters with a combination of uppercase, lowercase, special characters and numbers. - Enforce unique passwords for each user, including administrative accounts. **Enabling Multi-Factor Authentication (MFA)** – It adds additional layer of security beyond passwords. It can strongly protect against phishing and brute-force attempts. MFA should be enabled permanently for all users, especially administrators. - Require a second factor such as SMS code, face recognition, fingerprints, or authentication app for all users especially for the administrators. - MFA prevents attackers from accessing accounts even if passwords are compromised.

Implementing and Configuring Firewalls with Proper Traffic Filtering – It protects the network perimeter by controlling incoming and outgoing traffic. It can also limit the exposure to external threats and prevents malicious traffic from reaching critical assets. Firewall rules should be enforced continuously. Regularly update firewall rules to match changes in the network and threat landscape.

- Define and enforce rules for allowed and blocked traffic based on source, destination, and port.
- Monitor logs for suspicious activity and unauthorized access attempts.