

Manipulation

Column Constraints

Column constraints are the rules applied to the values of individual columns:

- **PRIMARY KEY** constraint can be used to uniquely identify the row.
- **UNIQUE** columns have a different value for every row.
- **NOT NULL** columns must have a value.
- **DEFAULT** assigns a default value for the column when no value is specified.

There can be only one **PRIMARY KEY** column per table and multiple **UNIQUE** columns.

```
CREATE TABLE student (
  id INTEGER PRIMARY KEY,
  name TEXT UNIQUE,
  grade INTEGER NOT NULL,
  age INTEGER DEFAULT 10
);
```

CREATE TABLE Statement

The **CREATE TABLE** statement creates a new table in a database. It allows one to specify the name of the table and the name of each column in the table.

```
CREATE TABLE table_name (
  column1 datatype,
  column2 datatype,
  column3 datatype
);
```

INSERT Statement

The **INSERT INTO** statement is used to add a new record (row) to a table.

It has two forms as shown:

- Insert into columns in order.
- Insert into columns by name.

```
-- Insert into columns in order:
INSERT INTO table_name
VALUES (value1, value2);
```

```
-- Insert into columns by name:
INSERT INTO table_name (column1,
column2)
VALUES (value1, value2);
```

ALTER TABLE Statement

The **ALTER TABLE** statement is used to modify the columns of an existing table. When combined with the **ADD COLUMN** clause, it is used to add a new column.

```
ALTER TABLE table_name
ADD column_name datatype;
```

DELETE Statement

The **DELETE** statement is used to delete records (rows) in a table. The **WHERE** clause specifies which record or records that should be deleted. If the **WHERE** clause is omitted, all records will be deleted.

```
DELETE FROM table_name
WHERE some_column = some_value;
```

UPDATE Statement

The **UPDATE** statement is used to edit records (rows) in a table. It includes a **SET** clause that indicates the column to edit and a **WHERE** clause for specifying the record(s).

```
UPDATE table_name
SET column1 = value1, column2 = value2
WHERE some_column = some_value;
```

 **Print**  **Share** ▼