

Language Understanding Systems

(Weighted) Finite State Transducers

Evgeny A. Stepanov

SISL, DISI, UniTN & VUI, Inc.

`evgeny.stepanov@unitn.it`

Outline

- 1 Finite State Acceptors & Transducers
- 2 FSA/FST Operations
- 3 FST Operations
- 4 Text to FSM
- 5 FSA/FST Exercises

Section 1

Finite State Acceptors & Transducers

Finite State Transducers

Acceptor

- FSM with 1 tape:
input
- accepts/recognizes
strings

Transducer

- FSM with 2 tapes:
input & output
- translates input to
output string

FSA File Format

FSM: A.txt

from_state to_state input_symbol (weight)

0 0 red 0.5

0 1 green 0.3

1 2 blue 0.0

1 2 yellow 0.6

2 0.8

Lexicon/Symbol File: A.lex

<eps> 0

red 1

green 2

blue 3

yellow 4

FST File Format

FSM: A.txt

from_state to_state input_symbol output_symbol (weight)

0 0 red yellow 0.5

0 1 green blue 0.3

1 2 blue green 0.0

1 2 yellow red 0.6

2 0.8

Lexicon/Symbol File: A.lex

<eps> 0

red 1

green 2

blue 3

yellow 4

Basic Commands: FSA

Compilation


```
fstcompile --acceptor --isymbols=A.lex A.txt > A.fsa
```

Printing

```
fstprint --acceptor --isymbols=A.lex A.fsa
```

Drawing

```
fstdraw --acceptor --isymbols=A.lex A.fsa |  
dot -Tpng > A.png
```



Basic Commands: FST

Compilation


```
fstcompile --isymbols=A.lex --osymbols=A.lex A.txt >
A.fst
```

Printing

```
fstprint --isymbols=A.lex --osymbols=A.lex A.fst
```

Drawing

```
fstdraw --isymbols=A.lex --osymbols=A.lex A.fst |
dot -Tpng > A.png
```



Section 2

FSA/FST Operations

Regular Expressions

- \emptyset is a Regular Expression
- Each symbol from Σ is a Regular Expression
- If α and β are Regular Expressions, then so is $(\alpha \circ \beta)$
- If α and β are Regular Expressions, then so is $(\alpha \cup \beta)$
- If α is a Regular Expression, then so is (α^*)

Languages expressed using Regular Expressions are called
Regular Languages

Closure Properties of Regular Languages

RL are closed under following operations:



- **Intersection:** if L_1 and L_2 are RL, then so is $L_1 \cap L_2$, the language consisting of the set of strings in both L_1 and L_2
- **Difference:** if L_1 and L_2 are RL, then so is $L_1 - L_2$, the language consisting of the set of strings in both L_1 and not in L_2
- **Complementation:** if L_1 is a RL, then so is its complement \bar{L}_1
- **Reversal:** if L_1 is a RL, then so is L_1^R , the set of reversals of all strings in L_1

FSA Operations

| Operation | Implementation |
|-------------------------|----------------------|
| Concatenation (Product) | fstconcat |
| Union (Sum) | fstunion |
| Kleene* | fstclosure |
| Intersection | fstintersect |
| Difference | fstdifference |
| Reversal | fstreverse |
| Complement | N/A |




Concatenation (Product)

- Equation: $C = AB$
- Command: `fstconcat A.fsa B.fsa > C.fsa`





Concatenation (Product)

- Equation: $C = AB$
- Command: `fstconcat A.fsa B.fsa > C.fsa`






Union (Sum)

- Equation: $C = A \cup B$ ($C = A + B$)
- Command: **fstunion A.fsa B.fsa > C.fsa**




Union (Sum)

- Equation: $C = A \cup B$ ($C = A + B$)
- Command: **fstunion A.fsa B.fsa > C.fsa**





(Concatenative) Closure

- Equation: $C = B^* = B^0 + B^1 + B^2 + \dots$
- Command: **fstclosure B.fsa > C.fsa**





(Concatenative) Closure

- Equation: $C = B^* = B^0 + B^1 + B^2 + \dots$
- Command: `fstclosure B.fsa > C.fsa`





Intersection

- Equation: $C = A \cap B$
- Command: `fstintersect A.fsa B.fsa > C.fsa`




Intersection

- Equation: $C = A \cap B$
- Command: `fstintersect A.fsa B.fsa > C.fsa`






Difference

- Equation: $C = A - B : B$ – Unweighted & Deterministic
- Command: **fstdifference A.fsa B.fsa > C.fsa**




Difference

- Equation: $C = A - B : B$ – Unweighted & Deterministic
- Command: **fstdifference A.fsa B.fsa > C.fsa**





Reversal

- Equation: $C = A^R$
- Command: **fstreverse A.fsa > C.fsa**



Reversal

- Equation: $C = A^R$
- Command: **fstreverse A.fsa > C.fsa**



Complement

- Equation: $C = A^{-1}$
- Command: **N/A**

Complement

- Equation: $C = A^{-1}$
- Command: **N/A**

WHY?

Complement

- Equation: $C = A^{-1}$
- Command: **N/A**

WHY?

- Alphabet issue
- Non-determinism issue



Epsilon Removal

- Command: `fstrmepsilon A.fsa > C.fsa`




Epsilon Removal

- Command: `fstrmepsilon A.fsa > C.fsa`





Trimming: Remove 'unreachable' states

- Command: `fstconnect A.fsa > C.fsa`




Trimming: Remove 'unreachable' states

- Command: `fstconnect A.fsa > C.fsa`





Determinization

- Command: `fstdeterminize A.fsa > C.fsa`




Determinization

- Command: `fstdeterminize A.fsa > C.fsa`




Minimization

- Command: **fstminimize A.fsa > C.fsa**
- returns the minimal deterministic FSM equivalent to the input FSM, which must be a deterministic acceptor. Epsilon arcs are treated the same as other symbols.



Minimization

- Command: **fstminimize A.fsa > C.fsa**
- returns the minimal deterministic FSM equivalent to the input FSM, which must be a deterministic acceptor.
Epsilon arcs are treated the same as other symbols.



FSM Utilities


- **fstarcsort** sorts the arcs in an FSM per state. Some operations depend on the FSM arcs being sorted. It is a good idea to always sort compiled FSMs prior to working on them.
- **fsttopsort** sorts an FSM so that all transitions are from lower to higher state IDs. It is useful to apply it before printing.
- **fstinfo** prints out information about an FSM.

Section 3

FST Operations



Projection

- Equation: $A = \pi_1(T)$
- Command: **fstproject A.fst > A.fsa**
- converts a *transducer* into an *acceptor* by retaining only the input or output (with `--project_output`) label on each transition




Projection

- Equation: $A = \pi_1(T)$
- Command: **fstproject A.fst > A.fsa**
- converts a *transducer* into an *acceptor* by retaining only the input or output (with `--project_output`) label on each transition





Inverse

- Command: **fstinvert A.fst > C.fst**
- inverts a transducer; transposes the input and output symbols on each transition




Inverse

- Command: **fstinvert A.fst > C.fst**
- inverts a transducer; transposes the input and output symbols on each transition




Composition

- Command: **fstcompose A.fst B.fst > C.fst**
- ‘composes’ FSMs:
given 2 FSMs: fst_1 that transduces from s_1 to s_2 and fst_2 that transduces from s_2 to s_3 , returns fst_3 that transduces from s_1 to s_3 with the 2 costs combined
- *acceptor* is treated as a transducer to itself



Composition

- Command: **fstcompose A.fst B.fst > C.fst**
- ‘composes’ FSMs:
 given 2 FSMs: fst_1 that transduces from s_1 to s_2 and fst_2 that transduces from s_2 to s_3 , returns fst_3 that transduces from s_1 to s_3 with the 2 costs combined
- *acceptor* is treated as a transducer to itself



Section 4


Text to FSM

Text as FSM

- How do we represent text as FSM?
- e.g.: *Lorem ipsum dolor sit amet*

Text as FSM

- How do we represent text as FSM?
- e.g.: *Lorem ipsum dolor sit amet*



Solution: text2fsa script (bash)

```
#!/bin/bash
# read input string from STDIN
str=$1
# parse it into array using space as separator
arr=($(echo $str | tr ' ' '\n'))
# set initial state
state=0
# iterate through array
# printing current and next states & token
for token in ${arr[@]}
do
    echo -e "$state\t$((state+1))\t$token"
    # increment state
    ((state++))
done
# print final state
echo $state
```

How do we test whether FSM accepts a string?

How do we test whether FSM accepts a string?

Intersect the string with the FSM.

How do we test whether FSM accepts a string?

Intersect the string with the FSM.

- ① Create an FSM of the string & compile it

How do we test whether FSM accepts a string?

Intersect the string with the FSM.

① Create an FSM of the string & compile it

- using script
- `echo 'star of thor' |
farcompilestrings --symbols=lex.txt
--unknown_symbol='<unk>' --generate_keys=1
--keep_symbols |
farextract --filename_suffix='.fst'`

How do we test whether FSM accepts a string?

Intersect the string with the FSM.

- ① Create an FSM of the string & compile it
 - using script
 - `echo 'star of thor' |
farcompilestrings --symbols=lex.txt
--unknown_symbol='<unk>' --generate_keys=1
--keep_symbols |
farextract --filename_suffix='.fst'`
- ② Intersect the string FSM with the FSM you are testing (e.g. LM)

How do we test whether FSM accepts a string?

Intersect the string with the FSM.

- ① Create an FSM of the string & compile it
 - using script
 - `echo 'star of thor' |
farcompilestrings --symbols=lex.txt
--unknown_symbol='<unk>' --generate_keys=1
--keep_symbols |
farextract --filename_suffix='.fst'`
- ② Intersect the string FSM with the FSM you are testing (e.g. LM)
 - `fstintersect string.fsa test.fsa > out.fsa`

How do we test whether FSM accepts a string?

Intersect the string with the FSM.

- ① Create an FSM of the string & compile it
 - using script
 - `echo 'star of thor' |
farcompilestrings --symbols=lex.txt
--unknown_symbol='<unk>' --generate_keys=1
--keep_symbols |
farextract --filename_suffix='.fst'`
- ② Intersect the string FSM with the FSM you are testing (e.g. LM)
 - `fstintersect string.fsa test.fsa > out.fsa`
- ③ Print the output FSM

How do we test whether FSM accepts a string?

Intersect the string with the FSM.

- ① Create an FSM of the string & compile it
 - using script
 - `echo 'star of thor' |
farcompilestrings --symbols=lex.txt
--unknown_symbol='<unk>' --generate_keys=1
--keep_symbols |
farextract --filename_suffix='.fst'`
- ② Intersect the string FSM with the FSM you are testing (e.g. LM)
 - `fstintersect string.fsa test.fsa > out.fsa`
- ③ Print the output FSM
 - `fstprint --isymbols=lex.txt --osymbols=lex.txt
out.fsa`

Clean Output

```
fstintersect string.fsa test.fsa |  
fstshortestpath |  
fstrmepsilon |  
fsttopsort |  
fstprint --isymbols=lex.txt --osymbols=lex.txt
```


Section 5

FSA/FST Exercises

FST/FSA Exercises

- Mohri et al. (1996) FSM Toolkit Exercises

Exercise 1

Given the alphabet $L = \{a, b, \dots, z, A, B, \dots, Z, < \text{space} >\}$, create an automaton that:

- a) accepts a letter in L (including space).
- b) accepts a single space.
- c) accepts a capitalized word (where a word is a string of letters in L excluding space and a capitalized word has its initial letter uppercase and remaining letters lowercase).
- d) accepts a word containing the letter a .

Exercise 2

Using the automata in Exercise 1 as the building blocks, use appropriate FSM operations on them to create an automaton that:

- a) accepts zero or more capitalized words followed by spaces.
- b) accepts a word that is capitalized and contains the letter *a*.
- c) accepts a word that is capitalized or does not contain an *a*.

Exercise 3

Epsilon-remove, determinize, and minimize each of the automata in Exercise 2. Give the number of states and arcs before and after these operations.

Exercise 4

Consider the automaton:

0 1 1

0 2 2

1 1 1

2

3 4 4

4 3 3

4

- a) How many states can be reached from the initial state?
- b) How many states can reach a final state?
- c) Compile this automaton and then remove all useless states.

Exercise 5

Given the alphabet $\{a, b, \dots, z, < \text{space} >\}$,

- a) create a transducer that implements *rot13* cipher: $a \rightarrow n$, $b \rightarrow o$, ..., $m \rightarrow z$, $n \rightarrow a$, $o \rightarrow b$, ..., $z \rightarrow m$.
- b) encode and decode the message “my secret message” (assume $< \text{space} > \rightarrow < \text{space} >$).

Exercise 9

Given the alphabet $L = \{A, G, T, C\}$,

- a) create transducer T that implements edit distance
$$d(x, x) = 0, x \in L$$
$$d(x, y) = d(x, \epsilon) = d(\epsilon, y) = 1, x \neq y \in L$$
- b) using T find the best alignment between the strings 'AGTCC' and 'GGTACC'