REPO RADAR

Sync-in: self-hosted file sync, quick guide

What it is: Sync-in is an open-source (AGPL-3.0) self-hosted platform for file storage, synchronization and team collaboration. Files stay readable on your own filesystem.

Source: https://github.com/Sync-in/server (README)

What it offers (from the README)

- Web interface, sharing links with passwords and expiry dates
- WebDAV support, so file explorers can mount it like a network drive
- Interface in more than 50 languages
- Desktop and CLI clients for Windows, macOS and Linux: https://github.com/Sync-in/desktop

Setup

The project documents two routes: Docker (https://sync-in.com/docs/setup-guide/docker) and npm (https://sync-in.com/docs/setup-guide/npm).

Its backend uses a MySQL-compatible database (`mysql2` driver in `backend/package.json`), so plan for one.

What we tested

In a throwaway sandbox on 2026-11-06 we cloned the repo and ran `npm ci --ignore-scripts`: 1,332 packages installed in about 22 seconds (Node 22).

We did NOT run a full server with a database, so we make no claim about runtime behaviour.

3 uses

1. Replace a paid cloud-storage plan with your own server.
2. Share files with a link that expires.
3. Mount a remote folder as a network drive through WebDAV.

Always read the licence and the docs yourself before exposing a server to the internet.

Free guide from Repo Radar. Information only, not financial, legal or medical advice.