REPO RADAR

Top 10 GitHub Repos This Week: links and install steps

Ranked by average stars per day since creation, GitHub data of October 23, 2026. Each README's install command is quoted as written by its authors: read it before you run anything. Stars change daily.

| # | Repo | License | What it is |

|---|------|---------|------------|

| 1 | https://github.com/deepseek-ai/deepseek-harness | MIT | Open source agent harness, "everything is a plugin" (developer preview) |

| 2 | https://github.com/storytold/photocraft | MIT or Apache-2.0 | Photoshop-style image editor in pure Rust (early alpha) |

| 3 | https://github.com/deepseek-ai/DeepInfer | Apache-2.0 | DeepSeek inference framework (needs NVIDIA SM100 or Ascend 950) |

| 4 | https://github.com/DietrichGebert/ponytail | MIT | Makes your AI agent write less code |

| 5 | https://github.com/wheresryan22/anatomy | MIT | Claude skill for interactive isometric figures |

| 6 | https://github.com/openclaw/openclaw | MIT | Open source personal AI assistant |

| 7 | https://github.com/mattpocock/skills | MIT | Agent skills for real engineers |

| 8 | https://github.com/google-research/harness2 | Apache-2.0 | Recursive agent harnessing |

| 9 | https://github.com/storytold/wordcraft | MIT or Apache-2.0 | Word processor in pure Rust |

| 10 | https://github.com/tangency-labs/solidcraft | MIT or Apache-2.0 | Parametric 3D CAD in pure Rust |

Install steps (from each README)

- **DeepSeek Harness**: install Node.js, then `npx @deepseek-ai/dsh web`. In our sandbox the npx launch failed with "dsh: not found" (package version 0.2.1-rc.2 exists on npm). Or from source: `pnpm install && pnpm run build && pnpm dsh web`.
- **Harness²** (we ran this): Linux, Python 3.12, uv. `uv venv --python 3.12 .venv`, `source .venv/bin/activate`, `uv pip install -e '.[render]'`, `harness2-demo --output runs/demo --k 2`. Result for us: 2 tasks completed, 0 failed.
- **Anatomy**: `npx skills add wheresryan22/anatomy -g`, then `/anatomy explain how a token bucket rate limiter works, interactive`.
- **Ponytail** (Claude Code): `/plugin marketplace add DietrichGebert/ponytail`, then `/plugin install ponytail@ponytail`.
- **Skills**: `claude plugin install mattpocock-skills@claude-plugins-official`, then run `/setup-matt-pocock-skills` once per repo.
- **WordCraft**: `cargo run --release -p wordcraft -- --sample` (needs Rust).
- **OpenClaw**: the README's main installer pipes a script into the shell. We did not run it. Read the script first, or use the npm package route in the README.
- **DeepInfer, PhotoCraft, SolidCraft**: see each README; DeepInfer needs a supported GPU, and the other two are Rust projects (cargo).

3 things to do

1. Open each README and check the license file before using a repo.
2. Try the one that fits your stack in a throwaway folder or container.
3. Check the repo's issues and last commit date before relying on it.

2 mistakes to avoid

1. Running `curl | sh` installers without reading them.
2. Treating a README's benchmark claims as proven: they are the authors' claims.

Glossary

- **Harness**: the system around a model (prompts, tools, memory, orchestration) that lets it act as an agent.
- **Inference**: running a trained model to get outputs.
- **Clean-room**: written without copying the original program's code, by the authors' own description.
- **MCP**: Model Context Protocol, a standard for connecting tools to AI agents.

Free guide from Repo Radar. Information only, not financial, legal or medical advice.