Concentrated Low-Odor Floor Stripper

Reorder No. 204013 / 5 gal.

Features

- Contains no ammonia
- Concentrated formula
- Works quickly and completely

Benefits

- Non-irritating to residents
- Economical in use
- Labor saving



Recommended Uses

Removal of metal cross linked floor finishes without ammonia odor.

Specifications

- Light orange color
- 12.0-13.0 pH use dilution
- No scent/odor
- Contains no phosphorus
- Clear, non-viscous liquid
- cRc approved
- Low foam

Important

Read and understand the label and Safety Data Sheet (SDS). These provide a description of hazards, precautions, personal protective equipment, first aid, 24 Hour Emergency lines, storage data and other safe handling information. The SDS is provided with each container shipped, it is also available from the distributor.

Product Directions

Equipment to use:

Clean mop and bucket, scrubbing machine with stripping pads, wet vacuum, personal protective equipment.

Directions for use:

Dilution: To remove metal complex finishes and most other polymer finishes, prepare a dilution with hot water of 10 ounces of product to 1 gallon of water. For heavy build-up and difficult-to-remove sealers, product may be diluted with hot water (up to 32 ounces of product to 1 gallon of water.)

Application and scrubbing: Apply the hot solution to area using a wet mop or from the solution feed tank of a floor machine. Apply the solution liberally to an area no larger than 10 feet by 12 feet. Allow 3 - 5 minutes for the solution to work before scrubbing. In most cases, a green or brown stripping pad is recommended. For hard surfaces with heavy build-ups, such as terrazzo and concrete, a black pad may be used.

Procedures for pick up and rinsing: The used stripping solution should be picked up using a wet vacuum or a mop and bucket. Wet vacuum: It is recommended that the floor be rinsed immediately to prevent small amounts of residue from drying on the floor. Mop and bucket: The floor should first be soaked with an unwrung mop. This will float the spent solution, along with the old finish, off the floor. Pick up this solution with a wrung-out mop. Rinse the floor completely with clean water. Double rinsing is recommended. After rinsing, you should be able to run your finger across the dry floor without picking up any powdery residue.

Procedures for detailing and edging: To remove heavy build-up along base boards, in corners, and around door stops, etc. Product may be diluted as strong as 1 gallon of product to 1 gallon of water. Protective gloves are recommended when solution comes in contact with hands.

Note: DO NOT use on wood or cork floors. Some grades of linoleum may be discolored by product. Always pre-test floor with a small amount of solution before stripping. Blockade areas to be stripped. Floors will become very slippery when stripper is applied. Exercise caution.

Distributed exclusively by Gordon Food Service®
P.O. Box 1787 • Grand Rapids, MI 49501 • (800) 968-6474
©2015 Gordon Food Service® • gfs.com