Concentrated Heavy Duty Floor Stripper

Reorder No. 204005 / 5 gal.

Features

- Non-ammoniated formula
- Powerful stripping action
- Stripping pads unnecessary



Benefits

- Low odor characteristics
- Quickly removes all finishes
- Easier on floors

Recommended Uses

Removal of multiple layers of floor finishes without the use of stripping pads.

Specifications

- Colorless to light yellow color
- Solvent odor
- Clear, non-viscous liquid
- Low foam
- >12.0 pH use dilution
- Contains no phosphorus
- cRc approved

Important

Read and understand the label and Safety Data Sheet (SDS). These provide a description of hazards, precautions, personal protective equipment, first aid, 24 Hour Emergency lines, storage data and other safe handling information. The SDS is provided with each container shipped, it is also available from the distributor.

Product Directions

Equipment to use:

Pail and mop wringer, scrubbing machine and pads.

Directions for use:

DILUTION – Mix with warm water. For light buildup dilute 1:12 - 1:14, moderate 1:8 - 1:10; heavy 1:2 - 1:4. APPLICATION – Use a wet mop or the solution tank on floor machine to apply solution. Cover an area about 50-60 square feet liberally with solution. Allow solution to work on floor finish for 4-6 minutes before scrubbing. Keep area wet - do not allow solution to dry on floor. PICK-UP AND RINSING – The used stripping solution should be picked up using a wet vacuum or a mop and bucket. When using a wet vacuum, it is recommended that the floor be rinsed immediately to prevent small amounts of residue from drying on the floor. When using a mop and bucket, the floor should first be soaked with an unwrung mop. This will float the spent solution, along with the old finish, off the floor. Pick up this solution with a wrung-out mop. Rinse the floor completely with clear water. Double rinsing is recommended. After rinsing, you should be able to run your finger across the dry floor without picking up any powdery residue. PROCEDURES FOR REMOVING FINISH FROM ASPHALT OR VINYL/ASBESTOS TILE FLOORS – 1. Keep floor adequately wet. 2. Operate machine at slow speed. 3. Use blue, green or red pads for stripping (scrubbing type). 4. Do not dry-strip or wet-strip unwaxed floors.
CAUTION: DO NOT USE ON WOOD, CORK OR MARBLE FLOORS. Blockade areas to be stripped. Floors will become very slippery when stripper is applied. Excercise caution.

Distributed exclusively by Gordon Food Service®
P.O. Box 1787 • Grand Rapids, MI 49501 • (800) 968-6474
©2015 Gordon Food Service® • gfs.com