

<テキスト資料> 螺旋運動ノードを作ってみよう

my_node.pyの変更

```
import rclpy
from rclpy.node import Node
from geometry_msgs.msg import Twist

class SpiralPublisher(Node):
    def __init__(self):
        super().__init__('spiral_publisher')
        self.publisher_ = self.create_publisher(Twist, '/turtle1/cmd_vel', 10)
        self.timer = self.create_timer(0.1, self.timer_callback) # 0.1秒ごとに送信
        self.count = 0

    def timer_callback(self):
        msg = Twist()
        msg.linear.x = 0.5 + 0.05 * self.count # 前進速度を徐々に増やす
        msg.angular.z = 1.0 # 回転速度は一定
        self.publisher_.publish(msg)
        self.get_logger().info(f'Publishing spiral: linear={msg.linear.x:.2f}, angular={msg.angular.z:.2f}')
        self.count += 1

def main(args=None):
    rclpy.init(args=args)
    node = SpiralPublisher()
    rclpy.spin(node)
    node.destroy_node()
    rclpy.shutdown()
```

パッケージのビルド

```
cd ~/colcon_ws
colcon build
source install/setup.bash
```

別ターミナルでTurtlesimを起動

```
ros2 run turtlesim turtlesim_node
```

元ターミナルで自作ノードを起動

```
ros2 run my_py_pkg my_node
```