

OVERVIEW

The Core Lifter is made of high quality alloy steel tubing that is specially heat treated to increase strength, toughness and wear life.

The core lifter is the second piece of the check valve system, It is designed to let the core sample move easily up into the inner tube when the core is pulled back, the core lifter grips the sample which results in it being pulled down further into the taper of the core lifter case. This action forces the slot in the core lifter to close even tighter onto the sample ensuring it does not slip as it is being retrieved out the hole.

TECHNICAL SPECS

Features

		
Slotted	Broached	Broached Helicoids
- Improved core lifter design. - Ideal for use in competent ground conditions. - Increased grip area with the core sample. - Also known as the Brown Core Lifter	- Ideal for use in broken ground. - Increased flexibility; ideal for use encountered irregular core shapes. - Also Known as the Fluted Core Lifter	- Ideal for use in broken ground. - Increased flexibility; ideal for use encountered irregular core shapes.

Sizes & Weights

	AO	BO	NO	HO	PO
Weight	0.02 kg / 0.04lb	0.03 kg / 0.06 lb	0.06 kg / 0.13 lb	0.11 kg / 0.24 lb	0.20 kg / 0.44 lb

Codes

	AO	BO	NO	HO	PO
Slotted	42010012000	42020012000	42030012000	42040012000	42050012000
Fluted	42010012005	42020012005	42030012005	42040012005	42050012005
Helicoid	No Available	42020012050	42030012050	42040012050	42050012050