

PERFORACIÓN DIAMANTINA

DIMENSIONES, PESO & VOLÚMENES



PULGADAS	PULGADAS	MILÍMETROS
33/64	0.5156	13.097
17/32	0.5312	13.494
35/64	0.5469	13.891
9/16	0.5625	14.287
37/64	0.5781	14.684
19/32	0.5937	15.081
39/64	0.6094	15.478
5/8	0.6250	15.875
41/64	0.6406	16.272
21/32	0.6562	16.669
43/64	0.6719	17.066
11/16	0.6875	17.462
45/64	0.7031	17.859
23/32	0.7187	18.256
47/64	0.7344	18.653
3/4	0.7500	19.050
49/64	0.7656	19.447
25/32	0.7812	19.844
51/64	0.7969	20.241
13/16	0.8125	20.637
53/64	0.8281	21.034
27/32	0.8437	21.431
55/64	0.8594	21.828
7/8	0.8750	22.225
57/64	0.8906	22.622
29/32	0.9062	23.019
59/64	0.9219	23.416
15/16	0.9375	23.812
61/64	0.9531	24.209
31/32	0.9687	24.606
63/64	0.9844	25.003
1	1.0000	25.400

BROCA DIAMANTINA					ESCARIADOR	
TAMAÑO	DÍAMETRO					
	OD (Pulgadas)	ID (Pulgadas)	OD (Milímetros)	ID (Milímetros)	OD (Pulgadas)	OD (Milímetros)
A0	1.875	1.062	47.625	26.975	1.890	48.006
A0TK	1.875	1.201	47.625	30.505	1.890	48.006
B0	2.345	1.433	59.563	36.398	2.360	59.944
B03	2.345	1.320	59.563	33.528	2.360	59.944
B0 (oversize)	2.440	1.433	61.976	36.398	2.440	61.976
B0TK	2.345	1.601	59.563	40.665	2.360	59.944
BTW	2.345	1.654	59.563	42.012	2.360	59.944
N0	2.965	1.875	75.311	47.625	2.980	75.692
N02	2.965	1.995	75.311	50.673	2.980	75.692
N03	2.965	1.775	75.311	45.085	2.980	75.692
N0 (oversize)	3.032	1.875	77.013	47.625	3.032	77.013
NTW	2.965	2.209	75.311	56.109	2.980	75.692
H0	3.763	2.500	95.580	63.500	3.783	96.088
H02	3.763	2.653	95.580	67.386	3.783	96.088
H03	3.763	2.406	95.580	61.112	3.783	96.088
H0 (oversize)	3.830	2.500	97.282	63.500	3.850	97.790
HTW	3.763	2.791	95.580	70.891	3.783	96.088
P0	4.805	3.345	122.047	84.963	4.828	122.631
P03	4.805	3.270	122.047	83.058	4.828	122.631

PULGADAS	PULGADAS	MILÍMETROS
1/64	0.0156	0.397
1/32	0.0312	0.794
3/64	0.0469	1.191
1/16	0.0625	1.587
5/64	0.0781	1.984
3/32	0.0937	2.381
7/64	0.1094	2.778
1/8	0.1250	3.175
9/64	0.1406	3.572
5/32	0.1562	3.969
11/64	0.1719	4.366
3/16	0.1875	4.762
13/64	0.2031	5.159
7/32	0.2187	5.556
15/64	0.2344	5.953
1/4	0.2500	6.350
17/64	0.2656	6.747
9/32	0.2812	7.144
19/64	0.2969	7.541
5/16	0.3125	7.937
21/64	0.3281	8.334
11/32	0.3437	8.731
23/64	0.3594	9.128
3/8	0.3750	9.525
25/64	0.4906	9.922
13/32	0.4062	10.319
27/64	0.4219	10.716
7/16	0.4375	11.112
29/64	0.4531	11.509
15/32	0.4687	11.906
31/64	0.4844	12.303
1/2	0.5000	12.700

**BROCA DIAMANTINA
STANDARD**

BROCA DIAMANTINA					ESCARIADOR	
TAMAÑO	DÍAMETRO					
	OD (Pulgadas)	ID (Pulgadas)	OD (Milímetros)	ID (Milímetros)	OD (Pulgadas)	OD (Milímetros)
RWT (XRT)	1.175	0.735	29.845	18.669	1.175	29.845
XRPS	1.295	0.890	32.893	22.606	1.295	32.893
EWG, EWL, EWM	1.470	0.845	37.338	21.463	1.485	37.719
IEW	1.470	0.995	37.338	25.273	1.485	37.719
TT46, LTK46	1.811	1.389	45.999	35.281	1.832	46.533
AWG, AWL, AWM	1.875	1.185	47.625	30.099	1.890	48.006
JKT48, LTK48	1.875	1.389	47.625	35.281	1.890	48.006
56.5 mm	2.224	1.535	56.490	38.989	2.240	56.896
BWG, BWL, BWM	2.345	1.655	59.563	42.037	2.360	59.944
NWG, NWL, NWM	2.965	2.155	75.311	54.737	2.980	75.692

**BROCAS & ZAPATAS DE
REVESTIMIENTO**

TAMAÑO	BROCA & ZAPATA		BROCA		ZAPATA	
	OD (Pulgadas)	OD (Milímetros)	ID (Pulgadas)	ID (Milímetros)	ID (Pulgadas)	ID (Milímetros)
RW	1.470	37.338	1.000	25.400	1.186	30.124
EW	1.875	47.625	1.405	35.678	1.500	38.100
AW / AX4R	2.345	59.563	1.780	45.212	1.905	48.387
BW / N / NTW	2.965	75.311	2.215	56.261	2.375	60.325
NW / H / HX / HXB	3.615	91.821	2.840	72.136	3.000	76.200
HW / HWT (antiguo)	4.625	177.475	3.778	95.961	3.975	100.965
HW / HWT (standard)	4.625	177.475	3.778	95.961	3.925	99.695
HW / HWT (oversize)	4.875	123.825	3.778	95.961	3.900	99.060
PW	5.650	143.510	4.632	117.653	4.858	123.393
SW	6.790	172.466	5.632	143.053	5.941	150.901
UW	7.800	198.120	6.755	171.577	6.906	175.412
ZW	8.810	223.774	7.755	196.977	7.977	202.616

TUBERÍA DE REVESTIMIENTO

<i>Tamaño</i>	<i>OD (Pulg.)</i>	<i>ID (Pulg.)</i>	<i>OD (mm)</i>	<i>ID (mm)</i>	<i>Peso (kg/3m)</i>	<i>Peso (lb/10 pies)</i>	<i>Volumen (US Gal/100 pies)</i>
<i>EW</i>	<i>1.81</i>	<i>1.50</i>	<i>46.0</i>	<i>38.1</i>	<i>13</i>	<i>28</i>	<i>9.2</i>
<i>AW</i>	<i>2.25</i>	<i>1.91</i>	<i>57.2</i>	<i>48.4</i>	<i>17</i>	<i>38</i>	<i>14.8</i>
<i>BW</i>	<i>2.88</i>	<i>2.38</i>	<i>73.0</i>	<i>60.3</i>	<i>32</i>	<i>72</i>	<i>23.0</i>
<i>NW</i>	<i>3.50</i>	<i>3.00</i>	<i>88.9</i>	<i>76.2</i>	<i>38</i>	<i>86</i>	<i>36.7</i>
<i>HW</i>	<i>4.50</i>	<i>4.00</i>	<i>114.3</i>	<i>101.6</i>	<i>51</i>	<i>113</i>	<i>65.2</i>
<i>HWT</i>	<i>4.50</i>	<i>4.00</i>	<i>114.3</i>	<i>101.6</i>	<i>51</i>	<i>114</i>	<i>65.8</i>
<i>PW</i>	<i>5.50</i>	<i>5.00</i>	<i>139.7</i>	<i>127.0</i>	<i>64</i>	<i>143</i>	<i>102.0</i>
<i>SW</i>	<i>6.63</i>	<i>6.00</i>	<i>168.4</i>	<i>152.4</i>	<i>96</i>	<i>215</i>	<i>146.8</i>
<i>UW</i>	<i>7.63</i>	<i>7.00</i>	<i>193.8</i>	<i>177.8</i>	<i>131</i>	<i>293</i>	<i>199.8</i>

TABLA DE CONVERSIÓN		
<i>Pulgadas</i>	<i>x 25.400</i>	<i>= Milímetros</i>
<i>Pies</i>	<i>x 0.305</i>	<i>= Metros</i>
<i>Pulg. Cúbicas</i>	<i>x 16.387</i>	<i>= Centímetros Cúbicos</i>
<i>Pies Cúbicos</i>	<i>x 0.028</i>	<i>= Metros Cúbicos</i>
<i>Libras</i>	<i>x 0.454</i>	<i>= Kilogramos</i>
<i>Galones (U.S.)</i>	<i>x 0.833</i>	<i>= Galones (Imperial)</i>
<i>Galones (U.S.)</i>	<i>x 3.785</i>	<i>= Litros</i>
<i>PSI</i>	<i>x 0.070</i>	<i>= Kilogramos por cm2</i>
<i>GMP (U.S.)</i>	<i>x 3.785</i>	<i>= Litros por minuto</i>

TAMAÑO DE BROCA	FLUJO DE FLUIDO	PESO SOBRE LA BROCA	VELOCIDAD DE ROTACIÓN	RATIO DE PENETRACIÓN (pulg/min)	
	<i>Gal / Min</i>	<i>Lb</i>	<i>RPM</i>	<i>200 RPI</i>	<i>250 RPI</i>
<i>TT-46</i>	<i>2.5 - 3.5</i>	<i>1,000 - 3,000</i>	<i>2,300</i>	<i>11.5</i>	<i>9.2</i>
			<i>1,400</i>	<i>7</i>	<i>5.6</i>
			<i>1,000</i>	<i>5</i>	<i>4</i>
<i>A0</i>	<i>4 - 5</i>	<i>2,000 - 5,000</i>	<i>2,000</i>	<i>10</i>	<i>8</i>
			<i>1,200</i>	<i>6</i>	<i>4.8</i>
			<i>850</i>	<i>4.25</i>	<i>3.4</i>
<i>B0</i>	<i>6 - 8</i>	<i>2,000 - 5,000</i>	<i>1,700</i>	<i>8.5</i>	<i>6.8</i>
			<i>1,000</i>	<i>5</i>	<i>4</i>
			<i>700</i>	<i>3.5</i>	<i>2.8</i>
<i>N0</i>	<i>8 - 10</i>	<i>3,000 - 6,000</i>	<i>1,350</i>	<i>6.75</i>	<i>5.4</i>
			<i>800</i>	<i>4</i>	<i>3.2</i>
			<i>550</i>	<i>2.75</i>	<i>2.2</i>
<i>H0</i>	<i>10 - 12</i>	<i>4,000 - 8,000</i>	<i>1,000</i>	<i>5</i>	<i>4</i>
			<i>600</i>	<i>3</i>	<i>2.4</i>
			<i>400</i>	<i>2</i>	<i>1.6</i>
<i>P0</i>	<i>18 - 23</i>	<i>5,000 - 10,000</i>	<i>800</i>	<i>4</i>	<i>3.2</i>
			<i>500</i>	<i>2.5</i>	<i>2</i>
			<i>350</i>	<i>1.75</i>	<i>1.4</i>

WIRELINE							
<i>Tamaño</i>	<i>OD (Pulgadas)</i>	<i>ID (Pulgadas)</i>	<i>OD (Milímetros)</i>	<i>ID (Milímetros)</i>	<i>Peso (kg/3m)</i>	<i>Peso (lb/10pies)</i>	<i>Volumen (Us Gal/100pies)</i>
<i>AO W/L</i>	<i>1.75</i>	<i>1.38</i>	<i>44.5</i>	<i>34.9</i>	<i>14</i>	<i>31</i>	<i>7.7</i>
<i>BO W/L</i>	<i>2.19</i>	<i>1.81</i>	<i>55.6</i>	<i>46.0</i>	<i>18</i>	<i>40</i>	<i>13.0</i>
<i>NO W/L</i>	<i>2.75</i>	<i>2.38</i>	<i>69.9</i>	<i>60.3</i>	<i>23</i>	<i>52</i>	<i>23.0</i>
<i>HO W/L</i>	<i>3.50</i>	<i>3.06</i>	<i>88.9</i>	<i>77.8</i>	<i>34</i>	<i>77</i>	<i>38.0</i>
<i>HWT DRILL ROD</i>	<i>4.50</i>	<i>4.00</i>	<i>114.3</i>	<i>101.6</i>	<i>51</i>	<i>114</i>	<i>65.8</i>
WIRELINE (Pared Delgada)							
<i>BTW</i>	<i>2.225</i>	<i>1.909</i>	<i>56.5</i>	<i>48.5</i>	<i>15.8</i>	<i>34.5</i>	<i>14.8</i>
<i>NTW</i>	<i>2.875</i>	<i>2.525</i>	<i>73.3</i>	<i>64.2</i>	<i>22.7</i>	<i>50.0</i>	<i>26.0</i>
<i>HTW</i>	<i>3.582</i>	<i>3.208</i>	<i>90.9</i>	<i>81.5</i>	<i>30.2</i>	<i>67.8</i>	<i>41.9</i>
STANDARD							
<i>EW</i>	<i>1.38</i>	<i>0.88</i>	<i>34.9</i>	<i>22.2</i>	<i>14</i>	<i>31</i>	<i>3.1</i>
<i>AW</i>	<i>1.75</i>	<i>1.25</i>	<i>44.5</i>	<i>31.8</i>	<i>19</i>	<i>42</i>	<i>6.3</i>
<i>BW</i>	<i>2.13</i>	<i>1.50</i>	<i>54.0</i>	<i>38.1</i>	<i>28</i>	<i>63</i>	<i>9.1</i>
<i>NW</i>	<i>2.63</i>	<i>2.00</i>	<i>66.7</i>	<i>50.8</i>	<i>36</i>	<i>80</i>	<i>16.1</i>
<i>HW</i>	<i>3.50</i>	<i>3.06</i>	<i>88.9</i>	<i>77.8</i>	<i>37</i>	<i>83</i>	<i>38.0</i>
<i>AWJ</i>	<i>1.75</i>	<i>1.38</i>	<i>44.5</i>	<i>35.1</i>	<i>15</i>	<i>34</i>	<i>7.7</i>
<i>BWJ</i>	<i>2.19</i>	<i>1.81</i>	<i>55.6</i>	<i>46.0</i>	<i>20</i>	<i>45</i>	<i>13.0</i>
<i>NWJ</i>	<i>2.75</i>	<i>2.38</i>	<i>69.9</i>	<i>60.5</i>	<i>26</i>	<i>58</i>	<i>23.0</i>

CUADRO DE SELECCIÓN DE BROCAS

CARACTERÍSTICAS DE FORMACIÓN		TIPO DE ROCA	SERIES UP	SERIE NG	
ABRASIVIDAD	FRACTURAMIENTO	MH			
		< 3	Caliza, Roca sedimentaria, Hálito, Brecha, Conglomerado	UP 2-4	
			Arenisca, Esquisto, Serpentina, Arcilla		
		3 - 4.5	Pizarra, Mármol, Esquisto, Dolomita	UP 4-7	
			Basalto, Gabro, Hematita, Magnetita, Obsidiana, Peridotita		
		4.5 - 6	Gabro, Gneis, Granito, Diorita	UP 7-10	NG 7
			Diorita, Andesita, Riolita, Ígnea, Pegmatita, Esquisto		UP 9+
		6 - 7	Pegmatita, Taconita, Cuarzita, Calcedonia, Esquisto, Formación en bandas de hierro: Itabirita, Jaspilita	UP 10-13	NG 9
					NG 11
		> 7			NG 11 ABRASIVA
COMPACTO					

