



**Date:** 2026-04-22

class: [16830] Sprache und Technologie - Language and Technology:: tutor: frankowsky :: term: SS26

snc: 16175.1

snc: 16132. ɪ ʃ ɔ : ɐ wer es [pɛlɛχɪl] ausspricht, und nicht [pɛrɛχɪl]

### TO GIT COMMIT

[and wwell if youre desperate about not working links in the downloaded pdf please consider as intended to switch to the online version of this document witch you will find linked near header sorry your inconvenience is my convenience...]

[1] "engine on..."

#### snc

- button.123456789
- chunk out

#### index

1. samling: margin notes general > [open](#)
2. LLM and LX theories, play claude
3. claude writes english story based on french grammar > [open](#), original: [claude](#)
4. play along model training on corpus: having Claude devise grammar from synthetic text > [link](#)

#### samling

- Frankowsky (2022)
  - how were dates attested technically?
  - what about the decow16 corpus?
    - \* possible to put that online (term paper) or is it? (Schäfer (2025))
    - \* corpus formats?

**zinsmeister**

**play**

## 1. skew divergence

```
# computing skew divergence score for noun-noun compound vectors
# Q: zinsmeister(2013)

#  $D(p||q) = \sum_i p_i \times \log(p_i/q_i)$ 
l1<-c(0.6,0.4,0) # milchzahn
l2<-c(0.25,0.5,0.25) # zahn
l3<-c(0,0,1) # löwenzahn
### test: löwenzahn::ziehen=1 occurrence instead 0
l4<-c(0,1,2)
l5<-unlist(lapply(l4,function(x){
  x/sum(l4)
})))
#####
# l2 is the reference p
# l1,l3 are the target q probabilities which are projected on /smoothed by reference p
#####
lx<-list(list(l2,l1),list(l2,l3),list(l2,l5))
#f<-sum(pi*(log(pi/qi)))
# latex entropy:  $H(X) := -\sum_{x \in \mathcal{X}} p(x) \log_2 p(x)$ 
#  $\sum\{p(i)(\log(p(i)/q(i)))\}$ 
w<-0.9
s1<-lapply(lx,function(l){
  print(l)
  # lapply(l,function(p){
  #   cat("p:",p,"\n")
  #   s<-array()
  #   for(i in 1:length(l[[1]])){
  #     p1<-l[[1]][i]
  #     q1<-l[[2]][i]
  #     qi<-(w*q1)+((1-w)*p1) # qi smoothed
  #     cat("qi:",qi,"\n")
  #     s[i]<-sum(pi*log((pi/qi)))
  #     s[i]<-p1*log(p1/qi)
  #     cat("s:",s[i],"\n")
  #   }
  # }
```

```

    spq<-sum(s)
    cat("skew div:",spq,"\n")
    return(s)
})

```

```

[[1]]
[1] 0.25 0.50 0.25

```

```

[[2]]
[1] 0.6 0.4 0.0

```

```

qi: 0.565
s: -0.2038412
qi: 0.41
s: 0.09922547
qi: 0.025
s: 0.5756463
skew div: 0.4710305
[[1]]
[1] 0.25 0.50 0.25

```

```

[[2]]
[1] 0 0 1

```

```

qi: 0.025
s: 0.5756463
qi: 0.05
s: 1.151293
qi: 0.925
s: -0.3270832
skew div: 1.399856
[[1]]
[1] 0.25 0.50 0.25

```

```

[[2]]
[1] 0.0000000 0.3333333 0.6666667

```

```

qi: 0.025
s: 0.5756463
qi: 0.35
s: 0.1783375
qi: 0.625

```

```
s: -0.2290727
skew div: 0.5249111
```


```
names(s1)<-c("milchzahn","löwenzahnA","löwenzahnB")
lapply(s1,sum) #chk.
```

```
$milchzahn
[1] 0.4710305
```

```
$löwenzahnA
[1] 1.399856
```

```
$löwenzahnB
[1] 0.5249111
```

```
par(las=2)
boxplot(s1,main="skew divergence scores, reference: zahn")
```



## 2. cosine similarity of vectors

```

# X = numeric matrix of token embeddings (rows = tokens, cols = features)
# Example:
# X <- as.matrix(df[, -1])
# rownames(X) <- df$t
# l1<-c(0.6,0.4,0) # milchzahn
# l2<-c(0.25,0.5,0.25) # zahn
# l3<-c(0,0,1) # löwenzahn
# ### test: löwenzahn::ziehen=1 occurrence instead 0
# l4<-c(0,1,2)
df<-data.frame(token=c("milchzahn","zahn","loewenzahnA","loewenzahnB"),NA,NA,NA)
df[1,2:4]<-l1
df[2,2:4]<-l2
df[3,2:4]<-l3
df[4,2:4]<-l4
#df
X<-as.matrix(df[, -1])
# 1. Row norms (Euclidean length of each token vector)
row_norms <- sqrt(rowSums(X^2))

# 2. Dot-product matrix
#   tcrossprod(X) == X %*% t(X)
dot_products <- tcrossprod(X)

# 3. Outer product of norms
#   Gives all pairwise ||x_i|| * ||x_j||
norm_matrix <- outer(row_norms, row_norms)

# 4. Cosine similarity matrix
cosine_sim <- dot_products / norm_matrix

# 5. Handle rows with zero norm (if any)
cosine_sim[!is.finite(cosine_sim)] <- 0

# 6. Add row/column names
rownames(cosine_sim) <- df$token
colnames(cosine_sim) <- df$token

# Example: similarity between "striker" and "goal"
print(cosine_sim)

```

|           | milchzahn | zahn      | loewenzahnA | loewenzahnB |
|-----------|-----------|-----------|-------------|-------------|
| milchzahn | 1.0000000 | 0.7925939 | 0.0000000   | 0.2480695   |

|             |           |           |           |           |
|-------------|-----------|-----------|-----------|-----------|
| zahn        | 0.7925939 | 1.0000000 | 0.4082483 | 0.7302967 |
| loewenzahnA | 0.0000000 | 0.4082483 | 1.0000000 | 0.8944272 |
| loewenzahnB | 0.2480695 | 0.7302967 | 0.8944272 | 1.0000000 |

```
cosine_sim["milchzahn", "zahn"]
```

```
[1] 0.7925939
```

```
# Example: top 5 nearest neighbors for "striker"
nearest_neighbors <- function(token, sim, k = 5) {
  s <- sim[token, ]
  s <- s[names(s) != token]      # remove self-similarity
  s <- sort(s, decreasing = TRUE)
  head(s, k)
}

nearest_neighbors("zahn", cosine_sim)
```

|           |             |             |
|-----------|-------------|-------------|
| milchzahn | loewenzahnB | loewenzahnA |
| 0.7925939 | 0.7302967   | 0.4082483   |


### 3. clustering embeddings

```
# Normalize counts to probabilities
# P <- counts / rowSums(counts)

# # Cosine similarity
# norms <- sqrt(rowSums(P^2))
# sim <- tcrossprod(P) / outer(norms, norms)
# sim[!is.finite(sim)] <- 0

# Cluster
hc2 <- hclust(as.dist(1 - cosine_sim), method = "average")

# Plot
plot(hc2)
```



#### notes

the tokens vector sujet gets interesting if following [this](#) theories (LFG: lexical functional grammar) where we may describe token categories in a vector space as well, undisputed of distribution. so if Zinsmeister (2013) investigate on similarity based on distribution of lexical items in a context window (cooccurrences) we may also (like in LLM embeddings) make statements about token relatedness based on the vector cosine similarity of tokens semantic / syntactic categories.

the skew divergence approach to measure similarities of their noun-noun compounds (which nevertheless can be applied to any type of comparison between two probability vectors = embeddings, Equation 1) applied by zinsmeister is fairly easy to implement in studies since it doesn't afford much manual annotation besides (in their study) to define the contextual words for which a cooccurrence is evaluated. playing with the width of a context window, the corpus base or other parameters that constrain cooccurrence can yield interesting results in semantic distance of items.

$$D(p||q) := \sum p(i)(\log(p(i)/q(i))) \quad (1)$$

besides, one could also include other parameters next to distributional, including syntactical information, to enlarge the dimension of the vector space and overall resolution of comparison.

## LLMs

i did think about consequences of future LLMs training data will most likely include

1. recent AI discourse subjects (papers on, discussions, public discourse)
2. recent generated content itself

so i asked gpt about Q2. [her answer](#).

**small model training G1 synthetic output**

[open](#)

## references

- Alemohammad, Sina, Josue Casco-Rodriguez, Lorenzo Luzi, Ahmed Imtiaz Humayun, Hossein Babaei, Daniel LeJeune, Ali Siahkoohi, and Richard Baraniuk. 2023a. “Self-Consuming Generative Models Go MAD.” October 2023. <https://openreview.net/forum?id=ShjMHfmPso>.
- . 2023b. “Self-Consuming Generative Models Go MAD.” October 2023. <https://openreview.net/forum?id=ShjMHfmPso>.
- chatGPT, and St. Schwarz. 2026. “How Recent Chats and Discourse Model Future LLM Output.” In *Cite Yourself Dummy. A Transformer Conversation.*, 1–16214. Berlin. <https://stschwarz.userpage.fu-berlin.de/links?title=gpt-con&ref=cite>.
- Claude, St. Schwarz, and chatGPT. 2026. “Strange Story. LLMs and Linguistic Theories.” In *Cite Yourself Dummy. A Transformer Conversation.*, 1–16225. Berlin. <https://stschwarz.userpage.fu-berlin.de/links?title=gpt-con-16225&ref=cite>.
- Falbel, Daniel, and Javier Luraschi. 2026. *Torch: Tensors and Neural Networks with 'GPU' Acceleration*. <https://doi.org/10.32614/CRAN.package.torch>.
- Frankowsky, Maximilian. 2022. *Extravagant Expressions Denoting Quite Normal Entities: Identical Constituent Compounds in German*. John Benjamins Publishing Company. <https://www.degruyterbrill.com/document/doi/10.1075/slcs.223.07fra/html>.
- Glaser, Guhl. 2024. *Benjaminfeldkraft. A German Language Literary Corpus for Exploring and Analysing Essays*. Postagged vertical graph. Edition rotfadenbuecher. <https://github.com/estescharz/benjaminfeldkraft/releases/tag/origin>.



- Gu, Yi, Lingyou Pang, Xiangkun Ye, Tianyu Wang, Jianyu Lin, Carey E. Priebe, and Alexander Aue. 2026. *SIGMA: Scalable Spectral Insights for LLM Model Collapse*. 2026. <https://doi.org/10.48550/arxiv.2601.03385>.
- Leipzig Corpora Collection. 2024. “Korpus: Deu\_news\_2024\_10K, 3.10.5 Entropy.” In *German Newspaper Dictionary Based on Material Crawled in 2024*. [https://cls.wortschatz-leipzig.de/de/deu\\_news\\_2024\\_10K/3.10.5\\_Entropy.html](https://cls.wortschatz-leipzig.de/de/deu_news_2024_10K/3.10.5_Entropy.html).
- Piantadosi, Steven T., Stefan Müller, Moshe Poliak, Geoffrey K. Pullum, Robert D. Van Valin Jr, Dafydd Gibbon, Iris Berent, et al. 2024. “Modern Language Models Refute Chomsky’s Approach to Language.” In *From Fieldwork to Linguistic Theory*, 353–415. Language Science Press. <https://langsci-press.org/catalog/book/434>.
- Schäfer, Roland. 2025. *What Happened to Webcorpora.org? | Roland Schäfer*. <https://rolandschaefer.net/archives/3663>.
- Schmid, Helmut, Arne Fitschen, and Ulrich Heid. 2004. “SMOR: A German Computational Morphology Covering Derivation, Composition and Inflection.” *Proceedings of the Language Resources and Evaluation Conference*, 2004. <https://api.semanticscholar.org/CorpusID:1146460>.
- Schwarz, St. 2026. *Model Collapse Essai*. <https://github.com/esteeschwarz/SPUND-LX/tree/main/play/quarto/test/modeling>.
- SFST | Institut Für Maschinelle Sprachverarbeitung | Universität Stuttgart. n.d. Accessed May 13, 2026. <https://www.ims.uni-stuttgart.de/forschung/ressourcen/werkzeuge/sfst/>.
- Sfst: Stuttgart Finite State Transducer System. n.d. Accessed May 13, 2026. <https://github.com/santhoshtr/sfst>.
- Shumailov, Ilia, Zakhar Shumaylov, Yiren Zhao, Nicolas Papernot, Ross Anderson, and Yarin Gal. 2024. “AI Models Collapse When Trained on Recursively Generated Data.” *Nature (London)* 631 (8022): 755–59. <https://doi.org/10.1038/s41586-024-07566-y>.
- TEI Initiative. 2006. *TEI: Feature Structures*. <https://tei-c.org/Vault/Workgroups/FS/>.
- Zinsmeister, Heike. 2013. “Corpus–Based Modeling of the Semantic Transparency of Noun–Noun Compounds.” In *A Festschrift for Susan Olsen*, edited by Holden Härtl, 303–21. Berlin: Akademie Verlag. <https://doi.org/doi:10.1524/9783050063799.303>.