

PSY9511: Seminar 4

Model selection, validation and testing

Esten H. Leonardsen

23.09.24




**UNIVERSITETET
I OSLO**

Model evaluation: Leave-one-out cross-validation


Dataset




Model evaluation: Leave-one-out cross-validation




Model evaluation: Leave-one-out cross-validation




Model evaluation: Leave-one-out cross-validation




Model evaluation: Leave-one-out cross-validation




Model evaluation: Leave-one-out cross-validation



Model evaluation: Leave-one-out cross-validation



Model evaluation: Leave-one-out cross-validation



Model evaluation: Leave-one-out cross-validation

Fits n models for n datapoints, each time leaving a single datapoint out for testing.

- + Uses all data to train models
- + Not dependent on arbitrary data splits
- + Unbiased (with regards to the full dataset)
- Computationally expensive
- Effectively gives a point estimate of the error
- All models are going to be trained on $> 99\%$ overlapping data
→ highly correlated




Model evaluation: Cross-validation


Dataset




Model evaluation: Cross-validation




Model evaluation: Cross-validation




Model evaluation: Cross-validation




Model evaluation: Cross-validation




Model evaluation: Cross-validation




Model evaluation: Cross-validation



Model evaluation: Cross-validation



Model evaluation: Cross-validation



Model evaluation: Cross-validation

Fits k (usually $k \in \{5, 10\}$) models for $n > k$ datapoints, each leaving n/k datapoints for out-of-sample testing.

- + Uses all data to train models
- + Yields multiple estimates of out-of-sample error
- Different choices of k (and exact splits) yields different results
- **No longer a single model from which information (e.g. parameter estimates and p-values) can be derived**




Model evaluation: Bootstrapping


Dataset




Model evaluation: Bootstrapping



Model evaluation: Bootstrapping




Model evaluation: Bootstrapping




Model evaluation: Bootstrapping


Dataset




Model evaluation: Bootstrapping




Model evaluation: Bootstrapping




Model evaluation: Bootstrapping




Model evaluation: Bootstrapping




Model evaluation: Bootstrapping



Model evaluation: Bootstrapping



Model evaluation: Bootstrapping



Model evaluation: Bootstrapping

Fits b models with m datapoints (typically $m < n$), sampled from the original dataset **with replacement**.

- + Uses all data to train models
- + Provides a dense distribution of model performances
- + **Versatile: Can be used for other things, e.g. getting a confidence interval for model parameters**
- Different choices of b (and exact splits) yields different results



Model evaluation: Bootstrapping

