scholia

Structured Visual Components for LaTeX Documents

Esther Poniatowski
esther.poniatowski@ens.psl.eu

Version 0.2.0
March 2026

Abstract

SCHOLIA is a LaTeX package for documents requiring consistent visual structure. It provides callouts, cards, semantic labels, numbering systems, typed pages, exercise environments, grading tools, shared icon handling, and Beamer-specific presentation helpers. Optional interactive hide/reveal commands support progressive disclosure in PDF workflows. The package supports article and Beamer modes with French/English localization.

Contents

I Overview **4**
1 Key Features . . . 4
2 Document Modes . . . 4
3 Pre-Defined Styles and Customization . . . 5

II Installation **5**
1 CTAN Installation . . . 5
2 Manual Installation . . . 5

III Loading the Package **5**
1 Basic Usage . . . 5
2 Package Options . . . 6
3 Localization . . . 6
4 Icons . . . 7

IV Quick Start **7**

V Features **8**

1 Callouts . . . 8
a Available Types . . . 8
b Usage Examples . . . 8
c Customization . . . 9
2 Cards . . . 9
a Generic Card Environment . . . 9
b Built-In Preset . . . 10
c Defining New Card Types . . . 10
3 Semantic Labels . . . 10
a Generic Frame . . . 10
b Semantic Inline Labels . . . 11
4 Numbering Systems . . . 11
a Squared Items (Steps) . . . 11
b Circled Items (Questions) . . . 12
c Counter Reset . . . 13
5 Typed Pages . . . 13
a Page Types . . . 13
b Creating a Typed Page . . . 13
c Full-Page Environments . . . 14
d Document Metadata . . . 14
e Cross-Referencing . . . 15
6 Exercises . . . 15
a Exercise Types . . . 15
b Exercise Environments . . . 15
c Two-Column Layout . . . 16
d Blanks and Hidden Solutions . . . 16
e Exercise Commands . . . 17
f Counter Management . . . 17
7 Grading . . . 17
a Grading Box . . . 17
b Grading Table . . . 18
c Inline Point Indicators . . . 18
d Summary and Rubric Environments . . . 18
e Automatic Point Tracking . . . 18
8 Beamer Tools . . . 19
a Headline Modes . . . 19

b Slide-Composition Helpers 19
c Minimalist Compatibility 19
9 Interactive PDF Toggles 20
10 Math Helpers 20

VI License **20**

VII Acknowledgments **21**

I. Overview

SCHOLIA provides environments and commands for documents requiring structured visual components. Typical applications include educational materials, technical tutorials, reports, and academic projects.

1. Key Features

The package offers nine user-facing feature categories:

Feature	Description
Callouts	13 styled box types (definitions, theorems, warnings, tips, etc.)
Cards	Floating-label callouts with icon badges and reusable presets
Semantic labels	Inline styled boxes for content categorization
Numbering	Steps/substeps and questions/subquestions with hanging indentation
Typed Pages	Standalone page layouts with banners and relative pagination
Exercises	5 environment types with difficulty indicators and solution control
Grading	Rubric tables and point allocation for assessments
Beamer tools	Headline modes, title-slide helpers, and minimalist compatibility
Interactive PDF toggles	Click-to-reveal content using Optional Content Groups

2. Document Modes

The package is designed to maintain consistent styling across multiple formats. This allows presenting the same content in both printed documents and slide presentations.

Two modes are supported:

Mode	Purpose	Features
Article (default)	Printed materials, handouts, worksheets	Callouts, cards, labels, numbering, typed pages, exercises, grading, and optional interactive toggles.
Beamer	Presentations, oral sessions	Typed-page layouts disabled. Callouts, cards, labels, numbering, exercises, grading, headline modes, progression helpers, and optional interactive toggles remain available.

3. Pre-Defined Styles and Customization

SCHOLIA offers two levels of usage:

- **Ready-to-use environments** — Variants in each feature, with pre-defined colors, icons, and styling. No configuration required. (13 callout types, 10 semantic labels, 5 exercise categories, 11 typed page registrations, 1 built-in card preset)
- **Customization framework** — Generic commands allow creating new variants in each feature. All visual elements can be redefined (colors, icons, spacing, borders) using the same underlying infrastructure.

II. Installation

1. CTAN Installation

Once available on CTAN, install via the standard TeX distribution tools:

```
# TeX Live
tlmgr install scholia

# MiKTeX
miktex-console --install=scholia
```

2. Manual Installation

Place the `scholia/` directory in a local texmf tree:

```
~/texmf/tex/latex/scholia/
```

Then refresh the filename database:

```
texhash ~/texmf
```

III. Loading the Package

1. Basic Usage

SCHOLIA is loaded in the preamble with `\usepackage`. The package detects the document class automatically: with `article`, `report`, or `book`, it operates in article mode; with `beamer`, it switches to presentation mode.

Load the top-level package `scholia`. The internal module files under `base/`, `beamer/`, `cards/`, `typedpages/`, and related directories are implementation details, not stable public entry points.

Standard article with English strings (default):

```latex
\documentclass{article}
\usepackage{scholia}
```

Article with French strings:

```latex
\documentclass{article}
\usepackage[french]{scholia}
```

Beamer presentation:

The `beamer` option can be specified explicitly, though it is auto-detected when using the `beamer` document class.

```latex
\documentclass{beamer}
\usepackage[beamer]{scholia}
```

2. Package Options

Option	Description
`english`	Use English strings (default)
`french`	Use French strings
`beamer`	Enable Beamer mode (auto-detected for `beamer` class)
`solutions`	Show solution text in exercise blanks and correction helpers
`interactive`	Enable OCG-based hide/reveal commands
`noicons`	Disable icon loading for text-only output
`minimal`	Minimal dependencies; implies `noicons`
`minimalistcompat`	Enable compatibility aliases for decks migrated from the minimalist theme
`draft`	Draft mode (reserved for future use)

3. Localization

All user-facing strings (labels, titles, prompts) are defined in localization files. The `french` and `english` options select the appropriate string set.

Element	French	English
Exercise label	Exercice	Exercise
Definition	Définition	Definition
Step	Étape	Step
Total	Total	Total

To override specific strings, redefine the internal macros after loading SCHOLIA:

```latex
\usepackage{scholia}
\def\scholia@str@exo@label{Problem}
```

4. Icons

Runtime icons are loaded from PDF files in `icons/pdf/`. The public icon command is `\scholiaicon`; frameworks such as callouts, cards, exercises, typed pages, summaries, and Beamer banners reuse the same rendering path.

```
\scholiaicon[height=1.2em, fallback={[idea]}]{lightbulb.pdf}
```

The `noicons` option disables icon loading package-wide and uses text-only fallbacks where available. This is useful for:

- Faster compilation during drafting
- Reduced output file size
- Plain-text fallback scenarios

The `minimal` option implies `noicons` and also skips table-related dependencies that are not needed in reduced builds.

IV. Quick Start

The following example demonstrates SCHOLIA in an article document with a definition callout and a guided exercise. The exercise uses numbered steps and a conditional answer blank.

```
\documentclass{article}
\usepackage[english]{scholia}

\begin{document}

\begin{definitionbox}[Derivative]
The derivative of $f$ at $x$ is the limit
$f'(x) = \lim_{h \to 0} \frac{f(x+h) - f(x)}{h}$
when this limit exists.
\end{definitionbox}

\begin{exguided}[Computing Derivatives]
\exstep{Find $f'(x)$ for $f(x) = x^2$.}

Apply the definition: $\lim_{h \to 0} \frac{(x+h)^2 - x^2}{h}$.

The answer is \solutionBlank{2cm}{$2x$}.
\end{exguided}

\end{document}
```

V. Features

This section documents each feature category in detail.

1. Callouts

Callouts are styled boxes for highlighting specific content types. Each callout type provides two environment variants:

- `<type>box` — Full box with optional title and body content
- `<type>mark` — Title-only bar (no body area)

a. Available Types

Environment	Color	Typical Use
`definitionbox`	Cyan	Mathematical definitions
`theorembox`	Red	Theorems and propositions
`proofbox`	Gray	Mathematical proofs
`warningbox`	Orange	Warnings, common mistakes
`errorbox`	Dark red	What NOT to do
`tipbox`	Yellow	Tips and strategies
`methodbox`	Blue	Step-by-step methods
`notationbox`	Brown-gray	Notation conventions
`objectivebox`	Green	Learning objectives
`summarybox`	Light gray	Summaries and recaps
`remarkbox`	Purple	Observations
`questionbox`	Blue	Questions for reflection
`instructionbox`	Gray	Instructions and directives

b. Usage Examples

Box with Title

```
\begin{definitionbox}[Some title]
Some content here.
\end{definitionbox}
```

Some title

Some content here.

Box without Title

```
\begin{tipbox}
Some content here.
```

```
\end{tipbox}
```

Some content here.

Title-Only Variant

The `*mark` variants are commands (not environments) for title-only banners:

```
\theoremmark{Some text}
```

Some text

The title-only variant accepts an optional first argument for tcolorbox options:

```
\theoremmark[centered]{Centered text}
```

c. Customization

Each callout type is defined by a color. To create a new callout type:

1. Define a color with `\definecolor`
2. Create the environment using `callout layout` (for boxes) or `callout titleonly` (for title-only variants)

```
\definecolor{callout-custom}{RGB}{100,150,200}
\newtcolorbox{custombox}[1][]{%
  callout layout=callout-custom,
  title={#1},
}
```

The styles are based on tcolorbox; any tcolorbox option can be added to further customize spacing, borders, or backgrounds.

2. Cards

Cards are an alternative callout family with a floating title label and a circular icon badge. They are useful for highlighting insights, design notes, or visual breaks that should differ from the standard callout title-bar layout.

a. Generic Card Environment

```
\begin{cardbox}[title={Key insight}, icon={lightbulb.pdf}, color=blue]
Card body content.
\end{cardbox}
```

The optional argument accepts keys from the `/scholia/card` family.

Key	Purpose
`title`	Floating label text
`icon`	Badge icon filename
`color`	Base semantic color for border and fills
`fill tint`, `border tint`, `badge tint`	Tint strengths for the three visual layers
`label fill`, `label border tint`	Floating-label styling
`badge size`, `badge xshift`, `label xshift`	Badge and label placement
`top padding`, `icon height`	Layout sizing
`box options`	Raw tcolorbox options forwarded to the box

b. Built-In Preset

SCHOLIA currently ships one built-in preset:

```
\begin{ideacard}[title={Key insight}]
Important observation.
\end{ideacard}
```

c. Defining New Card Types

Custom presets are registered with `\NewScholiaCardType`:

```
\NewScholiaCardType{research}{color=scholia-research, icon=telescope.pdf}
```

This defines a corresponding `researchcard` environment.

3. Semantic Labels

Semantic labels are inline styled boxes for categorizing and marking content. They provide visual consistency when referring to concepts, methods, or other resources. They are available in both article and Beamer documents.

a. Generic Frame

The `\inlineframebox` command creates a colored inline box:

```
See the \inlineframebox[cyan]{theory section} for details.
```

With navigation arrow (starred variant):

```
Continue to \inlineframebox[green]*{exercise}.
```

b. Semantic Inline Labels

Pre-defined commands for content categorization:

Command	Color/Purpose
`\notionlabel{text}`	Cyan (theory, definitions)
`\exerciselabel{text}`	Orange (practice activities)
`\solutionlabel{text}`	Green (answers, corrections)
`\methodlabel{text}`	Blue (methods, procedures)
`\assessmentlabel{text}`	Red (formal evaluations)
`\researchlabel{text}`	Reddish-orange (exploration)
`\autochecklabel{text}`	Purple (self-evaluation)
`\keypointlabel{text}`	Gold (key highlights)
`\summarylabel{text}`	Gray-brown (overviews)
`\diagnosticlabel{text}`	Steel blue (student records, diagnostics)

All labels accept a starred variant for the navigation arrow:

```
Refer to the \notionlabel*{definition of continuity}.
```

4. Numbering Systems

SCHOLIA provides two numbering systems for structured content, distinguished by their visual marker style. Each system offers both environment and inline command variants.

a. Squared Items (Steps)

Visual style: `[1]`, `[2]`, `[3]`... with lettered sub-items `(a)`, `(b)`, `(c)`...

The generic environments are `squareditem` and `squaredsubitem`. Semantic aliases `step` and `substep` are provided for procedural content. The subitem counter resets automatically when a new item begins.

Environment Syntax

```
\begin{step}[Preparation]
Gather all necessary materials.
\begin{substep}
Check equipment.
\end{substep}
\begin{substep}
Prepare workspace.
\end{substep}
\end{step}
```

1 **Preparation**

Gather all necessary materials. (a) Check equipment.

(b) Prepare workspace.

Inline Syntax For compact documents, use \squaremark and \squaresubmark (or aliases \s and \subs):

```
\s Gather materials.
\subs Check equipment.
\subs Prepare workspace.
```

b. Circled Items (Questions)

Visual style: ①, ②, ③... with circled sub-items ⓐ, ⓑ, ⓒ...

The generic environments are circleditem and circledsubitem. Semantic aliases question and subquestion are provided for assessment content. The subitem counter resets automatically when a new item begins.

Environment Syntax

```
\begin{question}
Solve $x^2 - 4 = 0$.
\begin{subquestion}
Factor the left side.
\end{subquestion}
\begin{subquestion}
Find all solutions.
\end{subquestion}
\end{question}
```

① Solve $x^2 - 4 = 0$. ⓐ Factor the left side.

ⓑ Find all solutions.

Inline Syntax For compact lists, use \circmark and \circsubmark (or aliases \q and \subq):

```
\q What is the capital of France?
\subq Name two rivers.
\subq Name the largest city.
```

Both syntaxes share the same counters and produce identical visual output.

c. Counter Reset

Counter	Reset Behavior
`scholia@squarednum`	Manual reset only
`scholia@squaredsubnum`	Resets when `scholia@squarednum` increments
`scholia@circlednum`	Resets when entering an exercise environment
`scholia@circledsubnum`	Resets when `scholia@circlednum` increments

5. Typed Pages

Typed pages are standalone page layouts with styled banners and relative page numbering. They are available only in article mode (disabled in Beamer).

a. Page Types

Type Key	Color	Purpose
`notion`	Cyan	Concepts and theory
`exercise`	Orange	Exercise sheets
`solution`	Green	Solutions
`autocheck`	Purple	Self-assessment
`method`	Blue	Methods and procedures
`assessment`	Red	Formal assessments
`summary`	Gray-brown	Chapter summaries
`keypoint`	Gold	Key points to memorize
`research`	Reddish-orange	Research activities
`presentation`	Slate blue	Presentation-oriented typed pages and summary aliases
`diagnostic`	Steel blue	Diagnostics and student-record material

b. Creating a Typed Page

The `\newTypedPage` command initializes a new typed page:

```
\newTypedPage{3e-func-N1}{notion}{Functions}{Images and Antecedents}
```

Arguments:

1. Reference identifier (for cross-referencing)
2. Type key (from table above)
3. Chapter title (displayed in gray)
4. Specific topic (displayed in bold)

This creates a banner with the appropriate icon, color, and titles, and sets up relative page numbering within the typed page section.

c. Full-Page Environments

For special emphasis, full-page framed environments wrap content in a distinctive border that spans the entire page. These are breakable across multiple pages.

Generic Full-Page Environment The `typedpagefull` environment is the generic mechanism for creating full-page framed content with any page type:

```
\begin{typedpagefull}{ref}{type}{Chapter}{Title}
Content here...
\end{typedpagefull}
```

An optional first argument controls styling:

```
\begin{typedpagefull}[norules]{ref}{keypoint}{Chapter}{Title}
Content with header/footer rules suppressed...
\end{typedpagefull}
```

Option	Effect
`norules`	Suppress header/footer separator lines (content preserved)

Convenience Wrappers Pre-defined environments wrap `typedpagefull` for common use cases:

Environment	Type	Options
`summarypage`	`summary`	(default styling)
`keypointpage`	`keypoint`	`norules`

Example usage:

```
\begin{summarypage}{ref}{Chapter}{Title}
Summary content here...
\end{summarypage}

\begin{keypointpage}{ref}{Chapter}{Title}
Key points here (no header/footer rules)...
\end{keypointpage}
```

Arguments: reference identifier, chapter title, specific topic.

d. Document Metadata

Typed pages display author and year information in the footer. Define these in the preamble:

```
\renewcommand{\Author}{Author Name}
```

```
\renewcommand{\Year}{2025--2026}
```

e. Cross-Referencing

Reference typed pages using the automatically created labels:

```
See \typedPageRef{3e-func-N1} for the definition.
```

6. Exercises

SCHOLIA provides five exercise environment types. These types are *visual categories* that indicate the pedagogical context; the actual content within each environment is entirely flexible.

a. Exercise Types

Environment	Visual Indication
`exguided`	Guided icon; suggests step-by-step assistance
`exsemiguided`	Semi-guided icon; partial hints expected
`exauto`	Difficulty stars (1–3); independent work
`exmodel`	Modeling icon; open-ended problem-solving
`excorrection`	Correction styling; for displaying solutions

b. Exercise Environments

All exercise environments share a common structure: an optional title in brackets, followed by the exercise content. The `exauto` environment additionally requires a mandatory difficulty level (1–3) displayed as stars.

Standard exercise with title

```
\begin{exguided}[Solving Quadratic Equations]
\exstep{Identify coefficients $a$, $b$, $c$.}
\exstep{Compute $\Delta = b^2 - 4ac$.}
\exstep{Apply the quadratic formula.}
\end{exguided}
```

Exercise 1 – Solving Quadratic Equations

a) Identify coefficients a, b, c.

b) Compute $\Delta = b^2 - 4ac$.

c) Apply the quadratic formula.

Autonomous exercise with difficulty level

```
\begin{exauto}[Integration Practice][2]
Compute $\int x^2 e^x \, dx$.
\end{exauto}
```

Exercise 2 – Integration Practice ★★

Compute $\int x^2 e^x \, dx$.

c. Two-Column Layout

The `extwocol` environment displays content in two columns with a dotted separator, useful for compact exercise sheets:

```
\begin{extwocol}
\begin{exauto}[][1]
Simplify $\frac{x^2 - 1}{x - 1}$.
\end{exauto}

\begin{exauto}[][1]
Factor $x^2 + 5x + 6$.
\end{exauto}
\end{extwocol}
```

d. Blanks and Hidden Solutions

SCHOLIA supports dual compilation: one version with answers hidden (for students) and one with answers visible (for teachers or answer keys). Blank commands insert placeholders that reveal their content only when solutions are enabled.

Blank Commands

Command	Description
`\solutionBlank{width}{answer}`	Underlined blank or answer
`\solutionDotsBlank{n}{answer}`	Dotted blank (n dots) or answer
`\fillBlank{width}`	Always show underlined blank
`\blankLine{width}`	Simple underline

Example usage:

```
The derivative is \solutionBlank{2cm}{$2x$}.
```

Enabling Solutions By default, solutions are hidden. Three methods enable solution display:

Method 1: Package option

```
\usepackage[solutions]{scholia}
```

Method 2: In the preamble

```latex
\usepackage{scholia}
\solutionstrue
```

Method 3: Via command line

```
pdflatex "\def\ForceSolutions{}\input{document}"
```

This allows generating both student and teacher versions from the same source file.

e. Exercise Commands

Command	Description
`\exstep[title]`	Numbered step (a, b, c, ...)
`\resetexsteps`	Reset step counter to zero
`\highlight{text}`	Subtle gray background

f. Counter Management

The exercise counter (`exonum`) increments automatically with each exercise environment. The step counter (`exoitem`) resets at each `\resetexsteps` call. The question counter (`scholia@circlednum`) resets automatically when entering any exercise environment.

7. Grading

The grading module provides tools for creating assessment rubrics and point allocation displays. These are intended for teacher documents (answer keys, grading sheets) rather than student-facing materials.

a. Grading Box

A simple point allocation display:

```latex
\begin{gradebox}[Point Distribution]
\gradeitem{Question 1}{2 pts}
\gradeitem{Question 2}{3 pts}
\gradetotal{5 pts}
\end{gradebox}
```

Grading Scale – Point Distribution

Question 1	2 pts
Question 2	3 pts
Total	**5 pts**

b. Grading Table

For detailed rubrics with criteria descriptions:

```
\begin{gradetable}{Assessment Rubric}
\graderow{Clarity}{Clear presentation}{2 pts}
\graderow{Accuracy}{Correct reasoning}{3 pts}
\graderowtotal{5 pts}
\end{gradetable}
```

c. Inline Point Indicators

Point values can be added inline within exercise text:

```
\begin{question}
Calculate $f(3)$. \gradeinline{2 pts}
\end{question}
```

When the document already uses `question` and `subquestion`, the shorter helpers `\gradeq` and `\gradesubq` place bracketed point values aligned with the numbering markers:

```
\begin{question}
Calculate $f(3)$. \gradeq{2 pts}
\begin{subquestion}
Explain the method. \gradesubq{1 pt}
\end{subquestion}
\end{question}
```

d. Summary and Rubric Environments

Environment	Purpose
`gradesummary`	Dotted-border summary box for total grading notes
`graderubric`	Longtable-based rubric for detailed criteria

Typical helper commands inside `graderubric` are `\gradedetailedrow`, `\gradedetailedrowlist`, and `\gradecompetency`.

e. Automatic Point Tracking

The grading module includes counters for automatic point summation:

```
\resetgradepoints
\gradeitemtracked{Q1}{Description}{2}
\gradeitemtracked{Q2}{Description}{3}
Total: \showgradetotal
```

8. Beamer Tools

When SCHOLIA runs in Beamer mode, it loads headline utilities and progression helpers in addition to the shared document features.

a. Headline Modes

The headline system exposes three mutually exclusive modes:

Mode	Behavior
`objective`	Default headline banner showing the persistent objective text
`frametitle`	Frametitle banner with an empty headline
`progressbar`	Thin headline progress bar plus underlined frametitle

The objective text is set with:

```
\setobjective{Persistent objective text}
```

Mode and headline appearance are configured with:

```
\scholiaBeamerSetup{headline mode=frametitle}
\scholiaBeamerSetup{headline mode=progressbar, show frame number=false}
```

Supported keys are: `headline mode`, `objective icon`, `progress color`, `progress background color`, `progress thickness`, `frametitle underline color`, and `show frame number`.

Legacy wrappers remain available: `\headlineshowsframetitle` and `\headlineshowsprogressbar`.

b. Slide-Composition Helpers

Command	Purpose
`\titlebackground{path}`	Overlay a full-bleed background image on the current frame
`\bottomtext{text}`	Push small source text to the bottom of the frame
`\fadedoval[keys]{text}`	Draw a shaded elliptical region with centered text

The `\fadedoval` command accepts keys `color`, `horizontal radius`, `vertical radius`, `text width`, `inner tint`, `outer tint`, and `baseline skip`.

c. Minimalist Compatibility

The `minimalistcompat` option enables aliases for decks migrated from the older minimalist Beamer theme.

```
\usepackage[beamer,minimalistcompat]{scholia}
```

Available compatibility helpers include: `\downarrowblack`, `\downarrowwhite`, `\twoheadsearrow`, `\droparrow`, `\lightbulb`, `\observation`, `\paper`, the `ideaboxgray` environment alias, `\setMinimalistTitleBackground{path`

and \setTitleBackground.

When \setTitleBackground is called without an explicit path, it reuses the background path configured with \setMinimalistTitleBackground. The compatibility layer also supports the legacy five-argument form of \fadedoval.

9. Interactive PDF Toggles

The interactive option enables clickable hide/reveal commands based on PDF Optional Content Groups through ocgx2. Viewers such as Adobe Reader and PDF.js handle these toggles; Apple Preview does not.

```
\usepackage[interactive]{scholia}
The derivative is \hide{\cos(x)}.
The secret is \hideNoUnderline{hidden}.
```

Command	Purpose
\hide{content}	Hidden content with dotted underline indicator
\hide[color]{content}	Hidden content with custom reveal color
\hideNoUnderline{content}	Hidden content without underline indicator
\Hide{hide}{show}{content}	Beamer-aware wrapper combining overlays with hide/reveal

The commands \revealAll and \hideAll currently issue package warnings only; they are placeholders, not implemented global toggles.

10. Math Helpers

The math module exposes a small set of expression helpers.

Command or Environment	Purpose
\StackRel{top}{middle}{bottom}	Three-line relation symbol
\tikzmarknode{name}{content}	Named TikZ anchor for expression markup
\ReplacementArrow{from}{to}	Arrow between two marked nodes
ReplacementPicture	Overlay environment for substitution sketches

The replacement-markup helpers are still marked experimental in the current implementation.

VI. License

SCHOLIA is distributed under the LaTeX Project Public License (LPPL) version 1.3c or later.

> This work may be distributed and/or modified under the conditions of the LaTeX Project Public License, either version 1.3c of this license or (at your option) any later version.

The latest version of this license is available at:
https://www.latex-project.org/lppl.txt

VII. Acknowledgments

SCHOLIA uses the following packages: tcolorbox, tikz, xparse, etoolbox, enumitem, xcolor, geometry, fancyhdr, and titlesec.

Icons are based on the Lucide icon set (https://lucide.dev).