

Challenge 7

Esther Kho Yining

2024-03-05

Challenge 7

I. ggplot2

```
# Load tidyverse and data (Slide 6)  
library(tidyverse)
```


```
## -- Attaching core tidyverse packages ----- tidyverse 2.0.0 --  
## v dplyr      1.1.4      v readr      2.1.5  
## v forcats    1.0.0      v stringr   1.5.1  
## v ggplot2     3.5.0      v tibble    3.2.1  
## v lubridate  1.9.3      v tidyr     1.3.0  
## v purrr      1.0.2  
## -- Conflicts ----- tidyverse_conflicts() --  
## x dplyr::filter() masks stats::filter()  
## x dplyr::lag()     masks stats::lag()  
## i Use the conflicted package (<http://conflicted.r-lib.org/>) to force all conflicts to become errors
```

```
library(palmerpenguins)  
glimpse(penguins)
```


```
## Rows: 344  
## Columns: 8  
## $ species      <fct> Adelie, Adelie, Adelie, Adelie, Adelie, Adelie, Adel~  
## $ island        <fct> Torgersen, Torgersen, Torgersen, Torgersen, Torgerse~  
## $ bill_length_mm <dbl> 39.1, 39.5, 40.3, NA, 36.7, 39.3, 38.9, 39.2, 34.1, ~  
## $ bill_depth_mm <dbl> 18.7, 17.4, 18.0, NA, 19.3, 20.6, 17.8, 19.6, 18.1, ~  
## $ flipper_length_mm <int> 181, 186, 195, NA, 193, 190, 181, 195, 193, 190, 186~  
## $ body_mass_g    <int> 3750, 3800, 3250, NA, 3450, 3650, 3625, 4675, 3475, ~  
## $ sex            <fct> male, female, female, NA, female, male, female, male~  
## $ year           <int> 2007, 2007, 2007, 2007, 2007, 2007, 2007, 2007, 2007~
```

Palmer Penguins

```
# a. start with the penguins data frame (Slide 8)  
library(ggplot2)  
ggplot(data = penguins)
```




```
# b. map bill depth to the x-axis (Slide 9)  
ggplot(data = penguins,  
  mapping = aes(x = bill_depth_mm))
```



c. Map bill length to the y-axis (Slide 10)


```
ggplot(data = penguins,  
  mapping = aes(x = bill_depth_mm,  
    y = bill_length_mm))
```



```
# d. Represent each observation with a point (Slide 11)
```

```
ggplot(data = penguins,  
  mapping = aes(x = bill_depth_mm,  
    y = bill_length_mm)) +  
  geom_point()
```


```
## Warning: Removed 2 rows containing missing values or values outside the scale range  
## ('geom_point()').
```



```
# e. Map species to the colour of each point (Slide 12)
```

```
ggplot(data = penguins,  
  mapping = aes(x = bill_depth_mm,  
    y = bill_length_mm,  
    colour = species)) +  
  geom_point()
```


```
## Warning: Removed 2 rows containing missing values or values outside the scale range  
## ('geom_point()').
```



```
# f. Title the plot "Bill depth and length (Slide 13)"
```

```
ggplot(data = penguins,  
  mapping = aes(x = bill_depth_mm,  
    y = bill_length_mm,  
    colour = species)) +  
  geom_point() +  
  labs(title = "Bill depth and length")
```

```
## Warning: Removed 2 rows containing missing values or values outside the scale range  
## ('geom_point()').
```




```
# g. Add the subtitle "Dimensions for Adelie, Chinstrap, and Gentoo Penguins" (Slide 14)
ggplot(data = penguins,
  mapping = aes(x = bill_depth_mm,
    y = bill_length_mm,
    colour = species)) +
  geom_point() +
  labs(title = "Bill depth and length",
    subtitle = "Dimensions for Adelie,
    Chinstrap, and Gentoo Penguins")
```

```
## Warning: Removed 2 rows containing missing values or values outside the scale range
## ('geom_point()').
```

Bill depth and length

Dimensions for Adelie,
Chinstrap, and Gentoo Penguins




```
# h. Label the x and y axes as "Bill depth (mm)" and "Bill length (mm)", respectively (Slide 15)
ggplot(data = penguins,
  mapping = aes(x = bill_depth_mm,
    y = bill_length_mm,
    colour = species)) +
  geom_point() +
  labs(title = "Bill depth and length",
    subtitle = "Dimensions for Adelie, Chinstrap, and Gentoo Penguins",
    x = "Bill depth (mm)",
    y = "Bill length (mm)")
```

```
## Warning: Removed 2 rows containing missing values or values outside the scale range
## ('geom_point()').
```


Bill depth and length


Dimensions for Adelie, Chinstrap, and Gentoo Penguins



```
# i. Label the legend "Species" (Slide 16)
```

```
ggplot(data = penguins,  
  mapping = aes(x = bill_depth_mm,  
    y = bill_length_mm,  
    colour = species)) +  
  geom_point() +  
  labs(title = "Bill depth and length",  
    subtitle = "Dimensions for Adelie, Chinstrap, and Gentoo Penguins",  
    x = "Bill depth (mm)", y = "Bill length (mm)",  
    colour = "Species")
```

```
## Warning: Removed 2 rows containing missing values or values outside the scale range  
## ('geom_point()').
```




j. Add a caption for the data source (Slide 17)

```
ggplot(data = penguins,
  mapping = aes(x = bill_depth_mm,
    y = bill_length_mm,
    colour = species)) +
  geom_point() +
  labs(title = "Bill depth and length",
    subtitle = "Dimensions for Adelie, Chinstrap, and Gentoo Penguins",
    x = "Bill depth (mm)", y = "Bill length (mm)",
    colour = "Species",
    caption = "Source: Palmer Station LTER / palmerpenguins package")
```

```
## Warning: Removed 2 rows containing missing values or values outside the scale range
## ('geom_point()').
```

Bill depth and length

Dimensions for Adelie, Chinstrap, and Gentoo Penguins




Source: Palmer Station LTER / palmerpenguins package

```
# k. Finally, use a discrete colour scale that is designed to be perceived by viewers with common forms
ggplot(data = penguins,
  mapping = aes(x = bill_depth_mm,
    y = bill_length_mm,
    colour = species)) +
  geom_point() +
  labs(title = "Bill depth and length", subtitle = "Dimensions for Adelie, Chinstrap, and Gentoo Penguins",
    x = "Bill depth (mm)", y = "Bill length (mm)",
    colour = "Species",
    caption = "Source: Palmer Station LTER / palmerpenguins package")
```

```
## Warning: Removed 2 rows containing missing values or values outside the scale range
## ('geom_point()').
```

Bill depth and length

Dimensions for Adelie, Chinstrap, and Gentoo Penguins



Source: Palmer Station LTER / palmerpenguins package


```
scale_colour_viridis_d()
```

```
## <ggproto object: Class ScaleDiscrete, Scale, gg>
##   aesthetics: colour
##   axis_order: function
##   break_info: function
##   break_positions: function
##   breaks: waiver
##   call: call
##   clone: function
##   dimension: function
##   drop: TRUE
##   expand: waiver
##   get_breaks: function
##   get_breaks_minor: function
##   get_labels: function
##   get_limits: function
##   get_transformation: function
##   guide: legend
##   is_discrete: function
##   is_empty: function
##   labels: waiver
##   limits: NULL
##   make_sec_title: function
##   make_title: function
```

```
##      map: function
##      map_df: function
##      n.breaks.cache: NULL
##      na.translate: TRUE
##      na.value: NA
##      name: waiver
##      palette: function
##      palette.cache: NULL
##      position: left
##      range: environment
##      rescale: function
##      reset: function
##      train: function
##      train_df: function
##      transform: function
##      transform_df: function
##      super: <ggproto object: Class ScaleDiscrete, Scale, gg>
```

```
# Palmer Penguins: Colour (Slide 22)
ggplot(penguins) + aes(x = bill_depth_mm, y = bill_length_mm,
  colour = species) +
  geom_point() +
  scale_colour_viridis_d()
```


```
## Warning: Removed 2 rows containing missing values or values outside the scale range
## ('geom_point()').
```



```
# Palmer Penguins: Shape 1 (Slide 23)
```

```
ggplot(penguins, aes(x = bill_depth_mm, y = bill_length_mm, colour = species,  
  shape = island)) +  
  geom_point() + scale_colour_viridis_d()
```


```
## Warning: Removed 2 rows containing missing values or values outside the scale range  
## ('geom_point()').
```



```
# Palmer Penguins: Shape 2 (Slide 24)
```


```
ggplot(penguins, aes(x = bill_depth_mm, y = bill_length_mm, colour = species,  
  shape = species)) +  
  geom_point() + scale_colour_viridis_d()
```

```
## Warning: Removed 2 rows containing missing values or values outside the scale range  
## ('geom_point()').
```




```
# Palmer Penguins: Size (Slide 25)
ggplot(penguins, aes(x = bill_depth_mm, y = bill_length_mm, colour = species, shape = species,
  size = body_mass_g)) +
  geom_point() + scale_colour_viridis_d()
```

```
## Warning: Removed 2 rows containing missing values or values outside the scale range
## ('geom_point()').
```



```
# Alpha
ggplot(penguins, aes(x = bill_depth_mm, y = bill_length_mm, colour = species,
  shape = species, size = body_mass_g, alpha = flipper_length_mm)) +
  geom_point() + scale_colour_viridis_d()
```


```
## Warning: Removed 2 rows containing missing values or values outside the scale range
## ('geom_point()').
```

Mapping vs. Setting


```
# Mapping
ggplot(penguins) +
  aes(x = bill_depth_mm,
      y = bill_length_mm,
      size = body_mass_g,
      alpha = flipper_length_mm) +
  geom_point()
```

```
## Warning: Removed 2 rows containing missing values or values outside the scale range
## ('geom_point()').
```



```
# Setting
ggplot(penguins) +
  aes(x = bill_depth_mm,
      y = bill_length_mm) +
  geom_point(size = 2, alpha = 0.5)
```


```
## Warning: Removed 2 rows containing missing values or values outside the scale range
## ('geom_point()').
```



Faceting

```
# Faceting (Slide 29)  
ggplot(penguins) +  
  aes(x = bill_depth_mm,  
      y = bill_length_mm) +  
  geom_point() +  
  facet_grid(species ~ island)
```


```
## Warning: Removed 2 rows containing missing values or values outside the scale range  
## ('geom_point()').
```



```
# Facet 2 (Slide 30)
```

```
ggplot(penguins, aes(x = bill_depth_mm, y = bill_length_mm)) + geom_point() +  
  facet_grid(species ~ sex)
```


```
## Warning: Removed 2 rows containing missing values or values outside the scale range  
## ('geom_point()').
```



```
# Facet 3 (Slide 31)
```

```
ggplot(penguins, aes(x = bill_depth_mm, y = bill_length_mm)) + geom_point() +  
  facet_grid(sex ~ species)
```


```
## Warning: Removed 2 rows containing missing values or values outside the scale range  
## ('geom_point()').
```



Facet 4 (Slide 32)

```
ggplot(penguins, aes(x = bill_depth_mm, y = bill_length_mm)) + geom_point() +  
  facet_wrap(~ species)
```


```
## Warning: Removed 2 rows containing missing values or values outside the scale range  
## ('geom_point()').
```



Facet 5 (Slide 33)

```
ggplot(penguins, aes(x = bill_depth_mm, y = bill_length_mm)) + geom_point() +  
  facet_wrap(~ species, ncol = 2)
```


```
## Warning: Removed 2 rows containing missing values or values outside the scale range  
## ('geom_point()').
```



Facet 6 (Slide 34)

```
ggplot(penguins, aes(x = bill_depth_mm, y = bill_length_mm)) + geom_point() +  
  facet_grid(. ~ species)
```


```
## Warning: Removed 2 rows containing missing values or values outside the scale range  
## ('geom_point()').
```

```
# Facet and colour (Slide 35)
```

```
ggplot(penguins, aes(x = bill_depth_mm, y = bill_length_mm, color = species)) +  
  geom_point() + facet_grid(species ~ sex) + scale_color_viridis_d()
```


```
## Warning: Removed 2 rows containing missing values or values outside the scale range  
## ('geom_point()').
```



```
# Facet and colour, no legend (Slide 36)
```

```
ggplot(penguins, aes(x = bill_depth_mm, y = bill_length_mm, color = species)) +  
  geom_point() + facet_grid(species ~ sex) + scale_color_viridis_d() +  
  guides(color = "none")
```

```
## Warning: Removed 2 rows containing missing values or values outside the scale range  
## ('geom_point()').
```



B. Visualising Numeric Variables

```
# Load openintro and data (Slide 39)
library(openintro)
```

```
## Loading required package: airports
```

```
## Loading required package: cherryblossom
```

```
## Loading required package: usdata
```

```
glimpse(loans_full_schema)
```

```
## Rows: 10,000
## Columns: 55
## $ emp_title      <chr> "global config engineer ", "warehouse~
## $ emp_length     <dbl> 3, 10, 3, 1, 10, NA, 10, 10, 10, 3, 1~
## $ state          <fct> NJ, HI, WI, PA, CA, KY, MI, AZ, NV, I~
## $ homeownership  <fct> MORTGAGE, RENT, RENT, RENT, RENT, OWN~
## $ annual_income  <dbl> 90000, 40000, 40000, 30000, 35000, 34~
## $ verified_income <fct> Verified, Not Verified, Source Verifi~
## $ debt_to_income <dbl> 18.01, 5.04, 21.15, 10.16, 57.96, 6.4~
```

```

## $ annual_income_joint      <dbl> NA, NA, NA, NA, 57000, NA, 155000, NA~
## $ verification_income_joint <fct> , , , , Verified, , Not Verified, , ~
## $ debt_to_income_joint     <dbl> NA, NA, NA, NA, 37.66, NA, 13.12, NA,~
## $ delinq_2y                <int> 0, 0, 0, 0, 0, 1, 0, 1, 1, 0, 0, 0, 0~
## $ months_since_last_delinq <int> 38, NA, 28, NA, NA, 3, NA, 19, 18, NA~
## $ earliest_credit_line     <dbl> 2001, 1996, 2006, 2007, 2008, 1990, 2~
## $ inquiries_last_12m      <int> 6, 1, 4, 0, 7, 6, 1, 1, 3, 0, 4, 4, 8~
## $ total_credit_lines       <int> 28, 30, 31, 4, 22, 32, 12, 30, 35, 9,~
## $ open_credit_lines        <int> 10, 14, 10, 4, 16, 12, 10, 15, 21, 6,~
## $ total_credit_limit       <int> 70795, 28800, 24193, 25400, 69839, 42~
## $ total_credit_utilized    <int> 38767, 4321, 16000, 4997, 52722, 3898~
## $ num_collections_last_12m <int> 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0~
## $ num_historical_failed_to_pay <int> 0, 1, 0, 1, 0, 0, 0, 0, 0, 0, 1, 0, 0~
## $ months_since_90d_late    <int> 38, NA, 28, NA, NA, 60, NA, 71, 18, N~
## $ current_accounts_delinq  <int> 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0~
## $ total_collection_amount_ever <int> 1250, 0, 432, 0, 0, 0, 0, 0, 0, 0, 0,~
## $ current_installment_accounts <int> 2, 0, 1, 1, 1, 0, 2, 2, 6, 1, 2, 1, 2~
## $ accounts_opened_24m      <int> 5, 11, 13, 1, 6, 2, 1, 4, 10, 5, 6, 7~
## $ months_since_last_credit_inquiry <int> 5, 8, 7, 15, 4, 5, 9, 7, 4, 17, 3, 4,~
## $ num_satisfactory_accounts <int> 10, 14, 10, 4, 16, 12, 10, 15, 21, 6,~
## $ num_accounts_120d_past_due <int> 0, 0, 0, 0, 0, 0, 0, NA, 0, 0, 0, 0, ~
## $ num_accounts_30d_past_due <int> 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0~
## $ num_active_debit_accounts <int> 2, 3, 3, 2, 10, 1, 3, 5, 11, 3, 2, 2,~
## $ total_debit_limit        <int> 11100, 16500, 4300, 19400, 32700, 272~
## $ num_total_cc_accounts    <int> 14, 24, 14, 3, 20, 27, 8, 16, 19, 7, ~
## $ num_open_cc_accounts     <int> 8, 14, 8, 3, 15, 12, 7, 12, 14, 5, 8,~
## $ num_cc_carrying_balance   <int> 6, 4, 6, 2, 13, 5, 6, 10, 14, 3, 5, 3~
## $ num_mort_accounts        <int> 1, 0, 0, 0, 0, 3, 2, 7, 2, 0, 2, 3, 3~
## $ account_never_delinq_percent <dbl> 92.9, 100.0, 93.5, 100.0, 100.0, 78.1~
## $ tax_liens                <int> 0, 0, 0, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0~
## $ public_record_bankrupt    <int> 0, 1, 0, 0, 0, 0, 0, 0, 0, 0, 1, 0, 0~
## $ loan_purpose                <fct> moving, debt_consolidation, other, de~
## $ application_type          <fct> individual, individual, individual, i~
## $ loan_amount               <int> 28000, 5000, 2000, 21600, 23000, 5000~
## $ term                      <dbl> 60, 36, 36, 36, 36, 36, 60, 60, 36, 3~
## $ interest_rate             <dbl> 14.07, 12.61, 17.09, 6.72, 14.07, 6.7~
## $ installment              <dbl> 652.53, 167.54, 71.40, 664.19, 786.87~
## $ grade                     <fct> C, C, D, A, C, A, C, B, C, A, C, B, C~
## $ sub_grade                 <fct> C3, C1, D1, A3, C3, A3, C2, B5, C2, A~
## $ issue_month               <fct> Mar-2018, Feb-2018, Feb-2018, Jan-201~
## $ loan_status               <fct> Current, Current, Current, Current, C~
## $ initial_listing_status     <fct> whole, whole, fractional, whole, whol~
## $ disbursement_method       <fct> Cash, Cash, Cash, Cash, Cash, Cash, C~
## $ balance                   <dbl> 27015.86, 4651.37, 1824.63, 18853.26,~
## $ paid_total                 <dbl> 1999.330, 499.120, 281.800, 3312.890,~
## $ paid_principal             <dbl> 984.14, 348.63, 175.37, 2746.74, 1569~
## $ paid_interest             <dbl> 1015.19, 150.49, 106.43, 566.15, 754.~
## $ paid_late_fees            <dbl> 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0~

```

Selected variables (Slide 40)

```

loans <- loans_full_schema %>%
  select(loan_amount, interest_rate, term, grade,
         state, annual_income, homeownership, debt_to_income)
glimpse(loans)


```

```
## Rows: 10,000
## Columns: 8
## $ loan_amount      <int> 28000, 5000, 2000, 21600, 23000, 5000, 24000, 20000, 20~
## $ interest_rate    <dbl> 14.07, 12.61, 17.09, 6.72, 14.07, 6.72, 13.59, 11.99, 1~
## $ term             <dbl> 60, 36, 36, 36, 36, 36, 60, 60, 36, 36, 60, 60, 36, 60,~
## $ grade            <fct> C, C, D, A, C, A, C, B, C, A, C, B, C, B, D, D, D, F, E~
## $ state            <fct> NJ, HI, WI, PA, CA, KY, MI, AZ, NV, IL, IL, FL, SC, CO,~
## $ annual_income    <dbl> 90000, 40000, 40000, 30000, 35000, 34000, 35000, 110000~
## $ homeownership    <fct> MORTGAGE, RENT, RENT, RENT, RENT, OWN, MORTGAGE, MORTGA~
## $ debt_to_income   <dbl> 18.01, 5.04, 21.15, 10.16, 57.96, 6.46, 23.66, 16.19, 3~
```


Histograms

```
# Histogram (Slide 46)
ggplot(loans) + aes(x = loan_amount) +
  geom_histogram()
```


```
## 'stat_bin()' using 'bins = 30'. Pick better value with 'binwidth'.
```




```
# Histogram and binwidth=1000 (Slide 47)
ggplot(loans, aes(x = loan_amount)) +
  geom_histogram(binwidth = 1000)
```




```
# Histogram and binwidth=5000 (Slide 48)
ggplot(loans, aes(x = loan_amount)) +
  geom_histogram(binwidth = 5000)
```



```
# Histogram and binwidth=2000 (Slide 49)  
ggplot(loans, aes(x = loan_amount)) +  
  geom_histogram(binwidth = 20000)
```




```
# Customising histograms (Slide 50)  
ggplot(loans, aes(x = loan_amount)) + geom_histogram(binwidth = 5000) +  
  labs(x = "Loan amount ($)", y = "Frequency", title = "Amounts of Lending Club loans" )
```

Categorical variable

```
# Fill with a categorical variable (Slide 51)  
ggplot(loans, aes(x = loan_amount, fill = homeownership)) +  
  geom_histogram(binwidth = 5000, alpha = 0.5) +  
  labs(x = "Loan amount ($)", y = "Frequency", title = "Amounts of Lending Club loans")
```




```
# Facet with a categorical variable (Slide 52)
ggplot(loans, aes(x = loan_amount, fill = homeownership)) + geom_histogram(binwidth = 5000) +
  labs(x = "Loan amount ($)", y = "Frequency", title = "Amounts of Lending Club loans") +
  facet_wrap(~ homeownership, nrow = 3)
```


Amounts of Lending Club loans




```
# Density plot (Slide 53)
ggplot(loans, aes(x = loan_amount)) +
  geom_density()
```




```
# Density plots and adjusting bandwidth 1 (Slide 54)  
ggplot(loans, aes(x = loan_amount)) +  
  geom_density(adjust = 0.5)
```




```
# Density plots and adjusting bandwidth 2 (Slide 55)  
ggplot(loans, aes(x = loan_amount)) +  
  geom_density(adjust = 1)
```




```
# Density plots and adjusting bandwidth 3 (Slide 56)  
ggplot(loans, aes(x = loan_amount)) +  
  geom_density(adjust = 2)
```



```
# Customising density plots (Slide 57)  
ggplot(loans, aes(x = loan_amount)) +  
  geom_density(adjust = 2) +  
  labs( x = "Loan amount ($)", y = "Density", title = "Amounts of Lending Club loans" )
```




```
# Adding a categorical variable (Slide 58)
ggplot(loans, aes(x = loan_amount, fill = homeownership)) +
  geom_density(adjust = 2, alpha = 0.5) +
  labs(x = "Loan amount ($)", y = "Density", title = "Amounts of Lending Club loans", fill = "Homeownership")
```





Box plot

```
# Box plot (Slide 59)
ggplot(loans, aes(x = interest_rate)) +
  geom_boxplot()
```




```
# Box plot and outliers (Slide 60)  
ggplot(loans, aes(x = annual_income)) +  
  geom_boxplot()
```




```
# Customizing box plot (Slide 61)
ggplot(loans, aes(x = interest_rate)) +geom_boxplot() +labs(x = "Interest rate (%)",y = NULL,
  title = "Interest rates of Lending Club loans") +
  theme( axis.ticks.y = element_blank(), axis.text.y = element_blank() )
```

Interest rates of Lending Club loans



```
# Adding a catoric variable (Slide 62)
ggplot(loans, aes(x = interest_rate,
y = grade)) +
  geom_boxplot() +
  labs(x = "Interest rate (%)", y = "Grade", title = "Interest rates of Lending Club loans", subtitle="by grade")
```


Interest rates of Lending Club loans by grade of loan



Scatterplot

```
# Scatterplot (Slide 63)
ggplot(loans, aes(x = debt_to_income, y = interest_rate)) + geom_point()
```


```
## Warning: Removed 24 rows containing missing values or values outside the scale range
## ('geom_point()').
```




Hex plot

```
# Hex plot 1 (Slide 64)
ggplot(loans, aes(x = debt_to_income, y = interest_rate)) +
  geom_hex()
```

```
## Warning: Removed 24 rows containing non-finite outside the scale range
## ('stat_binhex()').
```




```
# Hex plot 2 (Slide 65)  
ggplot(loans %>% filter(debt_to_income < 100), aes(x = debt_to_income, y = interest_rate)) +  
  geom_hex()
```




III. Visualizing categoric variables


```
# Bar plot (Slide 67)
ggplot(loans, aes(x = homeownership)) +
  geom_bar()
```

```
# Segmented bar plot 1 (Slide 68)  
ggplot(loans, aes(x = homeownership,  
  fill = grade)) +  
  geom_bar()
```



```
# Segmented bar plot 2 (Slide 69)
ggplot(loans, aes(x = homeownership, fill = grade)) +
  geom_bar(position = "fill")
```




Customising bar plots (Slide 71)

```
ggplot(loans, aes(y = homeownership, fill = grade)) + geom_bar(position = "fill") +  
labs( x = "Proportion", y = "Homeownership", fill = "Grade", title = "Grades of Lending Club loans", su
```



IV. Visualising variabes of varied types

```
# Violin plots (Slide 73)
ggplot(loans, aes(x = homeownership, y = loan_amount)) +
  geom_violin()
```



```
# Ridge plots (Slide 74)
```

```
library(ggribes)
```

```
ggplot(loans, aes(x = loan_amount, y = grade, fill = grade, color = grade)) +  
  geom_density_ridges(alpha = 0.5)
```

```
## Picking joint bandwidth of 2360
```

