

Cheat Sheet - Polars

Introduction

Library

```
import polars as pl
```

DataFrame

```
df = pl.DataFrame({
    "id": [1, 2, 3, 4]
    , "name": ["Alice", "Bob", "Charlie", "Diana"]
    , "age": [25, 30, 35, 28]
    , "score": [85.5, 90.0, 78.3, 92.1]
})
```

LazyFrame

```
lf = pl.LazyFrame({
    "id": [1, 2, 3, 4]
    , "name": ["Alice", "Bob", "Charlie", "Diana"]
    , "age": [25, 30, 35, 28]
    , "score": [85.5, 90.0, 78.3, 92.1]
})
```

Input/Output

Parquet

```
lf = pl.scan_parquet(
    source = filepath
    , n_rows = integer / None (default)
)

lf.sink_parquet(
    path = filepath
    , compression = string (default: 'zstd')
    , compression_level = int / None (default)
    , engine = EngineType (default: 'auto')
)
```

CSV

```
lf = pl.scan_csv(
    source = filepath
    , has_header = bool (default: True)
    , separator = string (default: ',')
    , quote_char = string (default: '"')
    , decimal_comma = bool (default: False)
    , schema_overrides = dictionary / None (default)
    , skip_rows = integer (default: 0)
    , skip_lines = integer (default: 0)
)

lf.sink_csv(
    path = filepath
    , include_header = bool (default: True)
    , separator = string (default: ',')
    , line_terminator = string (default: '\n')
    , quote_char = string (default: '"')
    , decimal_comma = bool (default: 'False')
    , engine = EngineType (default: 'auto')
)
```

Columns

```
lf.select(
    pl.col(['name', 'age', 'score'])
)
```

Special expressions: `pl.all()`, `pl.exclude('column-name-01', ..., 'column-name-n')`, `pl.col([pl.Int64, pl.Float64, pl.String])`

Generation

Index Column

```
lf = lf.with_row_index(name = 'index')
```

Custom Column(s)

```
lf.with_columns(
    age_round_01 = pl.col('age').round(0)
    , pl.col('age').round(0).alias('age_round_02')
    , pl.col('age').round(0).name.suffix('_round_03')
    , pl.col('age').name.prefix('original_')
)
```

Selection

Rows

```
lf.filter(
    (pl.col('age') > 27) | (pl.col('name') == 'Bob')
)

lf.filter(
    (pl.col('age') > 27) & (pl.col('name') == 'Bob')
)

lf.filter(
    pl.col('age') > 27
    , pl.col('name') == 'Bob'
)
```

Conditional Custom Column(s)

```
lf.select(
    pl.when(
        pl.col('score') > 80
    )
    .then('Pass')
    .when(
        pl.col('score') > 60
    )
    .then('Pending')
    .otherwise('Fail')
    .alias('result')
)
```