SQL Code

```sql
CREATE TABLE Student (
    ID INT,
    Name VARCHAR(20),
    Marks INT,
    Age INT
);

INSERT INTO Student VALUES
(1, 'Sushanth', 85, 20),
(2, 'Diganth', 75, 21),
(3, 'Deepak', 65, 20),
(4, 'Chiranth', 90, 22);

SELECT ID, Name, Marks + 5 AS Added_Marks FROM Student;

SELECT ID, Name, Marks - 5 AS Reduced_Marks FROM Student;

SELECT ID, Name, Marks * 2 AS Double_Marks FROM Student;

SELECT ID, Name, Marks / 2 AS Half_Marks FROM Student;

SELECT * FROM Student
WHERE Marks > 70;

SELECT * FROM Student
WHERE Marks = 85;

SELECT * FROM Student
WHERE Marks <> 65;

SELECT * FROM Student
WHERE Marks >= 75 AND Age = 20;

SELECT * FROM Student
WHERE Marks > 80 OR Age = 22;

SELECT * FROM Student
WHERE NOT Marks < 70;
```

Output:

ID	Name	Added_Marks
1	Sushanth	90
2	Diganth	80
3	Deepak	70
4	Chiranth	95

ID	Name	Reduced_Marks
1	Sushanth	80
2	Diganth	70
3	Deepak	60
4	Chiranth	85

ID	Name	Double_Marks
1	Sushanth	170
2	Diganth	150
3	Deepak	130
4	Chiranth	180

ID	Name	Half_Marks
1	Sushanth	42.5000
2	Diganth	37.5000
3	Deepak	32.5000
4	Chiranth	45.0000

ID	Name	Marks	Age
1	Sushanth	85	20
2	Diganth	75	21
4	Chiranth	90	22

ID	Name	Marks	Age
1	Sushanth	85	20

Output:

```
| ID   | Name      | Marks | Age  |
+------+-----------+-------+------+
|    1 | Sushanth  |    85 |   20 |
|    2 | Diganth   |    75 |   21 |
|    4 | Chiranth  |    90 |   22 |
+------+-----------+-------+------+

+------+-----------+-------+------+
| ID   | Name      | Marks | Age  |
+------+-----------+-------+------+
|    1 | Sushanth  |    85 |   20 |
+------+-----------+-------+------+

+------+-----------+-------+------+
| ID   | Name      | Marks | Age  |
+------+-----------+-------+------+
|    1 | Sushanth  |    85 |   20 |
|    4 | Chiranth  |    90 |   22 |
+------+-----------+-------+------+

+------+-----------+-------+------+
| ID   | Name      | Marks | Age  |
+------+-----------+-------+------+
|    1 | Sushanth  |    85 |   20 |
|    2 | Diganth   |    75 |   21 |
|    4 | Chiranth  |    90 |   22 |
```