

Java: Packages

Quiz

Question 1

R.java

```
package a;  
public class R { }
```

P.java

```
package a.b;  
public class P { }
```

D.java

```
package a.b.c;  
public class D {}
```

M.java

```
// insert code here  
public class M{ R r; P p; D; }
```

Which of options will make will make M compile?

- A. package a; import a.*;
- B. package a; import a.b.*; import a.b.c;
- C. package a.b.c; import a.*; import a.b.*;
- D. import a; import a.b;import a.b.c;

Question 1

R.java

```
package a;  
public class R { }
```

P.java

```
package a.b;  
public class P { }
```

D.java

```
package a.b.c;  
public class D {}
```

M.java

```
// insert code here  
public class M{  R r;  P p;  D; }
```

Which of options will make will make M compile?

- A. package a; import a.*;
- B. package a; import a.b.*; import a.b.c;
- ☒ C. package a.b.c; import a.*; import a.b.*;
- D. import a; import a.b;import a.b.c;

Question 2

Test1.java

```
package a;  
package b;  
public class Test1 {  
    public static void main(String[] args) {}  
    public class Test2{  
        public static void main(String[] args) {}  
    }  
}
```

What is/are the problems with the code?

- A. There are two package statements. There can be only 1.
- B. There are two main methods. There can be only 1.
- C. There are two public classes. There can be only 1.
- D. The file must be named as Test2.java.

Question 2

Test1.java

```
package a;  
package b;  
public class Test1 {  
    public static void main(String[] args) {}  
    public class Test2{  
        public static void main(String[] args) {}  
    }  
}
```

What is/are the problems with the code?

- ☒ A. There are two package statements. There can be only 1.
- ☐ B. There are two main methods. There can be only 1.
- ☒ C. There are two public classes. There can be only 1.
- ☐ D. The file must be named as Test2.java.

Question 3

Test.java

```
package a;  
class Test1 {  
    public static void main(String[] args) {  
        System.out.println("Test1");    }  
}  
class Test2{  
    public static void main(String[] args) {  
        System.out.println("Test2");    }  
}
```

Which command will print Test2 on the console?

- A. java Test
- B. java a.Test
- C. java a.Test1
- D. java a.Test2

Question 3

Test.java

```
package a;  
class Test1 {  
    public static void main(String[] args) {  
        System.out.println("Test1");    }  
}  
class Test2{  
    public static void main(String[] args) {  
        System.out.println("Test2");    }  
}
```

Which command will print Test2 on the console?

- A. java Test
- B. java a.Test
- C. java a.Test1
- ☒ D. java a.Test2

Question 4

A.java

```
package a;  
public class A{}  
class B{}
```

Which of the following are the valid ways of accessing class A from class B?

- A. A
- B. a.A
- C. A.a
- D. a.*

Question 4

A.java

```
package a;  
public class A{}  
class B{}
```

Which of the following are the valid ways of accessing class A from class B?

- ☒ A. A
- ☒ B. a.A
- C. A.a
- D. a.*

Question 5

Which of the following are package naming conventions?

- A. Must begin with lower case
- B. Must not contain numbers
- C. Must be all in lower case
- D. Must be a single letter

Question 5

Which of the following are package naming conventions?

- A. Must begin with lower case
- B. Must not contain numbers
- ☒ C. Must be all in lower case
- D. Must be a single letter

Question 6

Which packages are imported automatically?

- A. `javax.lang`
- B. `java.lang`
- C. `java.lang.System`
- D. `java.io`

Question 6

Which packages are imported automatically?

A. `javax.lang`

☒ B. `java.lang`

C. `java.lang.System`

D. `java.io`

Question 7

The **import** statement in Java

- A. includes the source file of the specified classes with the current file before compiling
- B. includes the class files of the specified classes with the current class file before after compiling
- C. loads the class files on demand
- D. allows the current code to access classes which are declared in other packages without using their full name.

Question 7

The **import** statement in Java

- A. includes the source file of the specified classes with the current file before compiling
- B. includes the class files of the specified classes with the current class file before after compiling
- C. loads the class files on demand
- ☒ D. allows the current code to access classes which are declared in other packages without using their full name.

Question 8

Which class(es) is(are) NOT available to java program without explicit import?

- A. Scanner**
- B. System**
- C. String**
- D. Grade**

Question 8

Which class(es) is(are) NOT available to java program without explicit import?

- ☒ A. Scanner
- ☐ B. System
- ☐ C. String
- ☒ D. Grade

Question 9

What can be done so that classes in multiple packages can be distributed without issues?

- A. Create ZIP file
- B. Create JAR file
- C. Set the classpath to the network location of class files
- D. Set the path to the network location of class files

Question 9

What can be done so that classes in multiple packages can be distributed without issues?

- A. Create ZIP file
- ☒ B. Create JAR file
- C. Set the classpath to the network location of class files
- D. Set the path to the network location of class files

Question 10

Select the code snippets which is/are NOT correct?

- A.

```
package Student;

import java.lang. *;    //Note the space is intentional

public class Grade{}
```
- B.

```
import java.lang.*;

package student;

public class Grade{}
```
- C.

```
package student;

import java.lang.*;

public class Grade{}

public class Teacher{}
```
- D.

```
import java.*;

import java.lang.*;

public class Grade{}
```

Question 10

Select the code snippets which is/are NOT correct?

A. `package Student;`

```
import java.lang. *;    //Note the space is intentional
public class Grade{}
```

B. `import java.lang.*;`
`package student;`
`public class Grade{}`

C. `package student;`
`import java.lang.*;`
`public class Grade{}`
`public class Teacher{}`

D. `import java.*;`
`import java.lang.*;`
`public class Grade{}`

Question 11

How can you change class-path through java code?

- A. Using “set classpath” command
- B. Using **System.setProperty()**
- C. Using **System.setClasspath()**
- D. This cannot be done

Question 11

How can you change class-path through java code?

- A. Using “set classpath” command
- ☒ B. Using **System.setProperty()**
- C. Using **System.setClasspath()**
- D. This cannot be done

Question 12

```
class Test{  
  
public static void main(String[] s){  
  
java.util.Scanner sc = new java.util.Scanner(in);  
  
int i = sc.nextInt();  
  
}}
```

What needs to be inserted in the code snippet to get the input from console?

- A. Change `in` to `System.in`
- B. Change `Scanner` to `System`
- C. Add `import System.* ;`
- D. Add `import static java.lang.System.*;`

Question 12

```
class Test{  
  
    public static void main(String[] s){  
  
        java.util.Scanner sc = new java.util.Scanner(in);  
  
        int i = sc.nextInt();  
  
    }  
}
```

What needs to be inserted in the code snippet to get the input from console?

- ☒ A. Change `in` to `System.in`
- ☐ B. Change `Scanner` to `System`
- ☐ C. Add `import System.* ;`
- ☒ D. Add `import static java.lang.System.*;`

Question 13

Scanner class is defined in which package?

- A. `java.lang`
- B. `java.io`
- C. `java.util`
- D. `java.net`

Question 13

Scanner class is defined in which package?

- A. `java.lang`
- B. `java.io`
- ☒ C. `java.util`
- D. `java.net`

Question 14

```
package a;  
class A{  
int i;      —————> A.java  
A() {}  
}
```

```
package b;      —————> B.java  
public class B{}
```

For class **B** to access **i** of class **A**, which of the following is/are together necessary?

- A. class **A** must be declared **public**
- B. Constructor **A() {}** must be declared **public**
- C. **int i** must be declared **public**
- D. None of the above

Question 14

```
package a;  
class A{  
int i;      —————→ A.java  
A() {}  
}
```

```
package b;      —————→ B.java  
public class B{}
```

For class **B** to access **i** of class **A**, which of the following is/are together necessary?

- ☒ **A.** class **A** must be declared **public**
- ☒ **B.** Constructor **A() {}** must be declared **public**
- ☒ **C.** **int i** must be declared **public**
- ☐ **D.** None of the above

Question 15

```
package a.b.c;
```

```
class A{}
```

On compiling using the command `javac -d . A.java`, `A.class` will be placed

- A. inside three folders namely 'a', 'b' and 'c'
- B. inside 'c' folder which in turn will be inside 'b' folder and that in turn will be inside a folder
- C. inside 'a' folder which in turn will be inside 'b' folder and that in turn will be inside 'c' folder
- D. Inside folder named 'a.b.c'

Question 15

```
package a.b.c;
```

```
class A{}
```

On compiling using the command `javac -d . A.java`, `A.class` will be placed

- A. inside three folders namely 'a', 'b' and 'c'
- ☒ B. inside 'c' folder which in turn will be inside 'b' folder and that in turn will be inside a folder
- C. inside 'a' folder which in turn will be inside 'b' folder and that in turn will be inside 'c' folder
- D. Inside folder named 'a.b.c'