

ORDER SYMBOL: PC B 65 T

EL.number

Sweden: 2536832 Denmark: 8212001488 3423501 Finland:

INCLUDING:

Enclosure body, cover with PUR gasket, 4 cover screws, and mounting screws.

EAN:

6418074001948

APPROVALS:


USA: UL Type 1, 4X, 12, 13 (E75645 Vol.1 Sec.3); UL 94-V2


EURO: IP 67; UL 94-V2


OTHERS: IEC 529, CE, EEI, FIMKO 197844-01, GL 94 513 HH, LR

90/00200 (E4), CSA LR 49336-8

This is a sample photo.







TECHNICAL INFORMATION:

Standard colour: **RAL 7035** Temp.range in cont. use: Max. +80 °C Ingress protection: IP 67 (IEC 529) Temp. range of material: - 40 °C - + 120 °C

UL 94-V2 Flame resistance:

ACCESSORIES

ACCESSORIES			
DIN-Rail	B-1	Fastening lug	FP 22046
DIN-Rail	B-3	Screw	MB S-20KN
DIN-Rail	CHM-1	Screw	MB S-40KN
DIN-Rail	CHM-3		
DIN-Rail	DH-1		
DIN-Rail	DH-3		
DIN-Rail	FM-1		
DIN-Rail	FM-3		
Fastening lug	FP 22040		