

	1	2	3	4	5	6	7	8	9	10																																																																																							
A	<div>Ordering Information</div> <div>RF130-X XX X X X R XXX 1</div> <div><div>HEIGHT OF HOUSING 1:Single-Row 2: Dual-Row 30:3.0mm</div><div>NO.OF PINS PER ROW 1~40P 2~40P</div><div>0:No Pitch 1:1.27 2:2.00 3:2.54 4:7.62 5:10.16 6:15.24 7:22.86</div><div>A=1u" B=2u" C=5u" D=10u" E=15u" F=30u"</div><div>A:PBT B:PA6T C:PA9T D:LCP G:PPS</div><div>LENGTH OF TERMINAL</div></div> <div><div><p>Right socket connector:single row Availability from:2 to 40 contacts Standard number of contacts 20, 25, 32 and 40</p></div><div><p>Right socket connector:double row Availability from:4 to 80 contacts Standard number of contacts 20, 40, 56, 60 and 72</p></div></div> <div><div>Specifications</div><div>Insulator : Black glass filled polyester PPS-GF30-FR Fiammability : UL94V-0 Sleeve : Brass CuZn 36Pb3(36000) Contact cilp (4 finger) : Beryllium copper (C17200) Mating pin Ø: 0.40 to 0.66 mm or 0.50SQ Forces : (polished steel gauge Ø0.46mm) -Insertion : 2 N typ. -Withdrawal : 1N typ. Mechancial life : min 500 cycles Rated current : 3Amp Contact resistance: Max 10mΩ Dielectric resistance : Min 1000V_{RMS}</div></div>																																																																																																
B																																																																																																	
C																																																																																																	
D																																																																																																	
E																																																																																																	
F																																																																																																	
G																																																																																																	
H	<table><tr><td></td><td></td><td></td><td></td><td></td><td></td><td>OPERATION</td><td colspan="2">SCALE</td><td>Fit</td><td rowspan="5"></td><td rowspan="5">东莞市宇熙精密连接器有限公司 Dongguan Yuxi Electronic Co.,Ltd.</td></tr><tr><td></td><td></td><td></td><td></td><td></td><td></td><td>X.X ±0.25</td><td colspan="2">UNIT</td><td>MM</td></tr><tr><td></td><td></td><td></td><td></td><td></td><td></td><td>X.XX ±0.20</td><td>SIZE</td><td>A4</td><td>DESIGN</td><td>卢小强</td><td>PART NO.</td><td>RF130-XXXXXXRXXX1</td></tr><tr><td></td><td></td><td></td><td></td><td></td><td></td><td>X.XXX ±0.10</td><td>SHEET</td><td>1/1</td><td>CHECK</td><td></td><td>TITLE:</td><td>2.54圆孔排母 塑高3.0 90度</td></tr><tr><td></td><td></td><td></td><td></td><td></td><td></td><td>Angle ±3°</td><td>PROJ.</td><td></td><td>APPROVE</td><td></td><td>Customer No.</td><td></td></tr><tr><td>REV</td><td>DATE</td><td colspan="3">MODIFICATION DESCRIPTION</td><td>CHANGE</td><td>APPROVE</td><td>DIM</td><td>TOL</td><td colspan="4"></td></tr><tr><td></td><td>1</td><td>2</td><td>3</td><td>4</td><td>5</td><td>6</td><td>7</td><td>8</td><td>9</td><td>10</td><td></td></tr></table>																OPERATION	SCALE		Fit		东莞市宇熙精密连接器有限公司 Dongguan Yuxi Electronic Co.,Ltd.							X.X ±0.25	UNIT		MM							X.XX ±0.20	SIZE	A4	DESIGN	卢小强	PART NO.	RF130-XXXXXXRXXX1							X.XXX ±0.10	SHEET	1/1	CHECK		TITLE:	2.54圆孔排母 塑高3.0 90度							Angle ±3°	PROJ.		APPROVE		Customer No.		REV	DATE	MODIFICATION DESCRIPTION			CHANGE	APPROVE	DIM	TOL						1	2	3	4	5	6	7	8	9	10		
						OPERATION	SCALE		Fit		东莞市宇熙精密连接器有限公司 Dongguan Yuxi Electronic Co.,Ltd.																																																																																						
						X.X ±0.25	UNIT		MM																																																																																								
						X.XX ±0.20	SIZE	A4	DESIGN			卢小强	PART NO.	RF130-XXXXXXRXXX1																																																																																			
						X.XXX ±0.10	SHEET	1/1	CHECK				TITLE:	2.54圆孔排母 塑高3.0 90度																																																																																			
						Angle ±3°	PROJ.		APPROVE				Customer No.																																																																																				
REV	DATE	MODIFICATION DESCRIPTION			CHANGE	APPROVE	DIM	TOL																																																																																									
	1	2	3	4	5	6	7	8	9	10																																																																																							