


GCA Analyzer: A Python Package for Group Conversation Analysis

Jianjun Xiao ¹

¹ Beijing Normal University

DOI: [10.xxxxxx/draft](https://doi.org/10.xxxxxx/draft)

Software

- [Review](#) 
- [Repository](#) 
- [Archive](#) 

Editor: [Open Journals](#) 

Reviewers:

- [@openjournals](#)

Submitted: 01 January 1970

Published: unpublished

License

Authors of papers retain copyright and release the work under a Creative Commons Attribution 4.0 International License ([CC BY 4.0](#)).

Summary

Group conversation analysis is crucial for understanding social dynamics, learning behaviors, and communication patterns in various settings, particularly in educational contexts. The GCA Analyzer is a Python package that implements a comprehensive set of metrics and methods for analyzing group conversations, with special emphasis on Chinese text processing capabilities. This tool provides quantitative measures for participation patterns, interaction dynamics, content novelty, and communication density, making it especially valuable for researchers in education, social psychology, and communication studies.

The GCA Analyzer builds upon foundational work in group cognition analysis and computational approaches to group communication (Dowell et al., 2019; Wang & Xiao, 2025). These works provide essential frameworks for understanding how participants interact and contribute in group discussions.

Statement of Need

The analysis of group conversations is crucial in various fields, particularly in educational research, organizational behavior studies, and online learning environments. While several tools exist for conversation analysis, there is a significant gap in tools that can effectively handle multilingual text and provide comprehensive interaction metrics. Existing tools like ...

The GCA Analyzer addresses these gaps by providing:

1. Robust participation analysis through participation matrices
2. Temporal interaction analysis using sliding windows
3. Content similarity and novelty metrics
4. Social impact and responsivity measurements
5. Visualization capabilities for interaction patterns

These features enable researchers to conduct detailed analyses of group conversations, MOOC interactions, and cross-cultural communication patterns, supporting both research and practical applications in various educational and social contexts. By providing a comprehensive toolkit for quantitative analysis of group dynamics, the GCA Analyzer facilitates deeper insights into collaborative learning processes, team communication effectiveness, and the evolution of ideas within group discussions.

Installation

Install GCA Analyzer using pip:

```
pip install gca-analyzer
```

Quick Start

Here's a simple example to analyze a group conversation:

```
from gca_analyzer import GCAAnalyzer

# Initialize the analyzer
analyzer = GCAAnalyzer()

# Load and analyze data
metrics = analyzer.analyze_conversation('conversation_1', data)
print(metrics)
```

Command Line Usage

```
python -m gca_analyzer --data your_data.csv
```

Input Data Format

The input data should be a CSV file with the following columns: - conversation_id: Identifier for the conversation - person_id: Identifier for each participant - text: The actual message content - time: Timestamp of the message

Configuration Options

Command line arguments: - --data: Path to input data file (required) - --output: Output directory for results (default: gca_results) - --best-window-indices: Window size optimization threshold (default: 0.3) - Range: 0.0-1.0 - Sparse conversations may benefit from smaller thresholds - --console-level: Logging level (default: INFO) - Options: DEBUG, INFO, WARNING, ERROR, CRITICAL - --model-name: LLM model for text processing - Default: sentence-transformers/paraphrase-multilingual-MiniLM-L12-v2

Example Results

After running the analysis, you'll get metrics including: - Participation patterns - Internal cohesion - Overall responsiveness - Social impact - Content newness - Communication density

```

=== Analyzing Conversation 1A ===
=== Found valid window size: 4 (current window threshold: 0.03) ===
=== Descriptive statistics for GCA measures ===

```

Measure	Minimum	Median	M	SD	Maximum	Count	Missing	CV
Participation	-0.79	-0.79	0.00	2.84	15.35	35	0	inf
Responsivity	0.00	0.02	0.04	0.06	0.39	35	0	1.66
Internal Cohesion	0.00	0.00	0.10	0.18	0.68	35	0	1.89
Social Impact	0.01	0.02	0.04	0.07	0.41	35	0	1.75
Newness	0.00	0.28	0.27	0.11	0.55	35	0	0.40
Comm Density	0.34	1.13	1.41	0.88	3.95	35	0	0.62

```

Saved descriptive statistics to: example/gca_results/descriptive_statistics_gca.csv

```

Figure 1: Example Results

You'll get interactive and informative visualizations for key GCA measures:




Figure 2: GCA Analysis Results

- **Radar Plots:** Compare multiple measures across participants
- **Distribution Plots:** Visualize the distribution of measures

Results are saved as interactive HTML files in the specified output directory, allowing for easy exploration and sharing of analysis outcomes.

Mathematics

The GCA Analyzer implements several key mathematical formulas for analyzing group conversations:

Participation Rate

For a participant a , the participation count $\|P_a\|$ and average participation rate \bar{p}_a are calculated as:

$$\|P_a\| = \sum_{t=1}^n M_{a,t}$$

$$\bar{p}_a = \frac{1}{n} \|P_a\|$$

where $M_{a,t}$ is 1 if person a contributes at time t , and 0 otherwise, and n is the total number of contributions.

Participation Standard Deviation

The participation standard deviation σ_a for participant a is:

$$\sigma_a = \sqrt{\frac{1}{n-1} \sum_{t=1}^n (M_{a,t} - \bar{p}_a)^2}$$

Normalized Participation Rate

The normalized participation rate (\hat{P}_a) is computed relative to equal participation:

$$\hat{P}_a = \frac{\bar{p}_a - \frac{1}{k}}{\frac{1}{k}}$$

where k is the number of participants.

Cross-Cohesion Matrix

The cross-cohesion matrix Ξ for analyzing temporal interactions is computed as:

$$\Xi_{ab} = \frac{1}{w} \sum_{\tau=1}^w \frac{\sum_{t \geq \tau} M_{a,t-\tau} M_{b,t} S_{t-\tau,t}}{\sum_{t \geq \tau} M_{a,t-\tau} M_{b,t}}$$

78 where: - w is the optimal window length - $S_{t-\tau,t}$ is the cosine similarity between messages at
79 times $t - \tau$ and t - $M_{a,t}$ and $M_{b,t}$ are participation indicators for persons a and b at time t

80 Internal Cohesion

81 For each participant a , internal cohesion is their self-interaction:

$$82 \quad C_a = \Xi_{aa}$$

83 Overall Responsivity

84 The overall responsivity R_a for participant a is:

$$85 \quad R_a = \frac{1}{k-1} \sum_{b \neq a} \Xi_{ab}$$

86 Social Impact

87 The social impact I_a for participant a is:

$$88 \quad I_a = \frac{1}{k-1} \sum_{b \neq a} \Xi_{ba}$$

89 Message Newness

90 For a message c_t at time t , its newness $n(c_t)$ is:

$$91 \quad n(c_t) = \frac{\|\text{proj}_{\perp H_t}(c_t)\|}{\|\text{proj}_{\perp H_t}(c_t)\| + \|c_t\|}$$

92 where: - H_t is the space spanned by all previous message vectors - $\text{proj}_{\perp H_t}$ is the orthogonal
93 projection onto the complement of H_t - $\|c_t\|$ is the norm of the current message vector

94 The overall newness N_a for participant a is:

$$95 \quad N_a = \frac{1}{\|P_a\|} \sum_{t \in T_a} n(c_t)$$

96 where T_a is the set of times when participant a contributed.

97 Communication Density

98 For a message c_t at time t , its density D_i is:

$$99 \quad D_i = \frac{\|c_t\|}{L_t}$$

100 where L_t is the word length of the message.

101 The average communication density \bar{D}_a for participant a is:

$$102 \quad \bar{D}_a = \frac{1}{\|P_a\|} \sum_{t \in T_a} D_i$$

103 References

- 104 Dowell, N. M. M., Nixon, T. M., & Graesser, A. C. (2019). Group communication analysis: A
105 computational linguistics approach for detecting sociocognitive roles in multiparty interactions.
106 Behavior Research Methods, 51(3), 1007–1041. <https://doi.org/10.3758/s13428-018-1102-z>
107 Pennebaker, J. W., Booth, R. J., & Francis, M. E. (2015). Linguistic inquiry and word count:
108 LIWC2015. Pennebaker Conglomerates.
109 Pennebaker, J. W. (2001). Linguistic inquiry and word count: LIWC 2001. Wang, C., &
110 Xiao, J. (2025). A role recognition model based on students' social-behavioural-cognitive-
111 emotional features during collaborative learning. Interactive Learning Environments, 0(0),
112 1–20. <https://doi.org/10.1080/10494820.2024.2442706>