

CONTENTS

1	Vibrodiagnostics package	1
1.1	extraction module	1
1.2	mafaulda module	6
1.3	models module	9
1.4	pumps module	13
1.5	ranking module	14
1.6	selection module	17
1.7	visualize module	17
	Python Module Index	21
	Index	23

VIBRODIAGNOSTICS PACKAGE

1.1 extraction module

`extraction.detrending_filter(dataframes, columns)`

Subtract average from each value in columns of multiple data frames

Parameters

- `dataframes` (*List [DataFrame]*) – list of data frames
- `columns` (*List [str]*) – attributes from which mean is removed

Returns

modified data frames with mean removed

Return type

List[DataFrame]

`extraction.downsample(x, k, fs_reduced, fs)`

Downsample the time series by a factor

Parameters

- `x` (*array*) – time series
- `k` (*int*) – factor for downsampling (when it is None, the factor is calculated as a ratio of sampling rates)
- `fs_reduced` (*int*) – desired sampling frequency
- `fs` (*int*) – original sampling frequency of the time series

Returns

downsampled time series

Return type

array

`extraction.energy(x)`

Calculate energy of the signal

Parameters

`x` (*array*) – input signal

Returns

energy of the signal

Return type

float

`extraction.envelope_signal(f, pxx)`

Approximate envelope of frequency spectrum with quadratic interpolation between peaks

Parameters

- `f` (*array*) – array of frequency bins
- `pxx` (*array*) – array of amplitudes at frequency bins

Returns

envelope of the amplitudes

Return type

array

`extraction.frequency_features_calc(df, col, fs, window)`

Extract complete set of features in frequency-domain (FD set)

Parameters

- `df` (*DataFrame*) – data frame with input time series in columns
- `col` (*str*) – column in data frame to use for extraction
- `fs` (*int*) – sampling frequency in Hz of the time series
- `window` (*int*) – length of FFT window

Returns

list of frequency-domain features in pairs of feature name with column prefix and its value

Return type

List[Tuple[str, DataFrame]]

`extraction.fs_list_files(root_path)`

List csv and tsv files in dataset in the directory

Parameters

`root_path` (*str*) – base path of dataset directory

Returns

list of filenames

Return type

List[str]

`extraction.harmonic_series_detection(f, pxx, fs, fft_window)`

Find all series of harmonic frequencies in the frequency spectrum according to paper: “Identification of harmonics and sidebands in a finite set of spectral components” (<https://hal.science/hal-00845120v2/document>)

Parameters

- `f` (*array*) – array of frequency bins
- `pxx` (*array*) – array of amplitudes at frequency bins
- `fs` (*int*) – sampling frequency in Hz
- `fft_window` (*int*) – length of FFT window for calculation of frequency bin resolution

Returns

list of harmonic frequency series with components described by their frequency and amplitude

Return type

List[List[Tuple[int, float]]]

`extraction.have_intersection(interval1, interval2)`

Check overlap of two numeric intervals

Parameters

- `interval1 (Tuple[float, float])` – numbers for bounds of the first interval
- `interval2 (Tuple[float, float])` – numbers for bounds of the second interval

Returns

overlap of intervals is present

Return type

bool

`extraction.list_files(dataset)`

List csv and tsv files in dataset within ZIP archive

Parameters

`dataset (ZipFile)` – dataset in zip archive

Returns

list of filenames

Return type

`List[str]`

`extraction.load_features(filename, axis, label_columns)`

Load features from csv file and aggregate values from chosen directions of movement

Parameters

- `filename (str)` – File path where extracted features are found
- `axis (List[str])` – Elements to combine one feature from
- `label_columns (List[str])` – Columns that are not features and are not processed just copied

Returns

data frame with columns of unique feature names

Return type

`Tuple[DataFrame, DataFrame]`

`extraction.load_files_split(dataset, func, parts=1, cores=4)`

Load files from the dataset in ZIP archive and process them with callback function

Parameters

- `dataset (ZipFile)` – dataset in zip archive
- `func (Callable)` – callback for file processing that takes dataset, filename, and number of parts to split file into as parameters
- `parts (int)` – number of partitions to split each file into
- `cores (int)` – number of cores to use in workload parallelization

Returns

data frame with extracted features and associated annotations for row

Return type

`DataFrame`

`extraction.mms_peak_finder(x, win_len=3)`

Robust non-parametric peak identification MMS algorithm according to description in paper: “Non-Parametric Local Maxima and Minima Finder with Filtering Techniques for Bioprocess” (<https://doi.org/10.4236/jsip.2016.74018>)

Parameters

- `x (array)` – time series

- `win_len (int)` – window length of points compared in peak finding

Returns

array of indexes where peaks are in the time series

Return type

array

`extraction.negentropy(x)`

Calculate negentropy of the signal

Parameters

`x (array)` – input signal

Returns

negentropy of the signal

Return type

float

`extraction.signal_to_noise(x)`

Calculate estimated signal to noise ratio (noisiness) of the signal. Formula is taken from: <https://www.geeksforgeeks.org/signal-to-noise-ratio-formula/>

Parameters

`x (array)` – input signal

Returns

SNR of the signal

Return type

float

`extraction.spectral_roll_off_frequency(f, pxx, percentage)`

Calculate roll-off frequency. Cumulative sum of energy in spectral bins below roll-off frequency is percentage of total energy

Parameters

- `f (array)` – array of frequency bins
- `pxx (array)` – array of amplitudes at frequency bins
- `percentage (float)` – ratio of total energy below the roll-off frequency

Returns

roll-off frequency in Hz

Return type

float

`extraction.spectral_transform(x, window, fs)`

Estimate frequency spectrum using Welch's method. Partition the signal with Hann window and 50% overlap.

Parameters

- `x (Series)` – input signal in time domain
- `window (int)` – length of Hann FFT window
- `fs (int)` – sampling frequency in Hz of the input signal

Returns

envelope of the amplitudes

Return type

Tuple[array, array]

`extraction.split_dataframe(dataframe, parts=None)`

Split to data frames to non overlapping parts

Parameters

- `dataframe` (*DataFrame*) – data frame to be split
- `parts` (*int*) – number of partitions to split data frame into

Returns

list of data frame parts

Return type

List[DataFrame]

`extraction.temporal_variation(x, window)`

Calculate temporal variations in successive frequency spectra. It is a inverse correlation of pairs formed from overlapping windows.

Parameters

- `x` (*Series*) – input signal in time domain
- `window` (*int*) – length of Hann FFT window

Returns

array of temporal variations

Return type

List[float]

`extraction.time_features_calc(df, col, fs, window)`

Extract complete set of features in time-domain (TD set)

Parameters

- `df` (*DataFrame*) – data frame with input time series in columns
- `col` (*str*) – column in data frame to use for extraction
- `fs` (*int*) – sampling frequency in Hz of the time series
- `window` (*int*) – length of FFT window (not used)

Returns

list of time-domain features in pairs of feature name with column prefix and its value

Return type

List[Tuple[str, DataFrame]]

`extraction.wavelet_features_calc(df, col, fs, window)`

Extract wavelet coefficients for Meyer wavelet and six levels deep. Each wavelet coefficient produces four features (energy, energy ratio, kurtosis, negentropy)

Parameters

- `df` (*DataFrame*) – data frame with input time series in columns
- `col` (*str*) – column in data frame to use for extraction
- `fs` (*int*) – sampling frequency in Hz of the time series
- `window` (*int*) – length of FFT window (not used)

Returns

list of wavelet-domain features in pairs of feature name with column prefix and its value

Return type

List[Tuple[str, DataFrame]]

1.2 mafaalda module

```
mafaalda.BEARINGS = {'ball_diameter': 0.7145, 'balls': 8, 'bpfi_factor': 5.002,
'bpfo_factor': 2.998, 'bsf_factor': 1.871, 'ftf_factor': 0.375, 'pitch_diameter':
2.8519}
```

Coefficients for bearing characteristic frequencies

```
mafaalda.FAULTS = {'A': {'horizontal-misalignment': 'misalignment', 'imbalance':
'imbalance', 'normal': 'normal', 'underhang-ball_fault': 'ball fault',
'underhang-cage_fault': 'cage fault', 'underhang-outer_race': 'outer race fault',
'vertical-misalignment': 'misalignment'}, 'B': {'horizontal-misalignment':
'misalignment', 'imbalance': 'imbalance', 'normal': 'normal', 'overhang-ball_fault':
'ball fault', 'overhang-cage_fault': 'cage fault', 'overhang-outer_race': 'outer
race fault', 'vertical-misalignment': 'misalignment'}}
```

Annotation of fault types by bearing placement

```
mafaalda.LABEL_COLUMNS = ['fault', 'severity', 'rpm']
```

Metadata columns extracted from file path within dataset

```
mafaalda.SAMPLING_RATE = 50000
```

Sampling frequency in Hz of the sensors

```
mafaalda.assign_labels(df, bearing, keep=False)
```

Assign labels to fault types for bearing and optionally clean up data frame to contain only annotated rows with faults

Parameters

- `df` (*DataFrame*) – data frame after feature extraction with column “fault”
- `bearing` (*str*) – bearing to determine labels of fault types (“A” or “B”)
- `keep` (*bool*) – do not remove metadata columns

Returns

annotated data frame

Return type

DataFrame

```
mafaalda.bearing_frequencies(rpm)
```

Calculate bearing characteristic frequencies for MaFaulDa machine simulator

Parameters

`rpm` (*int*) – Rotational speed of the machine

Returns

Bearing defect frequencies

Return type

Dict[*str*, *float*]

```
mafaalda.clean_columns(df)
```

Remove excessive columns with metadata and drop rows without label

Parameters

`df` (*DataFrame*) – data frame with excess labels

Returns

data frame that consists of columns with features and “label”

Return type

DataFrame


```
mafaulda.csv_import(dataset, filename)
```

Open a CSV file from MaFaulda zip archive

Parameters

- `dataset` (*ZipFile*) – ZIP archive of MaFaulDa dataset
- `filename` (*str*) – path to the file within dataset

Returns

data frame of the imported file

Return type

DataFrame

```
mafaulda.features_by_domain(features_calc, dataset, filename, window=None, parts=1,
                             multirow=False)
```

Open a CSV file from MaFaulda zip archive

Parameters

- `features_calc` (*Callable*) – callback feature extraction function that has parameters for data frame, column to process in data frame, sampling frequency, window length of segment
- `dataset` (*ZipFile*) – ZIP archive of MaFaulDa dataset
- `filename` (*str*) – path to the file within dataset
- `window` (*int*) – length of window (usually for FFT)
- `parts` (*int*) – number of parts the input time series is split into
- `multirow` (*bool*) – extracted features are in rows, not in columns

Returns

row(s) of features extracted from the file

Return type

DataFrame

```
mafaulda.get_classes(df, bearing)
```

Create column “label” in data frame according to chosen bearing

Parameters

- `df` (*DataFrame*) – data frame after feature extraction with column “fault”
- `bearing` (*str*) – bearing to determine labels of fault types (“A” or “B”)

Returns

data frame with “label” column

Return type

DataFrame

```
mafaulda.label_severity(df, bearing, level, debug=False, keep=False)
```

Relabel faults less than set relative severity level as “normal”

Parameters

- `df` (*DataFrame*) – data frame after feature extraction with column “fault”
- `bearing` (*str*) – bearing to determine labels of fault types (“A” or “B”)
- `debug` (*bool*) – print relative severity levels
- `keep` (*bool*) – do not remove metadata columns
- `level` (*float*)

Returns

data frame with relabeled observations

Return type

DataFrame

`mafaulda.load_source(domain, row, train_size=0.8)`

Load features according to domain and split the observations into training and testing set

Parameters

- `domain` (*str*) – complete feature set (“TD”, “FD”)
- `row` (*dict*) – parameters for data filtering, e.g.: {“placement”: “A”, online: False}
- `train_size` (*float*) – ratio of training set to testing set

Returns

X_train, X_test, Y_train, Y_test

Return type

tuple

`mafaulda.lowpass_filter(data, cutoff=10000, fs=50000, order=5)`

Low-pass filter of n-th order the input signal at the cutoff frequency

Parameters

- `data` (*Series*) – input signal
- `cutoff` (*int*) – cutoff frequency
- `fs` (*int*) – sampling frequency in Hz of the input signal
- `order` (*int*) – steps of the filter

Returns

output signal after filtering

Return type

Series

`mafaulda.lowpass_filter_extract(dataframes, columns)`

Apply low-pass filter to columns in multiple data frames

Parameters

- `frames` (*data*) – list of input dataframes to which filter is applied to
- `columns` (*List [str]*) – columns that filter is applied to
- `dataframes` (*List [DataFrame]*)

Returns

list of data frames after filtering

Return type

List [DataFrame]

`mafaulda.mark_severity(df, bearing, debug=False)`

Calculate relative severity levels for data frame with original metadata columns

Parameters

- `df` (*DataFrame*) – data frame after feature extraction with column “fault” and “severity”
- `bearing` (*str*) – bearing to determine labels of fault types (“A” or “B”)
- `debug` (*bool*) – print relative severity levels

Returns

data frame with columns for absolute and relative fault severity levels

Return type

DataFrame

`mafaulda.parse_filename(filename)`

Split path of file within dataset structure to label the time series

Parameters

`filename` (*str*) – path to file inside of zip archive

Returns

fault type, severity conditions, and file number

Return type

Tuple[*str*, *str*, *str*]

`mafaulda.rpm_calc(tachometer)`

Extract rotational speed in rpm units from tachometer pulse signal

Parameters

`tachometer` (*Series*) – tachometer signal

Returns

rotational speed in rpm

Return type

float

1.3 models module

`models accuracies_to_table(domain, set, distribution, accuracy)`

Format accuracy to a row with metadata about hyperparameter and compute percentiles in the model accuracy distribution

Parameters

- `domain` (*str*) – source domain from which the features are extracted (“TD” or “FD”)
- `set` (*str*) – Title for the feature set or selection method
- `distribution` (*DataFrame*) – accuracy distribution of the model
- `accuracy` (*DataFrame*) – accuracy of the model in training and testing set

Returns

formatted structure for row of accuracies and percentiles

Return type

dict

`models.all_features(X, Y, model_name='knn', power_transform=False, k_neighbors=[1, 5, 9, 13, 17, 21, 25, 29, 33, 37], k_folds=5)`

Evaluate complete feature sets in k-nearest neighbours classifier

with various k-value parameter

Parameters

- `X` (*DataFrame*) – data frame of predictor features
- `Y` (*Series*) – column of labels

- `model_name` (*str*) – name of the machine learning model to evaluate. Options are: “knn”, “lda”, “bayes”, “svm”
- `power_transform` (*bool*) – apply power transform of features in preprocessing instead of normalization
- `k_neighbors` (*list*) – number of neighbours for k-nearest neighbours model
- `kfolds` (*int*) – number of splits for k-fold cross-validation

Returns

training and testing accuracy for each value of k-neighbours

Return type

Dict[*str*, *float*]

```
models.enumerate_models(X, Y, domain, k_neighbors=(3, 5, 11, 15), num_of_features=(2, 3, 4, 5), kfolds=5, power_transform=False, model='knn')
```

Grid search of parameters k-nearest neighbours classifier with feature subset combinations

Parameters

- `X` (*DataFrame*) – data frame of predictor features
- `Y` (*DataFrame*) – column of labels
- `domain` (*str*) – source domain from which the features are extracted (“TD” or “FD”)
- `k_neighbors` (*Tuple* [*int*]) – neighbours for k-nearest neighbours model to search in
- `num_of_features` (*Tuple* [*int*]) – number of features in the subset to search in
- `kfolds` (*int*) – number of splits for k-fold cross-validation
- `power_transform` (*bool*) – apply power transform of features in preprocessing instead of normalization
- `model` – name of the machine learning model to evaluate. Options are: “knn”, “lda”, “bayes”, “svm”

Returns

training and testing accuracy for each hyperparameter and feature set combination

Return type

DataFrame

```
models.feature_combinations(X, Y, k_neighbors, num_of_features, kfolds, domain, model, power_transform=False)
```

Evaluate all combinations of feature subsets of given size out of complete sets

Parameters

- `X` (*DataFrame*) – data frame of predictor features
- `Y` (*DataFrame*) – column of labels
- `k_neighbors` (*int*) – number of neighbours for k-nearest neighbours model
- `num_of_features` (*int*) – number of features in the subset
- `kfolds` (*int*) – number of splits for k-fold cross-validation
- `domain` (*str*) – source domain from which the features are extracted
- `model` (*str*) – name of the machine learning model to evaluate. Options are: “knn”, “lda”, “bayes”, “svm”

- `power_transform (bool)` – apply power transform of features in preprocessing instead of normalization

Returns

training and testing accuracy for each combination of features

Return type

`List[dict]`

```
models.feature_selection_accuracies(X, Y, domain, models_summary, k_neighbors,
                                   number_of_features, power_transform=False)
```

Apply feature selection methods and evaluate accuracies for chosen number of neighbours and number of features

Parameters

- `X (DataFrame)` – data frame of predictor features
- `Y (DataFrame)` – column of labels
- `domain (str)` – source domain from which the features are extracted (“TD” or “FD”)
- `k_neighbors (int)` – neighbours for k-nearest neighbours model
- `number_of_features (int)` – number of features in the subset
- `power_transform (bool)` – apply power transform of features in preprocessing instead of normalization
- `models_summary (DataFrame)`

Params model_summary

accuracies from all feature subset combinations

Returns

accuracies and percentiles for all tested feature selection methods

Return type

`List[Dict[str, int]]`

```
models.find_best_subset(X, Y, metric, members, kfold=5)
```

Find the best subset of features based on supplied feature selection metric name

Parameters

- `X (DataFrame)` – data frame of predictor features
- `Y (Series)` – column of labels
- `metric (str)` – name of the bivariate similarity metric to compute for each feature and label
- `members (int)` – number of features in the subset
- `kfold (int)` – number of splits for k-fold cross validation

Returns

list of the best features according to feature selection metric

Return type

`List[str]`

```
models.kfold_accuracy(X, Y, k_neighbors, kfold, model_name='knn', power_transform=True,
                     knn_metric='euclidean')
```

Evaluate classifier accuracy in k-fold validation on a data frame of features after oversampling to the majority class

Parameters

- `X` (*DataFrame*) – data frame of predictor features
- `Y` (*Series*) – column of labels
- `k_neighbors` (*int*) – number of neighbours for k-nearest neighbours model
- `model_name` (*str*) – name of the machine learning model to evaluate. Options are: “knn”, “lda”, “bayes”, “svm”
- `kfolds` (*int*) – number of splits for k-fold cross-validation
- `power_transform` (*bool*) – apply power transform of features in preprocessing instead of normalization
- `knn_metric` – distance metric name for k-nearest neighbours model

Returns

average accuracy of model over k-folds in training and testing sets

Return type

Dict[*str*, *float*]

`models.knn_online_learn(X, Y, window_len=1, learn_skip=0, clusters=False, n_neighbors=5)`

Progressive valuation of k-nearest neighbours classifier trained with increamental learning

Parameters

- `X` (*DataFrame*) – data frame of predictor features
- `Y` (*DataFrame*) – column of labels
- `window_len` (*int*) – Length of the tumbling window
- `learn_skip` (*int*) – Gap of labeled observations in amount of samples
- `clusters` (*int*) – return data points instead of valuation
- `n_neighbors` (*int*) – number of neighbours for k-nearest neighbours model

Returns

performance of the model in progressive valuation over all generations

Return type

DataFrame

`models.model_boundaries(X, Y, n=5, model_name='knn', knn_metric='euclidean')`

Train k-nearest neighbours classifier to be used in determining its decision boundaries

Parameters

- `X` (*DataFrame*) – data frame of predictor features
- `Y` (*DataFrame*) – column of labels
- `n` (*int*) – number of neighbours for k-nearest neighbours model
- `model_name` (*str*) – name of the machine learning model to evaluate. Options are: “knn”, “lda”, “bayes”, “svm”
- `knn_metric` (*str*) – distance metric name for k-nearest neighbours model

Returns

model fitted with training data of 80% from the original dataset

`models.transform_to_pca(X, n)`

Transform features to their principal components after normalization

Parameters

- `dataset` – data frame with columns only for predictors
- `n` (*int*) – number of principal components

- `X (DataFrame)`

Returns

data frames with rows of features replaced for principal components

Return type

DataFrame

1.4 pumps module

```
pumps.LABEL_COLUMNS = ['date', 'device', 'position']
```

Metadata columns extracted from file path within dataset

```
pumps.SAMPLING_RATE = 26866
```

Sampling frequency in Hz of the sensors

```
pumps.assign_labels(df)
```

Assign labels to fault types into “label” column based on measurement placement

Parameters

`df (DataFrame)` – data frame after feature extraction with column “fault”

Returns

annotated data frame

Return type

DataFrame

```
pumps.beaglebone_measurement(filename, fs)
```

Import csv file recorded on BeagleBone Black with accelerometer ADXL335

Parameters

- `filename (str)` – file name of the recording
- `fs (int)` – sampling frequency in Hz

Returns

data frame of the recording

Return type

Tuple[*str*, *DataFrame*]

```
pumps.csv_import(dataset, filename)
```

Open a CSV file from Pump zip archive

Parameters

- `dataset (ZipFile)` – ZIP archive of Pump industrial dataset
- `filename (str)` – path to the file within dataset

Returns

data frame of the imported file

Return type

DataFrame

```
pumps.features_by_domain(features_calc, dataset, filename, window=None, parts=None)
```

Open a CSV file from Pump zip archive

Parameters

- `features_calc (Callable)` – callback feature extraction function that has parameters for data frame, column to process in data frame, sampling frequency, window length of segment

- `dataset` (*ZipFile*) – ZIP archive of Pump dataset
- `filename` (*str*) – path to the file within dataset
- `window` (*int*) – length of window (usually for FFT)
- `parts` (*int*) – number of parts the input time series is split into

Returns

row(s) of features extracted from the file

Return type

DataFrame

```
pumps.features_by_domain_no_metadata(features_calc, filename, window=None, parts=None)
```

Parameters

- `features_calc` (*Callable*)
- `filename` (*str*)
- `window` (*int*)
- `parts` (*int*)

Return type

DataFrame

```
pumps.get_classes(df, labels, keep=False)
```

Assign labels to fault types into “label” column and optionally clean up data frame to contain only annotated rows with faults

Parameters

- `df` (*DataFrame*) – data frame after feature extraction with column “fault”
- `labels` (*Dict[str, dict]*) – Labels to assign machine and measurement placement
- `keep` (*bool*) – do not remove metadata columns

Returns

annotated data frame

Return type

DataFrame

1.5 ranking module

```
class ranking.ExperimentOutput(value, names=None, *, module=None, qualname=None,
                               type=None, start=1, boundary=None)
```

Bases: Enum

Types of experimental scenarios for feature selection techniques

BEST_CORR = 7

BEST_F_STAT = 8

BEST_MI = 9

BEST_SET = 2

COUNTS = 1

PCA = 5

RANKS = 3

SCORES_RANGE = 4

SILHOUETTE = 6

`ranking.batch_feature_ranking(X, Y, mode='rank')`

Order features based on their importance

Parameters

- `X` (*DataFrame*) – data frame that contains features
- `Y` (*Series*) – labels for observations
- `mode` (*str*) – feature selection method, options: “corr”, “f_stat”, “mi”, “rank”

Returns

Sorted features with their scores

Return type

DataFrame

`ranking.best_columns(ranks, corr, n)`

Retain the best features that does not belong to correlated set

Parameters

- `ranks` (*DataFrame*) – features with their scores
- `corr` (*Set [Tuple [str, str]]*) – set of pairs with high correlations
- `n` (*int*) – number of best features to keep

Returns

list of best features

Return type

List[*str*]

`ranking.best_subset(ranks, corr, n)`

Retain the best features

Parameters

- `ranks` (*DataFrame*) – features with their scores
- `corr` (*Set [Tuple [str, str]]*) – set of pairs with high correlations
- `n` (*int*) – number of best features to keep

Returns

best features

Return type

DataFrame

`ranking.compute_correlations(X, corr_above)`

Find pairs of features correlated more than the threshold

Parameters

- `X` (*DataFrame*) – data frame that contains features
- `corr_above` (*float*) – correlation threshold level

Returns

pairs or correlated features

Return type*Set[Tuple[str, str]]*`ranking.online_feature_ranking(X, Y, mode='rank')`

Sort features by gradual process

Parameters

- `X` (*DataFrame*) – data frame with sequence of events
- `Y` (*Series*) – labels for observations
- `mode` (*str*) – feature selection method, options: “corr”, “f_stat”, “mi”, “rank”

Returns

leaderboard of the features

Return type*DataFrame*`ranking.pca_explained_variances(X_train, pc)`

Explained variances of the principal components

Parameters

- `X_train` (*DataFrame*) – data points of the training set
- `pc` (*int*) – number of principal components

Returns

dictionary of principal components and explained variances

Return type*Dict*[str, float]`ranking.silhouette_scores(X_train, X_test, Y_train, Y_test, best_features, pc)`

Calculate silhouette score of data points after normalization of training and testing set with and without the principal components analysis

Parameters

- `X_train` (*DataFrame*) – data points of the training set
- `X_test` (*DataFrame*) – data points of the testing set
- `Y_train` (*DataFrame*) – labels for the training set
- `Y_test` (*DataFrame*) – labels for the testing set
- `best_features` (*List* [*str*]) – list of chosen feature names
- `pc` (*int*) – number of principal components

Returns

silhouette scores for data points

Return type*Dict*[str, float]

1.6 selection module

```
class selection.Correlation
```

Bases: Bivariate

Online correlation to classes as dichotomous variables

`get()`

Return the current value of the statistic.

`update(x, y)`

Update and return the called instance.

```
class selection.FisherScore
```

Bases: Bivariate

Online F statistic

`get()`

Return the current value of the statistic.

`update(x, y)`

Update and return the called instance.

```
class selection.MutualInformation
```

Bases: Bivariate

Online Mutual information to binned labels

`get()`

Return the current value of the statistic.

`update(x, y)`

Update and return the called instance.

```
selection.corr_classif(X, y)
```

Calculate point-biserial correlations to features

Parameters

- `X` (*array*) – matrix of features
- `y` (*array*) – labels of observations

Returns

list of absolute value of correlations between classes and features

Return type

array

1.7 visualize module

```
visualize.DOMAIN_TITLES = {'FD': 'Frequency domain', 'TD': 'Time domain', 'TD+FD':  
'Time and Frequency domain'}
```

Titles for signal source domain abbreviation

```
visualize.boxplot_enumerate_models_accuracy(results, metric, plots_col, inplot_col)
```

Boxplot of model accuracy distributions for various
number of features or neighbours

Parameters

- `results` (*DataFrame*) – model accuracy distributions
- `metric` (*str*) – column of values to show in values for accuracy
- `plots_col` (*str*) – constant parameter for subplot (“f” or “k”)
- `inplot_col` (*str*) – comparison of different values for the parameter within subplot (“f” or “k”)

`visualize.cross_cuts_3d_cluster(X_train, cluster, title)`

Scatter plot of clusters in 3D feature space shown in planar cross-sections through coordinate axes

Parameters

- `X_train` (*DataFrame*) – data frame of features
- `cluster` (*str*) – clusters that observations belong to
- `title` (*str*) – figure title

`visualize.evolution_of_severity_levels(df)`

Line chart of the amount of observations at relative severity levels

Parameters

- `df` (*DataFrame*) – data frame with sorted “severity” level column

`visualize.loading_plot(loadings, feature_names, bottom, top)`

Loading plot of features

Parameters

- `loadings` (*list*) – Relation of features to coordinates that are created by two principal components
- `feature_names` (*List [str]*) – list of feature names corresponding to their loadings
- `bottom` (*float*) – lower limit of graph coordinates in x and y axes
- `top` (*float*) – upper limit of graph coordinates in x and y axes

`visualize.plot_all_knn(td_results, fd_results)`

Line chart of relationship of k-value to k-NN classifier accuracy

Parameters

- `td_results` (*Dict [str, float]*) – lists of k-values and accuracies for time-domain features in training and testing set
- `fd_results` (*Dict [str, float]*) – lists of k-values and accuracies for frequency-domain features in training and testing set

`visualize.plot_cumulative_explained_variance(td_variance, fd_variance)`

Line chart of relationship of number of principal components to total explained variance

Parameters

- `td_variance` (*array*) – Explained variances for time-domain features
- `fd_variance` (*array*) – Explained variances for frequency-domain features

`visualize.plot_label_occurrences(y)`

Line chart of counters for classes in incremental learning

Parameters

- `y` (*Series*) – sorted labels of observations

```
visualize.plot_models_performance_bar(results)
```

Bar chart of feature selection accuracy comparison

Parameters

results (*DataFrame*) – training and testing accuracies of seven feature selection methods in both source domains

```
visualize.project_classes(X, Y, size=(10, 8), boundary=False, model_name='knn', pc=None)
```

Scatter plot of two principal components of data points in feature space

Parameters

- **X** (*DataFrame*) – data frame of features
- **Y** (*DataFrame*) – labels of observations
- **size** (*tuple*) – figure size
- **boundary** (*bool*) – show decision boundary for k-NN model with 5 neighbours
- **model_name** (*str*) – name of the machine learning model to evaluate. Options are: “knn”, “lda”, “bayes”, “svm”
- **pc** (*int*) – number of principal components

```
visualize.project_classes_3d(X, Y, size=(15, 6))
```

Scatter plot of three principal components of data points in feature space shown in planar cross-sections through coordinate axes

Parameters

- **X** (*DataFrame*) – data frame of features
- **Y** (*DataFrame*) – labels of observations
- **size** (*tuple*) – figure size

```
visualize.project_classifier_map_plot(X, y_true, y_predict)
```

Scatter plots of two principal components from data points that shows mistakes in prediction versus true labels

Parameters

- **X** (*DataFrame*) – data frame of features
- **y_true** (*Series*) – true labels of observations
- **y_predict** (*Series*) – predicted labels of observations

```
visualize.scatter_classif(X, y_label, categories, colors, ax)
```

Scatter plot of data points with color based on their labels

Parameters

- **X** (*DataFrame*) – data frame of features
- **y_label** (*Series*) – labels of observations
- **categories** (*List [str]*) – list of unique classes
- **colors** (*List [str]*) – list of colors for classes
- **ax** – subplot axis

```
visualize.scatter_features_3d(X, Y, features, size=(15, 5), boundary=False,
                             model_name='knn', power_transform=False)
```

Scatter plot of data points in 3D feature space shown in planar cross-sections through coordinate axes

Parameters

- `X (DataFrame)` – data frame of features
- `Y (DataFrame)` – labels of observations
- `features (list)` – names of three features to display
- `size (tuple)` – figure size
- `boundary (bool)` – show decision boundary for k-NN model with 5 neighbours
- `model_name (str)` – name of the machine learning model to evaluate. Options are: “knn”, “lda”, “bayes”, “svm”
- `power_transform (bool)` – apply power transform of features in preprocessing instead of normalization

```
visualize.scatter_features_3d_plot(X, Y, features, size=(8, 8), boundary=False,  
                                  model_name='knn', power_transform=False)
```

Three dimensional scatter plot of data points in feature space

Parameters

- `X (DataFrame)` – data frame of features
- `Y (DataFrame)` – labels of observations
- `features (list)` – names of three features to display
- `size (tuple)` – figure size
- `boundary (bool)` – show decision boundary for k-NN model with 5 neighbours
- `model_name (str)` – name of the machine learning model to evaluate. Options are: “knn”, “lda”, “bayes”, “svm”
- `power_transform (bool)` – apply power transform of features in preprocessing instead of normalization

PYTHON MODULE INDEX

e

extraction, 1

m

mafaulda, 6

models, 9

p

pumps, 13

r

ranking, 14

s

selection, 17

v

visualize, 17

A

`accuracies_to_table()` (in module *models*), 9
`all_features()` (in module *models*), 9
`assign_labels()` (in module *mafaulda*), 6
`assign_labels()` (in module *pumps*), 13

B

`batch_feature_ranking()` (in module *ranking*), 15
`beaglebone_measurement()` (in module *pumps*), 13
`bearing_frequencies()` (in module *mafaulda*), 6
 BEARINGS (in module *mafaulda*), 6
`best_columns()` (in module *ranking*), 15
 BEST_CORR (*ranking.ExperimentOutput* attribute), 14
 BEST_F_STAT (*ranking.ExperimentOutput* attribute), 14
 BEST_MI (*ranking.ExperimentOutput* attribute), 14
 BEST_SET (*ranking.ExperimentOutput* attribute), 14
`best_subset()` (in module *ranking*), 15
`boxplot_enumerate_models_accuracy()` (in module *visualize*), 17

C

`clean_columns()` (in module *mafaulda*), 6
`compute_correlations()` (in module *ranking*), 15
`corr_classif()` (in module *selection*), 17
 Correlation (class in *selection*), 17
 COUNTS (*ranking.ExperimentOutput* attribute), 14
`cross_cuts_3d_cluster()` (in module *visualize*), 18
`csv_import()` (in module *mafaulda*), 6
`csv_import()` (in module *pumps*), 13

D

`detrending_filter()` (in module *extraction*), 1
 DOMAIN_TITLES (in module *visualize*), 17
`downsample()` (in module *extraction*), 1

E

`energy()` (in module *extraction*), 1
`enumerate_models()` (in module *models*), 10
`envelope_signal()` (in module *extraction*), 1

`evolution_of_severity_levels()` (in module *visualize*), 18

`ExperimentOutput` (class in *ranking*), 14

`extraction`
 module, 1

F

FAULTS (in module *mafaulda*), 6
`feature_combinations()` (in module *models*), 10
`feature_selection_accuracies()` (in module *models*), 11
`features_by_domain()` (in module *mafaulda*), 7
`features_by_domain()` (in module *pumps*), 13
`features_by_domain_no_metadata()` (in module *pumps*), 14
`find_best_subset()` (in module *models*), 11
 FisherScore (class in *selection*), 17
`frequency_features_calc()` (in module *extraction*), 2
`fs_list_files()` (in module *extraction*), 2

G

`get()` (*selection.Correlation* method), 17
`get()` (*selection.FisherScore* method), 17
`get()` (*selection.MutualInformation* method), 17
`get_classes()` (in module *mafaulda*), 7
`get_classes()` (in module *pumps*), 14

H

`harmonic_series_detection()` (in module *extraction*), 2
`have_intersection()` (in module *extraction*), 2

K

`kfold_accuracy()` (in module *models*), 11
`knn_online_learn()` (in module *models*), 12

L

LABEL_COLUMNS (in module *mafaulda*), 6
 LABEL_COLUMNS (in module *pumps*), 13
`label_severity()` (in module *mafaulda*), 7
`list_files()` (in module *extraction*), 3
`load_features()` (in module *extraction*), 3
`load_files_split()` (in module *extraction*), 3
`load_source()` (in module *mafaulda*), 8
`loading_plot()` (in module *visualize*), 18

lowpass_filter() (*in module mafaulda*), 8

lowpass_filter_extract() (*in module mafaulda*), 8

M

mafaulda
module, 6

mark_severity() (*in module mafaulda*), 8

mms_peak_finder() (*in module extraction*), 3

model_boundaries() (*in module models*), 12

models
module, 9

module

extraction, 1

mafaulda, 6

models, 9

pumps, 13

ranking, 14

selection, 17

visualize, 17

MutualInformation (*class in selection*), 17

N

negentropy() (*in module extraction*), 4

O

online_feature_ranking() (*in module ranking*), 16

P

parse_filename() (*in module mafaulda*), 9

PCA (*ranking.ExperimentOutput attribute*), 14

pca_explained_variances() (*in module ranking*), 16

plot_all_knn() (*in module visualize*), 18

plot_cumulative_explained_variance() (*in module visualize*), 18

plot_label_occurences() (*in module visualize*), 18

plot_models_performance_bar() (*in module visualize*), 18

project_classes() (*in module visualize*), 19

project_classes_3d() (*in module visualize*), 19

project_classifier_map_plot() (*in module visualize*), 19

pumps
module, 13

R

ranking
module, 14

RANKS (*ranking.ExperimentOutput attribute*), 15

rpm_calc() (*in module mafaulda*), 9

S

SAMPLING_RATE (*in module mafaulda*), 6

SAMPLING_RATE (*in module pumps*), 13

scatter_classif() (*in module visualize*), 19

scatter_features_3d() (*in module visualize*), 19

scatter_features_3d_plot() (*in module visualize*), 20

SCORES_RANGE (*ranking.ExperimentOutput attribute*), 15

selection
module, 17

signal_to_noise() (*in module extraction*), 4

SILHOUETTE (*ranking.ExperimentOutput attribute*), 15

silhouette_scores() (*in module ranking*), 16

spectral_roll_off_frequency() (*in module extraction*), 4

spectral_transform() (*in module extraction*), 4

split_dataframe() (*in module extraction*), 4

T

temporal_variation() (*in module extraction*), 5

time_features_calc() (*in module extraction*), 5

transform_to_pca() (*in module models*), 12

U

update() (*selection.Correlation method*), 17

update() (*selection.FisherScore method*), 17

update() (*selection.MutualInformation method*), 17

V

visualize
module, 17

W

wavelet_features_calc() (*in module extraction*), 5