Robustness Studies — Results Reporting Template

Complete this once you have run the specifications set out in the registered preregistration, and submit it with your results file and your code. Specification-level results are not reported here; they are in the results file. This document covers what that file does not: how the study was run, what differed from the registered preregistration, and your own reading of the result.

1. Study

Analyst	Eli Talbert
Paper ID	ODMK
Date completed	13 November 2026
Preregistration approved on	7 November 2026

2. Materials submitted

- ☒ results_ODMK.csv, as set out in the Results File Specification
- ☒ Your code, as run

3. Execution

Software. What you used and its version, including any add-on packages the analysis relies on.

Python 3.14.4; pandas 3.0.2; NumPy 2.4.4; SciPy 1.17.1; and PyYAML 6.0.3. An independent baseline-only check used R 4.6.1 with survey 4.5, haven 2.5.5, and digest 0.6.39.

The run. Anything about how the specifications were run that a reader would need to interpret the results.

The analysis ran from clean public Git commit 0e796cbc4457020587c76ad39df906bfc37ecd66 using the hash-locked 2024-05-07 NCI HINTS 5 Cycle 2 Stata file. The code verified the approved registry and source-data hashes before opening the data, reproduced the published Table 2 anchors, and then ran the complete 2 × 2 × 2 × 2 design. Survey designs were created from the full 3,504-record file before restricting the focal domains. No random or iterative procedure was used.

Specifications run. The number of rows in the results file, which is the registered count less any combinations the preregistration excluded.

16. All registered combinations were run; none was excluded.

Rows where `status` is not `ok`. How many, and what happened.

0. Every row has status = ok.

4. Differences from the registered preregistration

- ☒ None — the study ran as registered
- ☐ Differences, described below

Some differences are expected. An option can prove unworkable once you run it, or a dimension can collapse once the data are in hand. What matters is that the record is accurate. For each, give the dimension or option, what changed, and why.

Dimension / option	What changed	Why
None	The study ran as registered.	Not applicable
—	—	—

5. Prior work with this paper or these data

Have you worked with either before beginning this robustness study — reproducing this same paper in the reproduction workflow, another study drawing on the same data source, or anything else that left you already familiar with them?

- ☐ Yes
- ☒ No

Where yes, say what that work was.

Not applicable. Before this robustness study, the analyst had not worked with this paper or HINTS 5 Cycle 2.

6. Analyst's assessment

- ☒ Robust
- ☐ Mixed
- ☐ Not robust

Say why, in your own words and using whatever criteria you consider relevant.

All 16 reasonable, preregistered specifications supported the same conclusion: Asian respondents reported lower patient-provider communication quality than non-Hispanic White respondents. The Asian-minus-White difference ranged from -0.351 to -0.280 points on the 1–4 scale. Every 95% confidence interval was below zero (the closest upper bound was -0.078). Standard errors ranged from 0.091 to 0.117, and two-sided p-values ranged from 0.000496 to 0.007659. The inclusive any-Asian definition produced the largest shift in magnitude, while the partial-item scoring rule changed the estimate very little. The variance method changed uncertainty, as expected, but not point estimates.

7. Notes and caveats

Anything else bearing on how these results should be read: ambiguities in the article, features of the source data, parts of the pipeline that resisted variation, apparent errors in the original that came to light while rebuilding it, or anything a reader of the results file would otherwise misinterpret.

The assigned result is the unadjusted Table 2 comparison, not the adjusted model in Table 3. The focal estimate is the survey-weighted Asian-minus-non-Hispanic-White PPPCQ mean difference. The published baseline used all five displayed race/ethnicity groups (N = 2,611); the COS results file's n_analytic field reports only respondents contributing to the focal two-group contrast (baseline: 105 Asian + 1,703 White = 1,808). Other records stayed in the full survey design object for variance estimation. The analysis used NCI's remediated 2024-05-07 public file, which reproduced the published Table 2 anchors. JK1 rows used 49 denominator degrees of freedom; Taylor rows used 98. The optional COS se_procedure, se_unit, and se_n_units fields are blank because each survey standard error was calculated directly by its registered estimator, not added later as a correction.