

User Guide for Busyness Manager

First-Time Setup:

- Define business information
 - Input:
 - Business ID: A whole number
 - Business name: A set of words
 - Business password: A sequence of letters
 - Business type: FNB or RETAIL (case-sensitive)

Features:

- Login
 - Requires business ID and password.
 - Subsequent features can be accessed after logging in.
- Viewing Help: `help`
 - Provides possible command instructions and expected formatting.
- Adding a Product: `add`
 - Adds a product to the products-for-sale list.
- Deleting a Product: `delete`
 - Removes a product from the products-for-sale list.
- Changing Info of Products: `update`
 - Updates data of a specified product in the products-for-sale list.
 - Data to be updated must be specified during command input.
- Printing List of Products: `print`
 - Prints the entire list of products for sale (according to product ID).
- Incrementing Sold Product Value, Decrementing Inventory Value: `sold`
 - Changes the quantity of available inventory and the quantity sold.
- Clear the Quantity Sold: `clear`
 - Changes the quantity sold of a specified product to 0.
- Compute Total Amount of Sale Transactions: `revenue`
 - Adds up all the products sold, multiplied by their respective prices.
 - Given a product ID, provides the revenue of a specified product.
- Search for a Product: `search`

- Given a product name, searches for the corresponding product.
- Given a product ID, searches for the corresponding product.

Command Summary:

IMPORTANT: Add a slash (/) in front of any tag.

Adding a Product

```
add /name P_NAME /qty P_QTY /price P_PRICE
```

- Creates a new product object & attaches different attributes to it (with an auto-generated ID).
- Tags:
 - `/name` → Name of the product to create.
 - `/qty` → Quantity of the product to create that is available for sale.
 - `/price` → Price of the product to create.

Example:

- Input -> `add /name MILK /qty 50 /price 2.50`
- Output -> `Product added: ID_0001: MILK | Qty: 50 | Sold: 0 | Price: $2.50`

Deleting a Product

```
delete /id P_ID
```

- Deletes a specified product with the given ID.
- Tags:
 - `/id` → ID of the product to delete (just the non-zero part will suffice).

Example:

- Input -> `delete /id 1`
- Output -> `Product removed: ID_0001: MILK | Qty: 50 | Sold: 0 | Price: $2.50`

Updating a Product

```
update /id P_ID /name NEW_NAME /qty NEW_QTY /price NEW_PRICE
```

- Changes one or more attributes of a specified product.

- Tags:
 - `/id` → ID of the product to modify (just the non-zero part will suffice).
 - `/name` → New name of the product to modify.
 - `/qty` → New quantity of the product to modify.
 - `/price` → New price of the product to modify.

Example:

- Input -> `update /id 1 /name FRESH_MILK /qty 45 /price 3`
 - Output -> `Product updated: ID_0001: FRESH_MILK | Qty: 45 | Sold: 0 | Price: $3.00`
-

Printing Product List

`print`

- Prints the current list of products.
- Attributes displayed:
 - Product ID
 - Product name
 - Quantity of product not sold
 - Quantity of product sold
 - Product price

Example:

- Input -> `print`
- Output -> `Product list: (next line) ID_0001: FRESH_MILK | Qty: 45 | Sold: 0 | Price: $3.00`

Format of Product List: `ID_NUMBER: PRODUCT_NAME | QTY | QTY_SOLD | PRICE`

Recording a Sale

`sold /id P_ID /qty QTY_SOLD`

- Changes the sales record and updates the inventory list.
- Tags:
 - `/id` → ID of the product that was sold (just the non-zero part will suffice).
 - `/qty` → Quantity of the product that was sold.

Example:

- Input -> `sold /id 1 /qty 5`
 - Output -> `Sales recorded: Product ID: ID_0001, Quantity Sold: 5`
-

Clearing Sold Quantity

`clear /id P_ID`

- Sets the quantity sold to zero for the specified product.
- Tags:
 - `/id` → ID of the product to clear (just the non-zero part will suffice).

Example:

- Input -> `clear /id 1`
 - Output -> `Sales cleared: Product ID: ID_0001`
-

Computing Revenue

`revenue` OR `revenue /id P_ID`

- Computes the total amount of revenue.
- Optional `/id` tag (to check revenue for a specific product).

Example (Overall Revenue):

- Input -> `revenue`
- Output -> `Revenue of FRESH_MILK: 15.00 (next line) Total Revenue: 15.00`

Example (Specific Product Revenue):

- Input -> `revenue /id 1`
 - Output -> `Revenue of FRESH_MILK: 15.00`
-

Searching for a Product

`search /name P_NAME`

- Returns the ID of the product that matches the given name.
- Tags:
 - `/name` → Name of product to search for.

Example:

- Input -> `search /name FRESH_MILK`
 - Output -> `Product ID of FRESH_MILK: ID_0001`
-

Searching for a Product by ID

`search /id P_ID`

- Returns the name of the product that matches the given ID.
- Tags:
 - `/id` → ID of the product to search for (just the non-zero part will suffice).

Example:

- Input -> `search /id 1`
- Output -> `Product name of ID_0001: FRESH_MILK`