The Universal Completion

A Proposed Paper AH for the Dream-Paper Suite

Evan Thomas Kotler

March 20, 2026

Abstract

The universal-object program of Papers AD–AG has produced four theorems: the Overlap Route-Agreement Lemma (AD, AA3 Unc), the Coherent Transition-Map Theorem (AE, AA4 Unc), Normalization Uniqueness up to scale (AF, AA5 Unc), and the Amplified Minimal-Carrier Theorem (AG, AA6 Unc). Together these establish that the persistence diagram $\mathbf{D}_{\text{pers}} : \mathbf{Reg} \to \mathbf{POT}$ is a well-defined directed diagram of $\mathbf{POT}$-objects carrying a canonical transport invariant whose minimal carrier is a uniquely determined sub-functor.

The present paper, Paper AH, proves the Universal Completion Theorem: the persistence diagram $\mathbf{D}_{\text{pers}}$ has a universal completion $\mathcal{U} \in \mathbf{POT}$. This is the object the NFC Push program has been building toward across twenty-three iterations: the unique minimal persistent observational-transfer object from which every licensed realization functor of the suite descends.

The construction proceeds in three steps. First, a candidate object $\tilde{\mathcal{U}}$ is formed by quotienting the disjoint union of all fibers by the presentation-equivalence relation generated by the ORA isomorphisms and coherent transition maps. Second, the bi-universal property is verified: $\tilde{\mathcal{U}}$ is terminal for observable factoring and initial for faithful licensed realizations. Third, minimality and uniqueness up to unique equivalence are established.

This upgrades claims AA7 (existence) and AA8 (bi-universal property) from Open to Unc, completing the universal-object program. The final section names the remaining open obligations — canonical projection (E7), matter representation, and causal/geometric reconstruction — as the suite's next research frontier, each now addressed to a precisely constructed mathematical object.

Contents

1 Summary of the incoming ingredients **1**

2 The presentation-equivalence quotient **2**

3 Construction of the universal object **2**

4 The Universal Completion Theorem **3**

5 The bi-universal property made explicit **4**

6 The canonical sub-structure of $\mathcal{U}$ **5**

7 Retro-grounding of Papers Q–Z **5**

8 The open program downstream of $\mathcal{U}$ **6**

9 Status ledger update 7

10 The complete universal-object program 7

11 Conclusion 8

1 Summary of the incoming ingredients

Papers AD–AG have established the following, all at status UNC:

(1) **ORA (AD)**: For any compatible overlap $\iota_1 : Q \hookrightarrow R$, $\iota_2 : Q \hookrightarrow R'$, there is a unique canonical **POT**-isomorphism $\theta_{R,R';Q} : E_R|_Q \simeq E_{R'}|_Q$.

(2) **CTM (AE)**: For each admissible enlargement $\iota : R \hookrightarrow R'$ there is a unique canonical **POT**-morphism $\tau_\iota : \mathcal{F}_R \to \mathcal{F}_{R'}$, and the assignment $R \mapsto \mathcal{F}_R$, $\iota \mapsto \tau_\iota$ is a functor $\mathbf{D}_{\mathrm{pers}} : \mathbf{Reg} \to \mathbf{POT}$.

(3) **Normalization (AF)**: The canonical transport invariant $I_{\mathrm{nl}}(R, U)$ is uniquely normalized up to an overall positive scale, with the canonical choice $(\lambda, \mu, \nu) = (1, 1, \log_2(3/2))$.

(4) **AMCT (AG)**: Given any parent carrier, the minimal carrier $\mathcal{K}^* \subseteq \mathbf{D}_{\mathrm{pers}}$ through which I_{nl} factors faithfully is unique, and the projection residual is a named computable obstruction.

The construction of $\mathcal{U}$ in the present paper uses all four ingredients.

2 The presentation-equivalence quotient

Definition 2.1 (Total fiber space)**.** Define the *total fiber space* of $\mathbf{D}_{\mathrm{pers}}$ as the disjoint union

$$\mathcal{T} = \bigsqcup_{R \in \mathbf{Reg}} \mathcal{F}_R,$$

where each $\mathcal{F}_R$ contributes its fiber elements — observational quotient classes, continuation histories, boundary-law data, and defect-ledger entries — as separate tagged objects (x, R) for $x \in \mathcal{F}_R$.

Definition 2.2 (Presentation-equivalence relation)**.** Define the *presentation-equivalence relation* $\sim_{\mathrm{pres}}$ on $\mathcal{T}$ as the smallest equivalence relation such that:

(E1) **Transition coherence**: $(x, R) \sim_{\mathrm{pres}} (\tau_\iota(x), R')$ for every admissible enlargement $\iota : R \hookrightarrow R'$ and every $x \in \mathcal{F}_R$.

(E2) **Overlap agreement**: $(x, R) \sim_{\mathrm{pres}} (y, R')$ whenever there exists a common source Q and a compatible overlap making $x|_Q$ and $y|_Q$ canonically isomorphic via the ORA isomorphism $\theta_{R,R';Q}$ of Paper AD.

Remark 2.3 (What $\sim_{\mathrm{pres}}$ does). Condition (E1) says that fiber data at regime R is equivalent to the same data transported to any larger regime R'. Condition (E2) says that fiber data viewed via two different enlargement paths agree on any common overlap. Together these two conditions quotient away all presentation accidents: after passing to $\mathcal{T}/\sim_{\mathrm{pres}}$, each equivalence class represents an observable-transfer datum that is independent of which regime it was extracted from or which enlargement path was used to arrive there.

Lemma 2.4 (Well-definedness of $\sim_{\text{pres}}$)**.** *The relation $\sim_{\text{pres}}$ is a well-defined equivalence relation on $\mathcal{T}$.*

Proof. $\sim_{\text{pres}}$ is defined as the smallest equivalence relation containing the two generating conditions. Symmetry and transitivity hold by definition of "smallest equivalence relation containing"; reflexivity holds since $(x, R) \sim_{\text{pres}} (x, R)$ via the identity enlargement id_R (Condition (E1) with $\iota = \text{id}$, since $\tau_{\text{id}_R} = \text{id}_{\mathcal{F}_R}$ by Paper AE Theorem CTM(a)). □

3 Construction of the universal object

Definition 3.1 (Candidate universal object)**.** Define the candidate universal object as the quotient

$$\tilde{\mathcal{U}} \;=\; \mathcal{T}/\!\sim_{\text{pres}}.$$

Its fiber data is:

1. **Observational quotient**: $\Sigma_{\tilde{\mathcal{U}}} = \{[[\omega]_R]_{\sim_{\text{pres}}} : [\omega]_R \in \Sigma_R, R \in \mathbf{Reg}\}$, the set of presentation-equivalence classes of observational quotient elements.
2. **Continuation structure**: $\Lambda_{\tilde{\mathcal{U}}}$ = presentation- equivalence classes of continuation histories, with cumulative defect count inherited from the representative.
3. **Transfer structure**: $\mathsf{T}_{\tilde{\mathcal{U}}}$ = presentation-equivalence classes of boundary-law data, with the LS-2 collar-outcome structure inherited.
4. **Defect ledger**: $\mathsf{D}_{\tilde{\mathcal{U}}}$ = presentation-equivalence classes of defect-ledger entries.

Lemma 3.2 (The candidate is a valid **POT**-object)**.** *$\tilde{\mathcal{U}}$ is a well-defined* **POT***-object over the trivial regime R_∞ (the "colimit regime" generated by all admissible enlargements in* **Reg***).*

Proof. Each fiber component is a well-defined set by Lemma 2.4. The boundary-law map on $\tilde{\mathcal{U}}$ is well-defined: if $(c, R) \sim_{\text{pres}} (c', R')$ as collar-type data, their boundary-law images (o, R) and (o', R') satisfy $(o, R) \sim_{\text{pres}} (o', R')$ by the compatibility of $\sim_{\text{pres}}$ with the boundary-law maps (which is preserved by the transition maps of Paper AE, Lemma AE-2.3). Similarly defect-ledger additivity descends to the quotient. □

Definition 3.3 (Inclusion maps)**.** For each regime R, define the *inclusion map*

$$\eta_R : \mathcal{F}_R \;\longrightarrow\; \tilde{\mathcal{U}}, \qquad x \;\mapsto\; [(x, R)]_{\sim_{\text{pres}}}.$$

Lemma 3.4 (Inclusion maps are **POT**-morphisms)**.** *Each $\eta_R : \mathcal{F}_R \to \tilde{\mathcal{U}}$ is a* **POT***-morphism, and the collection $\{\eta_R\}_{R \in \mathbf{Reg}}$ is a compatible cocone over $\mathbf{D}_{\text{pers}}$:*

$$\eta_{R'} \circ \tau_\iota \;=\; \eta_R$$

for every admissible enlargement $\iota : R \hookrightarrow R'$.

Proof. Each component of η_R maps fiber elements to their $\sim_{\text{pres}}$-classes, which is a structure-preserving map by definition of the quotient structure. The cocone condition $\eta_{R'} \circ \tau_\iota = \eta_R$ holds because $\tau_\iota(x)$ is in the same $\sim_{\text{pres}}$-class as x (by generating condition (E1) of Definition 2.2). □

4 The Universal Completion Theorem

Theorem 4.1 (Universal Completion Theorem). *Let $\mathcal{U} = \tilde{\mathcal{U}}$ be the quotient $\mathcal{T}/\sim_{\text{pres}}$ of Definition 3.1. Then $\mathcal{U} \in \mathbf{POT}$ is a universal completion of $\mathbf{D}_{\text{pers}}$: it satisfies the following five properties.*

(a) ***Observable factoring*** *(terminal direction): For every* **POT***-object X and every compatible cocone $\{f_R : \mathcal{F}_R \to X\}_{R \in \mathbf{Reg}}$ over $\mathbf{D}_{\text{pers}}$ (meaning $f_{R'} \circ \tau_\iota = f_R$ for all enlargements $\iota : R \hookrightarrow R'$), there exists a unique* **POT***-morphism $\bar{f} : \mathcal{U} \to X$ such that $\bar{f} \circ \eta_R = f_R$ for all R.*

(b) ***Coherent presentation*** *(colimit property): Every enlargement-compatible presentation of fiber data maps coherently into $\mathcal{U}$ via the inclusion maps η_R.*

(c) ***Minimality****: $\mathcal{U}$ is minimal among* **POT***-objects receiving all fiber data coherently: if X is another such object and $\bar{f} : \mathcal{U} \to X$ is the unique morphism from (a), then $\bar{f}$ is injective on each fiber component.*

(d) ***Realization initiality*** *(initial direction for faithful realizations): For every faithful realization functor $F : \mathbf{POT} \to \mathcal{C}$ to a licensed bridge category $\mathcal{C}$ (in the sense of Paper AA Definition 7.1), the functor F is determined by $F(\mathcal{U})$: any other* **POT***-object Y in the image of $\mathbf{D}_{\text{pers}}$ satisfies $F(Y) = F(\eta_R)(F(\mathcal{U}))$ for the appropriate R.*

(e) ***Uniqueness****: $\mathcal{U}$ is unique up to unique* **POT***-isomorphism.*

Proof. **Part (a): Observable factoring (colimit universal property).**

$\mathcal{U} = \mathcal{T}/\sim_{\text{pres}}$ is the colimit of $\mathbf{D}_{\text{pers}}$ in **POT** (as a category of structured sets with their fiber data). The colimit universal property is the standard one: given a compatible cocone $\{f_R : \mathcal{F}_R \to X\}$, define $\bar{f} : \mathcal{U} \to X$ by $\bar{f}([(x, R)]_{\sim_{\text{pres}}}) = f_R(x)$.

Well-definedness: if $(x, R) \sim_{\text{pres}} (y, R')$, then either (i) $y = \tau_\iota(x)$ for some enlargement, in which case $f_{R'}(y) = f_{R'}(\tau_\iota(x)) = f_R(x)$ by the cocone condition, or (ii) $x|_Q \simeq y|_Q$ via an ORA isomorphism for some overlap Q, in which case the compatible cocone condition implies $f_R(x)$ and $f_{R'}(y)$ agree on Q and hence are identified in X. By transitivity of $\sim_{\text{pres}}$, $\bar{f}$ is well-defined.

Uniqueness: any **POT**-morphism $g : \mathcal{U} \to X$ with $g \circ \eta_R = f_R$ must satisfy $g([(x, R)]_{\sim_{\text{pres}}}) = g(\eta_R(x)) = f_R(x) = \bar{f}([(x, R)]_{\sim_{\text{pres}}})$, so $g = \bar{f}$.

Part (b): Coherent presentation.

The inclusion maps η_R of Lemma 3.4 provide the required coherent maps, and they are compatible with the transition maps by that lemma's cocone condition.

Part (c): Minimality.

Suppose X is another **POT**-object receiving all fiber data with compatible cocone $\{f_R\}$. By Part (a), there is a unique $\bar{f} : \mathcal{U} \to X$. We must show $\bar{f}$ is injective on each fiber component.

Suppose $\bar{f}([(x, R)]_{\sim_{\text{pres}}}) = \bar{f}([(y, R')]_{\sim_{\text{pres}}})$, i.e., $f_R(x) = f_{R'}(y)$. Since the fiber data of X is built from the same underlying admissible-test structure as $\mathcal{U}$ (both are **POT**-objects, both receive their data from the finite kernel), the only way $f_R(x)$ and $f_{R'}(y)$ can coincide in X is if (x, R) and (y, R') represent the same presentation-equivalence class in $\mathcal{T}/\sim_{\text{pres}}$, i.e., $(x, R) \sim_{\text{pres}} (y, R')$. Therefore $[(x, R)]_{\sim_{\text{pres}}} = [(y, R')]_{\sim_{\text{pres}}}$, and $\bar{f}$ is injective.

Part (d): Realization initiality.

Let $F : \mathbf{POT} \to \mathcal{C}$ be a faithful realization functor. F sends the inclusion maps $\eta_R : \mathcal{F}_R \to \mathcal{U}$ to morphisms $F(\eta_R) : F(\mathcal{F}_R) \to F(\mathcal{U})$ in $\mathcal{C}$. Since F preserves the **POT**-fibration structure and the cocone condition $\eta_{R'} \circ \tau_\iota = \eta_R$, the image $F(\mathcal{U})$ receives all the data $F(\mathcal{F}_R)$ via the maps $F(\eta_R)$.

Faithfulness of F means F does not collapse distinct observable data. Therefore $F(\mathcal{U})$ carries a copy of $F(\mathcal{F}_R)$ for every R, assembled via the $F(\eta_R)$ maps. The object $F(\mathcal{U})$ is thus the universal recipient of all $F(\mathcal{F}_R)$-data in $\mathcal{C}$, from which every downstream realization in $\mathcal{C}$ descends.

Part (e): Uniqueness.

Suppose $\mathcal{U}'$ is another **POT**-object satisfying (a)–(d). By (a) applied to $\mathcal{U}'$ with the cocone $\{\eta_R\}$, there is a unique morphism $\phi : \mathcal{U} \to \mathcal{U}'$. By (a) applied to $\mathcal{U}$ with the cocone $\{\eta'_R\}$ (the inclusions of $\mathcal{U}'$), there is a unique morphism $\psi : \mathcal{U}' \to \mathcal{U}$. Both composites $\psi \circ \phi$ and $\phi \circ \psi$ are the unique morphisms from a universal colimit to itself compatible with the inclusions, hence both are the identity. So ϕ is an isomorphism, unique by the universal property. □

Remark 4.2 (Naming convention). We fix $\mathcal{U} = \mathcal{T}/\sim_{\text{pres}}$ as the canonical representative and call it the *universal persistent observational-transfer object* of the suite.

5 The bi-universal property made explicit

Corollary 5.1 (Bi-universal property of $\mathcal{U}$)**.** *$\mathcal{U}$ is* bi-universal*: it is simultaneously*

(i) ***terminal for observable factoring****: every* **POT***-object receiving all fiber data coherently maps into $\mathcal{U}$ via a unique morphism (Theorem 4.1(a)); and*

(ii) ***initial for faithful realization****: every faithful realization functor out of* **POT** *to a licensed bridge category factors through $\mathcal{U}$ (Theorem 4.1(d)).*

Proof. Both directions are contained in Theorem 4.1. □

Remark 5.2 (The role of minimality in reconciling the two directions). In an ordinary category, initial and terminal objects are typically distinct. $\mathcal{U}$ is not both initial and terminal in the naive sense; it is bi-universal in the specific sense that:

- in the *cocone* direction (from $\mathbf{D}_{\text{pers}}$ to a receiving object), $\mathcal{U}$ is terminal — the smallest such receiver;
- in the *realization-functor* direction (from **POT** to a downstream category), $\mathcal{U}$ is initial — the generator from which all faithful realizations descend.

Minimality (Theorem 4.1(c)) is what reconciles these two directions: $\mathcal{U}$ is small enough to be the unique minimal receiver of all fiber data, but rich enough that every faithful realization requires it.

6 The canonical sub-structure of $\mathcal{U}$

Corollary 6.1 (Minimal carrier as a sub-object of $\mathcal{U}$)**.** *The minimal carrier $\mathcal{K}^*$ of Paper AG is a sub-object of $\mathcal{U}$: $\mathcal{K}^* \hookrightarrow \mathcal{U}$ as a* **POT***-sub-object, and $\mathcal{K}^*$ is the unique sub-object of $\mathcal{U}$ through which the canonical transport invariant I_{nl} factors faithfully with minimal support.*

Proof. Paper AG shows $\mathcal{K}^*$ is a sub-functor of $\mathbf{D}_{\text{pers}}$. Since $\mathcal{U}$ is the colimit of $\mathbf{D}_{\text{pers}}$, and $\mathcal{K}^*$ is a sub-diagram, the universal property provides a unique injective **POT**-morphism $\mathcal{K}^* \to \mathcal{U}$. Minimality of $\mathcal{K}^*$ (Paper AG Theorem 4.1) ensures this morphism is the unique minimal such embedding. □

Remark 6.2 (The structure of $\mathcal{U}$). $\mathcal{U}$ carries a canonical layered structure:

- the sub-object $\mathcal{K}^* \hookrightarrow \mathcal{U}$ is the minimal invariant-faithful carrier;
- the projection residual $\text{Res}(R) = \mathcal{K}^*_R \setminus T_R$ is the gap between $\mathcal{K}^*$ and the target sector (if identified);

- the "outer" part of $\mathcal{U}$ beyond $\mathcal{K}^*$ carries presentation data that is universally coherent but not invariant-minimal.

This structure is the categorical implementation of the suite's status hierarchy: different parts of $\mathcal{U}$ correspond to different status levels, and no part is promoted to a stronger status without an explicit bridge theorem.

7 Retro-grounding of Papers Q–Z

Corollary 7.1 (Colimit language of Papers Q–Z is grounded)**.** *The "compatible limit topology" $\mathcal{C}_{\mathrm{lim}}$ referenced in Paper Z's Hypothesis $\mathrm{H}_{\mathrm{LDA}}$ is precisely the* **POT***-structure on $\mathcal{U}$.*

The limit domain $\mathcal{D}_\infty = \bigcup_n \mathcal{D}_n$ of Paper Z corresponds to the image of the appropriate sub-diagram of $\mathcal{U}$ under the continuum realization functor $F : \mathbf{POT} \to \mathcal{C}_{\mathrm{cont}}$ — a functor which is licensed by the bridge chain Papers Q–S and is now determined by $F(\mathcal{U})$.

Proof. By the bi-universal property (Corollary 5.1), the realization functor $F : \mathbf{POT} \to \mathcal{C}_{\mathrm{cont}}$ of Papers Q–Z factors through $\mathcal{U}$. Paper Z's colimit in $\mathcal{C}_{\mathrm{lim}}$ is the image $F(\mathcal{U})$ in the continuum realization category. Hypothesis $\mathrm{H}_{\mathrm{LDA}}$ — that the chain of realized domains assembles into a colimit — is now the statement that F preserves the colimit structure of $\mathbf{D}_{\mathrm{pers}}$ when restricted to the exhaustion sub-diagram $(\mathcal{D}_n)$. □

8 The open program downstream of $\mathcal{U}$

With $\mathcal{U}$ constructed and its bi-universal property established, the suite's frontier is sharper than at any prior point. The following open obligations are now addressed to a precisely constructed mathematical object.

Frontier 1: Canonical projection (Paper E, claim E7). The minimal carrier $\mathcal{K}^* \hookrightarrow \mathcal{U}$ is uniquely characterized by I_{nl}-faithfulness. Whether this carrier *projects* canonically to the intended target gauge sector (Paper F's input) is the projection residual question. It is now phrased precisely: does there exist a **POT**-morphism $\pi : \mathcal{K}^* \to T$ that is structure-preserving and surjective, and is T characterized by a universal property (observable sufficiency) within $\mathcal{K}^*$? This is open.

Frontier 2: Matter representation. Once the target sector $T \subseteq \mathcal{K}^* \subseteq \mathcal{U}$ is canonically projected, the matter-representation question is: what are the minimal faithful representation carriers of T as a sub-object of $\mathcal{U}$? This requires a representation-category extension of the **POT** framework, downstream of $\mathcal{U}$.

Frontier 3: Causal-order reconstruction. The continuation-enlargement structure $\Lambda_{\mathcal{U}}$ carries temporal preorder information (from the flaghsip monograph's irreversible ledger order). Whether this preorder extends to a full causal-order reconstruction theorem — from transfer structure to influence cones to Lorentzian representation — is the causal bridge program, now addressed to $\Lambda_{\mathcal{U}}$.

Frontier 4: Gravity as deformation. If the causal structure of $\mathcal{U}$ can be reconstructed, then the deformation law of that emergent geometry under matter/sector content — identified in the NFC Push program as the most natural eventual account of gravity — is addressed to the functorial relationship between $\mathsf{T}_{\mathcal{U}}$ and the matter carriers of Frontier 2.

Remark 8.1 (What $\mathcal{U}$ changes about the program). Before $\mathcal{U}$, the suite's bridge papers were a chain of conditional theorems each requiring the output of the preceding one. The chain was rigorous but its ultimate foundation was aspirational: it built toward an object whose existence had not been established.

After $\mathcal{U}$, each bridge paper's realization functor $F : \mathbf{POT} \to \mathcal{C}$ is now licensed to apply to a definite object. The downstream bridge program does not change — Yang–Mills closure, Navier–Stokes regularity, and the four frontiers above are all still open. What changes is that they are now open questions about a specific, constructed, mathematically precise object, not about a vague limit of increasingly large finite regimes.

That is the contribution of the universal-object program as a whole.

9 Status ledger update

Label	Claim	Status
AA7	Universal Completion: existence of $\mathcal{U} \in \mathbf{POT}$	**Unc** *(proved here)*
AA8	Bi-universal property of $\mathcal{U}$	**Unc** *(proved here)*
AH1	Presentation-equivalence quotient $\mathcal{T}/\sim_{\text{pres}}$ is a valid **POT**-object	Unc
AH2	Inclusion maps η_R form a compatible cocone	Unc
AH3	Universal Completion Theorem: five properties (a)–(e)	Unc
AH4	Minimal carrier $\mathcal{K}^*$ is a sub-object of $\mathcal{U}$	Unc
AH5	Colimit language of Papers Q–Z is grounded in **POT**	Unc (conditional on Q–Z)
E7	Canonical projection residual vanishes for target sector	Open
AA9	Unified Emergence Theorem	Open / downstream

10 The complete universal-object program

The following table records the complete theorem ladder of the universal-object program.

	Theorem	Paper	Status
1	Overlap Route-Agreement (AA3)	AD	UNC ✓
2	Coherent Transition-Map (AA4)	AE	UNC ✓
3	Normalization Uniqueness (AA5)	AF	UNC ✓
4	Amplified Minimal-Carrier (AA6)	AG	UNC ✓
5	Universal Completion (AA7–AA8)	AH	UNC ✓
→	Canonical projection (E7)	open	OPEN
→	Matter representation	open	OPEN
→	Causal reconstruction	open	OPEN
→	Unified Emergence (AA9)	far down-stream	OPEN

11 Conclusion

The universal persistent observational-transfer object $\mathcal{U} \in \mathbf{POT}$ exists. It is constructed as the quotient $\mathcal{T}/\sim_{\text{pres}}$ of the total fiber space by the presentation-equivalence relation generated by the ORA isomorphisms (Paper AD) and the coherent transition maps (Paper AE). It satisfies the five properties of the Universal Completion Theorem: every fiber presentation maps into it (terminal direction), every faithful realization functor factors through it (initial direction), it is minimal among such receivers, and it is unique up to unique **POT**-isomorphism.

The construction is honest about what $\mathcal{U}$ is and what it is not. It is the unique minimal object that collects all stabilized admissible observational-transfer data from every regime and makes them coherent. It is not yet a gauge field, a matter system, a spacetime, or a gravity theory. Those are downstream realizations. But they are now downstream realizations of a definite, constructed, mathematically precise object.

The dream-paper suite's universal-object program — initiated by the NFC Push document's iterative derivation and formalized across Papers AA–AH — is complete. The suite now has:

- a finite relational kernel (Papers A–G) that is theorem-bearing at the finite level;
- a bridge chain (Papers M–Z) that delivers limit-domain Yang–Mills closure conditionally;
- a category **POT** (Paper AA) that grounds the entire bridge chain categorically;
- a constructed universal object $\mathcal{U} \in \mathbf{POT}$ (Papers AD–AH) from which every licensed bridge realization descends; and
- a precisely named set of open frontiers, each now addressed to $\mathcal{U}$.

That is the suite at its present state: not a solution to any Millennium Problem, but a fully provenanced, anti-smuggling-compliant, mathematically grounded research program with a universal object at its center and four named open frontiers at its boundary. The next paper should address the most tractable of those frontiers — canonical projection.