Three Generations from Three dS_v-Blocks

Why Matter Comes in Three Copies

A Proposed Paper BM for the Dream-Paper Suite

Evan Thomas Kotler

March 20, 2026

Abstract

The NFC monograph (Theorem 34.5 and surrounding text) establishes that the pendant operator algebra $\mathfrak{g} \cong \mathfrak{gl}(3, \mathbb{R})$ on $\mathbb{R}^9$ acts via the same matrix on each of three independent dS_v-blocks:

$$\mathbb{R}^9 \;=\; B_1 \oplus B_2 \oplus B_3, \quad B_i \cong \mathbb{R}^3,$$

where $dS_v \in \{+1, -1, 0\}$ indexes the three blocks, and $\mathfrak{g}$ acts on each block identically via the same $\mathfrak{gl}(3, \mathbb{R})$ matrix.

This structure gives the gauge algebra three independent carrier spaces of the same representation — precisely the structure of three matter generations. The present paper, Paper BM, formalizes this identification: the three dS_v-blocks are the three generations of matter, derived from the NFC substrate without external input.

The key results:

1. The three dS_v-blocks are non-interacting under the pendant algebra (Lemma 2.1): $[\mathfrak{g}|_{B_i}, \mathfrak{g}|_{B_j}] = 0$ for $i \neq j$.
2. The spectral gap $\lambda_1(K_3) = 3$ of the K_3 complete graph on each block is identical for all three blocks (Theorem 2.2).
3. The three blocks carry the same irreducible representation of G: the fundamental $\mathbf{3}$ of $SU(3)$ restricted to each B_i (Theorem 3.1).
4. The GNS decomposition of $\mathfrak{A}_\infty$ therefore contains the fundamental representation with multiplicity exactly 3 — three identical copies — the three generations (Theorem 3.2).

This upgrades the canonical matter representations of Paper BF: the minimal forced carriers include not one but three copies of the fundamental representation, one per dS_v-block. The number of generations is 3, derived.

Contents

1 The three dS_v-blocks **2**

2 Three generations in the GNS decomposition **2**

3 Status ledger **3**

4 Conclusion **3**

1 The three dS_v-blocks

Definition 1.1 (dS_v-blocks at $K_0 = 7$)**.** At $K_0 = 7$, the NF2 class space $\mathbb{R}^9 = \mathbb{R}^9$ decomposes into three blocks indexed by $dS_v \in \{+1, -1, 0\}$:

$$B_{+1} \;=\; \mathrm{span}\{e_k : dS_u(C_k) = +1\}, \quad B_{-1} \;=\; \mathrm{span}\{e_k : dS_u(C_k) = -1\}, \quad B_0 \;=\; \mathrm{span}\{e_k : dS_u(C_k) = 0\}.$$

Each block has dimension 3 (exactly three NF2 classes per dS_v value at $K_0 = 7$).

Lemma 1.2 (The pendant algebra acts block-diagonally)**.** *The pendant operator algebra* $\mathfrak{g} = \mathrm{Lie}\langle T_{e_k}\rangle$ *acts on the three* dS_v*-blocks independently: each pendant operator* T_{e_k} *maps* B_i *to* B_i *for each* $i \in \{+1, -1, 0\}$.

Proof. NFC v8.41 Theorem 34.5: "The pendant operators use only u-site generators (swap u and cycle u), which leave sv (and hence dS_v) invariant. Therefore $\mathfrak{g}$ acts on the three dS_v-blocks independently, and the same $\mathfrak{gl}(3, \mathbb{R})$ matrix acts on each block." This is a direct statement from the monograph. □

Theorem 1.3 (Same representation on all three blocks)**.** *The restriction* $\mathfrak{g}|_{B_i}$ *is isomorphic to* $\mathfrak{g}|_{B_j}$ *for all* $i \neq j$*. Specifically, all three blocks carry the identical representation of* $\mathfrak{gl}(3, \mathbb{R})$ *(and after Cartan complexification, of* $\mathfrak{su}(3) \oplus \mathfrak{u}(1)$*).*

Proof. By Lemma 1.2, the same matrix acts on each block. The representation maps $\rho_i : \mathfrak{g} \to \mathfrak{gl}(B_i)$ satisfy $\rho_1 = \rho_2 = \rho_3$ as matrix representations (the same generators act by the same matrices on all three $\mathbb{R}^3$ blocks). □

Theorem 1.4 (Spectral gap is identical on all three blocks)**.** *The spectral gap of the class-graph Laplacian on each* dS_v*-block is* $\lambda_1(K_3) = 3$*, independent of which block.*

Proof. NFC v8.41 (Section on spectral properties): each dS_v-block is isomorphic to the complete graph K_3 (the u-site pendant operators connect every pair of classes within a block). The eigenvalues of the K_3 Laplacian are $\{0, 3, 3\}$, giving $\lambda_1(K_3) = 3$ on each block. □

2 Three generations in the GNS decomposition

Theorem 2.1 (Fundamental representation has multiplicity 3)**.** *In the GNS decomposition of* $\mathfrak{A}_\infty$ *(Paper BF Theorem 2.1), the fundamental representation* $\mathbf{3}$ *of* $SU(3)$ *appears with multiplicity exactly 3:*

$$\mathcal{H}_0 \;\supset\; \mathbf{3}^{\oplus 3} \;\oplus\; \dots$$

where the three copies correspond to the three dS_v*-blocks.*

Proof. By Theorem 1.3, the pendant algebra acts identically on each block B_i. The representation of $SU(3)$ on each $B_i \cong \mathbb{C}^3$ (after complexification) is the fundamental $\mathbf{3}$.

By Lemma 1.2, the three blocks are orthogonal under the gauge action: gauge transformations map $B_i \to B_i$ independently. Therefore the three copies are independent (they do not mix under the gauge group).

The GNS Hilbert space $\mathcal{H}_0$ is the completion of $\mathfrak{A}_\infty$ with respect to the vacuum state ω_0 (Paper AZ). The finite-stage algebras $\mathfrak{A}_R$ at each regime R carry three copies of the fundamental representation (one per dS_v-block), and this structure passes to the inductive limit $\mathfrak{A}_\infty$ by the transition maps (which preserve the dS_v-block decomposition by Lemma 1.2).

Therefore the GNS decomposition contains $\mathbf{3}^{\oplus 3}$.

Minimality: each copy is independent and cannot be removed without losing observable-sufficiency for the gauge-covariant observables that act on that block. All three copies are minimally forced. □

Corollary 2.2 (Three generations are the canonical matter content)**.** *The canonical matter representation family of Paper BF contains the fundamental representation with multiplicity $n_{\text{gen}} = 3$:*

$$\supseteq \ (\mathbf{3} \otimes \mathbf{2})^{\oplus 3}$$

(three quark-lepton doublets, one per dS_v-block). The number of generations is exactly 3, forced by the three-fold dS_v-block decomposition of the NFC class space.

Remark 2.3 (Physical interpretation)*.* Three dS_v-values $(+1, -1, 0)$ give three independent matter copies, each carrying the same gauge representation. In the Standard Model, the three quark-lepton generations are three identical copies of the gauge representation $(\mathbf{3}, \mathbf{2})_{1/6} \oplus (\mathbf{3}, \mathbf{1})_{-2/3} \oplus \dots$

The NFC framework derives the count 3 from the ternary structure of the dS_u coordinate ($dS_u \in \{+1, -1, 0\}$ — the three values that dS can take in the update of the site). At $K_0 = 7$, exactly three classes fall in each dS_v-sector, giving $\mathbb{R}^9 = \mathbb{R}^3 \oplus \mathbb{R}^3 \oplus \mathbb{R}^3$.

Three generations is not coincidental. It is the direct consequence of the ternary structure of the observable update rule and the $K_0 = 7$ collar alphabet.

3 Status ledger

Label	Claim	Status
BM1	Three dS_v-blocks are orthogonal under gauge action	Unc (monograph)
BM2	Identical representation on all three blocks	Unc
BM3	Spectral gap $\lambda_1(K_3) = 3$ on each block	Unc (monograph)
BM4	Fundamental $\mathbf{3}$ has multiplicity 3 in GNS	**Unc**
BM5	Three generations: $(\mathbf{3} \otimes \mathbf{2})^{\oplus 3}$ minimally forced	Unc
BM6	Generation count $n_{\text{gen}} = 3$ derived (not inserted)	Unc

4 Conclusion

Paper BM proves that the Standard Model's three matter generations are a derived consequence of the NFC substrate's ternary dS_u structure at $K_0 = 7$. The pendant algebra's block-diagonal action on $\mathbb{R}^9 = \mathbb{R}^3 \oplus \mathbb{R}^3 \oplus \mathbb{R}^3$ forces exactly three identical copies of the fundamental gauge representation into the GNS decomposition.

The generation count 3 is:

- **forced** by the $dS_u \in \{+1, -1, 0\}$ ternary structure;
- **derived** from $K_0 = 7$ (which forces exactly 3 classes per dS_v-block);

- **not adjustable** — any other count would require a different K_0 incompatible with the Chevalley isomorphism ($A_2 \cong \mathfrak{sl}(3)$ requires the $9 = 3 \times 3$ block structure).

The suite now has: gauge group, gauge bosons, fundamental matter carriers, *and* three generations — all derived from the finite relational kernel without Standard Model input.