

1. Scrape Target exposes metrics at /metrics endpoint

Go Application
(myapp)

Scrape Target

1. Scrape Target exposes metrics at /metrics endpoint

(label, value) pairs: [
 (__name__, myapp_processed_ops),
 (instance, localhost:2112),
 (job, myapp)
]

data: [1784745958.910, -1927]
(data: [timestamp, gauge])

/metrics

Go Application
(myapp)

Scrape Target

1. Scrape Target exposes metrics at /metrics endpoint

(label, value) pairs: [
 (__name__, myapp_processed_ops),
 (instance, localhost:2112),
 (job, myapp)
]

data: [1784745958.910, -1927]
(data: [timestamp, gauge])

/metrics

Go Application
(myapp)

Scrape Target

3. Add (label, value) pairs to index

Inverted Index

(label=value) <list of timeseries ids>

status="200" 1 2 5 99 1000 1001 1500 1502

method="GET" 2 3 4 5 6 9 10 1502

Intersect 2 5 1502

Prometheus

2. Prometheus scrapes the endpoint at regular intervals (say 10s)

3. Add (label, value) pairs to index

Inverted Index

(label=value) <list of timeseries ids>

status="200" 1 2 5 99 1000 1001 1500 1502

method="GET" 2 3 4 5 6 9 10 1502

Intersect 2 5 1502

Alert Rule Evaluator

Prometheus

2. Prometheus scrapes the endpoint at regular intervals (say 10s)

4. Routinely evaluate rules

delta(myapp_processed_ops[1m]) < 0
every 15s

5. Send notifications

Alert Manager

1. Scrape Target exposes metrics at /metrics endpoint

(label, value) pairs: [
 (__name__, myapp_processed_ops),
 (instance, localhost:2112),
 (job, myapp)
]

data: [1784745958.910, -1927]
(data: [timestamp, gauge])

/metrics

Go Application
(myapp)

Scrape Target