

---

# Index

- $\epsilon$ -decreasing strategy, 163
- $\epsilon$ -first strategy, 163
- $\epsilon$ -greedy strategy, 163
- $k$ -shot learning, 225
- $n$ -way  $k$ -shot learning, 225, 239
  
- A3R, 31
- absorption, 287
- abstract operators, 132
- acquisition function, 110
- active testing (AT), 93
- adaptive batch classifiers, 203
- adaptive capping, 108
- adaptive dataset similarity, 117
- adaptive ensembles, 203
- adequacy of configuration spaces, 146
- aggregate functions, 278
- aggregate operator
  - in Rapid Miner, 279
- aggregating data, 278
- AI planning, 131
- algorithm
  - configuration (AC), 104
  - recommendation, 19
  - selection, 19
- algorithm recommendation
  - for data streams, 201
- algorithm selection, 77
- ALMA, 196
- AlphaD3M system, 136
- approximate ranking trees (ARTs), 93
- AR\*, 32
- arbitrating, 182
- ART forests, 93
  
- ART trees, 93
- attentive recurrent comparators, 241, 247
- Auto-WEKA
  - parameter space, 127
- Automated Statistician, 279
- automatic feature construction
  - in DNNs, 288
- automatic machine learning (AutoML), 104
- automating
  - data preprocessing, 274
  - data science, 269
  - report generation, 279
  - the design of complex systems, 283
  - workflow design, 123
- AutoML, 104
- average ranking, 27
  
- bagging, 170
- base-level operators, 132
- batch-incremental classifiers, 203
- best classifier on last interval, 209, 210
- best-first search, 107
- bias
  - control, 155
  - domain-specific, 155
  - weak/strong, 155
- bias vs. variance in metalearning, 231
- Blast, 209, 210
- Boltzmann exploration, 163
- boosting, 172
- bounds
  - for domain adaptation, 231
  - on generalization error, 229

- using algorithmic stability, 230
- budget, 24
- business problem, 270
- cascade generalization, 175
- cascading, 177
- CASH, 104
- catastrophic forgetting, 226
- CHADE, 196
- changing the granularity of representation, 278
- characterizing diversity, 159
  - by correlation of rankings, 159
- choice of base-classifiers, 213
- CITRUS, 136
- class overlap, 59
- class separability, 59
- classification models at meta-level, 83
- classifier output difference (COD), 153, 193, 213
- classifiers
  - adaptive, 203
  - batch-incremental, 203
- clause structure grammar, 290
- cleaning, 277
- clustering trees, 81
- CMA-ES, 107
- COD, 153, 213
- cold-start problem, 113
- combined algorithm selection and hyperparameter optimization (CASH), 104
- combined measure, 31
- combining
  - accuracy and time, 31
- combining base-learners, 169
- competence region, 195
- complete metadata, 159
- concept drift, 202
  - detector, 215
- conditional hyperparameter, 103, 145
- conditional neural processes, 241, 255
- conditional operators, 285
- configuration space, 144
  - continuous, 145
  - discrete, 145
- configuration spaces, 98, 143
  - adequacy, 146
  - principles of constitution, 147
  - reduction, 151
- constructive induction, 286
- context-free grammars (CFGs), 128
  - induction, 130
  - limitations, 130
- contextual-bandit problem, 164
- continuous configuration space, 145
- control layer
  - in two-layered architecture, 215
- controlling
  - bias, 155
- cuboids, 279
- data
  - characteristics, 53
  - preprocessing, 274
  - science, 269
  - transformation, 275
- data characterization
  - algorithm-specific, 68
  - dynamic, 68
  - in clustering, 63
  - in regression tasks, 60
  - in time series prediction, 62
  - in unsupervised learning, 63
  - iterative, 68
  - task-dependent, 54
  - useful for ranking pairs of algorithms, 69
- data envelopment analysis, 33
- data preprocessing
  - cleaning, 277
  - instance selection, 277
  - outlier elimination, 277
- data stream, 201
  - ensembles, 210
- data wrangling, 275
- dataset, 25
  - repositories, 157, 298
  - segmentation, 158
  - similarity, 25, 34
  - variants, 157
- datasets
  - 2D footprints, 158
  - synthetic, 157
  - which are needed?, 156
  - with discriminatory power, 158
- DEA, 33
- declarative bias, 125
- default settings, 104
- defining

- abstract operators, 289
- configuration space, 125
- delegating, 180
- descriptors of learning goals, 273
- discounted cumulative gain (DCG), 51
- discrete configuration space, 145
- DM processes, 123
- domain-specific
  - metafeatures, 271
- double-loop architecture, 225
- drift detection, 207
  - metafeatures, 207
- drift detector
  - ADWIN, 207
  - DDM, 207
- drill down/up, 278
- dynamic
  - algorithm selection, 205
  - classifier selection, 190, 195
  - data characterization, 68
  - selection of models, 195
- empirical risk, 228
- ensemble learning, 189
  - generation, 192
  - integration, 195
  - iterative process, 193
  - phases, 192
  - pruning, 192
- ensemble of surrogate models (SGPT), 116
- ensemble recommendation
  - by ensemble learning, 192
  - by selection, 191
- ensembles
  - accuracy-weighted, 214
  - adaptive, 203
  - for data streams, 210
  - heterogeneous, 191
  - hierarchical, 197
  - homogeneous, 191
  - in Auto-sklearn, 195
- ensembles of algorithms, 169
- entropy search, 111
- error correlation, 153
- establishing hyperparameter importance, 149
- evaluation, 30
  - by correlation, 45
  - of rankings, 30, 39
  - of recommendations, 39
- evolutionary computation (EC), 197
- evolutionary search, 107
- expected improvement (EI), 111
- expected loss, 228
- experiment design, 118
- explainability, 284
- fading factors, 211
- faithful symbolic model, 284
- feature drift, 213
- feature-based transfer learning, 222
- few-shot learning, 240
- Flashfill wrangler, 277
- folding and unfolding, 287
- FOOFAH wrangler, 276
- Friedman's test, 50
- functional transfer, 221
  - in neural networks, 223
- Gaussian mixture model (GMM), 159
- Gaussian processes (GPs), 80, 111
  - with multi-kernel learning (MKL-GP), 115
- goal dependency networks (GDN), 273
- golden standard, 46
- gradient descent, 108
- granularity of representation, 285
- graph neural networks, 241, 246
- grid search, 105
- Hasse diagrams, 20
- heterogeneous ensembles, 191
- heuristic ranker, 128
- heuristic search methods, 107
- hierarchical ensembles, 197
  - generation, 197
- hierarchical planning, 132
  - abstract operators, 132
  - base-level operators, 132
  - HTN planning, 133
  - ML-Plan, 133
- hill climbing, 107
- Hoeffding bound, 203
- Hoeffding tree, 203
- homogeneous ensembles, 191
- homogeneous transfer, 221
- HTN planning, 133, 289
- Hyperband, 109
- hypergradients, 108

- hyperparameter
  - categorical, 103
  - conditional, 103
  - numeric, 103
  - optimization (HPO), 104
- hyperparameter importance, 148
  - ablation analysis, 148
  - forward selection, 148
  - functional ANOVA, 148
- hyperparameter log-scale, 145
- hyperparameters
  - establishing importance, 149
- identifying the domain-specific
  - background knowledge, 273
  - data, 273
- identifying the task domain, 272
  - by classification, 273
  - by matching descriptors, 272
- incomplete metadata, 159
  - effects, 162
  - using estimates, 161
- inductive logic programming (ILP), 274, 288
- initialization
  - of configuration, 113
- inner loop, 225
- input warping, 145
- instance selection, 277
- instance-based transfer learning, 222
- Intelligent Discovery Assistant (IDA), 126
- inter-construction, 288
- interplay between subsymbolic and symbolic models, 284
- interval estimation strategy, 164
- interval of confidence, 22
- introducing new concepts, 285
  - autonomously, 286
  - by clustering, 286
  - from external sources, 285
- introduction of new concepts
  - absorption, 287
  - folding and unfolding, 287
  - inter-construction, 288
  - propositionalization, 288
- invariant transformations, 224
- iterated local search, 108
- iterative data characterization, 68
- iterative learning, 290
- iterative pairwise tests, 90
- KDD process, 124, 270
- Kendall's Tau correlation, 46
- kernel density estimation, 112
- landmarkers, 84
  - in ensemble learning, 197
- latent embedding optimization, 261
- layered learning, 289
- learning
  - $k$ -shot, 225
  - inter-dependent tasks, 292
  - multi-task, 223
  - nested, 225
  - rankings, 115
  - similarity, 225
  - with recurrent neural networks, 226
- learning goals, 272
  - schedule, 272
- learning similarity, 225
- learning-to-learn, 219, 229
- loose accuracy, 50
- loss curve, 31, 47
- loss-time curve, 49
- LSTM optimizer, 241, 257
- macro-operators, 136
- marginal, 149
- marginal contribution, 195
  - of algorithms, 148
  - Shapley value, 148
  - to performance, 148
- matching descriptors (metafeatures), 272
- matching networks, 241, 245
- median rank, 26
- memorization problem, 263
- memory-augmented neural networks, 226, 241, 249
- meta networks, 241, 251
- meta-decision trees, 183
- meta-level performance, 208
- meta-model, 24
  - instance-based (IBL), 80
  - regression-based, 78
- Meta-SGD, 261
- MetaBags, 196
- metadata, 24
  - complete, 159
  - incomplete, 159
  - repositories, 297
- metadistribution, 229

- metafeature-based approaches, 205
- metafeatures, 34, 53
  - aggregated, 65
  - complexity-based, 58
  - concept variation, 58
  - domain-specific, 271
  - in ensemble learning, 194
  - information-theoretic, 56
  - landmarker sets, 58
  - landmarkers, 57
  - model-based, 56
  - relational representation, 69
  - relative landmarks, 57
  - selection, 67
  - simple, 55
  - statistical, 55
  - subsampling landmarks, 58
- metalearning, 219, 225
  - approaches, 19
  - in ensemble construction, 189
  - in ensemble learning, 189, 195
  - metric-based, 237, 240, 241, 248, 263
  - model-based, 237, 241, 248, 255, 263
  - optimization-based, 237, 241, 256, 263
- metalearning approaches, 77
- metaparameter, 225
- MiningMart, 136
- ML-Plan, 133
- MOA framework, 213
- model, 24
  - meta-level, 24
- Model inference system (MIS), 290
- model-agnostic meta-learning, 241, 259
- model-based
  - metafeatures, 56
- Monte Carlo tree search (MCTS), 136
- multi-armed bandits (MAB), 162
- multi-criteria analysis, 33
- multi-fidelity techniques, 108
- multi-task learning, 223, 227
- multitarget prediction, 81
- Naive AutoML, 136
- negative transfer, 220
- Nemenyi test, 50
- nested learning, 225
- non-homogeneous transfer, 221
- non-propositional approaches, 98
- non-stationarity, 202
- normalizing performance, 42, 80
- obtaining data, 273
  - by planning, 273
  - from different sources, 274
  - from OLAP data cube, 274
- OLAP data cube, 274, 278
- online
  - bagging, 204
  - boosting, 204
  - learning, 202
  - MAML, 203
- ontologies, 126, 289
  - DM ontology of Intelligent Discovery Assistant (IDA), 126
  - shortcomings, 127
- OpenAI Gym, 299
- OpenML, 297, 299
  - dataset characteristics, 299
  - datasets, 299
  - flows, 301
  - integration in Python, 305
  - integration in R, 303
  - integration in Weka, 303
  - runs, 302
  - setups, 302
  - tasks, 300
- operators, 131
  - abstract, 132
  - base-level, 132
  - conditional, 285
  - manual selection, 131
  - post-conditions/effects, 132
  - preconditions, 132
  - repeat, 285
- optimistic reward estimate, 164
- order of experiments
  - does it matter?, 162
  - multi-armed bandits, 162
  - sequential model-based optimization, 162
- outer loop, 225
- outlier elimination, 277
- pairwise comparisons of algorithms, 83
- parameter-based transfer learning, 222
- partial
  - learning curves, 85
  - ranking, 90
- PCC-DES, 196
- performance, 22
  - aggregation, 26

- comparable, 22
- high-performance regions, 117
- loss, 47
- metadata, 24
- models, 80
- normalization, 80
- planning
  - exploiting metaknowledge, 135
- plans, 284
- portfolio, 144
  - characterizing diversity, 159
  - of algorithms, 191
  - of ensemble elements, 191
  - of successful workflows, 137
  - reduction, 151
- pricing strategies (POKER), 164
- probability matching strategy, 163
- probability of improvement (PI), 111
- problem
  - description, 270
  - understanding, 270
- procedural bias, 128
- programmatic access to datasets, 298
- propositionalization, 288
- prototypical networks, 246
- Q-statistic, 193
- quantile regression, 117
- quantile regression forest (QRF), 117
- query set, 240
- random forests (RFs), 80
  - as surrogate models, 112
- random search, 106
- rank correlation
  - Spearman's, 46
  - weighted, 47
- ranking, 20
  - accuracy, 46
  - average, 27
  - complete, 20
  - evaluation, 30
  - incomplete, 20, 34, 35
  - linear, 23
  - meta-model, 28
  - of successful plans (workflows), 136
  - partial, 20
  - quasi-linear (weak), 23
  - total, 20
- Rapid Miner
  - aggregate operator, 279
  - recommendation, 20
    - forms, 20
    - of algorithm, 20
    - of workflows (pipelines), 32
  - recurring meta-level models, 213
  - reducing
    - configuration spaces, 151
    - portfolios, 151
  - reduction
    - by envelopment curve, 154
  - reformulating
    - ontologies, 289
    - recursive definitions, 290
    - theories, 286
  - reformulation of theories
    - by specialization, 286
  - reinforcement learning optimizer, 241, 258
  - relation networks, 246
  - repeat operators, 285
  - report generation, 279
  - representation of goals, 273
  - representational transfer, 221
  - reproducibility, 298
  - reptile, 241, 261
  - rescaling, 42
  - reusing new concepts
    - in further learning, 289
    - to redefine ontologies, 289
  - reusing prior experiments, 298
  - reusing solutions, 289
  - Robot Scientist, 273
  - roll-up, 278
- schedule for learning goals, 272
- scheduling experiments, 162
  - $\epsilon$ -decreasing, 163
  - $\epsilon$ -first, 163
  - $\epsilon$ -greedy, 163
  - interval estimation strategy, 164
  - multi-armed bandits, 162
  - optimistic reward estimate, 164
  - pricing strategies (POKER), 164
  - probability matching, 163
  - SoftMax, 163
  - upper confidence bound (UCB), 164
- search
  - for the best workflow, 279
- search methods

- that exploit metaknowledge, 114
- selection
  - of preprocessing method, 278
  - of workflows, 278
- sequential model-based
  - optimization (SMBO), 110
  - search, 110
- SGPT, 116
- Shapley value, 148
- shifting window, 206
- Siamese neural networks, 241
- siamese neural networks, 244
- significant wins, 27
- similar learning curve, 86
- similarity
  - correlation-based, 70
  - cosine-based, 70
  - performance-based, 97
- similarity measures, 69
- simple neural attentive meta-learner, 241, 253
- SKILit, 290
- sliding window, 206
- SoftMax strategy, 163
- source domain, 220
- Spearman's rank correlation, 46
- SPegasos, 203
- stacking, 173
- statistical test, 22
- stochastic gradient descent (SGD), 108, 203, 226, 262
- stream classifiers, 213
- strong sufficiency, 274
- subsampling landmarks, 84
- successive halving, 108
- sum of wins and losses, 88
- supervised
  - learning, 238
  - metalearning, 238
- supervised transfer, 221
- support set, 240
- surrogate
  - collaborative tuning (SCoT), 115
  - model, 110
- SVM
  - effects of hyperparameters settings, 306
- SVMRank, 115
- SYNTH, 277
- Synth-a-Sizer wrangler, 277
- synthetic datasets, 157
- tabling, 136
- target domain, 220
- task
  - descriptor generation, 271
  - domain, 272
  - goals, 271
  - type, 271
- task embedding, 263
- task-dependent characterization, 54
- templates, 198
- top- $n$  strategy, 28
- TPOT, 133
- transfer
  - across tasks, 219
  - by clustering, 227
  - functional, 221
  - homogeneous, 221
  - in kernel methods, 227
  - in neural networks, 223
  - in parametric Bayesian models, 227
  - learning, 219, 220
  - negative, 220
  - non-homogeneous, 221
  - of knowledge, 219
  - representational, 221
  - supervised, 221
  - unsupervised, 221
- transfer acquisition function (TAF), 116
- transfer learning
  - feature-based, 222
  - instance-based, 222
  - parameter-based, 222
- transformation
  - of data, 274
- tree-structured Parzen estimator (TPE), 112
- Trifacta wrangler, 276
- true ranking, 46
- true risk, 228
- trusted AI, 284
- two-layered architecture
  - control layer, 215
- unsupervised transfer, 221
- upper confidence bound (UCB), 164
- upper confidence bounds (UCB), 111
- Vapnik–Chervonenkis (VC) dimension, 228
- version spaces, 154

warm-start strategy, 113

window size, 208

workflow design

    manual, 131

    using planning, 132

workflow/pipeline design, 123

workflows, 284

wrangling, 275

    Flashfill, 277

    FOOFAH, 276

    Synth-a-Sizer, 277

    Trifacta, 276