



96

89

73

100

Performance

Accessibility

Best Practices

SEO



Performance

Values are estimated and may vary. The [performance score is calculated](#) directly from these metrics. [See calculator.](#)



0–49



50–89



90–100



METRICS

[Expand view](#)

- First Contentful Paint

0.6 s

- Largest Contentful Paint

0.7 s

- Total Blocking Time

0 ms

- Cumulative Layout Shift

0.113

● Speed Index

96 89 73 100



Show audits relevant to: [All](#) [FCP](#) [LCP](#) [TBT](#) [CLS](#)

INSIGHTS

▲ Render-blocking requests — Est savings of 400 ms

Requests are blocking the page's initial render, which may delay LCP. [Deferring or inlining](#) can move these network requests out of the critical path. [FCP](#) [LCP](#) [Unscored](#)

☒ Show 3rd-party resources (3)

Cloudflare CDN Cdn	144.0 KiB	680 ms
...r128/three.min.js (cdnjs.cloudflare.com)	118.7 KiB	400 ms
...3.12.2/gsap.min.js (cdnjs.cloudflare.com)	25.3 KiB	280 ms
aesumpj.com 1st Party	25.8 KiB	80 ms
/css/style.css (aesumpj.com)	15.4 KiB	80 ms
/js/page-transition-v4.js (aesumpj.com)	10.4 KiB	
Google Fonts Cdn	1.5 KiB	220 ms
/css2?family=... (fonts.googleapis.com)	1.5 KiB	220 ms


▲ Font display — Est savings of 100 ms

URL	Transfer Size	Duration
aesumpj.com 1st Party		
/fonts/Anson.ttf (aesumpj.com)		100 ms

URL Est Savings

▲ Layout shift culprits

Layout shifts occur when elements move absent any user interaction. [Investigate the causes of layout shifts](#), such as elements being added, removed, or their fonts changing as the page loads. [CLS](#) [Unscored](#)



Merging Abstract Reality with Tech...

<div class="hero-overlay tilt-float">

0.112

...v24/tDbv2o-fl....woff2 (fonts.gstatic.com)

Web font

...v35/yMJRMllzd....woff2 (fonts.gstatic.com)

Web font

...v20/UcC73FwrK....woff2 (fonts.gstatic.com)

Web font



STUDIO

0.001

/fonts/Anson.ttf (aesumpj.com)


Web font



div#preloader > div.loader-content > div.loader-bar-container > div.loader-bar-glow

<div class="loader-bar-glow">


0.000



div#preloader > div.loader-content > div.loader-bar-container > div.loader-bar-glow

<div class="loader-bar-glow">

0.000



div#preloader > div.loader-content > div.loader-bar-container > div.loader-bar-glow

<div class="loader-bar-glow">

0.000

▲ Network dependency tree



[Avoid chaining critical requests](#) by reducing the length of chains, reducing the download size of resources, or deferring the download of unnecessary resources to improve page load. LCP

Unscored

Maximum critical path latency: 790 ms

Initial Navigation



Element

Layout shift

968973100

...v20/UcC73FwrK....woff2	(fonts.gstatic.com) - 390 ms, 47.83 KiB
...v35/yMJRMllzd....woff2	(fonts.gstatic.com) - 390 ms, 11.61 KiB
...v24/tDbv2o-fl....woff2	(fonts.gstatic.com) - 389 ms, 30.34 KiB
/js/3d-viewer.js	(aesumpj.com) - 363 ms, 1.23 KiB
/js/main.js	(aesumpj.com) - 242 ms, 8.58 KiB
/js/grid-distortion.js	(aesumpj.com) - 242 ms, 1.73 KiB
...r128/three.min.js	(cdnjs.cloudflare.com) - 191 ms, 118.67 KiB
...3.12.2/gsap.min.js	(cdnjs.cloudflare.com) - 191 ms, 25.33 KiB
/api/player.js	(player.vimeo.com) - 169 ms, 8.35 KiB
/js/page-transition-v4.js	(aesumpj.com) - 169 ms, 10.38 KiB

Preconnected origins

[preconnect](#) hints help the browser establish a connection earlier in the page load, saving time when the first request for that origin is made. The following are the origins that the page preconnected to.

Origin	Source
https://fonts.googleapis.com/	head > link <link rel="preconnect" href="https://fonts.googleapis.com">
https://fonts.gstatic.com/	head > link <link rel="preconnect" href="https://fonts.gstatic.com" crossorigin="">

Preconnect candidates

Add [preconnect](#) hints to your most important origins, but try to use no more than 4.

No additional origins are good candidates for preconnecting

Use efficient cache lifetimes — Est savings of 40 KiB

A long cache lifetime can speed up repeat visits to your page. [Learn more about caching.](#)

FCP LCP Unscored

Request	Cache TTL	Transfer Size
Vimeo Video		340 KiB
...js/player.module.js (f.vimeocdn.com)	14d	214 KiB
...js/vendor.module.js (f.vimeocdn.com)	14d	94 KiB

968973100

Improve image delivery — Est savings of 4,425 KiB

Reducing the download time of images can improve the perceived load time of the page and LCP. [Learn more about optimizing image size](#) FCP LCP Unscored

URL	Resource Size	Est Savings
aesumpj.com 1st Party	4,522.1 KiB	4,424.7 KiB
凱基銀行 2024 thumbnail 	/images/%E5%87%B1%E5%9F%BA%E9%8A%80%E8%A1%8C.png (aesumpj.com)	2,298.8 KiB 2,250.1 KiB
	Using a modern image format (WebP, AVIF) or increasing the image compression could improve this image's download size.	1,961.3 KiB
	This image file is larger than it needs to be (1920x1080) for its displayed dimensions (729x410). Use responsive images to reduce the image download size.	1,967.2 KiB
大金空調 100年 thumbnail 	/images/%E5%A4%A7%E9%87%91%E7%A9%BA%E8%AA%BF.png (aesumpj.com)	2,223.3 KiB 2,174.6 KiB
	Using a modern image format (WebP, AVIF) or increasing the image compression could improve this image's download size.	1,885.8 KiB
	This image file is larger than it needs to be (1920x1080) for its displayed dimensions	1,902.6 KiB

URL				Resource size	Est Savings
	96	89	73	100	

Optimize DOM size

A large DOM can increase the duration of style calculations and layout reflows, impacting page responsiveness. A large DOM will also increase memory usage. [Learn how to avoid an excessive DOM size](#). Unscored

Statistic	Element	Value
Total elements		271
DOM depth	div.skill-card > div.skill-icon > svg > circle <code><circle cx="20" cy="20" r="14" stroke="currentColor" stroke-width="1.5"></code>	10
Most children	 body.cyber-theme <code><body class="cyber-theme no-cursor"></code>	21

LCP breakdown

Each [subpart has specific improvement strategies](#). Ideally, most of the LCP time should be spent on loading the resources, not within delays. LCP Unscored

Subpart	Duration
Time to first byte	40 ms
Element render delay	300 ms



STUDIO
`<span class="word-studio glitch-studio" data-text="STUDIO">`

3rd parties

3rd party code can significantly impact load performance. [Reduce and defer loading of 3rd party code](#) to prioritize your page's content. Unscored

3rd party	Transfer size	Main thread time
fjoaledfpmneenckfbpdfhkmimnjocfa	0 KiB	60 ms
chrome-extension://fjoaledfpmneenckfbpdfhkmimnjocfa/csNotification.bundle.js	0 KiB	60 ms
Cloudflare CDN Cdn	144 KiB	18 ms

3rd party	Transfer	Main thread
	96	89
	73	100
cmehionkhpncndndgjdbohmhpeckk	0 KiB	2 ms
chrome-extension://cmehionkhpncndndgjdbohmhpeckk/contentscript.js	0 KiB	2 ms
Vimeo Video	80 KiB	2 ms
/api/player.js (player.vimeo.com)	8 KiB	2 ms
/video/213...-e9c1a19...-d_640?region=us (i.vimeocdn.com)	31 KiB	0 ms
/video/213...-b5df022...-d_640?region=us (i.vimeocdn.com)	29 KiB	0 ms
...video/117...json (vimeo.com)	6 KiB	0 ms
...video/117...json (vimeo.com)	6 KiB	0 ms
gmehookibnphigonphocphhcepbijeen	0 KiB	0 ms
chrome-extension://gmehookibnphigonphocphhcepbijeen/content.js	0 KiB	0 ms
Google Fonts Cdn	91 KiB	0 ms
...v20/UcC73FwrK....woff2 (fonts.gstatic.com)	48 KiB	0 ms
...v24/tDbv2o-fl....woff2 (fonts.gstatic.com)	30 KiB	0 ms
...v35/yMJRMllzd....woff2 (fonts.gstatic.com)	12 KiB	0 ms
/css2?family=... (fonts.googleapis.com)	1 KiB	0 ms

These insights are also available in the Chrome DevTools Performance Panel - [record a trace](#) to view more detailed information.

DIAGNOSTICS

 Reduce unused JavaScript — Est savings of 349 KiB 

Reduce unused JavaScript and defer loading scripts until they are required to decrease bytes consumed by network activity. [Learn how to reduce unused JavaScript](#). FCP LCP Unscored


URL	Transfer Size	Est Savings
VPN for Chrome: NordVPN proxy protection Chrome Extension	432.3 KiB	263.4 KiB
chrome-extension://fjoaledfpmneenckfbpdfhkmimnjocfa/csNotification.bundle.js	432.3 KiB	263.4 KiB
Cloudflare CDN Cdn	118.1 KiB	86.0 KiB

URL	Transfer	Est
	96	89
	73	100

Image elements do not have explicit `width` and `height`

Set an explicit width and height on image elements to reduce layout shifts and improve CLS.

[Learn how to set image dimensions](#) CLS Unscored

URL
aesumpj.com 1st Party
 header#main-nav > div.nav-left-wrap > a.logo > img.logo-img /images/LOGO_pj_BG_s.webp (aesumpj.com)
Unattributable
Aevum Studio Logo

Minify CSS — Est savings of 5 KiB

Minifying CSS files can reduce network payload sizes. [Learn how to minify CSS](#). FCP LCP

Unscored

URL	Transfer Size	Est Savings
aesumpj.com 1st Party	15.4 KiB	4.6 KiB
/css/style.css (aesumpj.com)	15.4 KiB	4.6 KiB

Minify JavaScript — Est savings of 13 KiB

Minifying JavaScript files can reduce payload sizes and script parse time. [Learn how to minify JavaScript](#). FCP LCP Unscored

URL	Transfer Size	Est Savings
aesumpj.com 1st Party	18.7 KiB	7.2 KiB

URL	Transfer	Est
	96	89
	73	100
/js/main.js (aesumpj.com)	8.5 KiB	3.0 KiB
Unattributable	33.9 KiB	6.0 KiB
chrome-extension://cmedhionkhpnakcndndgjdbohmhpcck/contentscript.js	33.9 KiB	6.0 KiB

■ Avoid enormous network payloads — Total size was 23,787 KiB






Large network payloads cost users real money and are highly correlated with long load times. [Learn how to reduce payload sizes.](#) Unscored

☒ Show 3rd-party resources (7)

URL	Transfer Size
Vimeo Video	16,224.6 KiB
...avf/4588a7d3-....mp4?pathsig=... (vod-adaptive-ak.vimeocdn.com)	4,199.3 KiB
...avf/4588a7d3-....mp4?pathsig=... (vod-adaptive-ak.vimeocdn.com)	4,135.7 KiB
...avf/4588a7d3-....mp4?pathsig=... (vod-adaptive-ak.vimeocdn.com)	3,797.1 KiB
...avf/4588a7d3-....mp4?pathsig=... (vod-adaptive-ak.vimeocdn.com)	3,780.0 KiB
...js/player.module.js (f.vimeocdn.com)	214.4 KiB
/video/213...-e9c1a19...-d?mw=2200&mh=1238&q=70 (i.vimeocdn.com)	98.1 KiB
aesumpj.com 1st Party	6,758.1 KiB
/images/%E5%87%B1%E5%9F%BA%E9%8A%80%E8%A1%8C.png (aesumpj.com)	2,300.2 KiB
/images/system_page.png (aesumpj.com)	2,233.3 KiB
/images/%E5%A4%A7%E9%87%91%E7%A9%BA%E8%AA%BF.png (aesumpj.com)	2,224.6 KiB
Cloudflare CDN Cdn	118.7 KiB
...r128/three.min.js (cdnjs.cloudflare.com)	118.7 KiB

○ Avoid non-composited animations — 7 animated elements found

Animations which are not composited can be janky and increase CLS. [Learn how to avoid non-composited animations](#) CLS Unscored

Element	Name
	968973100
	<::after>
Unsupported CSS Property: top	scrollAnim
	div.year-counter > div.digit-roller > div#digit-list > span.final-digit
Unsupported CSS Property: color	color
Unsupported CSS Property: text-shadow	text-shadow
	AEVUM STUDIO <h1 class="large-title">
Unsupported CSS Property: text-shadow	float3D
	div#preloader > div.loader-content > div.loader-bar-container > div#loader-bar <div class="loader-bar" id="loader-bar">
Unsupported CSS Property: width	loadProgress
	div#preloader > div.loader-content > div.loader-bar-container > div.loader-bar-glow <div class="loader-bar-glow">
Unsupported CSS Property: right	glowTrail
	div.hero-title-block > h1.large-title > span.word-studio > ::after <::after>
Unsupported CSS Property: clip	glitch-b
	div.hero-title-block > h1.large-title > span.word-studio > ::before <::before>

Element

Name

96

89

73

100

○ Avoid long main-thread tasks — 2 long tasks found



Lists the longest tasks on the main thread, useful for identifying worst contributors to input delay. [Learn how to avoid long main-thread tasks](#) TBT Unscored

☒ Show 3rd-party resources (1)

URL	Start Time	Duration
aesumpj.com 1st Party		57 ms
/js/page-transition-v4.js (aesumpj.com)	447 ms	57 ms
VPN for Chrome: NordVPN proxy protection Chrome Extension		50 ms
chrome-extension://fjoaledfpmneenckfbpdfhkmimnjocfa/csNotification.bundle.js	269 ms	50 ms

More information about the performance of your application. These numbers don't [directly affect](#) the Performance score.

PASSED AUDITS (13)

[Hide](#)

● Document request latency



Your first network request is the most important. [Reduce its latency](#) by avoiding redirects, ensuring a fast server response, and enabling text compression. FCP LCP Unscored

- ☒ Avoids redirects
- ☒ Server responds quickly (observed 39 ms)
- ☒ Applies text compression

● Duplicated JavaScript



Remove large, [duplicate JavaScript modules](#) from bundles to reduce unnecessary bytes consumed by network activity. FCP LCP Unscored

● Forced reflow



A forced reflow occurs when JavaScript queries geometric properties (such as `offsetWidth`)

96

89

73

100

☐ INP breakdown ^

Start investigating [how to improve INP](#) by looking at the longest subpart. Unscored

☐ LCP request discovery ^

[Optimize LCP](#) by making the LCP image discoverable from the HTML immediately, and avoiding lazy-loading Unscored

☒ Legacy JavaScript ^

Polyfills and transforms enable older browsers to use new JavaScript features. However, many aren't necessary for modern browsers. Consider modifying your JavaScript build process to not transpile [Baseline](#) features, unless you know you must support older browsers. [Learn why most sites can deploy ES6+ code without transpiling](#) FCP LCP Unscored

☒ Modern HTTP ^

HTTP/2 and HTTP/3 offer many benefits over HTTP/1.1, such as multiplexing. [Learn more about using modern HTTP](#) FCP LCP Unscored

☒ Optimize viewport for mobile ^

Tap interactions may be [delayed by up to 300 ms](#) if the viewport is not optimized for mobile. Unscored

head > meta

```
<meta name="viewport" content="width=device-width, initial-scale=1.0">
```

☒ Reduce unused CSS ^

Reduce unused rules from stylesheets and defer CSS not used for above-the-fold content to decrease bytes consumed by network activity. [Learn how to reduce unused CSS](#) FCP LCP Unscored

☐ User Timing marks and measures ^

Consider instrumenting your app with the User Timing API to measure your app's real-world

96 89 73 100

JavaScript execution time — 0.3 s

Consider reducing the time spent parsing, compiling, and executing JS. You may find delivering smaller JS payloads helps with this. [Learn how to reduce Javascript execution time.](#)

TBT Unscored

Show 3rd-party resources (1)

URL	Total CPU Time	Script Evaluation	Script Parse
aesumpj.com 1st Party	840 ms	242 ms	2 ms
/js/grid-distortion.js (aesumpj.com)	414 ms	163 ms	0 ms
/index.html (aesumpj.com)	358 ms	19 ms	2 ms
/js/page-transition-v4.js (aesumpj.com)	68 ms	59 ms	0 ms
Unattributable	149 ms	10 ms	0 ms
Unattributable	149 ms	10 ms	0 ms
VPN for Chrome: NordVPN proxy protection Chrome Extension	62 ms	33 ms	27 ms
chrome-extension://fjoaledfpmneenckfbpdfhkmimnjocfa/csNotification.bundle.js	62 ms	33 ms	27 ms

Minimizes main-thread work — 1.1 s

Consider reducing the time spent parsing, compiling and executing JS. You may find delivering smaller JS payloads helps with this. [Learn how to minimize main-thread work](#)

TBT Unscored

Category	Time Spent
Other	386 ms
Script Evaluation	312 ms
Style & Layout	263 ms
Rendering	105 ms
Script Parsing & Compilation	38 ms

96

89

73

100

● Page didn't prevent back/forward cache restoration

Many navigations are performed by going back to a previous page, or forwards again. The back/forward cache (bfcache) can speed up these return navigations. [Learn more about the bfcache](#) Unscored



Accessibility

These checks highlight opportunities to [improve the accessibility of your web app](#). Automatic detection can only detect a subset of issues and does not guarantee the accessibility of your web app, so [manual testing](#) is also encouraged.

CONTRAST

▲ Background and foreground colors do not have a sufficient contrast ratio.

Low-contrast text is difficult or impossible for many users to read. [Learn how to provide sufficient color contrast](#).

Failing Elements

凱基銀行 2024



body.cyber-theme

<body class="cyber-theme no-cursor">

大金空調 100年



body.cyber-theme



body.cyber-theme

<body class="cyber-theme no-cursor">

蘭諾 Lenor 衣物芳香豆



body.cyber-theme

<body class="cyber-theme no-cursor">

7-11 寶可夢 Pokémon



body.cyber-theme

<body class="cyber-theme no-cursor">

Available for commercial work worldwide.

<p class="footer-tagline">

AEVUM STUDIO TAIPEI, TAIWAN // APAC Available for commercial work worldwide. ...

<footer class="site-footer" id="contact">



body.cyber-theme

<body class="cyber-theme no-cursor">

Home

AEVUM STUDIO TAIPEI, TAIWAN // APAC Available for commercial work worldwide. ...

<footer class="site-footer" id="contact">



body.cyber-theme

<body class="cyber-theme no-cursor">

Portfolio Projects

AEVUM STUDIO TAIPEI, TAIWAN // APAC Available for commercial work worldwide. ...

<footer class="site-footer" id="contact">



body.cyber-theme

<body class="cyber-theme no-cursor">

Brand Story

AEVUM STUDIO TAIPEI, TAIWAN // APAC Available for commercial work worldwide. ...

<footer class="site-footer" id="contact">



body.cyber-theme

<body class="cyber-theme no-cursor">

Experiment



body.cyber-theme

<body class="cyber-theme no-cursor">

Games

AEVUM STUDIO TAIPEI, TAIWAN // APAC Available for commercial work worldwide. ...

<footer class="site-footer" id="contact">



body.cyber-theme

<body class="cyber-theme no-cursor">

eternalframePJ@gmail.com

<a href="#" class="footer-link"

onclick="navigator.clipboard.writeText('eternalframePJ@gmail.com'); alert('Copied t...">

AEVUM STUDIO TAIPEI, TAIWAN // APAC Available for commercial work worldwide. ...

<footer class="site-footer" id="contact">



body.cyber-theme

<body class="cyber-theme no-cursor">

ArtStation

AEVUM STUDIO TAIPEI, TAIWAN // APAC Available for commercial work worldwide. ...

<footer class="site-footer" id="contact">



body.cyber-theme

<body class="cyber-theme no-cursor">

Instagram

AEVUM STUDIO TAIPEI, TAIWAN // APAC Available for commercial work worldwide. ...

<footer class="site-footer" id="contact">



body.cyber-theme

<body class="cyber-theme no-cursor">

Vimeo

AEVUM STUDIO TAIPEI, TAIWAN // APAC Available for commercial work worldwide. ...

<footer class="site-footer" id="contact">



body.cyber-theme

<body class="cyber-theme no-cursor">

Open to freelance & studio collaboration.

<p class="footer-cta-text">

AEVUM STUDIO TAIPEI, TAIWAN // APAC Available for commercial work worldwide. ...

96

89

73

100

```
<body class="cyber-theme no-cursor">
```

© 2026 AEVUM STUDIO. All rights reserved.

```
<span class="footer-copy">
```

AEVUM STUDIO TAIPEI, TAIWAN // APAC Available for commercial work worldwide. ...

```
<footer class="site-footer" id="contact">
```



body.cyber-theme

```
<body class="cyber-theme no-cursor">
```

These are opportunities to improve the legibility of your content.

NAMES AND LABELS

▲ `<frame>` or `<iframe>` elements do not have a title



Screen reader users rely on frame titles to describe the contents of frames. [Learn more about frame titles.](#)

Failing Elements



main > section#hero > div.video-bg > iframe#hero-video

```
<iframe src="https://player.vimeo.com/video/1178407017?
```

```
background=1&autoplay=1&loop=1&b..." frameborder="0"
```

```
allow="autoplay; fullscreen" style="position: absolute; top: 50%; left: 50%; width: 100vw; height: 56.25vw;" id="hero-video" data-ready="true">
```

These are opportunities to improve the semantics of the controls in your application. This may enhance the experience for users of assistive technology, like a screen reader.

NAVIGATION

▲ Some elements have a `[tabindex]` value greater than 0



A value greater than 0 implies an explicit navigation ordering. Although technically valid, this often creates frustrating experiences for users who rely on assistive technologies. [Learn more about the tabindex attribute.](#)

These are opportunities to improve keyboard navigation in your application.

ADDITIONAL ITEMS TO MANUALLY CHECK (10)

Hide

- ☐ Interactive controls are keyboard focusable



Custom interactive controls are keyboard focusable and display a focus indicator. [Learn how to make custom controls focusable.](#) Unscored

- ☐ Interactive elements indicate their purpose and state



Interactive elements, such as links and buttons, should indicate their state and be distinguishable from non-interactive elements. [Learn how to decorate interactive elements with affordance hints.](#) Unscored

- ☐ The page has a logical tab order



Tabbing through the page follows the visual layout. Users cannot focus elements that are offscreen. [Learn more about logical tab ordering.](#) Unscored

- ☐ Visual order on the page follows DOM order



DOM order matches the visual order, improving navigation for assistive technology. [Learn more about DOM and visual ordering.](#) Unscored

- ☐ User focus is not accidentally trapped in a region



A user can tab into and out of any control or region without accidentally trapping their focus. [Learn how to avoid focus traps.](#) Unscored

- ☐ The user's focus is directed to new content added to the page



If new content, such as a dialog, is added to the page, the user's focus is directed to it. [Learn how to direct focus to new content.](#) Unscored

- ☐ HTML5 landmark elements are used to improve navigation



Landmark elements (<main>, <nav>, etc.) are used to improve the keyboard navigation of the page for assistive technology. [Learn more about landmark elements.](#) Unscored

Offscreen content is hidden from assistive technology

96 89 73 100

[hide onscreen content.](#) [Unscored]

Custom controls have associated labels

Custom interactive controls have associated labels, provided by aria-label or aria-labelledby. [Learn more about custom controls and labels.](#) [Unscored]

Custom controls have ARIA roles

Custom interactive controls have appropriate ARIA roles. [Learn how to add roles to custom controls.](#) [Unscored]

These items address areas which an automated testing tool cannot cover. Learn more in our guide on [conducting an accessibility review](#).

PASSED AUDITS (22)

Hide

[aria-*] attributes match their roles

Each ARIA role supports a specific subset of aria-* attributes. Mismatching these invalidates the aria-* attributes. [Learn how to match ARIA attributes to their roles.](#)

[aria-hidden="true"] is not present on the document <body>

Assistive technologies, like screen readers, work inconsistently when aria-hidden="true" is set on the document <body>. [Learn how aria-hidden affects the document body.](#)

[role]s have all required [aria-*] attributes

Some ARIA roles have required attributes that describe the state of the element to screen readers. [Learn more about roles and required attributes.](#)

Elements with an ARIA [role] that require children to contain a specific [role] have all required children.

Some ARIA parent roles must contain specific child roles to perform their intended accessibility functions. [Learn more about roles and required children elements.](#)

Some ARIA child roles must be contained by specific parent roles to properly perform their intended accessibility functions. [Learn more about ARIA roles and required parent element.](#)

● [role] values are valid ^

ARIA roles must have valid values in order to perform their intended accessibility functions. [Learn more about valid ARIA roles.](#)

● [aria-*) attributes have valid values ^

Assistive technologies, like screen readers, can't interpret ARIA attributes with invalid values. [Learn more about valid values for ARIA attributes.](#)

● [aria-*) attributes are valid and not misspelled ^

Assistive technologies, like screen readers, can't interpret ARIA attributes with invalid names. [Learn more about valid ARIA attributes.](#)

● Buttons have an accessible name ^

When a button doesn't have an accessible name, screen readers announce it as "button", making it unusable for users who rely on screen readers. [Learn how to make buttons more accessible.](#)

● Image elements have [alt] attributes ^

Informative elements should aim for short, descriptive alternate text. Decorative elements can be ignored with an empty alt attribute. [Learn more about the alt attribute.](#)

● [user-scalable="no"] is not used in the <meta name="viewport"> element and the [maximum-scale] attribute is not less than 5. ^

Disabling zooming is problematic for users with low vision who rely on screen magnification to properly see the contents of a web page. [Learn more about the viewport meta tag.](#)

Some ARIA attributes are only allowed on an element under certain conditions. [Learn more about conditional ARIA attributes.](#)

● `[aria-hidden="true"]` elements do not contain focusable descendents ^

Focusable descendents within an `[aria-hidden="true"]` element prevent those interactive elements from being available to users of assistive technologies like screen readers. [Learn how `aria-hidden` affects focusable elements.](#)

● Elements use only permitted ARIA attributes ^

Using ARIA attributes in roles where they are prohibited can mean that important information is not communicated to users of assistive technologies. [Learn more about prohibited ARIA roles.](#)

● Document has a `<title>` element ^

The title gives screen reader users an overview of the page, and search engine users rely on it heavily to determine if a page is relevant to their search. [Learn more about document titles.](#)

● `<html>` element has a `[lang]` attribute ^

If a page doesn't specify a `lang` attribute, a screen reader assumes that the page is in the default language that the user chose when setting up the screen reader. If the page isn't actually in the default language, then the screen reader might not announce the page's text correctly. [Learn more about the `lang` attribute.](#)

● `<html>` element has a valid value for its `[lang]` attribute ^

Specifying a valid [BCP 47 language](#) helps screen readers announce text properly. [Learn how to use the `lang` attribute.](#)

● Links have a discernible name ^

Link text (and alternate text for images, when used as links) that is discernible, unique, and

96

89

73

100

-
- Touch targets have sufficient size and spacing. ^

Touch targets with sufficient size and spacing help users who may have difficulty targeting small controls to activate the targets. [Learn more about touch targets.](#)

-
- Heading elements appear in a sequentially-descending order ^

Properly ordered headings that do not skip levels convey the semantic structure of the page, making it easier to navigate and understand when using assistive technologies. [Learn more about heading order.](#)

-
- Document has a main landmark. ^

One main landmark helps screen reader users navigate a web page. [Learn more about landmarks.](#)

-
- Deprecated ARIA roles were not used ^

Deprecated ARIA roles may not be processed correctly by assistive technology. [Learn more about deprecated ARIA roles.](#)

NOT APPLICABLE (35)

Hide

-
- `[accesskey]` values are unique ^

Access keys let users quickly focus a part of the page. For proper navigation, each access key must be unique. [Learn more about access keys.](#) Unscored

-
- `button`, `link`, and `menuitem` elements have accessible names ^

When an element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. [Learn how to make command elements more accessible.](#) Unscored

- ☐ Elements with `role="dialog"` or `role="alertdialog"` have accessible names. ^

96

89

73

100

[accessible.](#) Unscored

- ☐ ARIA input fields have accessible names ^

When an input field doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. [Learn more about input field labels.](#) Unscored

- ☐ ARIA `meter` elements have accessible names ^

When a meter element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. [Learn how to name meter elements.](#) Unscored

- ☐ ARIA `progressbar` elements have accessible names ^

When a progressbar element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. [Learn how to label progressbar elements.](#) Unscored

- ☐ Elements with the `role=text` attribute do not have focusable descendents. ^

Adding `role=text` around a text node split by markup enables VoiceOver to treat it as one phrase, but the element's focusable descendents will not be announced. [Learn more about the role=text attribute.](#) Unscored

- ☐ ARIA toggle fields have accessible names ^

When a toggle field doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. [Learn more about toggle fields.](#) Unscored

- ☐ ARIA `tooltip` elements have accessible names ^

When a tooltip element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. [Learn how to name tooltip elements.](#) Unscored

- ☐ ARIA `treeitem` elements have accessible names ^

When a `treeitem` element doesn't have an accessible name, screen readers announce it with

96

89

73

100

- ☐ The page contains a heading, skip link, or landmark region ^

Adding ways to bypass repetitive content lets keyboard users navigate the page more efficiently. [Learn more about bypass blocks.](#) Unscored

- ☐ `<d1>`'s contain only properly-ordered `<dt>` and `<dd>` groups, `<script>`, `<template>` or `<div>` elements. ^

When definition lists are not properly marked up, screen readers may produce confusing or inaccurate output. [Learn how to structure definition lists correctly.](#) Unscored

- ☐ Definition list items are wrapped in `<d1>` elements ^

Definition list items (`<dt>` and `<dd>`) must be wrapped in a parent `<d1>` element to ensure that screen readers can properly announce them. [Learn how to structure definition lists correctly.](#) Unscored

- ☐ ARIA IDs are unique ^

The value of an ARIA ID must be unique to prevent other instances from being overlooked by assistive technologies. [Learn how to fix duplicate ARIA IDs.](#) Unscored

- ☐ No form fields have multiple labels ^

Form fields with multiple labels can be confusingly announced by assistive technologies like screen readers which use either the first, the last, or all of the labels. [Learn how to use form labels.](#) Unscored

- ☐ `<html>` element has an `[xml:lang]` attribute with the same base language as the `[lang]` attribute. ^

If the webpage does not specify a consistent language, then the screen reader might not announce the page's text correctly. [Learn more about the lang attribute.](#) Unscored

- ☐ Input buttons have discernible text. ^

Adding discernable and accessible text to input buttons may help screen reader users understand the purpose of the input button. [Learn more about input buttons.](#) Unscored

- ☐ `<input type="image">` elements have `[alt]` text ^

When an image is being used as an `<input>` button, providing alternative text can help screen

96

89

73

100

-
- ☐ Form elements have associated labels ^

Labels ensure that form controls are announced properly by assistive technologies, like screen readers. [Learn more about form element labels.](#) Unscored

-
- ☐ Links are distinguishable without relying on color. ^

Low-contrast text is difficult or impossible for many users to read. Link text that is discernible improves the experience for users with low vision. [Learn how to make links distinguishable.](#) Unscored

-
- ☐ Lists contain only `<li>` elements and script supporting elements (`<script>` and `<template>`). ^

Screen readers have a specific way of announcing lists. Ensuring proper list structure aids screen reader output. [Learn more about proper list structure.](#) Unscored

-
- ☐ List items (`<li>`) are contained within `<ul>`, `<ol>` or `<menu>` parent elements ^

Screen readers require list items (`<li>`) to be contained within a parent `<ul>`, `<ol>` or `<menu>` to be announced properly. [Learn more about proper list structure.](#) Unscored

-
- ☐ The document does not use `<meta http-equiv="refresh">` ^

Users do not expect a page to refresh automatically, and doing so will move focus back to the top of the page. This may create a frustrating or confusing experience. [Learn more about the refresh meta tag.](#) Unscored

-
- ☐ `<object>` elements have alternate text ^

Screen readers cannot translate non-text content. Adding alternate text to `<object>` elements helps screen readers convey meaning to users. [Learn more about alt text for object elements.](#) Unscored

-
- ☐ Select elements have associated label elements. ^

Form elements without effective labels can create frustrating experiences for screen reader users. [Learn more about the select element.](#) Unscored

-
- ☐ Skip links are focusable. ^
-

Including a skip link can help users skip to the main content to save time. [Learn more about](#)

96

89

73

100

- ☐ Cells in a `<table>` element that use the `[headers]` attribute refer to table cells within the same table. ^

Screen readers have features to make navigating tables easier. Ensuring `<td>` cells using the `[headers]` attribute only refer to other cells in the same table may improve the experience for screen reader users. [Learn more about the headers attribute.](#) Unscored

- ☐ `<th>` elements and elements with `[role="columnheader"/"rowheader"]` have data cells they describe. ^

Screen readers have features to make navigating tables easier. Ensuring table headers always refer to some set of cells may improve the experience for screen reader users. [Learn more about table headers.](#) Unscored

- ☐ `[lang]` attributes have a valid value ^

Specifying a valid [BCP 47 language](#) on elements helps ensure that text is pronounced correctly by a screen reader. [Learn how to use the lang attribute.](#) Unscored

- ☐ `<video>` elements contain a `<track>` element with `[kind="captions"]` ^

When a video provides a caption it is easier for deaf and hearing impaired users to access its information. [Learn more about video captions.](#) Unscored

- ☐ Tables have different content in the summary attribute and `<caption>`. ^

The summary attribute should describe the table structure, while `<caption>` should have the onscreen title. Accurate table mark-up helps users of screen readers. [Learn more about summary and caption.](#) Unscored

- ☐ All heading elements contain content. ^

A heading with no content or inaccessible text prevent screen reader users from accessing information on the page's structure. [Learn more about headings.](#) Unscored

- ☐ Uses ARIA roles only on compatible elements ^

Many HTML elements can only be assigned certain ARIA roles. Using ARIA roles where they are not allowed can interfere with the accessibility of the web page. [Learn more about ARIA roles.](#) Unscored

- Image elements do not have `[alt]` attributes that are redundant text.



96

89

73

100

reader users, because the text will be read twice. [Learn more about the alt attribute.](#)

Unscored

- Identical links have the same purpose.



Links with the same destination should have the same description, to help users understand the link's purpose and decide whether to follow it. [Learn more about identical links.](#) Unscored



Best Practices

GENERAL

- ▲ Uses third-party cookies — 13 cookies found



Third-party cookies may be blocked in some contexts. [Learn more about preparing for third-party cookie restrictions.](#)

Name	URL
Vimeo Video	
vuid	/api/player.js (player.vimeo.com)
vimeo_gdpr_optin	/api/player.js (player.vimeo.com)
language	/api/player.js (player.vimeo.com)
has_uploaded	/api/player.js (player.vimeo.com)
joined_with_existing_account	/api/player.js (player.vimeo.com)
_gid	/api/player.js (player.vimeo.com)

Name	URL
	968973100
player	/api/player.js (player.vimeo.com)
_cfuvid	/api/player.js (player.vimeo.com)
redirect_url_after_social_join	/api/player.js (player.vimeo.com)
_ga	/api/player.js (player.vimeo.com)
vimeo	/api/player.js (player.vimeo.com)
__cf_bm	/api/player.js (player.vimeo.com)

▲ Browser errors were logged to the console ^

Errors logged to the console indicate unresolved problems. They can come from network request failures and other browser concerns. [Learn more about this errors in console diagnostic audit](#)

Source	Description
aesumpj.com 1st Party	
/js/main.js:531:23 (aesumpj.com)	TypeError: heroVideo?.play is not a function at https://aesumpj.com/js/main.js:531:24

▲ Issues were logged in the [Issues](#) panel in Chrome Devtools ^

Issues logged to the Issues panel in Chrome Devtools indicate unresolved problems. They can come from network request failures, insufficient security controls, and other browser concerns. Open up the Issues panel in Chrome DevTools for more details on each issue.

Issue type
Cookie
/api/player.js (player.vimeo.com)
...r128/three.min.js (cdnjs.cloudflare.com)
...3.12.2/gsap.min.js (cdnjs.cloudflare.com)
/video/117...?background=1&autoplay=1&loop=1&byline=0&title=0 (player.vimeo.com)
/add/player-stats?beacon=1&session-id=8ce5548... (arclight.vimeo.com)
/add/vimeo.play_video (lensflare.vimeo.com)

○ Detected JavaScript libraries ^

All front-end JavaScript libraries detected on the page. [Learn more about this JavaScript](#)

968973100

Name	Version
three.js	r128

TRUST AND SAFETY

○ Ensure CSP is effective against XSS attacks ^

A strong Content Security Policy (CSP) significantly reduces the risk of cross-site scripting (XSS) attacks. [Learn how to use a CSP to prevent XSS](#) Unscored

Description	Directive	Severity
No CSP found in enforcement mode		High

○ Use a strong HSTS policy ^

Deployment of the HSTS header significantly reduces the risk of downgrading HTTP connections and eavesdropping attacks. A rollout in stages, starting with a low max-age is recommended. [Learn more about using a strong HSTS policy.](#) Unscored

Description	Directive	Severity
No `includeSubDomains` directive found	includeSubDomains	Medium
No `preload` directive found	preload	Medium

○ Ensure proper origin isolation with COOP ^

The Cross-Origin-Opener-Policy (COOP) can be used to isolate the top-level window from other documents such as pop-ups. [Learn more about deploying the COOP header.](#) Unscored

Description	Directive	Severity
No COOP header found		High

○ Mitigate clickjacking with XFO or CSP ^

The X-Frame-Options (XFO) header or the frame-ancestors directive in the Content-Security-Policy (CSP) header control where a page can be embedded. These can mitigate

clickjacking attacks by blocking some or all sites from embedding the page. [Learn more](#)

100% (96/100) (89/100) (73/100) (100/100)

968973100

No frame control policy found

High

☐ Mitigate DOM-based XSS with Trusted Types

The `require-trusted-types-for` directive in the Content-Security-Policy (CSP) header instructs user agents to control the data passed to DOM XSS sink functions. [Learn more about mitigating DOM-based XSS with Trusted Types](#). Unscored

Description

Severity

No 'Content-Security-Policy' header with Trusted Types directive found

High

PASSED AUDITS (10)

Hide

☒ Uses HTTPS

All sites should be protected with HTTPS, even ones that don't handle sensitive data. This includes avoiding [mixed content](#), where some resources are loaded over HTTP despite the initial request being served over HTTPS. HTTPS prevents intruders from tampering with or passively listening in on the communications between your app and your users, and is a prerequisite for HTTP/2 and many new web platform APIs. [Learn more about HTTPS](#).

☒ Avoids deprecated APIs

Deprecated APIs will eventually be removed from the browser. [Learn more about deprecated APIs](#).

☒ Allows users to paste into input fields

Preventing input pasting is a bad practice for the UX, and weakens security by blocking password managers. [Learn more about user-friendly input fields](#).

☒ Avoids requesting the geolocation permission on page load

Users are mistrustful of or confused by sites that request their location without context.

96

89

73

100

● Avoids requesting the notification permission on page load ^

Users are mistrustful of or confused by sites that request to send notifications without context. Consider tying the request to user gestures instead. [Learn more about responsibly getting permission for notifications.](#)

● Displays images with correct aspect ratio ^

Image display dimensions should match natural aspect ratio. [Learn more about image aspect ratio.](#)

● Serves images with appropriate resolution ^

Image natural dimensions should be proportional to the display size and the pixel ratio to maximize image clarity. [Learn how to provide responsive images.](#)

● Page has the HTML doctype ^

Specifying a doctype prevents the browser from switching to quirks-mode. [Learn more about the doctype declaration.](#)

● Properly defines charset ^

A character encoding declaration is required. It can be done with a <meta> tag in the first 1024 bytes of the HTML or in the Content-Type HTTP response header. [Learn more about declaring the character encoding.](#)

● Page has valid source maps ^

Source maps translate minified code to the original source code. This helps developers debug in production. In addition, Lighthouse is able to provide further insights. Consider deploying source maps to take advantage of these benefits. [Learn more about source maps.](#) Unscored

96

89

73

100

Make sure that you redirect all HTTP traffic to HTTPS in order to enable secure web features for all your users. [Learn more.](#) Unscored



SEO

These checks ensure that your page is following basic search engine optimization advice. There are many additional factors Lighthouse does not score here that may affect your search ranking, including performance on [Core Web Vitals](#). [Learn more about Google Search Essentials.](#)

ADDITIONAL ITEMS TO MANUALLY CHECK (1)

Hide

☐ Structured data is valid ^

Run the [Structured Data Testing Tool](#) to validate structured data. [Learn more about Structured Data.](#) Unscored

Run these additional validators on your site to check additional SEO best practices.

PASSED AUDITS (8)

Hide

☒ Page isn't blocked from indexing ^

Search engines are unable to include your pages in search results if they don't have permission to crawl them. [Learn more about crawler directives.](#)

☒ Document has a `<title>` element ^

The title gives screen reader users an overview of the page, and search engine users rely on it

96

89

73

100

● Document has a meta description ^

Meta descriptions may be included in search results to concisely summarize page content.

[Learn more about the meta description.](#)

● Page has successful HTTP status code ^

Pages with unsuccessful HTTP status codes may not be indexed properly. [Learn more about HTTP status codes.](#)

● Links have descriptive text ^

Descriptive link text helps search engines understand your content. [Learn how to make links more accessible.](#)

● Links are crawlable ^

Search engines may use href attributes on links to crawl websites. Ensure that the href attribute of anchor elements links to an appropriate destination, so more pages of the site can be discovered. [Learn how to make links crawlable](#)

● Image elements have [alt] attributes ^

Informative elements should aim for short, descriptive alternate text. Decorative elements can be ignored with an empty alt attribute. [Learn more about the alt attribute.](#)

● Document has a valid hreflang ^

hreflang links tell search engines what version of a page they should list in search results for a given language or region. [Learn more about hreflang.](#)

NOT APPLICABLE (2)

Hide

○ robots.txt is valid ^

If your robots.txt file is malformed, crawlers may not be able to understand how you want

96 89 73 100

Document has a valid `rel=canonical`

Canonical links suggest which URL to show in search results. [Learn more about canonical links.](#) Unscored

 Captured at Jun 4, 2026, 4:13 PM
GMT+8

 Emulated Desktop with
Lighthouse 13.0.2

 Single page session

 Initial page load

 Custom throttling

 Using Chromium 148.0.0.0 with
devtools

Generated by **Lighthouse 13.0.2** | [File an issue](#)