IMAGE RECONSTRUCTION FROM DVS

Marcel Geppert, Samuel Bryner Petri Tanskanen

1. DYNAMIC VISION SENSOR



normal camera



event camera (DVS)

- a DVS delivers instantaneous **changes** in image brightness ("events") instead of periodic full frames
- event cameras suffer less from information loss through motion blur
- drastically reduced bandwith incurs significantly lower computational costs

2. MOTIVATION

- Increase robustness and speed of visual odometry / SLAM by replacing normal cameras with event cameras
- reduce SLAM problem to camera rotation in a static scene and reconstruction of a complete image

3. CORE ALGORITHM



Jointly track the global rotational motion of a camera and estimate the gradients of the scene around it. The gradient map is then upgraded to a full image-like mosaic.
Each of these components essentially believes that the current estimate from the other is correct.

ASSUMPTIONS

- a change in brigntness is caused by a movement of the camera (static scene)
- camera only rotating, no translation and therefore no parallax displacement

RECONSTRUCTION

Use movement between current and last event of the pixel to estimate gradient (intensity change) at event pixel.

- extended Kalmann filter reduces noise in the image
- Poisson-solver computes grayscale image from gradients.

MOVEMENT TRACKING

- rotation tracking with particle filter and constant position motion model
- When an event occurs: compare intensity at event position for every possible camera rotation to intensity at (assumed) position of last event:

$$z := \log(M(\mathbf{p}^{t})) - \log(M(\mathbf{p}^{t-1}))$$

the closer the intensity change to the camera's threshold the more likely is the proposed movement

4. RESULTS

SIMULATION



REAL DATA

integrated events when a dark cover was removed from the camera

CALIBRATION



- flickering display of normal checker-board pattern
- standard camera calibration toolbox

5. CONCLUSION

A dynamic vision sensor is a feasible option for rotational motion tracking. With some optimizations the system is easily real-time capable, especially when combined with other sensors, such as an IMU.

6. REFERENCES

[1] H. Kim, A. Handa, R. Benosman, S. Ieng, A. Davison, 2014
"Simultaneous Mosaicing and Tracking with an Event Camera"

[2] D. Weikersdorfer, D. Adrian, D. Cremers, Jörg Conradt, ICRA 2014
"Event-based 3D SLAM with a depth-augmented dynamic vision sensor"

[3] E. Mueggler, B. Huber, D. Scaramuzza, IROS 2014
"Event-based, 6-DOF Pose Tracking for High-Speed Maneuvers"

ETH zürich