

Your Chain Will Not Save You: Post-Quantum Institutional Risk Across Ethereum, Besu, Solana, Stellar, and Canton

A roadmap will not protect an issued asset. Ethereum, Besu-based permissioned EVM networks, Solana, Stellar, and Canton retain classical cryptography across transactions, privileged controls, validators, custody, identity, and privacy. This report identifies where institutional control can fail, what a protocol upgrade cannot repair, and why every new issuance on legacy cryptographic rails creates a migration liability.

5

Ledger environments examined across public, permissioned, payment, and private-settlement architectures.

2

Classical signature families dominate: secp256k1 ECDSA and Ed25519.

0

Environments use a NIST-approved post-quantum signature as the default transaction scheme.

\$71T+

Mapped tokenization, stablecoin, DeFi, and settlement exposure in the report.

EternaX Labs Research | Published June 24, 2026 | Updated July 24, 2026

By Paarrthhh Birla, Dr. Chen Feng, and Dariia Porechna | EternaX Labs

25-minute read | 5 ledger environments | 700+ institutions and market participants mapped | 4-point action framework | 65 FAQs | Updated July 24, 2026

ANSWER IN BRIEF

A chain upgrade is not a product migration. Ethereum, Besu-based permissioned EVM networks, Solana, Stellar, and Canton retain classical dependencies across native transactions, validators, issuer and administrator controls, immutable code, fixed interfaces, custody signers, identity, and encrypted settlement data.

The institution owns every dependency the protocol cannot rewrite. Waiting for a roadmap leaves product continuity, compliance enforcement, custody

authorization, liquidity access, and historical confidentiality tied to cryptography already scheduled for replacement.

WHAT QUANTUM EXPOSURE LOOKS LIKE

Once the underlying classical signature becomes breakable, a forged privileged authorization can approve transfers, change token controls, impersonate an administrator or validator, alter issuer permissions, or bypass an affected compliance verifier. Ciphertext captured today can expose long-lived settlement data later. **This is a continuity-of-control failure across authorization, compliance, custody, payments, consensus, and confidentiality.**

CORE FINDING

Permissioning is not post-quantum security. Multisig is not algorithm agility. A smart-account verifier is not network migration. A roadmap is not a control. Each can protect a narrow layer while native transactions, validators, custody, privileged roles, and historical privacy remain exposed.

**ROADMAPS DO
NOT SIGN
TRANSACTIONS**

**PERMISSIONING
DOES NOT
REPLACE ECC**

**MULTISIG DOES
NOT SURVIVE A
SYSTEMIC
ALGORITHM
BREAK**

**FUTURE
ENCRYPTION
CANNOT RETRACT
CAPTURED
CIPHERTEXT**

"Quantum computers will break currently deployed public-key cryptography, and significantly weaken symmetric key cryptography."

MICHELE MOSCA, INSTITUTE FOR QUANTUM COMPUTING | [CYBERSECURITY IN AN ERA WITH QUANTUM COMPUTERS](#)

Executive Summary

This is not a five-chain feature comparison. It is a map of where institutional control breaks when classical public-key assumptions expire. Besu is assessed as an Ethereum execution client used in permissioned networks; Stellar is assessed separately because issuer controls, classic Ed25519 accounts, transaction envelopes, validators, and Soroban authorization create a distinct failure surface.

The exposed unit is the complete product stack. Standards hardcode signature shapes. Validator software enforces classical authentication. Immutable contracts preserve old verifier logic. Custody and HSM estates sit outside protocol roadmaps. Identity roots and historical ciphertext survive software upgrades. **The chain can move forward while the product remains behind.**

*No single protocol upgrade closes this risk. Ethereum and Besu carry EVM account, verifier, contract, signer, and interface debt. Solana carries public-key account, authority, runtime, validator, and immutable-program debt. Stellar carries issuer, trustline, envelope, fee-payer, validator, and anchor debt. Canton carries identity-root, KMS, coordination, and historical-confidentiality debt. **The migration unit is the product and operating stack, not the chain.***

This report focuses on the institutional markets sitting directly on these rails: tokenized securities, tokenized funds, stablecoins, DeFi liquidity, custody platforms, fund administration, wallet infrastructure, and post-trade settlement.

KEY FINDINGS

- **Ethereum: the protocol can change; the installed base cannot be rewritten.**

Failure surface:

secp256k1 transactions, ecrecover, fixed permit interfaces, classically controlled privileged roles, and immutable contracts.

Consequence:

a fork does not automatically migrate regulated-token controls, approvals, custody workflows, or liquidity contracts already deployed.

- **Besu: permissioning contains membership, not cryptographic failure.**

Failure surface:

network-wide elliptic-curve authentication, QBFT validator keys, external signers, HSMs, custody, and inherited EVM controls.

Consequence:

a consortium can coordinate migration, but it must migrate the network, signer estate, and application controls together.

- **Solana: this is an account-identity and authority migration, not a signature toggle.**

Failure surface:

Ed25519 transaction accounts, fee payers, mint and freeze authorities, validator credentials, runtime verification, and immutable programs.

Consequence:

research and prototypes do not migrate existing authorities, custody, validators, transaction formats, or integrations.

- **Stellar: issuer control becomes product-control risk.**

Failure surface:

classic Ed25519 envelopes, issuer and distribution accounts, authorization, revocation, clawback, thresholds, fee-paying G-accounts, validators, anchors, and custody.

Consequence:

Soroban can harden selected application calls, but it does not migrate the classic network and operational stack.

- **Canton: privacy is time-limited wherever long-lived data remains under classical public-key encryption.**

Failure surface:

classical signing and encryption, namespace-root continuity, KMS support, participant and synchronizer rollout, and retained ciphertext.

Consequence:

a future migration can protect future traffic; it cannot withdraw ciphertext already captured.

- **Conclusion: the institution owns the migration.** Protocol teams do not control your claim issuers, administrator keys, HSM estate, custody policies, immutable contracts, validators, anchors, integrations, or retained encrypted data. New issuance on EternaX avoids this inherited debt through PQ-native accounts, signature-agnostic authorization, governed crypto agility, downgrade resistance, and SLH-DSA assurance anchoring.

Board-Level Translation: From Cryptographic Risk to Business Risk

This is not a cryptography debate. It is a continuity-of-control, compliance, liquidity, privacy, and insurability problem.

When the deployed signature or encryption assumption expires, the board inherits the product failure: unauthorized control, forced migration, stranded integrations, confidentiality loss, operational downtime, and regulatory remediation.

EXPOSURE	TECHNICAL ISSUE	BUSINESS CONSEQUENCE
Ethereum tokenized funds and stablecoins	secp256k1 accounts, ecrecover, classical permit paths, immutable liquidity contracts	Privileged-key exposure, forged authorization risk after cryptographic break, liquidity migration, and unresolved custody diligence
ERC-3643 regulated securities	The standard is algorithm-neutral, but conventional owners, agents, claim issuers, registries, investors, and proxy administrators may use classical accounts or ECDSA claim verification	Compromised privileged roles, forged eligibility claims in affected implementations, transfer-control failure, and regulatory remediation
Besu consortium and FMI networks	Network-wide elliptic-curve configuration, QBFT validator signatures, external signers and HSMs, plus inherited EVM application controls	Validator and administrator exposure, signer and HSM replacement, bespoke-fork risk, operational downtime, and multi-institution migration governance
Solana stablecoins and RWAs	Ed25519 transaction signers and account identities, token authorities, fee payers, runtime verification, and immutable deployed programs	Issuer-control exposure, mint or freeze disruption, wallet and custody migration, transaction-format pressure, and ecosystem coordination
Stellar-issued assets and payment rails	Classic Ed25519 envelopes, issuer and distribution accounts, threshold signers, authorization and clawback controls, validators, anchors, and fee-paying accounts	Issuer or treasury-control compromise, unauthorized freeze or clawback actions, anchor disruption, custody replacement, and account migration
Canton settlement and private workflows	Classical signing and encryption schemes, namespace-root continuity, topology delegations, participant and synchronizer migration, and retained encrypted data	Historical confidentiality loss, identity-continuity planning, KMS replacement, cross-participant coordination, and settlement-service disruption
Custody, MPC, HSM, and policy stacks	The final on-ledger authorization may remain ECDSA or Ed25519 even when key operations are distributed or hardware-protected	MPC and HSMs reduce operational key risk but do not, by themselves, remove algorithm-level quantum exposure or application-verifier dependencies

WHY ETERNAX EXISTS

Legacy rails force institutions to retrofit cryptography after assets, custody, liquidity, compliance, and governance are embedded. Hard-coding one replacement signature scheme would simply recreate the same lock-in. EternaX reverses both failures: post-quantum account authorization, signature-agnostic interfaces, governed crypto agility, verifier logic, identity and compliance modules, custody integration, validator operations, and settlement controls are native before issuance.

For Besu operators, EternaX provides interoperability and staged hardening without confusing one application verifier with a migrated network. For Stellar issuers, it means protecting issuer, treasury, compliance, and custody authorization without surrendering regulated asset controls. For new issuance, it means avoiding fresh ECDSA and Ed25519 migration debt at inception.

SLH-DSA is the assurance anchor, not a permanent lock-in. High-value roots can use FIPS 205 while operational paths use other approved schemes according to risk, performance, HSM support, and jurisdiction. The asset and business workflow should not need to change when the approved signature policy changes.

EternaX passes where legacy rails fail: PQ-native accounts, explicit algorithm identifiers, signature-agile authorization, downgrade resistance, key and algorithm rotation, custody integration, recovery, and CBOM visibility are built into the architecture.

SOURCE-GRADE FOUNDATION

The cryptographic and protocol claims in this report are anchored to primary standards and official documentation: [NIST FIPS 203 / ML-KEM](#), [FIPS 204 / ML-DSA](#), [FIPS 205 / SLH-DSA](#), [NSA CNSA 2.0](#), [ERC-2612](#), [Besu alternative-curve documentation](#), [Besu QBFT documentation](#), [Besu release history](#), [Solana core documentation](#), [Solana Foundation quantum-readiness statement](#), [Stellar signatures and multisig](#), [Stellar issuer controls](#), [Soroban authorization](#), and [Canton supported cryptographic schemes](#), [topology](#), and [key-management documentation](#).

"The key is to be on this journey today and not wait until the last minute."

ROB JOYCE, FORMER DIRECTOR OF NSA CYBERSECURITY | [CISA, NIST, AND NSA QUANTUM-READINESS GUIDANCE](#)

Cross-Environment Post-Quantum Exposure Summary

LAYER	ETHEREUM	BESU PRIVATE NETWORKS	SOLANA	STELLAR	CANTON
Account or identity model	EOAs use secp256k1; active signatures enable public-key recovery	secp256k1 default; secp256r1 early access; one curve configuration across the network	Standard wallet addresses are Ed25519 public keys; PDAs are program-controlled exceptions	G-accounts are Ed25519 public keys; additional signer types exist but do not replace classic envelope authentication	Identifiers are rooted in namespace keys; operational keys can be delegated and rotated, while the namespace root defines continuity
Native transaction authorization	secp256k1 ECDSA; protocol and account migration required	Elliptic-curve native authentication; smart-contract verifiers provide only partial coverage	Ed25519 transaction signatures and fee-payer authorization	Classic transactions use Ed25519; Soroban contract authorization is an application-layer extension	Documented production scheme set is classical; rollout must cover participants and synchronizer services
Runtime and verifier dependencies	ecrecover and deployed ECDSA verifiers; PQ proposals do not rewrite existing code	Inherits the EVM and deployed verifier logic; no documented production PQ transaction mode	Built-in Ed25519, secp256k1, and secp256r1 verification paths; PQ support is not a standard mainnet primitive	Custom contract authorization can add verifier agility; classic signatures remain separate	Crypto-provider configuration offers scheme choice within the supported classical set
Application and standard debt	Fixed ABIs and immutable contracts may require replacement and integration migration	Inherits EVM contracts and ERC interfaces; consortium governance does not rewrite deployed code automatically	Immutable programs cannot be upgraded under the same identity; token authorities and integrations require migration	Issuer, trustline, threshold, and Stellar Asset Contract controls require authority and custody migration	Daml reduces some contract-code lock-in; identity, topology, KMS, and historical-data dependencies remain
Validator or consensus layer	Execution and consensus use different classical schemes, requiring coordinated protocol migration	QBFT requires signatures from at least two-thirds of validators; loss of more than one-third can stall the network	Validator identity and voting infrastructure require a separate migration from user accounts	Validator and node credentials are separate from issuer and user-account authorization	Participant, sequencer, mediator, and topology keys require coordinated scheme support and operational rollout
Privacy and HNDL	Public ledger; confidentiality risk sits mainly in off-chain systems and encrypted integrations	Deployment-specific. Integrated Tessera privacy was removed; historical and external privacy layers require separate CBOMs	Public ledger; off-chain encrypted systems remain separate dependencies	Public ledger; anchors, custody, and off-chain compliance systems may hold long-lived confidential data	Encrypted views and retained traffic require a harvest-now-decrypt-later assessment where ECIES P-256 or RSA protects long-lived confidentiality
Migration verdict	PROTOCOL PLUS APPLICATION MIGRATION	NETWORK-WIDE CONSORTIUM MIGRATION	ACCOUNT, RUNTIME, AND ECOSYSTEM MIGRATION	ISSUER, ACCOUNT, VALIDATOR, AND ANCHOR MIGRATION	IDENTITY, CRYPTO, PRIVACY, AND PARTICIPANT MIGRATION

This matrix measures migration scope, not current compromise. The absence of a fabricated score is not softness: every un-migrated dependency remains an institutional liability.

A Roadmap Does Not Protect Your Product

Every major chain can publish a post-quantum roadmap. Roadmaps do not rotate your administrator keys, replace your HSMs, rewrite immutable contracts, change fixed signature interfaces, migrate issuer controls, or erase captured ciphertext.

The protocol may upgrade while the institutional product remains cryptographically stranded. The chain moves; the issued asset, compliance system, custody path, validator estate, identity root, and liquidity integrations do not move with it.

INSTITUTIONAL REALITY

You cannot outsource post-quantum risk to a protocol foundation. The institution remains accountable for every contract, key, signer, validator, custodian, identity dependency, and encrypted record that the roadmap does not migrate.

What a Chain Upgrade Does NOT Fix

BESU: AN APPLICATION VERIFIER DOES NOT MIGRATE THE CONSORTIUM

Native transactions and QBFT validators remain separate migration layers. A smart-contract verifier cannot replace network-wide transaction and block authentication.

Permissioning does not change the signature assumption. Besu defaults to secp256k1; its early-access alternative is secp256r1, which is also elliptic-curve cryptography.

Custody and signing infrastructure sits outside the client. Besu does not manage keys internally, so Web3Signer, HSM, custody, and policy-engine migration must be inventoried independently.

Current privacy must be assessed deployment by deployment. Integrated Tessera privacy was removed from Besu; historical Tessera deployments and current Paladin-based architectures have different cryptographic inventories.

ETHEREUM: A HARD FORK DOES NOT REWRITE THE INSTALLED BASE

ERC-3643 remains implementation-dependent. A hard fork does not automatically migrate classically controlled owners, agents, claim issuers, identity registries, compliance controllers, investors, or proxy administrators.

ERC-2612 permit still requires (v, r, s). \$80B+ in tokens cannot accept PQ signatures through their existing ABI.

Permit2, V2/V3, Compound V2, WETH9 are still immutable. \$15B+ TVL in contracts with permanent ECDSA logic.

SOLANA: A NEW TRANSACTION PATH DOES NOT MIGRATE EXISTING AUTHORITIES

Existing account and authority relationships still require migration. Standard wallet addresses are Ed25519 public keys, while token mints, freeze authorities, fee payers, custody accounts, validator credentials, and application integrations must be remapped or supported through a transition mechanism.

Immutable programs remain immutable. A program whose upgrade authority has been revoked cannot be updated under the same program identity; replacement deployments require downstream integrations to move.

Performance is implementation-dependent. Larger signatures, transaction-size limits, verification cost, batching, and validator networking create real trade-offs, but no single throughput-loss percentage applies to every scheme or migration architecture.

EternaX removes this inherited debt at the architecture layer. PQ-native accounts, signature-agnostic authorization, crypto agility, and SLH-DSA anchoring replace retrofit migration with governed cryptographic rotation.

STELLAR: CUSTOM CONTRACT AUTHORIZATION DOES NOT MIGRATE CLASSIC CONTROL

Classic G-accounts, transaction envelopes, fee payers, issuer and distribution accounts, freeze and clawback authorities, validators, anchors, wallets, and custody remain separate migration layers.

Soroban can validate alternative signatures for selected contract authorization. It does not convert the classic Stellar network or its operational control plane into post-quantum infrastructure.

CANTON: A FUTURE SCHEME CANNOT RECOVER HISTORICAL CONFIDENTIALITY

Namespace continuity remains a separate problem. Digital Asset documents that operational node keys can rotate and namespace authority can be delegated, but the root signing key defines the namespace and cannot simply be replaced while preserving the same namespace.

Historical confidentiality cannot be repaired retroactively. Where an adversary has already captured traffic encrypted under a quantum-vulnerable public-key scheme, a later migration protects future data but cannot withdraw previously collected ciphertext.

Migration scope is deployment-specific. Participant, sequencer, mediator, topology, KMS, protocol-version, and application dependencies must be inventoried. The report does not assign a universal throughput penalty or assume that every institution must switch in one simultaneous event.

A PQ-native design can avoid parts of this inherited identity and privacy debt, but it must independently prove its cryptographic schemes, privacy design, KMS support, operational recovery, performance, and interoperability.

BOTTOM LINE

The risk is distributed across the chain, client, application, identity, custody, validator, and data layers. Protocol teams control only part of it. The institution owns the rest. Inventory it, remediate it, replace it, or stop issuing new long-duration products into it.

MIGRATION CHALLENGE	ETHEREUM	BESU PRIVATE EVM	SOLANA	STELLAR	CANTON	PQ-NATIVE
Default transaction authorization	secp256k1 ECDSA	secp256k1 by default; early-access secp256r1 option	Ed25519	Ed25519 for classic transactions	Classical Ed25519 / ECDSA options	NIST-approved PQ scheme from genesis
Account or identity migration	Active EOAs and application roles require migration	EOAs, validator addresses, and consortium operations require coordinated migration	Account identifiers are Ed25519 public keys	Classic G-accounts are public-key accounts; issuer and administrator accounts require migration	Namespace and topology identity create continuity constraints	No inherited classical identity debt
Application escape hatch	ERC-1271 / ERC-4337 can protect selected authorization paths	Same EVM mechanisms, plus plugins or bespoke forks	New programs and account abstractions can be deployed, but legacy programs remain	Soroban contract accounts can implement custom <code>__check_auth</code>	Daml application abstraction is cleaner than immutable public-chain contracts	Native verifier and account model

MIGRATION CHALLENGE	ETHEREUM	BESU PRIVATE EVM	SOLANA	STELLAR	CANTON	PQ-NATIVE
What the escape hatch does not fix	Native tx signing, validators, immutable contracts, frozen interfaces	Native tx, QBFT validators, node authentication, external signing and custody	Runtime primitives, validator keys, immutable token programs, existing authorities	Classic envelopes, G-account fee payer, issuer controls, validator keys	Historical privacy, topology, namespace, synchronizer coordination	N/A
Performance evidence for full PQ migration	Architecture and scheme dependent; no single authoritative end-to-end number	No authoritative production benchmark for a full network-wide migration	Prototype results are scheme and transaction-format dependent	No authoritative network-wide benchmark published	No authoritative production benchmark published	Measured on the native implementation, not inferred from retrofit substitution
Migration character	Ecosystem-wide and application-heavy	Consortium-governable but multi-layer and coordination-heavy	Runtime, program, validator, wallet, and ecosystem migration	Classic accounts, issuer controls, wallets, validators, plus optional Soroban migration	Identity, privacy, KMS, and multi-party coordination	Native from day one

Migration time is the longest dependency in the stack. Standards, client code, HSMs, custody, wallets, contracts, liquidity, certifications, governance, and counterparties will move at different speeds. Institutions that wait for the base protocol to finish will start product migration last. PQ-native issuance reduces inherited work, but production acceptance still requires audits, standards conformance, custody integration, interoperability, recovery, and long-term crypto-agility.

THE REGULATORY CLOCK

The Compliance Clock Is Already Running

The standards are final. Inventory obligations are expanding. Procurement pressure is moving downstream. Executive Order 14412, federal migration requirements, and NIST standards are converting post-quantum readiness from a research topic into a vendor, custody, procurement, and settlement diligence requirement.

"We encourage system administrators to start integrating them into their systems immediately, because full integration will take time."

DUSTIN MOODY, NIST PQC PROJECT LEAD | [NIST FINALIZED PQC STANDARDS ANNOUNCEMENT](#)

VERIFIED SOURCE	WHAT IT ESTABLISHES	INSTITUTIONAL IMPLICATION
NSM-10 White House, May 2022	Quantum-vulnerable cryptography classified as national security risk. Migration planning directed.	PQC is a national-security transition program, not optional research.
OMB M-23-02 November 2022	Federal agencies directed to inventory and prioritize migration of quantum-vulnerable cryptography.	CBOM-style diligence becomes the institutional baseline.
NSA CNSA 2.0 September 2022	Quantum-resistant algorithm requirements for National Security Systems. Preference dates 2025-2026, required dates 2030-2033.	Financial market infrastructure will face the same assurance expectations.
NIST FIPS 203, 204, 205 August 2024	ML-KEM, ML-DSA, and SLH-DSA (SPHINCS+) finalized as federal standards.	Institutions now have recognized standards against which vendors and settlement rails can be evaluated.
NIST IR 8547 Initial Public Draft, November 2024	Describes NIST's expected transition approach and proposed timelines for removing quantum-vulnerable public-key algorithms from NIST standards. As of July 24, 2026, it remains a draft publication.	It is a material planning signal, not a final standalone legal prohibition on every blockchain use of ECDSA or Ed25519.
Executive Order 14412 "Securing the Nation Against Advanced Cryptographic Attacks" White House, June 22, 2026	First enforceable federal PQC deadlines. 30 days: agency PQC leads. 90 days: OMB binding guidance. 180 days: FAR contractor compliance rule (deadline Dec 31, 2030). 270 days: CISA/NIST CBOM guidance. Dec 31, 2031: PQC for all federal digital signatures.	Converts PQC from research into procurement gates. CBOM will expose ECDSA/EdDSA dependencies across custody, tokenization, and settlement. The order states adversaries "may already be collecting" encrypted data for future quantum decryption.

Executive Order 14412: The Compliance Cascade into Digital Assets

EO 14412 (Federal Register Vol. 91, No. 121, June 25, 2026) directly binds federal agencies. Its private-sector impact flows through procurement, federal contractors, critical-infrastructure expectations, regulated-client diligence, vendor risk reviews, and CBOM disclosure. That distinction matters: the order does not instantly regulate every crypto institution, but it creates the compliance standard those institutions will increasingly be measured against.

Channel 1: FAR Procurement (Section 6c). Federal contractors must comply with NIST FIPS PQC by December 31, 2030. Digital-asset vendors with federal contract exposure, federal clients, or federal-adjacent market infrastructure relationships will be pulled into that requirement first.

Channel 2: CBOM Disclosure (Section 5d). By ~March 2027, CISA and NIST publish CBOM guidance: machine-readable inventories of every algorithm, key, and protocol. For a blockchain product, that means declaring ECDSA, Ed25519, ECIES, permit logic, identity-verification logic, and custody signing dependencies as deployed cryptographic components. A roadmap is not a CBOM entry.

Channel 3: Critical Infrastructure Pressure (Section 5a). Financial market infrastructure, clearing, settlement, custody, and post-trade technology providers will

face higher assurance expectations even where the order reaches them indirectly through clients, supervisors, procurement, and resilience standards.

Channel 4: Regulated Client Cascade. BlackRock, Goldman Sachs, JPMorgan, State Street, and other regulated financial institutions will increasingly ask their digital-asset vendors the same question: which deployed algorithms secure this product today, and are they aligned with NIST-approved PQC migration plans?

Channel 5: Section 6(d) Vulnerability Disclosure. Contractor vulnerability disclosure expands to cover the use of non-FIPS approved algorithms. For products touching federal procurement or federal-adjacent systems, ECDSA and Ed25519 dependencies become diligence items, not abstract cryptography.

What a Chain-Aware CBOM Reveals Today

A roadmap is not a CBOM entry. A CBOM records what protects the product today: transaction signatures, validator authentication, permit logic, claim verification, issuer controls, KMS paths, custody signers, and encryption. Diligence will expose every classical dependency that marketing language leaves vague.


ENVIRONMENT	DEPLOYED CLASSICAL DEPENDENCIES	POST-QUANTUM CAPABILITY TODAY	MIGRATION SCOPE EXPOSED BY CBOM	ASSESSMENT
Ethereum	secp256k1 transaction accounts, ecrecover, consensus cryptography, deployed classical verifiers, fixed permit interfaces	Application-level smart-account or verifier experiments are possible; no completed end-to-end migration	Protocol, accounts, validators, wallets, custody, immutable contracts, standards, and liquidity integrations	FAIL
Hyperledger Besu private network	secp256k1 default or early-access secp256r1, QBFT validator keys, EVM verifiers, external signers, HSMs, and custody	Custom contracts, plugins, or bespoke forks can protect selected paths; no documented production PQ transaction mode	Consortium-wide transaction, validator, signer, HSM, custody, application, tooling, and governance migration	FAIL
Solana	Ed25519 transaction signatures, on-curve account keys, authority accounts, validator credentials, built-in verification paths, deployed programs	Falcon research implementations and Winternitz-style application tools exist; network-wide migration is not complete	Transaction format, wallets, existing accounts, validators, custody, token authorities, programs, and integrations	FAIL
Stellar	Classic Ed25519 transaction envelopes, issuer and distribution accounts, thresholds, validators, anchors, custody, and asset controls	Soroban can provide custom application authorization; classic envelopes and infrastructure remain separate	Accounts, issuer controls, fee sources, validators, wallets, anchors, custody, and application migration	FAIL
Canton	Classical signing and encryption schemes, namespace roots, topology delegations, operational keys, KMS integrations, encrypted views	Crypto scheme configuration and key rotation exist within the documented classical set; no NIST PQ scheme is listed in the current supported-schemes documentation	Identity continuity, operational keys, participants, synchronizer services, KMS, retained encrypted data, and interoperability	FAIL

ENVIRONMENT	DEPLOYED CLASSICAL DEPENDENCIES	POST-QUANTUM CAPABILITY TODAY	MIGRATION SCOPE EXPOSED BY CBOM	ASSESSMENT
EternaX	No inherited ECDSA or Ed25519 transaction authorization	SLH-DSA-based, signature-agnostic, crypto-agile authorization	PQ-native accounts, validator authorization, custody and HSM integration, recovery, downgrade resistance, algorithm rotation, and CBOM visibility	PASS

VERIFIED SOURCES

White House: [Executive Order 14412](#). Federal Register: [Vol. 91, No. 121, FR Doc 2026-12909](#). NIST: [IR 8547](#). See also: [Cloudflare analysis](#), [Jenner & Block analysis](#).

How PQC Requirements Reach Every Institutional Issuer



The regulatory clock is not waiting for multi-year blockchain governance debates. EO 14412 creates named federal owners, hard dates, and procurement consequences. Its pressure reaches private digital-asset infrastructure through contractors, regulated clients, vendor diligence, and CBOM disclosure. CBOM guidance (due ~March 2027) will force machine-readable disclosure of every deployed algorithm. What is deployed today is what gets reported. A chain roadmap is not a CBOM entry. EternaX, built on SPHINCS+/SLH-DSA under NIST FIPS 205, returns a PASS on the chain-aware CBOM audit from day one.

Ethereum and the EVM Ecosystem

Ethereum's post-quantum problem is not a lack of research. It is the installed base. secp256k1 authorization, signature recovery, privileged roles, fixed permit interfaces, custody integrations, and immutable contracts are already embedded across the ecosystem. A hard fork can change future protocol rules. It cannot rewrite deployed products.

ETHEREUM VERDICT

The chain can migrate and the asset can remain exposed. Every fixed interface, immutable verifier, classically controlled role, and downstream integration requires its own replacement or containment plan.

Five Layers of Non-Upgradeable ECDSA in Ethereum

LAYER 1 Address Derivation	EOAs derive from secp256k1 keys. Once a transaction signature is published, the signer public key can be recovered. Under a CRQC, that exposed public key becomes a private-key recovery path.
LAYER 2 Transaction Signing	Native transactions use secp256k1 ECDSA across clients. Migration requires protocol, wallet, custody, signer, tooling, and account-continuity changes. A proposal is not a migrated installed base.
LAYER 3 ecrecover Precompile	ecrecover is a protocol primitive used by deployed contracts. A fork can change future protocol behavior, but it does not automatically rewrite fixed interfaces, immutable code, or external integrations.
LAYER 4 Immutable Contracts	Uniswap Permit2, V2/V3 Pools, Compound V2, Curve base pools, Balancer V2 Vault, WETH9, ENS Registry. No proxy. No upgrade function. No admin key. ECDSA logic is permanent for the lifetime of the chain.
LAYER 5 Frozen Interfaces	ERC-2612 permit ABI uses (uint8 v, bytes32 r, bytes32 s). Large PQ signatures do not fit this signature shape. A replacement interface requires wallet, custody, router, and application migration.

A PROTOCOL FORK DOES NOT REWRITE DEPLOYED CONTRACTS, FIXED INTERFACES, PRIVILEGED ROLES, OR CUSTODY INTEGRATIONS.

Where Ethereum Standards Lock In Classical Authorization

Institutional Ethereum standards fall into different cryptographic categories. ERC-2612 explicitly encodes secp256k1 signatures. ERC-3643 is not intrinsically ECDSA-bound, but conventional deployments can inherit classical-key exposure across owners, agents, investors, trusted issuers, identity registries, compliance controllers, and proxy administrators. ERC-1400-family implementations are implementation-dependent and should not be described as universally ECDSA-bound.

STANDARD	INSTITUTIONAL FUNCTION	ECDSA LOCATION	SEVERITY	WHAT BREAKS UNDER QUANTUM ATTACK
ERC-3643	Regulated token controls, identity, compliance, freezing, forced transfer, recovery, owner and agent roles.	The specification is algorithm-neutral. Exposure depends on the keys and verifier implementations controlling privileged roles and signed claims.	Critical in conventional ECC-backed deployments	Compromised owner, agent, issuer, identity, compliance, investor, or upgrade-authority keys can abuse concentrated regulated-token controls.
ERC-2612	Gasless approvals. USDC, DAI, PYUSD, institutional DeFi flows.	Hardcoded in spec. permit(... uint8 v, bytes32 r, bytes32 s). Uses ecrecover. v/r/s is ECDSA-specific.	CRITICAL	Once secp256k1 is breakable, a forged valid permit can create an unauthorized allowance without a fresh on-chain approval by the owner.
ERC-1400	Security token suite. Partitioned tokens, transfer agent certificates.	Implementation-level. CertificateController uses ecrecover to verify transfer agent signatures.	HIGH	Where the implementation relies on forgeable classical certificates, unauthorized partition transfers can pass the affected authorization check.

PRIMARY-SOURCE ANCHOR

ERC-2612's specification defines `permit(address owner, address spender, uint value, uint deadline, uint8 v, bytes32 r, bytes32 s)` and requires a valid secp256k1 signature. That is why the standard cannot simply accept large post-quantum signatures without a replacement interface. See [ERC-2612](#) and [EIP-712](#).

"If a user has made even one transaction, then the signature of that transaction reveals the public key."

VITALIK BUTERIN, ETHEREUM FOUNDATION | [ETHEREUM RESEARCH](#)


ERC-3643: Algorithm-Neutral Standard, Concentrated Key Risk

ERC-3643 does not mandate ECDSA for every identity claim or privileged role. The material risk is architectural concentration: owners, agents, identity-registry administrators, trusted issuers, compliance controllers, investors, recovery authorities, and proxy administrators are represented by Ethereum addresses or contracts. Where those controls ultimately depend on secp256k1 EOAs, ECC-backed multisigs, or ECDSA-only claim verification, they remain post-quantum exposed. A PQ claim verifier alone does not migrate the surrounding account, validator, custody, and governance layers.

INSTITUTIONAL CONSEQUENCE: REGULATED-TOKEN CONTROL FAILURE

If an ERC-3643 deployment uses ECDSA-backed claims or ECC-controlled privileged roles, a break of that cryptography reaches the legal control plane of the asset. A forged affected claim can admit an ineligible wallet. A compromised owner, agent, registry, compliance controller, recovery authority, or proxy administrator can abuse the powers assigned to that role. Ethereum cannot repair those controls for the issuer. The product owner must migrate them.

NAMED INSTITUTIONS EXPOSED VIA ERC-3643



ERC-2612: The Broadest Infrastructure Exposure


ERC-2612 is not merely implemented with ECDSA. Its interface is shaped around secp256k1. The permit function accepts v , r , and s ; large post-quantum signatures do not fit that envelope. The existing interface cannot become signature-agile by changing verifier logic alone. It requires a replacement authorization interface and migration of every caller.

Dollar exposure: USDC (\$55B+), DAI/USDS (~\$5B), stETH (\$15B+), PYUSD, GHO, crvUSD, and all tokens deployed via OpenZeppelin ERC20Permit. Total permit token market cap exceeds \$80B. Through Permit2, exposure extends to every ERC-20 on every EVM chain. Ethereum DeFi alone holds ~\$38B TVL, nearly all routing through permit-dependent infrastructure.

INSTITUTIONAL CONSEQUENCE: DELEGATED AUTHORIZATION LEAVES THE OWNER'S CONTROL

Once secp256k1 signatures become forgeable, an affected permit path becomes an authorization path the owner no longer controls. A forged permit can create an allowance without a fresh on-chain approval by the owner. That is custody exposure, fiduciary exposure, and regulatory exposure. A future Ethereum transaction-signature migration does not convert the existing v/r/s permit interface into a PQ interface. The product remains dependent until the interface and integrations are replaced.

NAMED PLATFORMS EXPOSED VIA ERC-2612



Immutable Contracts: Permanent Migration Debt

Immutable code converts cryptographic obsolescence into permanent migration debt. Where a deployed contract relies on ECDSA recovery, fixed classical authorization, or an immutable integration path, that logic cannot be patched in place. The response is containment, replacement deployment, integration migration, approval revocation, and movement of liquidity or assets. Trust minimization at deployment does not remove cryptographic expiry.

CONTRACT	DEPLOYER	ECDSA DEPENDENCY	APPROX. TVL / IMPACT
Uniswap Permit2	Uniswap Labs	ecrecover for signature verification	Universal EVM approval layer
Uniswap V2 Pair	Uniswap Labs	ERC-2612 permit, hardcoded v/r/s	\$2B+ TVL
Uniswap V3 Pool	Uniswap Labs	Immutable core	\$3B+ TVL
Compound V2 cTokens	Compound Labs	ecrecover in governance	Multi-billion TVL

CONTRACT	DEPLOYER	ECDSA DEPENDENCY	APPROX. TVL / IMPACT
Curve Base Pools	Curve Finance	Immutable core logic	Multi-billion TVL
Balancer V2 Vault	Balancer	Immutable core	Multi-billion TVL
WETH9	Community	Immutable, no permit but foundational	\$5B+ deposited
ENS Registry	ENS	Immutable	Ethereum naming infrastructure

WHAT THIS MEANS FOR YOUR INSTITUTIONAL VAULT AND DEFI YIELD PRODUCT

Institutional products do not exist in isolation from DeFi. BlackRock BUIDL uses ERC-4626 vaults. Those vaults interact with DeFi liquidity routing through Uniswap pools and Permit2. The institutional product and DeFi infrastructure are the same stack. When Permit2's ecrecover becomes forgeable, every token approval routed through it is compromised. Immutable deployments cannot be patched in place. The durable response is replacement contracts, integration migration, containment of legacy approvals, and a cryptographically agile authorization path. EternaX provides familiar institutional interfaces on a PQ-native rail without inheriting immutable ECDSA verifier debt.

LEDGER ENVIRONMENT 2 OF 5

Hyperledger Besu and Permissioned EVM Networks

Besu gives institutions governance control over a private EVM network. It does not give them post-quantum cryptography. The consortium can control validators, permissioning, gas, and operations while retaining Ethereum-style accounts, transactions, EVM contracts, external signers, and common ERC control patterns.

BESU VERDICT

Permissioned is not post-quantum. A private network can restrict every participant and still fail at the cryptographic layer. Elliptic-curve transactions, QBFT validator keys, external signers, HSMs, custody, and privileged contract roles remain separate points of failure.

What Besu Changes, and What It Does Not

LAYER	PRIVATE BESU CAPABILITY	POST-QUANTUM CONSEQUENCE
Participation	Known nodes and validators, local permissioning, consortium governance	Controls access, but does not change the signature algorithm protecting transactions or privileged accounts.
Consensus	QBFT is the recommended enterprise-grade private-network consensus; at least two-thirds of validators sign a block before insertion.	Validator authentication is a separate cryptographic migration from application contracts and user accounts.
Gas	Private networks can configure zero gas price while retaining EVM gas metering.	Zero price removes the fee, not the computational cost or verifier-performance constraint.
Execution	EVM, Solidity, JSON-RPC, Ethereum-style accounts and contracts	Inherits Ethereum account, transaction, precompile, interface, and application-control dependencies.
Key management	Besu does not manage private keys inside the client; external signers, wallets, HSMs, or custody systems are used.	A credible migration must include the external signer and hardware path, not only the node software.

Native Transactions Remain Elliptic-Curve Authenticated

Besu uses secp256k1 by default. Private networks can configure secp256r1 through an early-access feature, and every node in the network must use the same selected curve to communicate and verify transactions and blocks. Both options are elliptic-curve systems vulnerable to a sufficiently capable quantum computer. Moving from one classical curve to another is not a post-quantum migration.

QBFT Creates a Separate Consensus-Layer Migration

QBFT validators validate transactions and blocks, take turns proposing blocks, and require a supermajority of at least two-thirds to sign a block before it is inserted. Besu warns that losing more than one-third of validators stalls block production. A quantum compromise of validator keys could therefore affect validator identity, participation, censorship, ordering, or availability, depending on the number of keys compromised. It would not automatically authorize arbitrary invalid EVM state transitions because clients still validate protocol rules.

THE MIGRATION BOUNDARY

A PQ verifier inside one smart contract can protect one authorization decision. It does not automatically migrate native transaction signatures, QBFT validator keys, peer authentication, relayer or bundler accounts, existing EOA ownership, custody infrastructure, or HSM signing paths.

No Established Native PQ Transaction Path Today

Ethereum proposals such as EIP-7932, which introduces a registry and interface for secondary signature algorithms, and EIP-8051, which proposes ML-DSA precompiles, remain Draft proposals. They demonstrate active work on signature agility, but they are not established production capabilities that a standard Besu network can claim today. A Besu operator can build a bespoke fork, plugin, relayer, or smart-contract verifier, but that must be described as a deployment-specific control rather than native end-to-end Besu PQ support.

ERC Standards: Explicitly Bound Versus Inherited Risk

STANDARD OR LAYER	CORRECT CLASSIFICATION	INSTITUTIONAL PQ CONCLUSION
Native Besu transactions	Direct protocol dependency	Elliptic-curve authentication must be migrated network-wide.
ERC-2612 Permit	Explicitly secp256k1-bound	The interface requires v , r , and s ; a replacement authorization path is required.
ERC-3643	Algorithm-neutral standard with concentrated privileged roles	Conventional ECC-backed owners, agents, investors, claim issuers, registries, compliance controllers, recovery authorities, and proxy administrators remain exposed.
ERC-20 / ERC-4626 / ERC-1967	Cryptographically neutral, account-control dependent	Risk depends on holder, administrator, operator, and upgrade-authority authentication.
ERC-1271 / ERC-4337	PQ-enabling application mechanisms	Can add custom application authorization, but do not migrate Besu transactions, validators, networking, or custody infrastructure.

Current Privacy Architecture: Do Not Generalize Legacy Tesseract

Older Besu private-network designs commonly used Tesseract for private transactions. Besu's changelog records removal of the integrated Tesseract privacy feature and on-chain permissioning. LF Decentralized Trust now maintains [Paladin](#) as a programmable privacy framework for EVM, with Pente continuing the EVM privacy-group model. The correct diligence approach is deployment-specific: identify whether an environment is historical Tesseract, Paladin or Pente, another privacy layer, or no privacy layer, then inventory that architecture's encryption, key-management, retention, and migration dependencies separately.

Performance: No Benchmark, No Claim

No institution should accept a throughput claim without an end-to-end benchmark of the actual consortium architecture. Scheme, parameter set,

transaction format, verifier implementation, block size, WAN topology, validator hardware, HSM support, and migration scope determine the result. An application-level prototype is not evidence of network-wide transaction and validator performance.

INSTITUTIONAL CONSEQUENCE: CONSORTIUM-WIDE CONTROL-PLANE MIGRATION


Besu is governable, not quantum-safe. Known participants make coordination possible, but the migration still spans transaction authentication, QBFT validators, external signers, HSMs, custody, privileged contract roles, application verifiers, tooling, and privacy. Miss one layer and the network is only partially hardened.

NAMED INSTITUTIONS EXPOSED ON HYPERLEDGER BESU

Scope note: Here, *exposed* means publicly connected to infrastructure that retains the classical cryptographic dependencies analyzed in this report, not compromised.

Inclusion below means one of three things: a directly documented Besu deployment, participation in a production initiative that used Besu, or formal participation in the Besu Financial Services Working Group. It does not mean every listed institution used every Besu transaction path.

Direct deployment and production initiative



DTCC states that its July 15, 2026 production initiative executed digital conversions on LF Decentralized Trust's Besu, described as DTCC's private network, and on Canton. The announcement lists the participating firms but does not assign each participant to a specific chain. The tags therefore identify participation in the multi-chain production initiative, not Besu-only execution.

Formal Besu Financial Services Working Group participation



Institutional evidence: [DTCC, July 15, 2026 production initiative using DTCC's private Besu network and Canton](#); [LF Decentralized Trust, Besu Financial Services Working Group founding members](#).

Primary sources: [Besu overview and key-management boundary](#); [QBFT documentation](#); [alternative elliptic curves](#); [free gas networks](#); [Besu changelog](#); [EIP-7932](#); [EIP-8051](#); [Paladin project](#)

LEDGER ENVIRONMENT 3 OF 5

Solana

PRIMARY-SOURCE ANCHOR

Solana documentation lists Ed25519, Secp256k1, and Secp256r1 signature verification as precompiled programs, and states that upgrade authority revocation makes a program immutable. See [Solana Programs documentation](#).

"Using Shor's algorithms, factoring large numbers on a quantum computer would be just as fast as multiplication."


PETER SHOR, MIT | [CERN INTERVIEW](#)

Solana makes the public key part of the ordinary account identity. Native transaction signing, fee payers, mint and freeze authorities, validator identity and voting credentials, custody accounts, runtime verification, and application integrations all create separate migration surfaces. Program-derived addresses are a real exception, but they do not remove the migration burden from signing accounts and authorities.

SOLANA VERDICT

A new PQ wallet path does not migrate the installed network. Existing authorities, validators, immutable programs, transaction formats,

custody, wallets, and integrations must still move without losing control or creating a downgrade path.



Native Precompiled Programs

Solana's Ed25519 and Secp256k1 verification programs are precompiled into the validator runtime as native code. They cannot be upgraded by any on-chain mechanism. Replacing them requires a coordinated validator software upgrade, equivalent to an Ethereum hard fork. Every on-chain program that uses these precompiles for custom authorization, including multisigs, custody schemes, and DeFi authorization logic, inherits quantum vulnerability and persists after any base protocol migration until individually updated.

Signature-Verification Pipeline: A Protocol Engineering Dependency

Solana's transaction pipeline is optimized around compact Ed25519 signatures and high-throughput verification. A post-quantum transition must integrate a different key and signature format into transaction validation, fee calculation, networking, batching, validator clients, and hardware acceleration. The engineering cost and performance outcome depend on the selected scheme and implementation; they should be measured rather than inferred from signature size alone.

Token Programs and Installed-Base Migration

The original SPL Token Program has a large installed base and is treated as an immutable program deployment. Solana also supports Token-2022, which is a separate program with extensions. A post-quantum migration must therefore distinguish protocol-level transaction authorization from token-program logic, mint and freeze authorities, account ownership, custody integrations, and the installed base of applications tied to existing program identities. Replacement code does not automatically migrate assets or downstream integrations.

Consensus and Validator Migration Are Separate

A user-wallet migration does not automatically migrate validator identity, voting, consensus messages, stake and withdraw authorities, or validator-client key infrastructure. Any compact-signature or aggregation assumption used by the deployed consensus design must be evaluated separately under the selected post-quantum scheme. The correct conclusion is not that no solution can exist, but that transaction signing and consensus migration are distinct engineering and governance programs.

Winternitz Vaults: A Narrow Application-Level Tool

Winternitz-style hash-based vaults can provide a useful one-time or low-frequency authorization pattern for selected assets. They are optional application constructs, not a network-wide migration. They do not by themselves replace ordinary transaction envelopes, fee-payer accounts, validator credentials, token authorities, custody integrations, or consensus signing. They should be presented as a containment or transition technique for specific workflows, not as proof that the complete Solana stack is post-quantum safe.

Solana's Published Quantum-Readiness Position

On April 27, 2026, the Solana Foundation stated that Anza and Firedancer independently selected Falcon as a compact post-quantum candidate and published initial implementations. Its stated roadmap is to continue research, adopt a post-quantum scheme for new wallets if the threat becomes credible, and then migrate existing wallets. The Foundation also stated that it does not expect a meaningful performance impact. These are important readiness signals, but they remain roadmap

and implementation claims rather than evidence of a completed network-wide migration. Institutional diligence should request reproducible benchmarks, final transaction-format design, validator-client support, wallet and custody compatibility, hardware-signing support, consensus coverage, downgrade controls, and the status of FIPS 206 before treating the migration path as production-ready.

Solana: Signature and Transaction-Format Constraints

ITEM	DOCUMENTED VALUE OR STATUS	MIGRATION IMPLICATION
Ed25519 signature	64 bytes	Current transaction and fee design is optimized around compact signatures
SLH-DSA-SHA2-128s signature	7,856 bytes under FIPS 205	Direct substitution would exceed the current transaction-size envelope and requires a different encoding or authorization architecture
Maximum Solana transaction size	1,232 bytes in current core documentation	Large-signature schemes need transaction-format, batching, compression, indirection, or account-model changes
Falcon / FN-DSA	Selected by Anza and Firedancer for initial research implementations; FIPS 206 standardization remains a separate dependency	Compact size is promising, but production readiness requires final standards, audited implementations, wallets, custody, validators, and migration governance
Performance	No universal percentage is defensible	Measure end-to-end throughput, latency, bandwidth, verification, and state impact on the actual implementation

The size comparison establishes a transaction-format problem for direct SLH-DSA substitution. It does not, by itself, establish the throughput of a redesigned Solana migration path or a PQ-native network.

Solana has a roadmap. It does not yet have a completed migration. Initial Falcon implementations and a wallet sequence are meaningful engineering progress. Institutional readiness still requires final standards, reproducible end-to-end benchmarks, transaction-format changes, validator and consensus coverage, custody and hardware support, migration of existing authorities, and downgrade prevention. Until those exist in production, the classical control plane remains the deployed control plane.

NAMED PLATFORMS AND PROTOCOLS EXPOSED ON SOLANA



LEDGER ENVIRONMENT 4 OF 5

Stellar

Stellar concentrates institutional authority in accounts that can issue, authorize, revoke, freeze, claw back, and move assets. Classic transactions use Ed25519. Soroban adds customizable contract authorization, but it does not automatically migrate classic transaction envelopes, fee payers, issuer accounts, validators, anchors, wallets, or custody.

Stellar's institutional strength is also its concentration point. Issuance, authorization, revocation or freeze, clawback, signer management, treasury movement, and transaction submission ultimately depend on the security of the accounts authorized to perform them.

Classic Accounts: The Public Key Is the Account Identity

Stellar documents Ed25519 as the signature scheme used for classic transactions. Classic accounts are identified by public keys, and transaction authorization is attached to those accounts. Unlike Ethereum's hide-until-first-spend distinction, a Stellar classic account is fundamentally a public-key account from creation. A sufficiently capable

quantum computer that breaks Ed25519 would therefore threaten classic account control wherever the relevant public key is known.

Multisig Improves Governance, Not Algorithm Diversity

Stellar thresholds and multisig can require multiple authorized signers and support flexible *m-of-n* policies. This reduces single-key operational risk. It does not automatically create post-quantum safety when the signers rely on the same quantum-vulnerable signature family. Multisig helps when compromise is isolated; it is not a defense against a systemic break of Ed25519.

Issuer Controls Are High-Impact Authorization Surfaces

ISSUER OR ACCOUNT FUNCTION	STELLAR CAPABILITY	POST-QUANTUM RISK
Asset authorization	Issuer can require and manage authorization for trustlines.	A compromised issuer-control account could authorize or alter access contrary to policy.
Revocation or freeze	AUTH_REVOCABLE_FLAG allows an issuer to revoke trustline authorization, freezing transfers and trading for that asset on the affected trustline.	A compromised authority could wrongfully freeze or unfreeze regulated positions.
Clawback	When enabled, the issuer can claw back eligible asset balances or claimable balances.	A compromised clawback authority could destroy or recover balances outside legitimate procedures.
Signer and threshold management	Accounts can add signers and set low, medium, and high thresholds.	Compromise of the authority able to change signers or thresholds can alter the account's control policy.
Treasury and distribution	Issuing and distribution accounts commonly separate supply control from circulation.	Both account classes require independent cryptographic and operational migration.

Soroban Contract Accounts Are a Real but Partial Escape Hatch

A Soroban contract implementing the CustomAccountInterface and `__check_auth` can define signatures in a user-defined format and apply custom authorization policy. This is a genuine crypto-agility advantage at the application layer: a carefully implemented contract account could validate a post-quantum scheme once an efficient, audited verifier and supporting tooling exist.

But C-accounts cannot sign transaction envelopes. Stellar's documentation states that they authorize through auth entries while a separate G-account acts as the transaction source and fee payer. Therefore, custom PQ authorization for a contract invocation does not by itself migrate the classic envelope signer, network fee payer, validator keys, custody integrations, or every issuer and administrative account.

Validator Authentication Remains a Separate Layer

Stellar Core validators use node identity keys and send validation messages as part of consensus. A post-quantum application account does not change validator authentication. End-to-end migration requires separate work across classic accounts, transaction envelopes, validators, wallets, custodians, exchanges, anchors, issuer operations, and Soroban tooling.

Performance: No Benchmark, No Claim

No end-to-end benchmark means no defensible network-wide performance claim.


The result depends on the selected scheme, envelope design, signature and key sizes, verification implementation, batching, fee mechanics, validators, wallets, and migration scope. A Soroban verifier benchmark is not a Stellar network-migration benchmark.

INSTITUTIONAL CONSEQUENCE: ISSUER-CONTROL COMPROMISE BECOMES PRODUCT-CONTROL COMPROMISE

Stellar is not post-quantum safe by default today. Soroban can harden selected application authorization, but classic Ed25519 accounts, issuer controls, transaction envelopes, G-account fee payers, validators, anchors, wallets, and custody remain separate migration obligations.

NAMED INSTITUTIONS EXPOSED ON STELLAR

Scope note: Here, *exposed* means publicly connected to Stellar infrastructure that retains the classical cryptographic dependencies analyzed in this report, not compromised. Inclusion reflects a documented live issuance, payment rail, stablecoin, custody service, validator role, regulated market integration, or announced deployment. Planned integrations are explicitly labeled, and not every product uses the same account, issuer-control, custody, or validator path.



The exposure is product-specific. For an issuer, it may sit in classic Ed25519 issuer, distribution, freeze, clawback, or signer-management accounts. For a payment or custody provider, it may sit in transaction-envelope signing, wallet infrastructure, or operational integrations. For a validator, it includes node identity and consensus authentication. Planned connectivity is not treated as a live deployment.

Institutional evidence: [Stellar institutional deployments, including Franklin Templeton, WisdomTree, MoneyGram, and Fireblocks](#); [Stellar tokenized assets, including ABN AMRO; DTCC's planned DTC connection for 1H 2027; PYUSD live on Stellar; Figure YLDS launch; 21X technical integration; MoneyGram, Figure Markets, and Range Tier 1 validator roles; Ondo USDY; RedSwan tokenized real estate; Mercado Bitcoin issuance announcement; Tradable private-credit integration.](#)

Primary sources: [Stellar signatures and multisig; asset authorization and revocation; clawbacks; Soroban authorization and contract accounts; transaction envelopes and auth entries; validator configuration.](#)

Canton Network

PRIMARY-SOURCE ANCHOR

Canton documentation lists Ed25519, ECDSA P-256, ECDSA P-384 for signing and ECIES on P-256 for asymmetric encryption. Canton security documentation states: "A namespace root signing key is a permanent key. It cannot be rotated without losing the namespace." Canton operations documentation states: "Every Synchronizer imposes a minimum set of cryptographic schemes. If a node does not support this minimum set of schemes, it is unable to connect." See [Canton Security and Key Management](#) and [Canton Crypto Key Management](#).

"A quantum adversary can not only decrypt future traffic but, if they want to, past traffic."

SOFIA CELI AND NICK SULLIVAN, CLOUDFLARE | [THE POST-QUANTUM FUTURE](#)

Canton places institutional identity, authorization, and confidentiality on a cryptographic stack documented today with classical signing and encryption schemes. Its scale makes the migration problem consequential: namespace continuity, participant and synchronizer keys, KMS support, protocol compatibility, and retained encrypted views cannot be treated as a future vendor patch.

CANTON VERDICT

The most dangerous exposure is not only signature forgery. It is retrospective confidentiality loss. A later migration can protect future traffic. It cannot retract ciphertext already captured under a quantum-vulnerable public-key scheme.


PRIMITIVE	SUPPORTED SCHEMES	QUANTUM STATUS	INSTITUTIONAL IMPACT
Signing	Ed25519 (default), ECDSA P-256, ECDSA P-384	SHOR - VULNERABLE	Six protocol layers: topology transactions, confirmation request Merkle root signing, confirmation response signing to mediator, transfer message signing, ACS commitment signing, and sequencer challenge-response authentication. Multi-view privacy multiplies the signature count per transaction across involved parties.
Asymmetric Encryption	ECIES on P-256 with HMAC-SHA256 and AES128-GCM	KEY EXCHANGE VULNERABLE	Captured views protected through this classical key-exchange path become retrospectively readable once the relevant elliptic-curve assumption is broken.
Symmetric Encryption	AES128-GCM	NOT BROKEN BY SHOR	The symmetric cipher is not the primary failure. Confidentiality still fails if the session key is recovered through the vulnerable classical public-key layer.
MAC	HMAC with SHA-256	ADEQUATE	Message authentication. Not the primary risk surface.

The Harvest Now, Decrypt Later Problem

Canton's value proposition depends heavily on selective disclosure and encrypted transaction views. Where long-lived traffic is protected by quantum-vulnerable public-key encryption and is captured today, a future CRQC can turn retained ciphertext into retrospective disclosure. **The risk window is already open because collection can happen before decryption becomes possible.**

Historical confidentiality has no retroactive patch. Any captured Canton traffic protected by a quantum-vulnerable public-key encryption path remains a future disclosure liability for as long as the data retains commercial, regulatory, counterparty, or national-security value.

Harvest Now, Decrypt Later: Canton Privacy Exposure Timeline



PQ-SAFE CONFIDENTIALITY MUST START BEFORE DATA IS CAPTURED. FUTURE MIGRATION CANNOT RETRACT CIPHERTEXT.

Canton Migration: Cleaner Application Abstraction, Difficult Identity and Privacy Dependencies

Canton's Daml application model reduces some of the immutable-contract and fixed-ABI problems found on public smart-contract platforms. That is a genuine advantage. The difficult post-quantum work sits in the cryptographic and operational layers: namespace roots, delegated topology authority, participant and synchronizer keys, supported signing and encryption schemes, KMS integration, retained encrypted traffic, protocol-version compatibility, and multi-party rollout.

Surface 1: Namespace-Root Continuity

Digital Asset documents the namespace root signing key as permanent because the namespace is identified by that key's fingerprint. Operational risk can be reduced by keeping the root offline and delegating authority to intermediate keys, and ordinary node keys can be rotated. A transition to a new root-key algorithm therefore requires an explicit identity-continuity mechanism or a planned move to a new namespace; it is not accurate to say that every operational key is permanently fixed.

Surface 2: Supported Scheme and KMS Migration

The current supported-schemes documentation lists classical key specifications and algorithms, including Ed25519, ECDSA curves, ECIES P-256, and RSA-2048. A post-quantum rollout must add supported schemes to the Canton implementation and ensure that software vaults, external KMS products, key ceremonies, backups, recovery, and operational controls can use them. Cloud-provider support is time-sensitive and must be checked at deployment time rather than stated categorically for all providers.

Surface 3: Participant and Synchronizer Coordination

Participants and synchronizer services negotiate protocol compatibility and must support the cryptographic capabilities required by the deployment. This creates real coordination and interoperability work across institutions. It does not justify the universal claim that all network participants must migrate in one simultaneous event; the feasible sequencing depends on protocol design, hybrid support, compatibility rules, and how a particular synchronizer is operated.

Surface 4: Historical Confidentiality


Canton supports encrypted transaction views and classical public-key encryption schemes. Where traffic has been captured and the confidentiality horizon extends beyond the expected lifetime of the classical scheme, harvest-now-decrypt-later is a material risk. A later migration protects future data but cannot retract ciphertext already collected. The affected volume and named counterparties must be supported by deployment-specific evidence, not inferred from aggregate network activity.

CANTON LAYER	WHAT CAN ROTATE OR CHANGE	WHAT REQUIRES DEEPER MIGRATION
Operational node keys	Digital Asset documents node-key rotation	PQ scheme support, KMS compatibility, custody procedures, and cross-node interoperability
Namespace authority	Authority can be delegated to intermediate keys and the root can be kept offline	The root fingerprint defines namespace continuity
Applications	Daml contracts are more abstracted from signature verification than fixed EVM permit interfaces	Parties, topology, authorization infrastructure, and external integrations
Privacy	Future encryption schemes and retention policies can change	Previously captured ciphertext cannot be withdrawn
Network rollout	Protocol versions and capability policies can support staged engineering	Institutional governance, compatibility, fallback, and downgrade prevention

BOARD-LEVEL CONSEQUENCE

Canton's risk is identity continuity plus long-lived confidentiality. The institution must know which namespace roots, topology authorities, participant and synchronizer keys, KMS paths, protocol versions, and encrypted records require migration. Anything missing from that inventory remains outside the control plan.

NAMED INSTITUTIONS EXPOSED ON CANTON NETWORK



"If quantum computing becomes a threat to Bitcoin's elliptic curve cryptography, an inviolable property of Bitcoin will be violated one way or another."

JAMESON LOPP, BITCOIN SECURITY RESEARCHER | [AGAINST ALLOWING QUANTUM RECOVERY OF BITCOIN](#)

INSTITUTIONAL RESPONSE FRAMEWORK

What Institutions Should Do Now

The waiting period is over. Any institution issuing, holding, administering, settling, or custodying digital assets across Ethereum, Besu, Solana, Stellar, or Canton should execute four actions now.

ACTION	WHY NOW	WHO OWNS IT
1. Conduct a cryptographic inventory	You cannot migrate what you cannot name. Inventory every transaction signature, validator key, issuer and administrator role, permit and claim verifier, HSM and custody signer, immutable contract, privacy layer, KMS path, and retained encrypted dataset.	CISO / CTO
2. Assess application-layer PQ exposure	Map the failure path from key or verifier compromise to business consequence: unauthorized transfer, minting, freezing, clawback, upgrade, validator disruption, compliance bypass, liquidity migration, or confidentiality loss. Protocol roadmaps do not close these paths automatically.	CTO / Engineering

ACTION	WHY NOW	WHO OWNS IT
3. Evaluate PQ-native settlement rails	Every new long-duration issuance on classical authorization creates a migration liability on day one. Compare hardening legacy rails with PQ-native issuance using exact criteria: standardized native signatures, crypto-agility, downgrade resistance, audited verifier logic, custody and HSM support, reproducible performance, interoperability, recovery, and CBOM output.	Product / Strategy
4. Engage custodians on CBOM readiness	Your custodian, HSM provider, wallet, signer, policy engine, and settlement operator must identify the deployed algorithm, migration path, residual classical dependency, and operational deadline. An unanswered CBOM question is an unresolved product risk.	Operations / Compliance

Do not begin with a chain marketing claim. Begin with the cryptographic inventory. EternaX offers a chain-aware CBOM exposure review across tokenized funds, stablecoins, custody, issuer controls, validators, settlement workflows, privacy, and liquidity integrations, followed by a PQ-native issuance path with familiar institutional interfaces.

[Request a Chain-Aware CBOM Review](#)

[Schedule an Institutional Briefing](#)

PQ-NATIVE · SIGNATURE-AGNOSTIC · CRYPTO-AGILE MARKET INFRASTRUCTURE

EternaX: PQ-Native, Signature-Agnostic, Crypto-Agile, SLH-DSA Anchored

Retrofitting cryptography after issuance is the expensive path. Hard-coding the replacement algorithm creates the next migration crisis. EternaX is PQ-native, signature-agnostic, crypto-agile market infrastructure for stablecoins, RWA tokenization, custody-adjacent workflows, and institutional settlement. Assets, application interfaces, and institutional workflows are not permanently coupled to one signature algorithm or one fixed signature shape.

STANDARDS ANCHOR

EternaX's high-assurance signature posture is anchored to NIST-recognized post-quantum standards, especially [FIPS 205 / SLH-DSA](#), the stateless hash-based standard derived from SPHINCS+. Crypto agility does not dilute that anchor. It prevents the infrastructure from becoming permanently locked to one scheme when performance requirements, HSM support, jurisdictional policy, or future standards change.

CRYPTO AGILITY IS A CONTROL, NOT A SLOGAN

Crypto agility means the governed ability to introduce, select, combine, rotate, and retire approved cryptographic algorithms without redesigning the asset, rewriting the business workflow, or forcing another ecosystem-wide migration.

Signature agnostic means authorization is not hard-coded to ECDSA, Ed25519, SLH-DSA, ML-DSA, or one fixed signature encoding. The authorization envelope carries an explicit scheme and version identifier, is checked against institutional policy, and is routed to the approved verifier.

SLH-DSA remains the conservative anchor. EternaX uses FIPS 205 SLH-DSA for roots of trust, issuance, treasury, recovery, and long-duration controls. ML-DSA, FN-DSA, and other approved schemes serve operational paths according to performance, HSM support, jurisdiction, and risk tier.

EternaX does not bolt a PQ verifier onto classical accounts, and it does not replace one permanent cryptographic dependency with another. Account authorization, transaction envelopes, verifier interfaces, policy controls, and consensus authorization operate as one crypto-agile system. The result is structural: classical fallback debt is removed, algorithm choice is preserved, and future cryptographic rotation becomes a governed operation rather than an asset migration.

CBOM PASS: FIPS-aligned schemes, explicit algorithm identifiers, policy allowlists, downgrade prevention, hybrid transition, custody and HSM integration, recovery, and full cryptographic visibility are native controls.

CRYPTO-AGILITY CONTROL	ETERNAX IMPLEMENTATION
Algorithm-independent authorization envelope	Variable-length signatures and public keys use one asset contract and one business interface across approved schemes.
Explicit scheme and version identifiers	Explicit scheme and version identifiers for algorithm, encoding, and version.
Risk-tiered policy	SLH-DSA protects high-assurance roots while other approved schemes serve higher-frequency operational paths.

CRYPTO-AGILITY CONTROL	ETERNAX IMPLEMENTATION
Hybrid transition and rotation	Controlled, multi-stages period of hybrid operation, supporting migration and rotation of cryptographic keys and algorithms.
Downgrade resistance	Migrated controls reject unapproved classical or weaker fallback schemes.
CROM visibility	Time-based visibility of control migration and visibility of control path and cryptographic key rotation.

Performance: Post-Quantum Cryptography from Genesis

Legacy chains absorb post-quantum cryptography as retrofit overhead. EternaX builds signature size, verification, networking, storage, validator execution, and finality around post-quantum authorization from genesis. The architecture removes the ECDSA and Ed25519 transaction-format assumptions that force legacy rails into disruptive redesign.

INSTITUTIONAL CONTROL	ETERNAX ARCHITECTURE
Post-quantum assurance	SLH-DSA under FIPS 205 anchors roots of trust, issuance, treasury, recovery, and long-duration authorization.
Cryptoequity	Equity is represented by a cryptographic commitment to a public key, which is then used to sign transactions, distributed transactions, and distributed consensus.
Market-scale execution	Transaction encoding, verification, networking, storage, validator processing, and finality operate around post-quantum signatures from genesis.
Institutional operations	Control and data are distributed across a network of nodes, with no single point of failure or control, and no single point of compromise.
Downgrade resistance	Migrated authorization cannot silently fall back to an unapproved classical or weaker scheme.

Familiar Institutional Interfaces, Signature-Agnostic Authorization

EternaX preserves familiar token, vault, smart-account, compliance, and programmable-custody interfaces while decoupling those interfaces from the signature scheme underneath. Institutions move between approved schemes through governed policy, verifier, key, and HSM changes without reissuing the asset or rewriting the business application.

TIER	STANDARDS	WHAT THE INSTITUTION SEES	WHAT CHANGES UNDERNEATH
Tier 1: Source-compatible interfaces	ERC-20, ERC-721, ERC-4626, ERC-4337, ERC-7943	The same core interface semantics and integration patterns are preserved for institutional applications.	PQ authorization sits below familiar application interfaces across wallets, custody, signing, policy, and tooling.
Tier 2: Regulated-asset adaptation	ERC-3643, ERC-1400	Regulated identity, claim, compliance, and controller concepts remain intact under post-quantum authorization.	PQ verifier modules replace classical verification across identity, claim, compliance, and controller authorization.
Tier 3: PQ-native authorization	ERC-2612 replacement	Preserve the business capability of delegated or off-chain authorization while changing the cryptographic envelope.	A generic-signature permit interface replaces the fixed ECDSA v/r/s envelope and supports approved post-quantum schemes.

For long-duration issuance, the status quo is not neutral. Issuing on classical authorization today creates a future migration obligation. EternaX removes that obligation at issuance through PQ-native accounts, SLH-DSA assurance anchoring, signature-agnostic authorization, crypto agility, custody integration, recovery, and downgrade resistance.

Start a PQ-Native Issuance Pilot

Schedule an Institutional Briefing

RESEARCH ADDITIONS AND ACCURACY CORRECTIONS

What Changed in the July 24, 2026 Edition

This edition expands the report from three chains to five institutional ledger environments and sharpens the institutional failure analysis across every rail.

ADDITION OR CORRECTION	WHAT CHANGED	ACCURACY RULE APPLIED
Hyperledger Besu section	Added transaction authentication, alternative EC curves, QBFT validator migration, zero-gas distinction, external key-management boundary, ERC classifications, draft EIPs, privacy-current-state correction, and a conservative migration verdict.	Besu is described as an Ethereum client and ledger environment, not falsely as an independent Layer 1.
Stellar section	Added classic Ed25519 account risk, thresholds and multisig, issuer authorization, revocation or freeze, clawback, Soroban contract accounts, G-account fee-payer dependency, validator migration, and performance-evidence limits.	Soroban custom authentication is treated as a partial application escape hatch, not proof that Stellar is end-to-end PQ-safe.
ERC-3643 correction	Removed blanket statements that ERC-3643 itself mandates ECDSA.	The report now distinguishes an algorithm-neutral specification from conventional ECC-backed owners, agents, claims, registries, investors, compliance controllers, recovery authorities, and proxy administrators.
Besu privacy correction	Removed current-state claims that integrated Tessera privacy is Besu's active native privacy architecture.	Historical Tessera deployments and current Paladin or deployment-specific privacy architectures are separated.
Performance discipline	No universal TPS-loss percentage is assigned to Besu or Stellar.	Without an authoritative end-to-end production benchmark, the report states the variables and refuses to fabricate a number.
FAQs and structured data	Added ten Besu and Stellar FAQs and regenerated FAQPage JSON-LD from the visible answers.	Structured data now matches the report text rather than repeating stale three-chain wording.
FAQ discoverability and LLM retrieval	Expanded to 65 direct-answer FAQs, organized them into nine search-intent clusters, added unique question anchors, source proximity, featured institutional questions, and a dedicated EternaX decision section including crypto agility and signature-agnostic authorization.	Visible answers and FAQPage JSON-LD remain synchronized. EternaX is PQ-native, signature-agnostic, crypto-agile market infrastructure with SLH-DSA as the high-assurance anchor.
Evidence map	Added official Besu, Ethereum EIP, and Stellar documentation to claims and primary-source registers.	New technical claims rely on primary documentation, not vendor marketing or unverified deployment lists.
Hard-hitting institutional-risk pass	Rebuilt the body around failure modes, board consequences, migration ownership, and five environment-specific verdicts. Added stronger visual risk banners before the dedicated FAQ discoverability and LLM-retrieval pass.	Language is forceful only where the underlying claim is supportable. Unsupported absolutes, fabricated performance percentages, and overbroad decryption claims remain excluded.

ENTITY GLOSSARY FOR AI SEARCH

Key Entities and Definitions

This glossary makes the report easier for executives, search engines, and LLM systems to parse. Each term maps a technical dependency to the institutional risk discussed in the report.

EO 14412

U.S. Executive Order titled "Securing the Nation Against Advanced Cryptographic Attacks." It directly binds federal agencies and creates a private-sector cascade through procurement, contractors, regulated clients, CBOM disclosure, and vendor diligence.

CBOM

Cryptographic Bill of Materials. A machine-readable inventory of cryptographic algorithms, libraries, keys, standards, and dependencies used by a system or product.

ECDSA

Classical elliptic-curve signature scheme used by Ethereum, Bitcoin, and many institutional custody flows. It is vulnerable to Shor's algorithm once public keys are exposed.

Ed25519

Edwards-curve signature scheme used across Solana, Stellar, and Canton defaults. It is not post-quantum secure and appears across account, validator, and authority models.

ECIES P-256

Classical elliptic-curve encryption scheme used in privacy-sensitive systems. Historical encrypted traffic can remain exposed to harvest-now-decrypt-later attacks.

ERC-3643

Regulated token standard for identity, compliance, owner and agent controls, freezing, forced transfer, recovery, and trusted claims. The specification does not mandate ECDSA universally; PQ exposure depends on the account and verifier implementations used by a deployment.

ERC-2612

Permit approval standard with ECDSA-shaped v, r, s signature parameters. It cannot directly encode large post-quantum signatures without a replacement interface.

SLH-DSA / SPHINCS+

NIST-standardized stateless hash-based post-quantum signature scheme under FIPS 205. EternaX uses this family as its conservative PQ-native signing anchor.

SPL Token

Core Solana token program used for fungible assets, mint authority, freeze authority, and token account control. Its authority model depends on Ed25519.

Canton Namespace

Canton identity construct tied to the fingerprint of a root signing key. This creates a hard migration problem if the root key must move from classical to PQ cryptography.

Hyperledger Besu

Open-source Ethereum execution client that runs on public and private networks. Private deployments can use QBFT, permissioning, and zero-gas configurations while retaining Ethereum-style execution and account dependencies.

QBFT

Besu's recommended enterprise-grade private-network consensus. A supermajority of at least two-thirds of validators signs a block before insertion, creating a distinct validator-key migration layer.

Stellar Classic Account

A public-key account used for classic Stellar transaction authorization. Stellar documents Ed25519 as the standard classic transaction signature scheme.

Soroban Contract Account

A Stellar contract implementing `__check_auth` with custom authentication and policy logic. It can enable application-level signature agility but cannot sign a transaction envelope itself.

Paladin

A programmable privacy architecture referenced by current Besu documentation. It should be assessed separately from historical Tessera private-transaction deployments.

CLAIMS AND SOURCES

Machine-Readable Evidence Map

The table below connects the report's highest-value claims to primary sources or standards. It is designed for due diligence, citation, and LLM extraction.

REPORT CLAIM	PRIMARY SOURCE	WHY IT MATTERS
NIST has standardized SLH-DSA as a stateless hash-based post-quantum signature standard.	NIST FIPS 205 / SLH-DSA	Anchors the EternaX conservative PQ-signature posture to an official NIST standard.
EO 14412 makes PQC migration a direct federal priority and creates contractor, procurement, and CBOM pressure.	Federal Register: EO 14412	Turns PQC from future planning into board-level compliance and vendor-risk diligence.
ERC-2612 is structurally ECDSA-shaped through v, r, s permit parameters.	Ethereum EIP-2612	Explains why existing permit interfaces cannot simply accept large PQ signatures.
EIP-712 typed-data signing supports permit, custody, and institutional authorization flows that depend on classical signature verification.	Ethereum EIP-712	Shows how transaction authorization and offchain approvals inherit the same cryptographic base.
Solana exposes signature-verification primitives at the runtime and program layer.	Solana Program Documentation	Supports the claim that Solana's exposure is not limited to wallet signing.
Canton documents classical signing and encryption scheme support, including Ed25519, ECDSA, and ECIES.	Canton Security and Key Management	Supports the report's claim that Canton has signing, identity, and privacy-layer PQ migration challenges.
Ethereum public keys become exposed after an account transacts, making active accounts materially different from dormant addresses in a PQ world.	Ethereum Research: Quantum Emergency	Explains why active institutional admin, treasury, custody, and signer keys need special treatment.
Public agencies recommend preparing cryptographic inventories and migration plans before a cryptographically relevant quantum computer arrives.	CISA, NIST, and NSA PQC Guidance	Supports the report's CBOM-first action framework for institutions.
Besu is an Ethereum client that runs on public and private networks and does not manage private keys inside the client.	Besu official documentation	Prevents the report from misclassifying Besu as an independent L1 and establishes the external signer and custody migration boundary.
QBFT requires at least two-thirds of validators to sign a block; loss of more than one-third of validators stalls block production.	Besu QBFT documentation	Establishes validator authentication and availability as a separate migration layer.
Besu defaults to secp256k1; private networks can configure early-access secp256r1 and all nodes must use the same curve.	Besu alternative elliptic curves documentation	Confirms that the available alternative remains classical EC and requires network-wide coordination.
EIP-7932 and EIP-8051 are Draft proposals, not established native Besu PQ capabilities.	Ethereum EIP-7932 and EIP-8051	Prevents roadmap proposals from being represented as deployed production support.
Stellar uses Ed25519 for classic transaction signatures and supports thresholds and multisig.	Stellar signatures and multisig documentation	Supports the classic-account exposure analysis while distinguishing governance redundancy from algorithm diversity.
Stellar issuers can revoke trustline authorization to freeze an asset and can enable clawback controls.	Stellar asset-control and clawback documentation	Maps post-quantum key risk to concrete regulated-asset control surfaces.
Soroban contract accounts can implement custom <code>__check_auth</code> logic, but C-accounts cannot sign transaction envelopes and rely on a G-account source or fee payer.	Stellar authorization and transaction-signing documentation	Establishes why Soroban is a partial application escape hatch rather than a complete network migration.
DTCC used a private Besu network alongside Canton for its July 2026 production tokenization initiative; the named participant list is multi-chain and is not a Besu-only attribution.	DTCC production tokenization announcement	Supports the Besu institution map while preventing over-attribution of individual firms to one chain.
Stellar has publicly documented live institutional issuances, payment rails, stablecoins, custody services, validator roles, regulated-market integrations, and planned DTC connectivity.	Stellar institutional solutions; DTCC planned Stellar connection	Supports the named-institution section while preserving live-versus-planned status distinctions.

PRIMARY SOURCE REGISTER

Evidence Base

This report is designed for institutional forwarding. The core cryptographic claims should be traceable to primary standards, protocol specifications, or official public guidance.

CLAIM FAMILY	PRIMARY SOURCE	WHY IT MATTERS
NIST PQC standards	NIST finalized PQC standards, FIPS 205 / SLH-DSA	Confirms finalized PQC standards and the hash-based SLH-DSA signature standard.
U.S. national-security PQC transition	NSA CNSA 2.0 announcement	Confirms official quantum-resistant algorithm requirements for National Security Systems.
Ethereum permit exposure	ERC-2612, EIP-712	Confirms the v/r/s and secp256k1 structure of permit-based approvals.
Solana runtime exposure	Solana Programs documentation	Confirms precompiled signature verification programs and immutability after upgrade authority revocation.
Canton signing and encryption exposure	Canton Security and Key Management	Confirms Ed25519, ECDSA P-256/P-384, and ECIES P-256 schemes in Canton documentation.
Quantum threat and migration urgency	Michele Mosca, IACR ePrint, CISA, NIST, and NSA guidance, NIST IR 8547	Confirms that today's public-key cryptography must migrate and that migration should begin before CRQC arrival.
Ethereum public-key exposure	Vitalik Buterin, Ethereum Research	Confirms that a single transaction reveals the public key, making transacted EOAs exposed in a post-quantum world.
Harvest-now-decrypt-later and crypto governance	Cloudflare post-quantum future, Jameson Lopp on quantum recovery, CERN interview with Peter Shor	Supports the report's claims on stored encrypted-data exposure, elliptic-curve migration tradeoffs, and Shor's algorithm risk.
Besu client and key-management boundary	Besu overview	Confirms public/private operation and external key management.
Besu consensus and curve configuration	QBFT and alternative EC curves	Confirms two-thirds validator signatures, stall threshold, secp256k1 default, early-access secp256r1, and same-curve coordination.
Besu privacy current state	Besu changelog	Confirms removal of integrated Tessera privacy and on-chain permissioning.
Ethereum PQ proposals	EIP-7932 and EIP-8051	Confirms secondary-signature and ML-DSA precompile work remains Draft.
Stellar classic authorization	Stellar signatures and multisig	Confirms Ed25519 classic transaction signing, thresholds, and multisig.
Stellar regulated-asset controls	Asset authorization and clawbacks	Confirms revocation or freeze and clawback capabilities.
Soroban application authorization	Soroban authorization and auth-entry signing	Confirms custom contract-account authentication and the separate G-account transaction-envelope role.
Paladin programmable privacy	LF Decentralized Trust Paladin project	Confirms Pente as the current EVM privacy-group continuation beyond Tessera.
Besu institutional participation	DTCC production initiative; Besu Financial Services Working Group	Separates direct Besu deployment and multi-chain production participation from working-group membership.

CLAIM FAMILY	PRIMARY SOURCE	WHY IT MATTERS
Stellar institutional activity	Stellar institutional solutions ; Stellar official press releases ; DTCC planned Stellar connection	Supports named live deployments, validator roles, custody services, regulated-market integrations, and explicitly labeled future connectivity.

CONTINUE ETERNAX RESEARCH

For deeper diligence, read the [Post-Quantum Signature Security Ranking 2026](#), the [PQC Risk Framework for Institutions](#), the [PQ Exposure Map for Institutional Crypto and Tokenized Assets](#), and [Why EternaX](#).

INSTITUTIONAL POST-QUANTUM FAQ

Post-Quantum Blockchain, Tokenization, Custody, and EternaX FAQs

65 primary-source-aligned answers covering Ethereum, Hyperledger Besu, Solana, Stellar, Canton Network, stablecoins, tokenized funds, RWAs, custody, MPC, CBOM, Executive Order 14412, NIST standards, and EternaX. Each answer leads with the conclusion, then explains the technical dependency and institutional consequence.

Last reviewed: July 24, 2026 Authors: Paarrthhh Birla, Dr. Chen Feng, Dariia Porechna

[Verify claims and sources](#)

START WITH THE DECISIONS INSTITUTIONS CANNOT DEFER

Are Ethereum, Besu, Solana, Stellar, or Canton fully post-quantum safe in 2026? READ ANSWER	Will a chain's post-quantum roadmap automatically protect institutional products? READ ANSWER
What would a post-quantum CBOM reveal about Ethereum, Besu, Solana, Stellar, and Canton? READ ANSWER	What is EternaX? READ ANSWER
	Can EternaX harden products on Ethereum, Besu, Solana,

What is crypto agility, and why is EternaX signature agnostic?

[READ](#) [ANSWER](#)

Stellar, or Canton without replacing the underlying chain?

[READ](#) [ANSWER](#)

What should institutional issuers, custodians, and settlement participants do now?

[READ](#) [ANSWER](#)

[Quantum Threat](#)

[Regulation and CBOM](#)

[Ethereum and ERC Standards](#)

[Solana](#)

[Canton Network](#)

[Custody and Tokenization](#)

[Hyperledger Besu](#)

[Stellar](#)

[EternaX](#)

QUANTUM THREAT

Quantum Computing and Blockchain Security

Direct answers on Shor's algorithm, ECDSA, Ed25519, SLH-DSA, migration timing, and what a chain upgrade can and cannot repair.

Primary evidence: NIST FIPS 205, NIST FIPS 204, and the report source register.

Can a quantum computer break blockchain cryptography?

A sufficiently capable, fault-tolerant quantum computer could break widely deployed public-key schemes such as ECDSA and Ed25519 by using Shor's algorithm.

That would threaten transaction authorization, validator or node identities, administrative keys, custody controls, and any application logic that trusts those signatures. It would not automatically break hash functions, rewrite finalized history, or compromise every blockchain component at once. The correct assessment is layer-specific: identify which signatures, encryption schemes, keys, contracts, and operational dependencies are quantum-vulnerable.

When could quantum computers threaten Bitcoin and Ethereum?

No authoritative source can give a reliable date for a cryptanalytically relevant quantum computer.

Institutions should therefore plan against three variables: the confidentiality or asset-control lifetime, the time required to inventory and migrate the stack, and the risk tolerance for exposed public keys. Harvest-now-decrypt-later applies to encrypted data collected today. Signature risk is different: once a capable quantum computer exists, exposed elliptic-curve public keys could become a route to forged authorization.

Are Ethereum, Besu, Solana, Stellar, or Canton fully post-quantum safe in 2026?

No environment reviewed in this report is end-to-end post-quantum safe by default.

Ethereum and conventional Besu deployments rely on elliptic-curve transaction authentication; Solana and Stellar classic transactions rely on Ed25519; Canton currently documents classical signing and encryption schemes. Solana has published Falcon research and early implementations, while Ethereum has draft signature-agility proposals and Stellar contract accounts support custom authorization. These are important migration tools, but they are not equivalent to a completed network, custody, wallet, validator, application, and governance migration.

Is Bitcoin post-quantum safe today?

No.

Bitcoin currently relies on secp256k1 ECDSA and, for Taproot, secp256k1 Schnorr signatures. Both are elliptic-curve signature schemes vulnerable to Shor's algorithm once a sufficiently capable quantum computer exists. Exposure differs by output type and spending history: some public keys are revealed only when spent, while Taproot output keys are visible in the output itself. Bitcoin can adopt new rules through consensus, but migration would still require new output types, wallet and custody support, and a policy for funds whose public keys are already exposed.

What is SLH-DSA, formerly SPHINCS+, and why is it relevant to blockchains?

SLH-DSA is NIST's stateless hash-based digital-signature standard, published as FIPS 205 in August 2024 and derived from SPHINCS+.

Its principal strategic value is assumption diversity: security is based on hash-function properties rather than the lattice assumptions used by ML-DSA or the still-developing FN-DSA standard. The trade-off is large signatures and non-trivial signing or verification cost. Whether SLH-DSA is appropriate for every transaction, only high-assurance roots, or a hybrid design depends on throughput, storage, HSM support, key frequency, and the required assurance horizon.

Would Falcon alone make Solana fully post-quantum safe?

No.

Solana Foundation reporting says Anza and Firedancer independently converged on Falcon and produced early implementations. Falcon could provide a compact post-quantum signature path if standardized, integrated, activated, and supported across the ecosystem. It would not by itself migrate existing Ed25519 accounts and authorities, validators, wallets, custody systems, hardware signers, programs that verify classical signatures, fee-paying flows, or issued assets. NIST has selected Falcon for FN-DSA, but FIPS 206 remains in development as of July 2026.

Can an existing blockchain be upgraded to post-quantum safety?

Yes, but only through a coordinated, multi-layer migration.

Protocol rules can add new signature schemes or account types, yet existing products may still depend on classical administrator keys, immutable verifier logic, fixed signature interfaces, custody workflows, hardware support, bridges, relayers, and historical encrypted data. The difficulty varies by architecture. The defensible question is not whether a hard fork is theoretically possible, but which dependencies can be upgraded in place, which require replacement, and which require asset or identity migration.

Will a chain's post-quantum roadmap automatically protect institutional products?

No.

A base-layer roadmap does not automatically migrate the product stack. Ethereum applications may retain immutable contracts, fixed permit interfaces, and classically controlled roles. Besu networks need coordinated changes across native transactions, QBFT validators, external signers, HSMs, custody, and applications. Solana must address existing Ed25519 accounts, authorities, validators, wallets, and programs. Stellar contract-account flexibility does not automatically migrate classic envelopes, issuer accounts, fee payers, validators, anchors, or custody. Canton must address supported scheme sets, namespace-root continuity, operational keys, and historical confidentiality.

REGULATION AND CBOM

Executive Order 14412, NIST, and Cryptographic Inventories

What U.S. post-quantum requirements mean for agencies, contractors, custodians, infrastructure vendors, and institutional digital-asset diligence.

Primary evidence: Executive Order 14412, NIST IR 8547, and claims and sources.

Which U.S. post-quantum requirements should digital-asset institutions track?

Track Executive Order 14412, NSM-10, OMB M-23-02, the Quantum Computing Cybersecurity Preparedness Act, NSA CNSA 2.0, NIST FIPS 203, 204, and 205, NIST migration guidance, and forthcoming CISA and NIST CBOM guidance.

The exact legal obligation depends on whether the organization is a federal agency, a covered contractor, part of a regulated supply chain, or a critical-infrastructure operator. For digital assets, the practical requirement is a chain-aware cryptographic inventory covering transaction signatures, validators, account models, smart-contract verification, custody, HSMs, wallets, bridges, identity, privacy, and upgrade authority.

What is Executive Order 14412, and why does it matter for digital assets?

Executive Order 14412, signed on June 22, 2026, accelerates the U.S.

Federal Government's migration to NIST-approved post-quantum cryptography. It sets deadlines for high-value assets and high-impact systems, directs public CBOM guidance, initiates a NIST migration pilot, and directs proposed FAR rules for covered contractors. It does not automatically regulate every blockchain company. Its significance is the procurement and diligence cascade: agencies, contractors, banks, custodians, infrastructure providers, and software vendors will increasingly need to identify what cryptography is deployed, where it is used, and how it will migrate.

What are the key deadlines in Executive Order 14412?

Within 30 days of June 22, 2026, agency heads must identify a PQC migration lead.

Within 90 days, OMB must issue guidance requiring agencies to review high-value assets and high-impact systems, transition key establishment by December 31, 2030, transition digital signatures by December 31, 2031, and submit migration plans. Within 180 days, NIST must initiate a pilot to finish by December 31, 2027; the FAR Council must publish a proposed contractor-compliance rule; and the cryptographic-module validation process must be reviewed for acceleration. Within 270 days, CISA and NIST must publish minimum CBOM guidance, and the FAR Council must propose cryptographic-vulnerability disclosure requirements. NIST's broader 2035 transition target is separate guidance, not an EO 14412 deadline.

How can Executive Order 14412 affect private blockchain and custody infrastructure?

Primarily through procurement, covered federal contracts, critical-infrastructure assistance, vendor diligence, cryptographic inventory requests, and vulnerability-disclosure expectations.

The order does not directly impose the same duties on every private blockchain company. However, a provider serving agencies, contractors, regulated institutions, custodians, or financial-market infrastructure should expect increasing requests for NIST-aligned algorithms, migration plans, validated modules, residual-risk disclosure, and machine-readable cryptographic inventories.

What would a post-quantum CBOM reveal about Ethereum, Besu, Solana, Stellar, and Canton?

A chain-aware post-quantum CBOM produces a clear PASS or FAIL assessment for the deployed cryptographic control plane.

For the environments reviewed here, it would identify classical transaction or account signatures, validator and node keys, application verifiers, custody and HSM dependencies, wallet and relay keys, issuer and administrator controls, and any classical encryption protecting confidential data. It would also record compensating controls and migration capabilities, such as smart-account verification, contract-account authorization, alternate signer types, or draft protocol proposals. For the environments reviewed here, Ethereum, Besu, Solana, Stellar, and Canton FAIL; EternaX PASSES.

ETHEREUM AND ERC STANDARDS

Ethereum, ERC-3643, ERC-2612, Permit2, Stablecoins, and Tokenized Funds

Application-layer exposure across accounts, ecrecover, permits, identity claims, immutable contracts, regulated securities, stablecoins, and tokenized funds.

Primary evidence: ERC-2612, ERC-1271, and Ethereum and ERC sources.

Can Ethereum hard fork to post-quantum cryptography and fully fix ECDSA exposure?

Not fully.

A hard fork can change future protocol rules, but it cannot retroactively make existing application-layer infrastructure quantum safe. Ethereum has five layers of ECDSA exposure: address derivation, transaction signing, the ecrecover precompile, immutable smart contracts, and frozen permit interfaces. Address derivation exposes public keys once an EOA transacts. Transaction signing requires coordination across clients, validators, wallets, L2s, and infrastructure providers. ecrecover is a protocol-level primitive. Immutable contracts cannot be patched. ERC-2612 permit interfaces cannot accept PQ signatures because their ABI is ECDSA-specific. A hard fork may protect part of future transaction validation, but it does not rewrite the institutional application stack.

Why does one Ethereum transaction create post-quantum exposure?

An Ethereum externally owned account is derived from a secp256k1 public key.

Before an account sends its first transaction, the public key is not visible onchain, only the address is visible. Once the account signs and sends a transaction, the signature reveals enough information for the public key to be recovered. Under classical assumptions this is acceptable. Under a cryptographically relevant quantum computer, elliptic-curve public keys become a path to private-key recovery through Shor's algorithm. That means any Ethereum address with an exposed public key becomes materially different from a never-used address. For institutions, this matters because operational wallets, admin keys, signer keys, custody keys, and treasury addresses are usually active, not dormant.

Is ERC-3643 quantum safe?

ERC-3643 is not inherently tied to one signature algorithm, so the specification itself should not be called ECDSA-only.

A conventional deployment can nevertheless remain materially post-quantum exposed because owners, agents, investors, claim issuers, identity registries, compliance controllers, recovery authorities, and proxy administrators are commonly controlled through classical Ethereum accounts or ECC-backed governance. Claim-signature security is implementation-dependent. A PQ claim verifier alone does not migrate the surrounding accounts, validators, custody, and upgrade controls.

When does ONCHAINID create ECDSA-based ERC-3643 exposure?

ONCHAINID-style identities contain claims signed by trusted issuers, but the applicable signature scheme depends on the implementation.

Where claim validation uses ECDSA or management keys are controlled by ECDSA accounts, a quantum compromise of the relevant issuer or identity-management key could enable forged eligibility claims or unauthorized identity changes. The accurate conclusion is implementation-specific: an ECDSA-only claim path is exposed, while a PQ claim path managed by an ECDSA owner is only partially migrated.

Who should assess ERC-3643 and ONCHAINID post-quantum exposure?

Any issuer, transfer agent, identity provider, claim issuer, custodian, wallet provider, compliance operator, exchange, or infrastructure vendor supporting an ERC-3643 deployment should assess the implementation.

Association membership or ecosystem participation alone does not prove that an institution runs an exposed production system. The diligence question is specific: which accounts control owners, agents, registries, claims, recovery, compliance, and upgrades; which signature schemes validate claims; and which network, custody, and HSM keys ultimately authorize those actions?

Can the existing ERC-2612 permit interface accept post-quantum signatures?

Not in a scheme-agnostic way.

The canonical interface encodes a signature as v, r, and s, matching Ethereum's secp256k1 convention. Most post-quantum signatures do not fit that representation. An upgradeable token can add a new authorization function, support contract-wallet validation through a different path, or deploy a replacement interface using opaque bytes and an explicit algorithm identifier. It should not claim that the original ERC-2612 ABI itself has become post-quantum signature-agile.

Can a stablecoin issuer retain ERC-2612 and still become fully post-quantum safe?

Not for the ERC-2612 authorization path itself.

An issuer can disable or deprecate permit, restrict its use, add a separate signature-agile authorization method, migrate users to smart accounts, or issue an upgraded token version. Existing integrations may continue to call the original v, r, s interface, so a complete migration also requires wallet, custody, relayer, paymaster, exchange, and application changes. The relevant exposure exists only where ERC-2612 is implemented and used.

Is USDC end-to-end post-quantum safe on Ethereum or Solana?

No, not as an end-to-end property of the current rails.

On EVM networks, USDC authorization and administrative workflows can involve secp256k1 accounts and EIP-2612, EIP-3009, or external Permit2 integrations, depending on the chain and application. On Solana, USDC depends on Solana's current account, transaction, authority, wallet, custody, and token-program environment. Circle can upgrade some contract logic and operational controls, but full post-quantum safety also requires migration of the underlying chain authorization, user and issuer keys, custody, wallets, integrations, and any fixed classical signature interfaces.

Is Uniswap Permit2 post-quantum safe?

Permit2's deployed authorization model relies on Ethereum-style signatures and contract verification that were designed for classical keys.

The canonical deployment is intentionally non-upgradeable, so it cannot be patched in place to add a new signature format. Applications can stop trusting it, deploy replacement approval infrastructure, use contract-wallet validation where supported, and migrate integrations. The precise risk depends on the signature path used and the exposure of the authorizing key; the durable remediation is replacement and ecosystem migration, not an Ethereum client update alone.

What happens when an immutable contract contains quantum-vulnerable verification logic?

Its bytecode cannot be patched in place.

If authorization or verification is hard-coded to a quantum-vulnerable scheme, the contract will continue to apply that rule for as long as it is used. This does not mean every immutable contract is automatically exploitable or that all pool logic directly verifies signatures. Owners and protocols can remove approvals, stop integrations, deploy replacements, migrate liquidity or assets, and change surrounding account controls. The institutional problem is the coordination and residual exposure created by code that cannot itself be upgraded.

What should an ERC-3643 issuer do now about post-quantum risk?

Start with an implementation-specific cryptographic inventory: token owner, agents, investors, identity-registry administrators, trusted issuers, claim topics, claim-signature schemes, compliance controllers, recovery authorities, proxy administrators, transaction signers, custody, validators, and HSM paths.

Classify each control as classical, hybrid, PQ-capable, or unverifiable. Then design application-level signature agility and a separate network-layer migration plan. Do not describe an ERC-3643 deployment as end-to-end PQ-safe merely because one claim verifier accepts a PQ signature.

SOLANA

Solana Ed25519, Falcon, Token Authorities, and Migration Risk

What Falcon can address, what remains outside a signature upgrade, and why token, wallet, validator, and authority migration must be evaluated separately.

Primary evidence: Solana quantum-readiness update and the Solana source register.

Where does Solana inherit Ed25519 post-quantum exposure?

Solana currently uses Ed25519 for standard transaction signatures, and public keys serve directly as account addresses.

Operational authority can also sit in transaction signers, mint and freeze authorities, program-upgrade authorities, stake and vote accounts, wallets, custody systems, and validator operations. A sufficiently capable quantum computer would threaten Ed25519. Solana has taken substantive preparatory steps, including Project Eleven testnet work and early Falcon implementations from Anza and Firedancer, but these are readiness measures rather than a completed mainnet and ecosystem migration.

What can a Solana Winternitz-style vault protect?

A Winternitz-style vault can use hash-based one-time authorization to protect a specific asset-control path, particularly for low-frequency or pre-planned withdrawals.

It is not a replacement for Solana's default transaction scheme. It does not automatically migrate validators, ordinary accounts, fee-paying source accounts, token authorities, program-upgrade keys, wallets, custodians, or applications. One-time-signature designs also require strict key-use and rotation discipline. It should be described as a targeted containment mechanism, not system-wide post-quantum safety.

How difficult is post-quantum migration for Solana token infrastructure?

The challenge is ecosystem-wide rather than a claim that every token program is permanently unfixable.

Widely used token programs and deployed assets rely on existing account and authority conventions. A new or extended program can introduce different authorization patterns, but issuers, wallets, exchanges, custodians, DeFi applications, indexers, and users must adopt it and move authority or asset flows. Legacy programs and existing keys may remain active during transition. Institutions should inventory the exact token program, loader and upgrade status, mint and freeze authorities, multisig configuration, and custody path for each asset.

Does Solana's Alpenglow consensus redesign solve post-quantum security?

No.

Alpenglow is a consensus and performance redesign, not a complete cryptographic migration. Faster finality or a different consensus protocol does not automatically replace Ed25519 transaction signatures, user and authority keys, validator operational keys, wallet and custody integrations, token-program controls, or application-level signature verification. Post-quantum readiness must be evaluated separately across consensus, transaction authorization, accounts, programs, and operational infrastructure.

CANTON NETWORK

Canton Identity, Signing, Encryption, and Settlement Privacy

Post-quantum constraints across namespace roots, delegated keys, signing schemes, ECIES-based confidentiality, synchronizers, and long-lived institutional data.

Primary evidence: [Digital Asset key management](#) and [Canton documentation sources](#).

Is Canton Network end-to-end post-quantum safe today?

Not by default.

Current Canton documentation lists classical signing schemes such as Ed25519 and ECDSA variants, and classical asymmetric-encryption options including ECIES over P-256. Canton supports key rotation and delegation for many operational keys, but the namespace root is structurally tied to its key fingerprint and cannot simply be rolled without creating a new namespace. A complete migration would require supported post-quantum schemes, synchronizer compatibility, KMS and custody support, operational-key migration, namespace-continuity design, and a plan for already-captured encrypted traffic.

Why is Canton's namespace root a post-quantum migration constraint?

A Canton namespace is identified by the fingerprint of its root signing key.

Digital Asset documentation states that the root namespace key cannot be rolled because a new key would define a new namespace. Operators can keep the root offline and delegate authority to rotatable intermediate keys, which substantially reduces day-to-day exposure. However, replacing the root trust anchor with a different cryptographic scheme raises an identity-continuity problem: the system needs a governed way to preserve or transition identifiers, delegations, parties, references, and legal or operational mappings without treating the new key as an unrelated namespace.

What is Canton's harvest-now-decrypt-later exposure?

Canton uses confidentiality mechanisms that can involve classical public-key encryption, including documented ECIES P-256 configurations.

An adversary able to record encrypted traffic or stored ciphertext today could attempt to decrypt it later if a cryptanalytically relevant quantum computer becomes available and the ciphertext remains obtainable. The severity depends on the actual scheme, session-key design, data captured, retention period, network access, and confidentiality lifetime. Future migration protects new traffic; it cannot recall ciphertext already copied by an adversary.

What should a Canton participant do about post-quantum signing and privacy risk?

Inventory the configured signing and encryption schemes, namespace-root and delegated keys, protocol and authentication keys, synchronizer requirements, KMS capabilities, certificate and TLS dependencies, encrypted-data retention, and the confidentiality horizon of transaction information.

Separate root-identity continuity from ordinary key rotation, and separate future signing migration from historical ciphertext exposure. Ask the operator or vendor for a scheme-agility roadmap, interoperability plan, downgrade controls, and treatment of data already encrypted under classical public-key assumptions.

CUSTODY AND TOKENIZATION

MPC, Custody, CBOM, DeFi, Tokenized Funds, and Institutional Action

Board-level answers on where algorithm risk survives operational controls and how institutions should inventory, classify, and remediate exposure.

Primary evidence: [claims and sources](#), [PQC Risk Framework](#), and [PQ Exposure Map](#).

Can MPC custody make ECDSA or Ed25519 assets post-quantum safe?

No.

MPC changes key management, not the underlying signature scheme. An MPC wallet can split control of an ECDSA or Ed25519 private key across multiple parties, reducing single-point custody risk under classical assumptions. But if the final onchain signature is ECDSA or Ed25519, the asset still depends on a quantum-vulnerable public-key scheme. Once a cryptographically relevant quantum computer can recover private keys from exposed public keys, distributing the key shares does not make the signature algorithm quantum safe. MPC is valuable custody infrastructure. It is not a substitute for post-quantum signatures, post-quantum address design, and post-quantum verification logic.

Does MPC custody make Fireblocks-supported assets post-quantum safe?

Not automatically.

Fireblocks and other MPC custody platforms can materially reduce single-key and operational risk, but MPC does not change the signature algorithm ultimately accepted by the blockchain or application. If an asset movement, permit, validator action, or administrative function is authorized by ECDSA or Ed25519, that authorization remains dependent on the classical scheme. A complete assessment must distinguish Fireblocks' internal controls from the chain, token, smart-contract, wallet, bridge, and external-signature dependencies of the specific workflow.

How should a tokenized fund such as BUIDL assess post-quantum exposure?

At the infrastructure level, a tokenized fund inherits the cryptography of each chain, wallet, custodian, transfer-agent workflow, administrator account, bridge, liquidity venue, and smart contract it uses.

The token interface itself may be portable or upgradeable, while surrounding authorization paths remain classical. This is not a claim that BUIDL or any named fund is presently compromised. It is a diligence requirement: map every representation and control path, then distinguish upgradeable contracts from immutable integrations and classically controlled operational roles.

How can quantum computing affect DeFi and institutional tokenization?

The common exposure is not 'blockchain' in the abstract; it is classical public-key cryptography embedded across user accounts, validators, custody, issuer roles, permits, identity claims, upgrade authorities, bridges, and encrypted settlement data.

Ethereum and Besu commonly rely on secp256k1, Solana and Stellar classic transactions use Ed25519, and Canton documents classical signing and encryption options. Failure at one authorization or confidentiality layer can propagate into tokenized funds, stablecoins, regulated securities, collateral, and settlement workflows even when the token contract itself is technically sound.

What is a Cryptographic Bill of Materials, or CBOM, for blockchain products?

A Cryptographic Bill of Materials is an inventory of the cryptographic algorithms, libraries, keys, and dependencies used by a system.

For blockchain products, a CBOM cannot stop at the issuer's backend. It must include the underlying chain, signature algorithm, address derivation method, precompiles, smart-contract standards, identity systems, custody signing flows, wallet integrations, hardware security modules, MPC providers, encrypted settlement data, and immutable contracts. A tokenized product that says it is institution-grade but cannot name its ECDSA, Ed25519, ECIES, permit, and ONCHAINID dependencies is not ready for serious post-quantum diligence.

How should post-quantum throughput impact be reported responsibly?

There is no universal percentage.

Results depend on the algorithm and parameter set, signature and public-key sizes, transaction format, verification implementation, block and message limits, batching, hardware, HSM support, consensus, network topology, and whether the migration covers transactions, validators, applications, or all three. Publish measured test conditions, software versions, hardware, workload, latency percentiles, bandwidth, storage growth, and security parameter. Label modeled results as models and prototypes as prototypes; do not convert them into a production-wide claim.

Can tokenized funds continue using Ethereum while becoming fully post-quantum safe?

Only partially.

Some standards, including ERC-20, ERC-721, ERC-4626, ERC-4337, and newer signature-agnostic standards, can be ported or adapted more cleanly. But full post-quantum safety requires more than a clean token interface. It requires PQ-safe wallets, PQ-safe custody flows, PQ-safe admin controls, PQ-safe permit or approval mechanisms, PQ-safe identity and compliance logic, and avoidance of immutable classical contracts. A tokenized fund can reduce exposure on Ethereum, but it cannot make the full legacy environment disappear. For new issuance, the cleaner strategic choice is to separate future institutional products from avoidable cryptographic debt.

Which standards are not the main problem and why does this report exclude them?

The report distinguishes standards that explicitly encode classical signatures from those that are cryptographically neutral or signature-agile.

ERC-2612 is explicitly secp256k1-shaped. ERC-20, ERC-721, ERC-4626, ERC-1967, ERC-3643, and ERC-7943 do not universally mandate ECDSA, but conventional deployments can inherit classical account and administrator risk. ERC-1271 and ERC-4337 can enable custom authorization, but do not migrate the underlying network. This classification avoids claiming that every ERC is intrinsically broken.

What should institutional issuers, custodians, and settlement participants do now?

Institutions should stop treating post-quantum migration as a protocol-team problem.

The immediate task is a cryptographic exposure map covering every chain, signature scheme, address model, smart-contract standard, permit flow, custody provider, MPC or HSM dependency, compliance verifier, immutable contract, and encrypted settlement path used by the product. Classify each dependency as clean-port, replaceable, coordination-heavy, or non-upgradeable; then assign an owner, migration trigger, budget, and deadline. Existing products may need containment and staged hardening. New products should use rails where post-quantum security and cryptographic agility are native. EternaX provides that new-issuance path and hardens critical authorization across legacy rails.

HYPERLEDGER BESU

Hyperledger Besu, Permissioned EVM, QBFT, and PQ Migration

Why permissioning does not change cryptographic security and what a real Besu migration must cover across transactions, validators, signers, HSMs, custody, and applications.

Primary evidence: Besu elliptic-curve configuration, QBFT documentation, and Besu sources.

What is Hyperledger Besu, and why is it analyzed separately from Ethereum?

Besu is an Ethereum execution client.

It can participate in public Ethereum or run private and consortium networks using configurations such as QBFT, known validators, permissioning, and enterprise-specific gas and governance policies. On public Ethereum, its protocol-level behavior follows Ethereum. In private mode, governance and consensus differ, but the EVM, Ethereum transaction model, address conventions, tooling, and application standards can preserve many of the same cryptographic dependencies. It is therefore a distinct institutional migration case, not a separate cryptographic family.

Is a standard Hyperledger Besu deployment end-to-end post-quantum safe today?

No.

Standard Besu transaction and account authentication remains elliptic-curve based. Private networks can configure secp256r1 in early-access mode instead of secp256k1, but both are classical elliptic curves. Full migration must cover transaction authentication, QBFT validator keys, external signers, HSMs, custody, privileged smart-contract roles, wallets, relayers, tooling, TLS and node authentication where applicable, and any separate privacy or middleware layer. A PQ verifier inside one contract protects only that authorization decision.

Does permissioning make a Besu network post-quantum safe?

No.

Permissioning controls who may connect, submit transactions, or validate. It can reduce the attack surface and make governance more coordinated, but it does not change the mathematical security of the signatures or encryption used by approved participants. A permissioned network can still depend on quantum-vulnerable transaction keys, validator keys, administrator accounts, custody systems, TLS certificates, and application signatures.

Can ERC-1271 or ERC-4337 make a Besu application post-quantum safe?

They can make selected smart-account authorization paths signature-agile.

ERC-1271 lets a contract define signature validity, and ERC-4337 lets a smart account define UserOperation validation. Neither automatically changes Besu's native transaction authentication, QBFT validator keys, bundler and relayer accounts, network authentication, custody, HSMs, or other classically controlled contracts. The accurate claim is application-level PQ authorization, unless the complete network and operational stack has also migrated.

Does Besu natively support standardized post-quantum transaction signing?

Not as a standard production transaction scheme as of July 2026.

Ethereum proposals such as EIP-7932 and EIP-8051 address alternative algorithms and ML-DSA verification, but remain Draft. A verifier contract, plugin, relayer, meta-transaction system, or bespoke Besu fork can demonstrate or deploy a selected PQ path, but that capability is deployment-specific. It must not be described as upstream, network-wide Besu support unless the transaction, validator, tooling, and interoperability layers actually implement it.

STELLAR

Stellar Ed25519, Multisig, Soroban, Issuer Controls, and Asset Contracts

Where Stellar classic accounts remain exposed, what Soroban custom authorization can protect, and why issuer, fee-payer, validator, anchor, and custody migration still matters.

Primary evidence: [Stellar signatures and multisig](#), [issuer controls](#), and [Soroban authorization](#).

Is Stellar end-to-end post-quantum safe today?

No.

Stellar documentation identifies Ed25519 as the standard signature scheme for classic transactions, although the protocol also supports alternate signer types such as pre-authorized transactions and hash(x). Thresholds and multisig improve governance, while Soroban contract accounts provide programmable authorization. None of those features by itself migrates classic transaction envelopes, issuer and distribution accounts, validators, wallets, anchors, exchanges, custody systems, or fee-paying source accounts to a standardized post-quantum signature scheme.

Does Stellar multisig provide post-quantum protection?

Not when the required signers all rely on the same quantum-vulnerable public-key family.

Thresholds and multiple signers can reduce single-key compromise risk, separate duties, and preserve control when one signer is unavailable. Against a future adversary capable of attacking Ed25519 at scale, multiple Ed25519 signers add operational separation but not cryptographic assumption diversity. A defensible design needs at least one genuinely post-quantum authorization path, plus downgrade prevention and a migration plan for the envelope and fee-paying layers.

Can Soroban contract accounts verify post-quantum signatures?

In principle, yes.

A Soroban contract account implements custom `__check_auth` logic and can validate a user-defined authorization format, subject to host capabilities, resource limits, implementation correctness, and auditability. This can protect the contract-account authorization path. Stellar documentation also makes clear that C-accounts cannot sign transaction envelopes or pay fees directly; a separate G-account must submit the transaction and pay XLM fees. Therefore, PQ contract authorization does not by itself migrate the envelope source, fee payer, validator, wallet, custody, or ecosystem layers.

Which Stellar issuer controls are high-impact post-quantum concentration points?

Issuing-account and distribution-account control, authorization flags, trustline authorization or revocation, clawback, signer and threshold changes, treasury movement, and administrative operations are high-impact surfaces.

These controls are legitimate features for regulated assets. The risk arises when the accounts and signers authorized to exercise them rely only on quantum-vulnerable keys. Institutions should also inventory anchors, custodians, exchanges, relayers, and recovery procedures that can influence or depend on those accounts.

Does a Stellar Asset Contract make the underlying asset fully post-quantum safe?

No.

A Stellar Asset Contract exposes a classic asset to Soroban and can participate in programmable contract workflows. A contract account can add custom authorization for selected holders or applications. The underlying classic asset, issuer and distribution accounts, trustline controls, transaction-envelope source, G-account fee payer, validators, wallets, anchors, custody, exchanges, and other integrations may still use classical authorization. The contract layer can improve selected paths; it does not automatically complete a network-wide migration.

ETERNAX

EternaX, PQ-Native Issuance, Cryptographic Agility, and Institutional Deployment

How EternaX solves cryptographic migration debt across issuance, custody authorization, token controls, and institutional settlement.

EternaX architecture: [Why EternaX](#), [Post-Quantum Signature Ranking](#), and [PQC Risk Framework](#).

What is a PQ-native blockchain?

A PQ-native blockchain is infrastructure built around post-quantum cryptography from genesis, not a classical chain trying to retrofit PQ later.

It uses post-quantum signature assumptions for accounts, transaction authorization, verifier logic, and system architecture from the start. It avoids legacy ECDSA or Ed25519 address debt, frozen permit interfaces, immutable classical verifier contracts, and historical privacy systems based on quantum-vulnerable elliptic curves. The point is not simply adding one PQ algorithm. The point is removing inherited cryptographic debt across the full stack: keys, addresses, signatures, contracts, standards, custody flows, settlement privacy, and governance dependencies.

Why is PQ-native infrastructure safer than migrating Ethereum, Besu, Solana, Stellar, or Canton later?

PQ-native infrastructure avoids coordinated migration of already-deployed economic systems.

Ethereum carries immutable contracts and frozen interfaces. Besu adds consortium-wide transaction, validator, signer, HSM, custody, and application coordination. Solana carries runtime, account-authority, and deployed-program dependencies. Stellar combines classic Ed25519 accounts, issuer controls, G-account envelope signing, validators, and ecosystem integrations, despite Soroban custom-auth flexibility. Canton adds identity continuity and historical privacy exposure. A native architecture starts with the target cryptographic model before liquidity, custody, compliance, and governance dependencies become migration liabilities. That is the architectural thesis behind EternaX: prevent cryptographic debt before institutions are forced to unwind it.

How does EternaX address post-quantum risk structurally rather than as a patch?

EternaX addresses the problem at the architecture layer, not through a single verifier, wrapper, or relayer.

EternaX is post-quantum-native institutional market infrastructure with accounts, transaction authorization, verifier interfaces, institutional application standards, and cryptographic agility operating as one system from inception. It avoids fixed ECDSA permit interfaces, legacy EVM verifier debt, Solana Ed25519 authority migration, Stellar classic-account dependencies, and Canton root-identity and historical-encryption constraints.

What is EternaX?

EternaX is post-quantum market infrastructure for stablecoin issuance, RWA tokenization, and institutional settlement.

It is a PQ-native, signature-agnostic, crypto-agile environment rather than a classical chain with a late cryptographic retrofit. The architecture treats accounts, transaction authorization, verifier logic, compliance modules, custody integrations, and settlement workflows as one migration surface. This gives institutions a clean path for new issuance while preserving the option to harden selected authorization flows on existing rails.

What institutional problem does EternaX solve?

EternaX addresses cryptographic migration debt.

Institutional products on Ethereum, Besu, Solana, Stellar, and Canton can depend on custody keys, administrator roles, permit flows, compliance controls, validators, wallets, HSMs, and privacy systems that a chain roadmap does not automatically migrate. EternaX moves post-quantum security and cryptographic agility to the beginning of the product lifecycle, before liquidity, legal rights, custody operations, and governance become expensive to change. EternaX serves long-duration stablecoins, tokenized deposits, securities, funds, collateral, and settlement records.

Is EternaX a custody provider or a replacement for existing custody?

No.

EternaX is not a custody provider. It is infrastructure that enables issuers, custodians, HSM providers, wallets, policy engines, and settlement operators to use post-quantum or hybrid authorization paths. Institutions retain their custody governance and operational controls while EternaX upgrades the cryptographic authorization layer across custody, HSM, wallet, policy-engine, and settlement workflows. For new issuance, EternaX provides a PQ-native rail instead of asking custody providers to compensate indefinitely for a classically signed network.

Can EternaX harden products on Ethereum, Besu, Solana, Stellar, or Canton without replacing the underlying chain?

Yes. EternaX hardens critical authorization surfaces on existing chains and provides PQ-native issuance where legacy cryptographic debt cannot be rewritten.

EternaX protects custody approvals, administrator controls, claim issuance, smart-account validation, treasury actions, and settlement authorization on existing rails. Non-rewriteable legacy dependencies move to EternaX through PQ-native issuance. The result is a complete two-track strategy: harden existing authorization and eliminate inherited debt for new products.

What is crypto agility, and why is EternaX signature agnostic?

Crypto agility means institutions can introduce, select, combine, rotate, and retire approved cryptographic schemes without redesigning the asset or repeating an ecosystem-wide migration.

Signature agnostic does not mean accepting arbitrary signatures. EternaX authorization is not hard-coded to one algorithm or fixed signature shape. Each authorization carries an explicit algorithm and version identifier, is checked against institutional policy and risk-tier allowlists, and is routed to the approved verifier. SLH-DSA under FIPS 205 remains the conservative anchor for roots of trust, issuance, treasury, recovery, and long-duration controls. ML-DSA, FN-DSA, and other approved schemes serve operational paths according to performance, HSM support, jurisdictional policy, and risk tier. EternaX includes downgrade resistance, hybrid transition, key and algorithm rotation, retirement procedures, CBOM visibility, and auditable governance.

Which post-quantum signature schemes does EternaX support?

EternaX is crypto-agile and does not depend on one permanent signature scheme.

EternaX supports SLH-DSA under FIPS 205, ML-DSA under FIPS 204, FN-DSA, and other approved schemes through governed policy. Scheme selection follows risk tier, performance, HSM support, jurisdiction, key frequency, and assurance horizon. The critical controls are explicit algorithm identifiers, upgrade governance, and downgrade resistance.

Why does EternaX prioritize SLH-DSA for high-assurance institutional authorization?

SLH-DSA is the conservative high-assurance option because its security rests on hash-function assumptions rather than a newer algebraic hardness assumption.

EternaX reserves SLH-DSA for roots of trust, treasury controls, issuance authorities, recovery, and long-duration assets while allowing other approved schemes for higher-frequency operations. That avoids the false choice between maximum cryptographic conservatism and market-scale performance. SLH-DSA anchors the highest-assurance control paths, while crypto agility assigns other approved schemes to operational paths according to performance, HSM support, jurisdiction, and risk tier.

How is EternaX different from adding a post-quantum verifier to an existing blockchain?

A verifier contract protects one authorization decision; EternaX removes classical dependencies across the authorization stack.

A post-quantum verifier on Ethereum, Besu, Stellar, or another chain does not automatically migrate native transactions, fee payers, validators, HSMs, wallets, custody, bridges, relayers, or privileged roles. EternaX treats account design, transaction format, verification, institutional standards, and operational integration as one architecture. That is the difference between adding a cryptographic feature and deploying a PQ-native market rail.

Which institutional products does EternaX serve?

EternaX serves institutional products whose control or confidentiality horizons extend beyond the current cryptographic lifecycle.

EternaX serves stablecoin issuance, tokenized deposits, RWA and security-token issuance, tokenized funds, custody authorization, collateral movement, delivery-versus-payment, and institutional settlement. It eliminates migration debt across new issuance and high-assurance control surfaces.

Why does EternaX pass a chain-aware CBOM audit?

EternaX passes because post-quantum authorization and crypto agility are native to the architecture.

Its CBOM records SLH-DSA and other approved post-quantum schemes, explicit algorithm and version identifiers, signature-agile verification, validator and account authorization, custody and HSM integration, key rotation, recovery, downgrade resistance, and algorithm retirement. Ethereum, Besu, Solana, Stellar, and Canton fail because their deployed control planes retain ECDSA, Ed25519, or other classical public-key dependencies.

Why should new stablecoins, tokenized funds, and RWAs consider PQ-native issuance now?

Because assets issued today can remain outstanding after classical signatures enter formal deprecation and migration windows.

Waiting transfers the cost into asset migration, legal re-papering, custody changes, liquidity fragmentation, wallet upgrades, exchange coordination, and multi-party governance. PQ-native issuance moves the cryptographic decision to the beginning, when architecture is still flexible and integration debt is lowest. For institutions, the relevant comparison is not only today's transaction cost; it is the total future cost and execution risk of cryptographic migration debt.

INSTITUTIONAL DECISION

Do not wait for a chain roadmap to become your product migration plan.

Map the cryptographic exposure now, harden what can remain, and move new issuance onto EternaX, where post-quantum security and cryptographic agility are native from inception.

[REQUEST AN EXPOSURE ASSESSMENT](#)

[WHY ETERNAX](#)

FOUNDING TEAM

10+ Years at the Intersection of Blockchain Infrastructure, Institutional Finance, and Post-Quantum Cryptography

The team behind EternaX combines protocol research, cryptography, distributed systems, institutional digital-assets strategy, and post-quantum market-infrastructure execution.

Dariia Porechna

CO-FOUNDER

Cryptographer and distributed systems architect; Head of Protocol, Subspace; Research Engineer, Wolfram|Alpha. Co-author, SILMARILS.

[LINKEDIN](#) [X](#)

Paarrthhh Birla

CO-FOUNDER

Ex-Polygon (VP Growth Office); Head of Partnerships, Subspace Protocol; digital-assets strategy at EYP, advised Visa and State Street; MBA, CPA.

[LINKEDIN](#) [X](#)

Dr. Chen Feng

CHIEF SCIENTIST

Associate Professor at University of British Columbia; PhD, University of Toronto; 100+ peer-reviewed papers; quantum communications, blockchain, and TEE privacy. Co-author, SILMARILS.

[LINKEDIN](#) [SCHOLAR](#)

Ready to evaluate
PQ-native
issuance for your
institution?

START A PQ-NATIVE PILOT

BOOK A CALL

Quantum-safe Settlement at Market Speed

EternaX Labs | [eternax.ai](#) | [Start a PQ-Native Pilot](#) | [Schedule an Institutional Briefing](#)