

LDD Advanced Technologies

6 Hashiloah Street

Petach

Tikva

49130

Israel



4225



Attention : Yossi Amoyal

Date : 24th December, 2024

Your reference : Smadar 62400002

Our reference : Test Report 24/21293 Batch 1

Location : Smadar 3-5 Ramat-Gan

Date samples received : 12th December, 2024

Status : Final Report

Issue : 202412240840

One sample was received for analysis on 12th December, 2024 and was scheduled for analysis. Please find attached our Test Report which should be read with notes at the end of the report and should include all sections if reproduced. Interpretations and opinions are outside the scope of any accreditation, and all results relate only to samples supplied.

All analysis is carried out on as received samples and reported on a dry weight basis unless stated otherwise. Results are not surrogate corrected.

The greenhouse gas emissions generated (in Carbon – Co2e) to obtain the results in this report are estimated as:

Scope 1&2 emissions - 1.593 kg of CO2

Scope 1&2&3 emissions - 3.764 kg of CO2

Authorised By:**Paul Boden BSc**

Senior Technical Account Manager

Please include all sections of this report if it is reproduced

Element Materials Technology

Client Name: LDD Advanced Technologies
Reference: Smadar 62400002
Location: Smadar 3-5 Ramat-Gan
Contact: Yossi Amoyal
EMT Job No: 24/21293

Report : Liquid

Liquids/products: V=40ml vial, G=glass bottle, P=plastic bottle
H=H₂SO₄, Z=ZnAc, N=NaOH, HN=HNO₃

EMT Sample No.	1-5										Please see attached notes for all abbreviations and acronyms		
Sample ID	Main												
Depth													
COC No / misc													
Containers	V HN P												
Sample Date	09/12/2024												
Sample Type	Ground Water												
Batch Number	1										LOD/LOR	Units	Method No.
Date of Receipt	12/12/2024												
Dissolved Arsenic #	<2.5										<2.5	ug/l	TM30/PM14
Dissolved Barium #	191										<3	ug/l	TM30/PM14
Dissolved Beryllium	<0.5										<0.5	ug/l	TM30/PM14
Dissolved Boron	197										<12	ug/l	TM30/PM14
Dissolved Cadmium #	<0.5										<0.5	ug/l	TM30/PM14
Dissolved Calcium #	152.4										<0.2	mg/l	TM30/PM14
Total Dissolved Chromium #	2.6										<1.5	ug/l	TM30/PM14
Dissolved Copper #	<7										<7	ug/l	TM30/PM14
Dissolved Lead #	<5										<5	ug/l	TM30/PM14
Dissolved Magnesium #	15.3										<0.1	mg/l	TM30/PM14
Dissolved Mercury #	<1										<1	ug/l	TM30/PM14
Dissolved Nickel #	9										<2	ug/l	TM30/PM14
Dissolved Potassium #	2.0										<0.1	mg/l	TM30/PM14
Dissolved Selenium #	<3										<3	ug/l	TM30/PM14
Dissolved Sodium #	66.8										<0.1	mg/l	TM30/PM14
Dissolved Vanadium #	4.6										<1.5	ug/l	TM30/PM14
Dissolved Zinc #	60										<3	ug/l	TM30/PM14
Bromide	0.78 ^{AA}										<0.05	mg/l	TM27/PM0
Fluoride	<0.3										<0.3	mg/l	TM173/PM0
Sulphate as SO4 #	63.0										<0.5	mg/l	TM38/PM0
Chloride #	241.6										<0.3	mg/l	TM38/PM0
Nitrate as NO3 #	9.5										<0.2	mg/l	TM38/PM0
Ortho Phosphate as PO4 #	<0.06										<0.06	mg/l	TM38/PM0
Hexavalent Chromium	<6										<6	ug/l	TM38/PM0
Total Dissolved Chromium III	<6										<6	ug/l	TM0/PM0
Bicarbonate Alkalinity as CaCO3 (water soluble)	205										<1	mg/l	TM75/PM0
Total Organic Carbon #	<2										<2	mg/l	TM60/PM0
Total Nitrogen	3.2										<0.5	mg/l	TM38/TM125/PM0

Element Materials Technology

Client Name: LDD Advanced Technologies
Reference: Smadar 62400002
Location: Smadar 3-5 Ramat-Gan
Contact: Yossi Amoyal
EMT Job No: 24/21293

VOC Report : Liquid

EMT Sample No.	1-5										Please see attached notes for all abbreviations and acronyms		
Sample ID	Main												
Depth													
COC No / misc													
Containers	V HN P												
Sample Date	09/12/2024												
Sample Type	Ground Water												
Batch Number	1												
Date of Receipt	12/12/2024										LOD/LOR	Units	Method No.
VOC MS													
Dichlorodifluoromethane	<2										<2	ug/l	TM15/PM10
Methyl Tertiary Butyl Ether #	<0.1										<0.1	ug/l	TM15/PM10
Chloromethane #	<3										<3	ug/l	TM15/PM10
Vinyl Chloride #	<0.1										<0.1	ug/l	TM15/PM10
Bromomethane	<1										<1	ug/l	TM15/PM10
Chloroethane #	<3										<3	ug/l	TM15/PM10
Trichlorofluoromethane #	<3										<3	ug/l	TM15/PM10
1,1-Dichloroethene (1,1 DCE) #	<3										<3	ug/l	TM15/PM10
Dichloromethane (DCM) #	<3										<3	ug/l	TM15/PM10
trans-1-2-Dichloroethene #	<3										<3	ug/l	TM15/PM10
1,1-Dichloroethane #	<3										<3	ug/l	TM15/PM10
cis-1-2-Dichloroethene #	<3										<3	ug/l	TM15/PM10
2,2-Dichloropropane	<1										<1	ug/l	TM15/PM10
Bromochloromethane #	<2										<2	ug/l	TM15/PM10
Chloroform #	<2										<2	ug/l	TM15/PM10
1,1,1-Trichloroethane #	<2										<2	ug/l	TM15/PM10
1,1-Dichloropropene #	<3										<3	ug/l	TM15/PM10
Carbon tetrachloride #	<2										<2	ug/l	TM15/PM10
1,2-Dichloroethane #	<2										<2	ug/l	TM15/PM10
Benzene #	<0.5										<0.5	ug/l	TM15/PM10
Trichloroethene (TCE) #	<3										<3	ug/l	TM15/PM10
1,2-Dichloropropane #	<2										<2	ug/l	TM15/PM10
Dibromomethane #	<3										<3	ug/l	TM15/PM10
Bromodichloromethane #	<2										<2	ug/l	TM15/PM10
cis-1-3-Dichloropropene	<2										<2	ug/l	TM15/PM10
Toluene #	<5										<5	ug/l	TM15/PM10
trans-1-3-Dichloropropene	<2										<2	ug/l	TM15/PM10
1,1,2-Trichloroethane #	<2										<2	ug/l	TM15/PM10
Tetrachloroethene (PCE) #	<3										<3	ug/l	TM15/PM10
1,3-Dichloropropane #	<2										<2	ug/l	TM15/PM10
Dibromochloromethane #	<2										<2	ug/l	TM15/PM10
1,2-Dibromoethane #	<2										<2	ug/l	TM15/PM10
Chlorobenzene #	<2										<2	ug/l	TM15/PM10
1,1,1,2-Tetrachloroethane #	<2										<2	ug/l	TM15/PM10
Ethylbenzene #	<1										<1	ug/l	TM15/PM10
m/p-Xylene #	<2										<2	ug/l	TM15/PM10
o-Xylene #	<1										<1	ug/l	TM15/PM10
Styrene	<2										<2	ug/l	TM15/PM10
Bromoform #	<2										<2	ug/l	TM15/PM10
Isopropylbenzene #	<3										<3	ug/l	TM15/PM10
1,1,1,2,2-Tetrachloroethane	<4										<4	ug/l	TM15/PM10
Bromobenzene #	<2										<2	ug/l	TM15/PM10
1,2,3-Trichloropropane #	<3										<3	ug/l	TM15/PM10
Propylbenzene #	<3										<3	ug/l	TM15/PM10
2-Chlorotoluene #	<3										<3	ug/l	TM15/PM10
1,3,5-Trimethylbenzene #	<3										<3	ug/l	TM15/PM10
4-Chlorotoluene #	<3										<3	ug/l	TM15/PM10
tert-Butylbenzene #	<3										<3	ug/l	TM15/PM10
1,2,4-Trimethylbenzene #	<3										<3	ug/l	TM15/PM10
sec-Butylbenzene #	<3										<3	ug/l	TM15/PM10
4-Isopropyltoluene #	<3										<3	ug/l	TM15/PM10
1,3-Dichlorobenzene #	<3										<3	ug/l	TM15/PM10
1,4-Dichlorobenzene #	<3										<3	ug/l	TM15/PM10
n-Butylbenzene #	<3										<3	ug/l	TM15/PM10
1,2-Dichlorobenzene #	<3										<3	ug/l	TM15/PM10
1,2-Dibromo-3-chloropropane	<2										<2	ug/l	TM15/PM10
1,2,4-Trichlorobenzene	<3										<3	ug/l	TM15/PM10
Hexachlorobutadiene	<3										<3	ug/l	TM15/PM10
Naphthalene	<2										<2	ug/l	TM15/PM10
1,2,3-Trichlorobenzene	<3										<3	ug/l	TM15/PM10
Surrogate Recovery Toluene D8	115										<0	%	TM15/PM10
Surrogate Recovery 4-Bromofluorobenzene	104										<0	%	TM15/PM10

Element Materials Technology

Notification of Deviating Samples

Notification of Deviating Samples

Client Name: LDD Advanced Technologies

Reference: Smadar 62400002

Location: Smadar 3-5 Ramat-Gan

Contact: Yossi Amoyal

[illegible]

Please note that only samples that are deviating are mentioned in this report. If no samples are listed it is because none were deviating. Only analyses which are accredited are recorded as deviating if set criteria are not met.

It is a requirement under ISO 17025 that we inform clients if samples are deviating i.e. outside what is expected. A deviating sample indicates that the sample 'may' be compromised but not necessarily will be compromised. The result is still accredited and our analytical reports will still show accreditation on the relevant analytes.

NOTES TO ACCOMPANY ALL SCHEDULES AND REPORTS

EMT Job No.: 24/21293

SOILS and ASH

Please note we are only MCERTS accredited (UK soils only) for sand, loam and clay and any other matrix is outside our scope of accreditation.

Where an MCERTS report has been requested, you will be notified within 48 hours of any samples that have been identified as being outside our MCERTS scope. As validation has been performed on clay, sand and loam, only samples that are predominantly these matrices, or combinations of them will be within our MCERTS scope. If samples are not one of a combination of the above matrices they will not be marked as MCERTS accredited.

It is assumed that you have taken representative samples on site and require analysis on a representative subsample. Stones will generally be included unless we are requested to remove them.

All samples will be discarded one month after the date of reporting, unless we are instructed to the contrary. Asbestos samples are retained for 6 months.

If you have not already done so, please send us a purchase order if this is required by your company.

Where appropriate please make sure that our detection limits are suitable for your needs, if they are not, please notify us immediately.

All analysis is reported on a dry weight basis unless stated otherwise. Limits of detection for analyses carried out on as received samples are not moisture content corrected. Results are not surrogate corrected. Samples are dried at 35°C ±5°C unless otherwise stated. Moisture content for CEN Leachate tests are dried at 105°C ±5°C. Ash samples are dried at 35°C ±5°C.

Where Mineral Oil is quoted, this refers to Total Aliphatics C10-C40.

Where a CEN 10:1 ZERO Headspace VOC test has been carried out, a 10:1 ratio of water to wet (as received) soil has been used.

% Asbestos in Asbestos Containing Materials (ACMs) is determined by reference to HSG 264 The Survey Guide - Appendix 2 : ACMs in buildings listed in order of ease of fibre release.

Sufficient amount of sample must be received to carry out the testing specified. Where an insufficient amount of sample has been received the testing may not meet the requirements of our accredited methods, as such accreditation may be removed.

Negative Neutralization Potential (NP) values are obtained when the volume of NaOH (0.1N) titrated (pH 8.3) is greater than the volume of HCl (1N) to reduce the pH of the sample to 2.0 - 2.5. Any negative NP values are corrected to 0.

The calculation of Pyrite content assumes that all oxidisable sulphides present in the sample are pyrite. This may not be the case. The calculation may be an overestimate when other sulphides such as Barite (Barium Sulphate) are present.

WATERS

Please note we are not a UK Drinking Water Inspectorate (DWI) Approved Laboratory .

ISO17025 accreditation applies to surface water and groundwater and usually one other matrix which is analysis specific, any other liquids are outside our scope of accreditation.

As surface waters require different sample preparation to groundwaters the laboratory must be informed of the water type when submitting samples.

Where Mineral Oil is quoted, this refers to Total Aliphatics C10-C40.

STACK EMISSIONS

Where an MCERTS report has been requested, you will be notified within 48 hours of any samples that have been identified as being outside our MCERTS scope. As validation for Dioxins and Furans and Dioxin like PCBs has been performed on XAD-2 Resin, only samples which use this resin will be within our MCERTS scope.

Where appropriate please make sure that our detection limits are suitable for your needs, if they are not, please notify us immediately.

DEVIATING SAMPLES

All samples should be submitted to the laboratory in suitable containers with sufficient ice packs to sustain an appropriate temperature for the requested analysis. The temperature of sample receipt is recorded on the confirmation schedules in order that the client can make an informed decision as to whether testing should still be undertaken.

SURROGATES

Surrogate compounds are added during the preparation process to monitor recovery of analytes. However low recovery in soils is often due to peat, clay or other organic rich matrices. For waters this can be due to oxidants, surfactants, organic rich sediments or remediation fluids. Acceptable limits for most organic methods are 70 - 130% and for VOCs are 50 - 150%. When surrogate recoveries are outside the performance criteria but the associated AQC passes this is assumed to be due to matrix effect. Results are not surrogate corrected.

DILUTIONS

A dilution suffix indicates a dilution has been performed and the reported result takes this into account. No further calculation is required.

BLANKS

Where analytes have been found in the blank, the sample will be treated in accordance with our laboratory procedure for dealing with contaminated blanks.

NOTE

Data is only reported if the laboratory is confident that the data is a true reflection of the samples analysed. Data is only reported as accredited when all the requirements of our Quality System have been met. In certain circumstances where all the requirements of the Quality System have not been met, for instance if the associated AQC has failed, the reason is fully investigated and documented. The sample data is then evaluated alongside the other quality control checks performed during analysis to determine its suitability. Following this evaluation, provided the sample results have not been effected, the data is reported but accreditation is removed. It is a requirement of our Accreditation Body for data not reported as accredited to be considered indicative only, but this does not mean the data is not valid.

Where possible, and if requested, samples will be re-extracted and a revised report issued with accredited results. Please do not hesitate to contact the laboratory if further details are required of the circumstances which have led to the removal of accreditation.

Laboratory records are kept for a period of no less than 6 years.

REPORTS FROM THE SOUTH AFRICA LABORATORY

Any method number not prefixed with SA has been undertaken in our UK laboratory unless reported as subcontracted.

Measurement Uncertainty

Measurement uncertainty defines the range of values that could reasonably be attributed to the measured quantity. This range of values has not been included within the reported results. Uncertainty expressed as a percentage can be provided upon request.

Customer Provided Information

Sample ID and depth is information provided by the customer.

Age of Diesel

The age of release estimation is based on the nC17/pristane ratio only as prescribed by Christensen and Larsen (1993) and Kaplan, Galperin, Alimi et al., (1996).

Age estimation should be treated with caution as it can be influenced by site specific factors of which the laboratory are not aware.

Tentatively Identified Compounds (TICs)

Where Tentatively Identified Compounds (TICs) are reported, up to 10 Tentatively Identified Compounds will be listed where there is found to be a greater than 80% match with the NIST library. The reported concentration is determined semi-quantitatively, with a matrix specific limit of detection.

Note, other compounds may be present but are not reported.

ABBREVIATIONS and ACRONYMS USED

#	ISO17025 (UKAS Ref No. 4225) accredited - UK.
SA	ISO17025 (SANAS Ref No.T0729) accredited - South Africa
B	Indicates analyte found in associated method blank.
DR	Dilution required.
M	MCERTS accredited.
NA	Not applicable
NAD	No Asbestos Detected.
ND	None Detected (usually refers to VOC and/SVOC TICs).
NDP	No Determination Possible
SS	Calibrated against a single substance
SV	Surrogate recovery outside performance criteria. This may be due to a matrix effect.
W	Results expressed on as received basis.
+	AQC failure, accreditation has been removed from this result, if appropriate, see 'Note' on previous page.
>>	Results above quantitative calibration range. The result should be considered the minimum value and is indicative only. The actual result could be significantly higher.
*	Analysis subcontracted to an Element Materials Technology approved laboratory.
CO	Suspected carry over
LOD/LOR	Limit of Detection (Limit of Reporting) in line with ISO 17025 and MCERTS
ME	Matrix Effect
NFD	No Fibres Detected
BS	AQC Sample
LB	Blank Sample
N	Client Sample
TB	Trip Blank Sample
OC	Outside Calibration Range
AA	x5 Dilution

EMT Job No: 24/21293

Test Method No.	Description	Prep Method No. (if appropriate)	Description	ISO 17025 (UKAS/ANAS)	MCERTS (UK soils only)	Analysis done on As Received (AR) or Dried (AD)	Reported on dry weight basis
TM0	Not available	PM0	No preparation is required.				
TM15	Modified USEPA 8260B v2:1996. Quantitative Determination of Volatile Organic Compounds (VOCs) by Headspace GC-MS.	PM10	Modified US EPA method 5021A v2:2014. Preparation of solid and liquid samples for GC headspace analysis.				
TM15	Modified USEPA 8260B v2:1996. Quantitative Determination of Volatile Organic Compounds (VOCs) by Headspace GC-MS.	PM10	Modified US EPA method 5021A v2:2014. Preparation of solid and liquid samples for GC headspace analysis.	Yes			
TM27	Modified US EPA method 9056/EPA 0300.0 (1993) Determination of water soluble anions using Dionex (Ion-Chromatography).	PM0	No preparation is required.				
TM30	Determination of Trace Metals by ICP-OES (Inductively Coupled Plasma-Optical Emission Spectrometry); WATERS by Modified USEPA Method 200.7, Rev. 4.4, 1994; Modified EPA Method 6010B, Rev.2, Dec 1996; Modified BS EN ISO 11885:2009: SOILS by Modified USEP 6010B, Rev.2, Dec.1996; Modified EPA Method 3050B, Rev.2, Dec.1996	PM14	Preparation of waters and leachates for metals by ICP OES/ICP MS. Samples are filtered for Dissolved metals, and remain unfiltered for Total metals then acidified				
TM30	Determination of Trace Metals by ICP-OES (Inductively Coupled Plasma-Optical Emission Spectrometry); WATERS by Modified USEPA Method 200.7, Rev. 4.4, 1994; Modified EPA Method 6010B, Rev.2, Dec 1996; Modified BS EN ISO 11885:2009: SOILS by Modified USEP 6010B, Rev.2, Dec.1996; Modified EPA Method 3050B, Rev.2, Dec.1996	PM14	Preparation of waters and leachates for metals by ICP OES/ICP MS. Samples are filtered for Dissolved metals, and remain unfiltered for Total metals then acidified	Yes			
TM38	Soluble Ion analysis using Discrete Analyser. Modified US EPA methods: Chloride 325.2 (1978), Sulphate 375.4 (Rev.2 1993), o-Phosphate 365.2 (Rev.2 1993), TON 353.1 (Rev.2 1993), Nitrite 354.1 (1971), Hex Cr 7196A (1992), NH4+ 350.1 (Rev.2 1993) - All anions comparable to BS ISO 15923-1: 2013I	PM0	No preparation is required.				
TM38	Soluble Ion analysis using Discrete Analyser. Modified US EPA methods: Chloride 325.2 (1978), Sulphate 375.4 (Rev.2 1993), o-Phosphate 365.2 (Rev.2 1993), TON 353.1 (Rev.2 1993), Nitrite 354.1 (1971), Hex Cr 7196A (1992), NH4+ 350.1 (Rev.2 1993) - All anions comparable to BS ISO 15923-1: 2013I	PM0	No preparation is required.	Yes			
TM38/TM125	Total Nitrogen/Organic Nitrogen by calculation	PM0	No preparation is required.				
TM60	TC/TOC analysis of Waters by High Temperature Combustion followed by NDIR detection. Based on the following modified standard methods: USEPA 9060A (2002), APHA SMEWW 5310B:1999 22nd Edition, ASTM D 7573, and USEPA 415.1.	PM0	No preparation is required.	Yes			

EMT Job No: 24/21293

Test Method No.	Description	Prep Method No. (if appropriate)	Description	ISO 17025 (UKAS/S ANAS)	MCERTS (UK soils only)	Analysis done on As Received (AR) or Dried (AD)	Reported on dry weight basis
TM75	Modified US EPA method 310.1 (1978). Determination of Alkalinity by Metrohm automated titration analyser.	PM0	No preparation is required.				
TM173	Analysis of fluoride by ISE (Ion Selective Electrode) using modified ISE method 9214 - 340.2 (EPA 1998)	PM0	No preparation is required.				