GEPA

Reflective prompt evolution (Agrawal et al., ICLR 2026)

Carlos Cotrini

ETH Zurich

6 October 2026

1

Section 1

The problem

GSM8K: grade-school maths word problems

Q: Alannah, Beatrix, and Queen are preparing for the new school year and have been given books by their parents. Alannah has 20 more books than Beatrix. Queen has 1/5 times more books than Alannah. If Beatrix has 30 books, how many books do the three have together?

A: The instruction goes here — Then the working, then a number

At the start of the answer

The answer on file: **140**

Right if they match



7,473 training problems

To optimise on (a 3.5% sample)




1,319 test problems

To check the result on

Yang et al. 2024, Fig. 3 and section 5

Same model, different instruction



Yang et al. 2024, section 5.2.3, p. 13

One instruction, before and after GEPA


The seed instruction

`create_query_hop2`

Given the fields `question`, `summary_1`, produce the fields `query`.

Lessons written by the reflecting model

System's test score, HotpotQA, GPT-4.1 Mini



GEPA's instruction, GPT-4.1 Mini — Agrawal et al. 2026, Fig. 2, Table 2

`create_query_hop2`

[…] **Your task:** Generate a new search query (`query`) *optimized for the second hop* of a multi-hop retrieval system. […]

Key Observations and Lessons:

- First-hop documents often cover one entity or aspect.
- Remaining relevant documents often involve connected or higher-level concepts mentioned in `summary_1` but not explicitly asked in the original question. […]
- If `summary_1` describes a population for a small civil parish, but the question wants the total population of the wider region, your query should target that wider region (e.g., "Madeira archipelago population in 2011"). […]

The optimisation problem

$$\langle \Pi^*, \Theta^* \rangle = \text{the instructions and weights that maximise}$$

$$\mathbb{E}\Big[\, \mu\big(\Phi(x; \underbrace{\langle \Pi, \Theta \rangle}), m\big) \,\Big] \quad \text{subject to} \quad \#\text{rollouts} \le B$$

Metric, a score in $[0, 1]$

An input

Gold answer, a rubric or unit tests

Π: all instructions; Θ: all weights

Budget

Output y of the system Φ

Over (x, m) drawn from the task distribution

A rollout: one run of Φ on one input, scored by μ.

GEPA: weights frozen, instructions searched


Agrawal et al. 2026, eq. (1) and (2)

2

Section 2

Learning from text

The metric can be an LLM



Agrawal et al. 2026, pp. 4, 5, 25; DSPy tutorial "GEPA for Privacy-Conscious Delegation"

A rollout returns a score and text

`system_prompt` — The seed instruction

You are a helpful assistant. You are given a question and you need to answer it. The answer should be given at the end of your response in exactly the format '### <final answer>'

Problem x (2022 AIME I, problem 6)

Find the number of ordered pairs of integers (a, b) such that the sequence 3, 4, 5, a, b, 30, 40, 50 is strictly increasing and no set of four (not necessarily consecutive) terms forms an arithmetic progression.

Gold answer m: `### 228`

GEPA's recorded AIME test; Agrawal et al. 2026, pp. 6, 7

→

○○○ — Execution trace of GPT-4.1 nano, last line

```
### <final answer> 234
```

Metric μ: is `### 228` in the response? No: score 0

Feedback function μ_f returns the score and this text:

`Feedback` — Evaluation trace: what the metric wrote


The generated response is incorrect. The correct answer is '### 228'. Ensure that the correct answer is included in the response exactly as it is. Here is some additional context that might be helpful: solution: [...]

3

Section 3


The GEPA loop

GEPA's loop, with the lines of Algorithm 1



Agrawal et al. 2026, Fig. 3 and Alg. 1

GEPA grows a tree of candidates




Each child is its parent with one instruction rewritten after reflection.

Pool $\mathcal{P}$:
all the candidates


Agrawal et al. 2026, Alg. 1 and Fig. 6

The Pareto front of the pool



Agrawal et al. 2026, p. 7 and Alg. 2

Setup



Split $\mathcal{D}_{\text{train}}$ into $\mathcal{D}_{\text{feedback}}$, $\mathcal{D}_{\text{pareto}}$, s.t. $|\mathcal{D}_{\text{pareto}}| = n_{\text{pareto}}$

Initialize candidates $\mathcal{P} \leftarrow [\Phi]$ *// Φ: the seed*

for each (x_i, m_i) in $\mathcal{D}_{\text{pareto}}$ do *// all 300 questions*

  $S_\Phi[i] \leftarrow \mu(\Phi(x_i), m_i)$ *// S_Φ: one row of scores*

Agrawal et al. 2026, Alg. 1, pp. 8, 23, 27

Algorithm 1 in words

Algorithm 1, GEPA

while the budget B is not exhausted **do**
  $\Phi \leftarrow$ select a candidate from the pool $\mathcal{P}$
  $\mathcal{M} \leftarrow$ sample a few questions from $\mathcal{D}_{\text{feedback}}$
  Use Φ to solve $\mathcal{M}$. Collect feedback F, score σ, traces
  $\Phi' \leftarrow$ update Φ with F, σ and the traces
  Get the score σ' of Φ' on $\mathcal{M}$
  if $\sigma' > \sigma$ **then**
  - **Add Φ' to $\mathcal{P}$ as a child of Φ**

Algorithm 1: one iteration

Algorithm 1, GEPA Agrawal et al. 2026, p. 6; GEPA library

6 **while** budget B not exhausted **do** // B in rollouts
7 $k \leftarrow \textsc{SelectCandidate}(\mathcal{P}, S)$ // draw a parent
8 $j \leftarrow \textsc{SelectModule}(\Phi_k)$ // which instruction, round robin
9 $\mathcal{M} \leftarrow$ minibatch of size b from $\mathcal{D}_{\text{feedback}}$ // $b = 3$ training examples
10 Gather feedback, scores, traces for $\Phi_k[j]$ on $\mathcal{M}$ using μ_f // parent rerun, with traces
11 $\pi'_j \leftarrow \textsc{UpdatePrompt}(\pi_j, \text{feedbacks}, \text{traces}[j])$ // an LLM rewrites instruction π_j
12 $\Phi' \leftarrow$ Copy of Φ_k w/ module j updated by π'_j // the child
13 $\sigma, \sigma' \leftarrow$ avg score on $\mathcal{M}$ (before, after) // same b examples
14 **if** σ' improved **then** // strictly better
15 Add Φ' to $\mathcal{P}$; Add k to $\mathcal{A}$ // $\mathcal{P}$: pool; $\mathcal{A}$: parents
▸ 16 **for each** (x_i, m_i) **in** $\mathcal{D}_{\text{pareto}}$: $S_{\Phi'}[i] \leftarrow \mu(\Phi'(x_i), m_i)$ // $S_{\Phi'}$: all validation scores
▸ 21 **return** Φ^* **maximizing average score on** $\mathcal{D}_{\text{pareto}}$ // best average


4

Section 4

Choosing the parent

The score matrix of a real run

After iteration 5: 45 validation problems, grouped by who solves them



Φ is best on problem i when no candidate scores higher on i

Dominance: as high on every problem, and higher on one

DSPy tutorial "GEPA for AIME": GPT-4.1 Mini solves, GPT-5 reflects

Algorithm 2 in words

Algorithm 2, Pareto-based candidate selection

function SELECTCANDIDATE($\mathcal{P}$)
  $\mathcal{C} \leftarrow \emptyset$
  for each problem q in the validation set $\mathcal{D}_{\text{pareto}}$ **do**
    Add to $\mathcal{C}$ all Φ in the pool $\mathcal{P}$ that best answer q
  Remove from $\mathcal{C}$ any Φ dominated by another. What is left: $\hat{\mathcal{C}}$
- **For Φ in $\hat{\mathcal{C}}$, let $f(\Phi)$ be the number of problems where Φ gives the best answer**
- **Sample Φ from $\hat{\mathcal{C}}$ with probability proportional to $f(\Phi)$**

Algorithm 2 on the matrix

Algorithm 2, Pareto-based candidate selection Agrawal et al. 2026; DSPy tutorial

function SELECTCANDIDATE($\mathcal{P}, S$) *// the run's pool, scores*
  for each i **do** *// i: 45 validation problems*
    $s^*[i] \leftarrow \max_k S_{\mathcal{P}[k]}[i]$ *// top score on i*
    $\mathcal{P}^*[i] \leftarrow \{\mathcal{P}[k] : S_{\mathcal{P}[k]}[i] = s^*[i]\}$ *// best sets, shown before*
  $\mathcal{C} \leftarrow$ unique candidates in $\bigcup_i \mathcal{P}^*[i]$ *// Pareto front: Φ_0, Φ_1, Φ_2*
  $D \leftarrow \emptyset$ *// D: the dominated*
  while there exists $\Phi \in \mathcal{C} \setminus D$ dominated by another in $\mathcal{C} \setminus D$ **do** *// none here*
    $D \leftarrow D \cup \{\Phi\}$ *// $\hat{\mathcal{C}} = \mathcal{C} \setminus D$*
  Remove D from each $\mathcal{P}^*[i]$ to get $\hat{\mathcal{P}}^*[i]$ *// nothing removed*
  Let $f[\Phi]$ = number of i for which $\Phi \in \hat{\mathcal{P}}^*[i]$ *// $f = 34, 36, 41$*
▸ **Sample Φ_k from $\hat{\mathcal{C}}$ with probability $\propto f[\Phi_k]$** *// $34/111, 36/111, 41/111$*
▸ **return index k of Φ_k in $\mathcal{P}$** *// run drew Φ_1, then Φ_2*

GEPA against GRPO and MIPROv2, per task


Qwen3 8B, test score (%)

GRPO ahead: 38.00 against 32.00

	HotpotQA	IFBench	HoVer	PUPA	AIME 2025	LiveBench Math	Aggregate
Baseline	42.33	36.90	35.33	80.82	27.33	48.70	45.23
GRPO	43.33	35.88	38.67	86.66	**38.00**	51.26	48.91
MIPROv2 Instructions and examples, chosen by Bayesian search	55.33	36.22	47.33	81.55	20.00	46.60	47.84
GEPA	62.33	38.61	52.33	91.85	32.00	51.95	54.85
Rollouts, GRPO	24,000	24,000	24,000	24,000	24,000	24,000	
Rollouts, GEPA	6,871	3,593	7,051	2,426	1,839	1,839	

Agrawal et al. 2026, Table 1; Opsahl-Ong et al. 2024

GEPA, assembled



Agrawal et al. 2026, Fig. 3 and Alg. 1 and 2

References

Lakshya A. Agrawal, Shangyin Tan, Dilara Soylu, Noah Ziems, Rishi Khare, Krista Opsahl-Ong, Arnav Singhvi, Herumb Shandilya, Michael J. Ryan, Meng Jiang, Christopher Potts, Koushik Sen, Alexandros G. Dimakis, Ion Stoica, Dan Klein, Matei Zaharia and Omar Khattab. GEPA: reflective prompt evolution can outperform reinforcement learning. *ICLR*, 2026 (oral). arxiv.org/abs/2507.19457; code github.com/gepa-ai/gepa and github.com/gepa-ai/gepa-artifact

Chengrun Yang, Xuezhi Wang, Yifeng Lu, Hanxiao Liu, Quoc V. Le, Denny Zhou and Xinyun Chen. Large language models as optimizers. *ICLR*, 2024. arxiv.org/abs/2309.03409

Karl Cobbe and others. Training verifiers to solve math word problems (GSM8K), 2021. arxiv.org/abs/2110.14168

Krista Opsahl-Ong, Michael J. Ryan, Josh Purtell, David Broman, Christopher Potts, Matei Zaharia and Omar Khattab. Optimizing instructions and demonstrations for multi-stage language model programs. *EMNLP*, 2024. arxiv.org/abs/2406.11695

Zhihong Shao and others. DeepSeekMath: pushing the limits of mathematical reasoning in open language models, 2024. arxiv.org/abs/2402.03300

References, continued

Zhilin Yang and others. HotpotQA: a dataset for diverse, explainable multi-hop question answering. *EMNLP*, 2018. aclanthology.org/D18-1259

Siyan Li, Vethavikashini Chithrra Raghuram, Omar Khattab, Julia Hirschberg and Zhou Yu. PAPILLON: privacy preservation from Internet-based and local language model ensembles (the PUPA task). *NAACL*, 2025. aclanthology.org/2025.naacl-long.173

Runs quoted in this lecture: the GEPA library's recorded AIME test, `tests/test_aime_prompt_optimization` at commit `d771eb2`; the DSPy tutorials "GEPA for AIME", a run of 12 August 2025, and "GEPA for Privacy-Conscious Delegation", dspy.ai/tutorials/gepa_aime and dspy.ai/tutorials/gepa_papillon