

lavaanExtra: Convenience Functions for Package *lavaan*

Rémi Thériault ¹

¹ Department of Psychology, Université du Québec à Montréal, Québec, Canada

DOI: [10.xxxxxx/draft](https://doi.org/10.xxxxxx/draft)

Software

- [Review](#) 
- [Repository](#) 
- [Archive](#) 

Editor: [Open Journals](#) 

Reviewers:

- [@openjournals](#)

Submitted: 01 January 1970

Published: unpublished

License

Authors of papers retain copyright and release the work under a Creative Commons Attribution 4.0 International License ([CC BY 4.0](#)).

Summary

`{lavaanExtra}` is an R package that offers an alternative and vector-based syntax to the package `{lavaan}`, as well as other convenience functions such as naming paths and defining indirect effects automatically. It also offers convenience formatting optimized for publication and script sharing workflows.

Statement of need

`{lavaan}` (Rosseel, 2012) is a very popular R package for structural equation modeling (SEM). The package relies on specific operators to define latent variables, regressions, covariances, indirect effects, and so on. However, some individuals (e.g., beginners to R and `{lavaan}`)—or in some cases power users—may prefer not having to specify the operators themselves, or would like to see some steps automatized, such as generating the `{lavaan}` model layout or defining indirect effects. Furthermore, for researchers, it can be relatively difficult to extract relevant statistical outputs in the form of tables and figures that are suitable for scientific publication.

`{lavaanExtra}` does mainly two things to address these issues. First, it offers an alternative, code-efficient flexible modular syntax that allows automatizing certain steps, such as defining indirect effects in certain scenarios or the desired structure of a SEM model to be plotted (however, note that `{lavaan}` is also compatible with a modular approach). Second, it facilitates the analysis-to-publication workflow by providing publication-ready tables and figures following the style requirements of the American Psychological Association (APA).

Usage

There is a single function at the center of the proposed alternative syntax, `write_lavaan()`. The idea behind `write_lavaan()` is to define individual components (regressions, covariances, latent variables, etc.), provide them to the function, and have it write the `lavaan` model, so the user does not have to worry about making typos in the specific symbols required for each aspect of the model.

There are several benefits to this approach. Some `lavaan` models can become very large. By defining the entire model every time, such as is typical with `{lavaan}` users, not only do we break the DRY (Don't Repeat Yourself) principle, but our scripts can also become long and unwieldy. This problem gets worse in the scenario where we want to compare several variations of the same general model. `write_lavaan()` allows the user to reuse code components, say, only the latent variables, for future models.

This aspect also allows better control over the user's code. If the user makes a mistake in one of, say, five SEM models definition, the user will have to change it at all five places within the

39 script. With `write_lavaan()`, users only need to define the reusable component the first time,
40 or until they need to change that component again.

41 The vector-based approach also allows the use of functions to define components. For example,
42 if all scale items are named consistently, say `x1` to `x50`, one can use `paste0("x", 1:50)`
43 instead of typing all the items by hand and risk making mistakes. However, note that reusable
44 components through functions is also compatible with `{lavaan}`.

45 Another issue with `lavaan` models is the readability of the code defining the model. One can
46 go to lengths to make it pretty, but not everyone does, and many people do not use the same
47 strategies to organize the information of the model definition. With `write_lavaan()`, not
48 only is the model information standardized, but it is also neatly divided into clear and useful
49 categories.

50 Finally, for beginners, it can be difficult to remember the correct `lavaan` symbols for each
51 specific operation. `write_lavaan()` uses familiar names to convert the information to the
52 correct symbols. Even for people familiar with `lavaan` syntax, this approach can save time.
53 The function also offers the possibility to define the named paths automatically with clear and
54 intuitive names.

55 I provide a simple Confirmatory Factor Analysis (CFA) example below using the
56 `HolzingerSwineford1939` dataset ([Holzinger & Swineford, 1939](#)). The dataset con-
57 tains the mental ability test scores of children. In this example, we want to define the latent
58 variables `visual` (visual perception ability), `textual` (reading and writing ability), and `speed`
59 (processing speed ability), which are defined by items 1 to 9, respectively. We can then use
60 the `cat()` function on the resulting object (of type character) to read it in the traditional way
61 and make sure we have not made any mistake.

```
library(lavaanExtra)

x <- paste0("x", 1:9)
latent <- list(
  visual = x[1:3],
  textual = x[4:6],
  speed = x[7:9]
)

model.cfa <- write_lavaan(latent = latent)
cat(model.cfa)

62 ## #####
63 ## # [-----Latent variables (measurement model)-----]
64 ##
65 ## visual =~ x1 + x2 + x3
66 ## textual =~ x4 + x5 + x6
67 ## speed =~ x7 + x8 + x9
```

68 Should we want to use these latent variables in a full SEM model, we do not need to define
69 the latent variables again, only the new components. In the example below, I add regressions,
70 covariances, and indirect effects to the model. Two of our latent variables (`textual` and `speed`)
71 are now predicted by our mediating variable, `visual`. In turn, `visual` is now predicted by our
72 independent variables, `grade` (the students' grade) and `ageyr` (the students' age, in years).

73 With the `lavaanExtra` syntax, when defining our lists of components, we can think of the
74 `=` sign as "predicted by", a bit like `~` for regression. There is an exception to this for the
75 indirect object, which also allows specifying our variables directly instead. When such is the
76 case, `write_lavaan()` will define all indirect paths automatically.

```
DV <- c("textual", "speed")
```

```

M <- "visual"
IV <- c("grade", "ageyr")

mediation <- list(speed = M, textual = M, visual = IV)
regression <- list(speed = IV, textual = IV)
covariance <- list(speed = "textual", ageyr = "grade", x4 = x[5:6])
indirect <- list(IV = IV, M = M, DV = DV)

model.sem <- writelavaan(mediation = mediation,
                          regression = regression,
                          covariance = covariance,
                          indirect = indirect,
                          latent = latent,
                          label = TRUE)

cat(model.sem)
77 ## #####
78 ## # [-----Latent variables (measurement model)-----]
79 ##
80 ## visual =~ x1 + x2 + x3
81 ## textual =~ x4 + x5 + x6
82 ## speed =~ x7 + x8 + x9
83 ##
84 ## #####
85 ## # [-----Mediations (named paths)-----]
86 ##
87 ## speed ~ visual_speed*visual
88 ## textual ~ visual_textual*visual
89 ## visual ~ grade_visual*grade + ageyr_visual*ageyr
90 ##
91 ## #####
92 ## # [-----Regressions (Direct effects)-----]
93 ##
94 ## speed ~ grade + ageyr
95 ## textual ~ grade + ageyr
96 ##
97 ## #####
98 ## # [-----Covariances-----]
99 ##
100 ## speed ~~ textual
101 ## ageyr ~~ grade
102 ## x4 ~~ x5 + x6
103 ##
104 ## #####
105 ## # [-----Mediations (indirect effects)-----]
106 ##
107 ## grade_visual_textual := grade_visual * visual_textual
108 ## grade_visual_speed := grade_visual * visual_speed
109 ## ageyr_visual_textual := ageyr_visual * visual_textual
110 ## ageyr_visual_speed := ageyr_visual * visual_speed

```

111 Tables

112 The nice_fit() function extracts only some of the most popular fit indices and organize them
 113 such that it is easy to compare models. There is an option to format the table as an APA

114 {flextable} (Gohel & Skintzos, 2023), through the {rempsyc} package (Thériault, 2022), using
115 option nice_table = TRUE. This flextable object can then be easily exported to Microsoft
116 Word. Below we fit our two earlier models and feed them to nice_fit() as a named list:

```
library(lavaan)
fit.cfa <- cfa(model.cfa, data = HolzingerSwineford1939)
fit.sem <- sem(model.sem, data = HolzingerSwineford1939)

list.mods <- list(`CFA model` = fit.cfa, `SEM model` = fit.sem)
fit_table <- nice_fit(list.mods, nice_table = TRUE)

fit_table
```

Model	χ^2	df	χ^2/df	p	CFI	TLI	RMSEA [90% CI]	SRMR	AIC	BIC
fit.cfa	85.31	24	3.55	<.001	.93	.90	.09 [.07, .11]	.06	7,517.49	7,595.34
fit.sem	114.20	34	3.36	<.001	.93	.88	.09 [.07, .11]	.06	8,640.07	8,758.59
Ideal Value^a	—	—	< 2 or 3	>.05	≥ .95	≥ .95	<.05 [.00, .08]	≤ .08	Smaller	Smaller

^aAs proposed by Schreiber (2017).

117

118 The table can then be saved to word simply using flextable::save_as_docx() on the resulting
119 flextable object.

```
flextable::save_as_docx(fit_table, path = "fit_table.docx")
```

120 It will also render to PDF in an rmarkdown document with output: pdf_document, but using
121 latex_engine: xelatex is necessary when including Unicode symbols in tables like with the
122 nice_fit() function.

123 It is similarly possible to prepare APA tables in Word with the regression coefficients
124 (lavaan_reg()), covariances (lavaan_cov()), correlations (lavaan_cor()), or indirect effects
125 (lavaan_ind()). For example, for indirect effects:

```
lavaan_ind(fit.sem, nice_table = TRUE)
```

Indirect Effect	Paths	p	β	95% CI
grade → visual → textual	grade_visual*visual_textual	.001***	0.13	[0.05, 0.20]
grade → visual → speed	grade_visual*visual_speed	.001**	0.13	[0.05, 0.21]
ageyr → visual → textual	ageyr_visual*visual_textual	.012*	-0.08	[-0.14, -0.02]
ageyr → visual → speed	ageyr_visual*visual_speed	.016*	-0.08	[-0.15, -0.02]

126


127 Figures

128 There are several packages designed to plot SEM models, but few that people consider satisfying
129 or sufficiently good for publication by default. There are two packages that stand out however,
130 {lavaanPlot} (Lishinski, 2021) and {tidySEM} (van Lissa, 2023b). Yet, even for those excellent


131 packages, most people do not view them as publication-ready or at least optimized in the best
132 possible way.

133 This is what nice_lavaanPlot and nice_tidySEM aim to correct. Let's compare the default
134 lavaanPlot() and nice_lavaanPlot() outputs side-by-side for demonstration purposes.

```
lavaanPlot::lavaanPlot(model = fit.sem)
```



```
nice_lavaanPlot(fit.sem)
```



136

137 For reference, nice_lavaanPlot() is a simple wrapper around lavaanPlot::lavaanPlot() and
138 an identical figure can be obtained using only lavaanPlot with the following code:

```
lavaanPlot::lavaanPlot(  
  model = fit.sem,  
  node_options = list(shape = "box", fontname = "Helvetica"),  
  coefs = TRUE,
```


```
stand = TRUE,
stars = c("regress", "latent", "covs"),
graph_options = c(rankdir = "LR"),
sig = .05
)
```

As these figures demonstrate, `nice_lavaanPlot()` has several elements frequently requested by researchers (especially in psychology): (a) a horizontal, rather than vertical, layout; (b) the coefficients appear by default (but only significant ones); (c) significance stars; and (d) the use of a sans serif font (as required by APA style for figures).

Even so, `nice_lavaanPlot` is not perfectly optimal for publication, for example for the use of curved lines, which many researchers dislike. Nonetheless, it will still yield excellent and satisfying results for a quick and easy check.

The best option for publication then is `nice_tidySEM`. Let's first look at the default output of the base `tidySEM::graph_sem()` for reference.

```
tidySEM::graph_sem(fit.sem)
```




The author of the `{tidySEM}` package notes that

This uses a default layout, provided by the `igraph` package. However, the node placement is not very aesthetically pleasing. One of the areas where `tidySEM` really excels is customization. (van Lissa, 2023a)

In this sense, most of the time, both `tidySEM` and `nice_tidySEM` will need a layout in order to yield the best result. One of the benefits of `nice_tidySEM` is that when our model is simply made of three “levels”: independent variables, mediators, and dependent variables (e.g., for a path analysis, or if we do not want to draw the items for a full SEM), it is possible to automatically specify a proper layout by simply feeding it the indirect object that we created earlier.

```
nice_tidySEM(fit.sem, layout = indirect)
```



159

160 For reference, below I provide the code necessary to reproduce this figure using the tidySEM
161 package only.

```
library(tidySEM)


mylayout <- data.frame(
  IV = c("grade", "ageyr"),
  M = c("", "visual"),
  DV = c("textual", "speed")
)
p <- prepare_graph(fit.sem, layout = mylayout)
p <- hide_var(p)
x <- p$edges$est_sig_std
x <- sub("^0", "", x)
x <- sub("^-0", "-", x)
p$edges$label <- x
p$edges$linetype <- 1
p$edges$arrow <- ifelse(p$edges$arrow == "none", "both", p$edges$arrow)
plot(p)
```

162 For the time being, nice_tidySEM only supports this three-level automatic layout, but designs
163 with more levels are in the works. In the meantime, when the model is more complex (or that
164 we want to include items), it is necessary to specify the layout manually using a matrix or data
165 frame, which allows fine-grained control over the generated figure.

```
mylayout <- data.frame(
  IV = c("x1", "grade", "", "ageyr", ""),
  M = c("x2", "", "visual", "", ""),
  DV = c("x3", "textual", "", "speed", "x9"),
  DV.items = c(paste0("x", 4:8)))
as.matrix(mylayout)

##      IV      M      DV      DV.items
## [1,] "x1"    "x2"    "x3"    "x4"
## [2,] "grade" ""      "textual" "x5"
## [3,] ""      "visual" ""      "x6"
## [4,] "ageyr" ""      "speed"  "x7"
## [5,] ""      ""      "x9"     "x8"

nice_tidySEM(fit.sem, layout = mylayout, label_location = 0.70)
```




172

173 If the figure is still not sufficiently satisfying, it is possible to store the output as a tidy_sem
 174 object (by using `plot = FALSE`), which can then be modified according to regular tidySEM
 175 syntax. This can be useful to fine-tune and finalize the figure.

```

x <- nice_tidySEM(fit.sem, layout = mylayout, label_location = 0.65,
  reduce_items = c(x = 0.4, y = 0.2), plot = FALSE)
from <- x$edges$from
to <- x$edges$to
x$edges[from == "grade" & to == "speed", "curvature"] <- 40
x$edges[from == "ageyr" & to == "textual", "curvature"] <- -40
plot(x)

```

176

177 The resulting figure can be saved using `ggplot2::ggsave()` (Wickham, 2016):

```
ggplot2::ggsave("my_semPlot.pdf", width = 8, height = 6)
```

178 For reference, below I provide the code necessary to reproduce this figure using the tidySEM
179 package only.

```
library(tidySEM)

p <- prepare_graph(fit.sem, layout = mylayout)
p <- edit_graph(p, { label_location <- 0.65 })
p <- hide_var(p)
x <- p$edges$est_sig_std
x <- sub("^0", "", x)
x <- sub("^-0", "-", x)
p$edges$label <- x
items <- p$edges[p$edges$op == "~", "rhs"]
i <- p$nodes$name %in% items
p$nodes[i, ]$node_xmin <- p$nodes[i, ]$node_xmin + 0.4
p$nodes[i, ]$node_xmax <- p$nodes[i, ]$node_xmax - 0.4
p$nodes[i, ]$node_ymin <- p$nodes[i, ]$node_ymin + 0.2
p$nodes[i, ]$node_ymax <- p$nodes[i, ]$node_ymax - 0.2
p$edges$linetype <- 1
p$edges$arrow <- ifelse(p$edges$arrow == "none", "both", p$edges$arrow)
from <- p$edges$from
to <- p$edges$to
p$edges[from == "grade" & to == "speed", "curvature"] <- 40
p$edges[from == "ageyr" & to == "textual", "curvature"] <- -40
plot(p)
```

180 Other differences between `{tidySEM}` and `nice_tidySEM()` are that: (a) the latter displays
181 standardized coefficients by default (but unstandardized coefficients can be specified with

est_std = FALSE), (b) if using standardized coefficients, the leading zero is omitted (as preferred by many researchers); (c) does not plot the variances by default, (d) uses full double-headed arrows instead of dashed lines with no arrows for covariances, (e) has further arguments for easy customization (e.g., `reduce_items`), and (f) allows defining an automatic layout in specific cases (as described earlier).

Finally, the base function, `tidySEM::graph_sem()`, is difficult to customize in depth. For the aesthetics of `nice_tidySEM()`, for example, we need to rely instead on the `{tidySEM}`'s `prepare_graph()`, `edit_graph()`, and numerous conditional formatting functions. In contrast to `nice_tidySEM()`, these `tidySEM` functions act more like a grammar of SEM plotting, akin to the popular grammar of graphics, `{ggplot2}` (Wickham, 2016). This provides great flexibility, but for the occasional user, also comes with an additional burden, as users may for example need to skim through almost 400 undocumented functions, should they want to conditionally edit the resulting `tidy_sem` object.

Availability

The `{lavaanExtra}` package is licensed under the MIT License. It is available on CRAN, and can be installed using `install.packages("lavaanExtra")`. The full tutorial website can be accessed at: <https://lavaanExtra.remi-theriault.com/>. All code is open-source and hosted on GitHub, and bugs can be reported at <https://github.com/rempsyc/lavaanExtra/issues/>.

Acknowledgements

I would like to thank Hugues Leduc, Jany St-Cyr, Andreea Gavrila, Patrick Coulombe, Jay Olson, Charles-Étienne Lavoie, and Björn Büdenbender for statistical or technical advice that helped inform some functions of this package and/or useful feedback on this manuscript. I would also like to acknowledge funding from the Social Sciences and Humanities Research Council of Canada.

References

- Gohel, D., & Skintzos, P. (2023). *flextable: Functions for tabular reporting*. <https://CRAN.R-project.org/package=flextable>
- Holzing, K. J., & Swineford, F. (1939). A study in factor analysis: The stability of a bi-factor solution. *Supplementary Educational Monographs*.
- Lishinski, A. (2021). *lavaanPlot: Path diagrams for 'lavaan' models via 'DiagrammeR'*. <https://CRAN.R-project.org/package=lavaanPlot>
- Rosseel, Y. (2012). lavaan: An R package for structural equation modeling. *Journal of Statistical Software*, 48(2), 1–36. <https://doi.org/10.18637/jss.v048.i02>
- Thériault, R. (2022). *rempsyc: Convenience functions for psychology*. <https://rempsyc.remi-theriault.com>
- van Lissa, C. J. (2023a). *Plotting graphs for structural equation models*. https://civanlissa.github.io/tidySEM/articles/Plotting_graphs.html
- van Lissa, C. J. (2023b). *tidySEM: Tidy structural equation modeling*. <https://CRAN.R-project.org/package=tidySEM>
- Wickham, H. (2016). *ggplot2: Elegant graphics for data analysis*. Springer-Verlag New York. <https://ggplot2.tidyverse.org>