

Deep learning for medical imaging

Olivier Colliot, PhD
Research Director at CNRS
Co-Head of the ARAMIS Lab –
www.aramislab.fr
PRAIRIE – Paris Artificial Intelligence
Research Institute

Maria Vakalopoulou, PhD
Assistant Professor at
CentraleSupélec
Center for Visual Computing



Master 2 - MVA

Course website: <http://www.aramislab.fr/teaching/DLMI-2019-2020/>
Piazza (for registered students):
<https://piazza.com/centralesupelec/spring2020/mvadlmi/>

Part 8 – Registration


(“*Recalage*” in French)

Part 8 – Registration

8.1 Introduction


What is image registration?

Registration=Establish spatial correspondences between images




$$\begin{pmatrix} x' \\ y' \end{pmatrix} = T \begin{pmatrix} x \\ y \end{pmatrix}$$

What is image registration?



Coordinate systems


Image coordinate system



s_x, s_y, s_z : voxel size
(in millimeters)

Medical often have
non-isotropic
voxels/pixels
 $s_x \neq s_y \neq s_z$


3D images



Remember:
many medical
images are 3D

Some of the
course's
equations will
be given in 2D
but real
applications are
most often in
3D

3D images



Voxel=volume element





Image source: <https://en.wikipedia.org/wiki/Voxel>

Remember:
many medical
images are 3D

Some of the
course's
equations will
be given in 2D
but real
applications are
most often in
3D

Coordinate systems

World coordinate system




Coordinate systems

Image to world

$$\begin{pmatrix} X \\ Y \\ 1 \end{pmatrix} = \begin{bmatrix} 1 & 0 & \textcolor{red}{ox} \\ 0 & 1 & \textcolor{red}{oy} \\ 0 & 0 & 1 \end{bmatrix} \underbrace{\begin{bmatrix} dxx & dyx & 0 \\ dxy & dyy & 0 \\ 0 & 0 & 1 \end{bmatrix}}_{T_{ItW}} \underbrace{\begin{bmatrix} sx & 0 & 0 \\ 0 & sy & 0 \\ 0 & 0 & 1 \end{bmatrix}}_{\text{camera matrix}} \begin{pmatrix} x \\ y \\ 1 \end{pmatrix}$$

World to image

$$\begin{pmatrix} x \\ y \\ 1 \end{pmatrix} = T_{ItW}^{-1} \begin{pmatrix} X \\ Y \\ 1 \end{pmatrix}$$




Introduction

Although deep learning based registration methods have been developed, **they are not (yet) the standard** for this task (unlike, for example, for segmentation)

Part 8 – Registration

8.2 Transformation models

Transformation models



Part 8 – Registration

8.2 Transformation models

8.2.1 Linear transformations

Linear transformations

Parameterisation of linear transformation (using homogeneous coordinates)

2D affine: translation (2), rotation (1), scaling (2), shear(1) = 6 DOF

Translation

$$T = \begin{bmatrix} 1 & 0 & t_x \\ 0 & 1 & t_y \\ 0 & 0 & 1 \end{bmatrix}$$

Rotation




$$R = \begin{bmatrix} \cos \theta & \sin \theta & 0 \\ -\sin \theta & \cos \theta & 0 \\ 0 & 0 & 1 \end{bmatrix}$$

Scaling

$$S = \begin{bmatrix} s_x & 0 & 0 \\ 0 & s_y & 0 \\ 0 & 0 & 1 \end{bmatrix}$$

Shearing

$$H = \begin{bmatrix} \cos \omega & \sin \omega & 0 \\ -\sin \omega & \cos \omega & 0 \\ 0 & 0 & 1 \end{bmatrix}$$



?

Linear transformations

Parameterisation of linear transformation (using homogeneous coordinates)

2D affine: translation (2), rotation (1), scaling (2), shear(1) = 6 DOF

Translation

$$T = \begin{bmatrix} 1 & 0 & t_x \\ 0 & 1 & t_y \\ 0 & 0 & 1 \end{bmatrix}$$

Rotation




$$R = \begin{bmatrix} \cos \theta & \sin \theta & 0 \\ -\sin \theta & \cos \theta & 0 \\ 0 & 0 & 1 \end{bmatrix}$$

Scaling

$$S = \begin{bmatrix} s_x & 0 & 0 \\ 0 & s_y & 0 \\ 0 & 0 & 1 \end{bmatrix}$$

Shearing

$$H = \begin{bmatrix} \cos \omega & \sin \omega & 0 \\ -\sin \omega & \cos \omega & 0 \\ 0 & 0 & 1 \end{bmatrix}$$



$$H S H^{-1}$$

Linear transformations

Parameterisation of linear transformation (using homogeneous coordinates)

2D affine: translation (2), rotation (1), scaling (2), shear(1) = 6 DOF

Translation

$$T = \begin{bmatrix} 1 & 0 & t_x \\ 0 & 1 & t_y \\ 0 & 0 & 1 \end{bmatrix}$$

Rotation





$$R = \begin{bmatrix} \cos \theta & \sin \theta & 0 \\ -\sin \theta & \cos \theta & 0 \\ 0 & 0 & 1 \end{bmatrix}$$

Scaling

$$S = \begin{bmatrix} s_x & 0 & 0 \\ 0 & s_y & 0 \\ 0 & 0 & 1 \end{bmatrix}$$

Shearing

$$H = \begin{bmatrix} \cos \omega & \sin \omega & 0 \\ -\sin \omega & \cos \omega & 0 \\ 0 & 0 & 1 \end{bmatrix}$$



Linear transformations

Parameterisation of linear transformation (using homogeneous coordinates)

2D affine: translation (2), rotation (1), scaling (2), shear(1) = 6 DOF

Translation

$$T = \begin{bmatrix} 1 & 0 & t_x \\ 0 & 1 & t_y \\ 0 & 0 & 1 \end{bmatrix}$$

Rotation





$$R = \begin{bmatrix} \cos \theta & \sin \theta & 0 \\ -\sin \theta & \cos \theta & 0 \\ 0 & 0 & 1 \end{bmatrix}$$

Scaling

$$S = \begin{bmatrix} s_x & 0 & 0 \\ 0 & s_y & 0 \\ 0 & 0 & 1 \end{bmatrix}$$

Shearing

$$H = \begin{bmatrix} \cos \omega & \sin \omega & 0 \\ -\sin \omega & \cos \omega & 0 \\ 0 & 0 & 1 \end{bmatrix}$$



Linear transformations

Parameterisation of linear transformation (using homogeneous coordinates)

2D affine: translation (2), rotation (1), scaling (2), shear(1) = 6 DOF

Translation

$$T = \begin{bmatrix} 1 & 0 & t_x \\ 0 & 1 & t_y \\ 0 & 0 & 1 \end{bmatrix}$$

Rotation





$$R = \begin{bmatrix} \cos \theta & \sin \theta & 0 \\ -\sin \theta & \cos \theta & 0 \\ 0 & 0 & 1 \end{bmatrix}$$

Scaling

$$S = \begin{bmatrix} s_x & 0 & 0 \\ 0 & s_y & 0 \\ 0 & 0 & 1 \end{bmatrix}$$

Shearing

$$H = \begin{bmatrix} \cos \omega & \sin \omega & 0 \\ -\sin \omega & \cos \omega & 0 \\ 0 & 0 & 1 \end{bmatrix}$$



Linear transformations

Parameterisation of linear transformation (using homogeneous coordinates)

2D affine: translation (2), rotation (1), scaling (2), shear(1) = 6 DOF

Translation	Rotation	Scaling	Shearing
$T = \begin{bmatrix} 1 & 0 & t_x \\ 0 & 1 & t_y \\ 0 & 0 & 1 \end{bmatrix}$	$R = \begin{bmatrix} \cos \theta & \sin \theta & 0 \\ -\sin \theta & \cos \theta & 0 \\ 0 & 0 & 1 \end{bmatrix}$	$S = \begin{bmatrix} s_x & 0 & 0 \\ 0 & s_y & 0 \\ 0 & 0 & 1 \end{bmatrix}$	$H = \begin{bmatrix} \cos \omega & \sin \omega & 0 \\ -\sin \omega & \cos \omega & 0 \\ 0 & 0 & 1 \end{bmatrix}$


$$A = H S H^{-1} R T = \begin{bmatrix} a_{11} & a_{12} & a_{13} \\ a_{21} & a_{22} & a_{23} \\ 0 & 0 & 1 \end{bmatrix}$$

Part 8 – Registration

8.2 Transformation models

8.2.2 Non-linear transformations

Free-form deformations (FFD)



Principle:

Deform an object
by manipulating
an underlying
mesh of control
points

Source: B. Glocker/D. Rueckert – Course on Machine Learning for Imaging – Imperial College London

Reference: Rueckert et al, IEEE TMI, 1999

Free-form deformations (FFD)

The deformation is defined with **B-splines**

Let Φ denote a $n_x \times n_y \times n_z$ mesh of control points $\phi_{i,j,k}$ with uniform spacing δ . Then, the FFD can be written as the 3 -D tensor product of the familiar 1 -D cubic B-splines


$$\begin{aligned} \mathbf{T}_{\text{local}}(x, y, z) &= \sum_{l=0}^3 \sum_{m=0}^3 \sum_{n=0}^3 B_l(u) B_m(v) B_n(w) \phi_{i+l, j+m, k+n} \\ \text{where } i &= \lfloor x/n_x \rfloor - 1, j = \lfloor y/n_y \rfloor - 1, k = \lfloor z/n_z \rfloor - 1 \\ u &= x/n_x - \lfloor x/n_x \rfloor, v = y/n_y - \lfloor y/n_y \rfloor, w = z/n_z - \lfloor z/n_z \rfloor \end{aligned}$$

and where B_l represents the l th basis function of the B-spline

$$\begin{aligned} B_0(u) &= (1-u)^3/6 \\ B_1(u) &= (3u^3 - 6u^2 + 4)/6 \\ B_2(u) &= (-3u^3 + 3u^2 + 3u + 1)/6 \\ B_3(u) &= u^3/6 \end{aligned}$$

Free-form deformations (FFD)

Low-dimensional deformation model



Source: B. Glocker/D. Rueckert – Course on Machine Learning for Imaging – Imperial College London

Reference: Rueckert et al, IEEE TMI, 1999

Free-form deformations (FFD)

Number of control points

More control points means a more flexible transformation

Free-form deformations (FFD)

In order to produce reasonably realistic deformations, one needs to **add a smoothness constraint** on the transformation

$$\begin{aligned} \mathcal{C}_{\text{smooth}} = & \frac{1}{V} \int_0^X \int_0^Y \int_0^Z \left[\left(\frac{\partial^2 \mathbf{T}}{\partial x^2} \right)^2 + \left(\frac{\partial^2 \mathbf{T}}{\partial y^2} \right)^2 \right. \\ & + \left(\frac{\partial^2 \mathbf{T}}{\partial z^2} \right)^2 + 2 \left(\frac{\partial^2 \mathbf{T}}{\partial xy} \right)^2 + 2 \left(\frac{\partial^2 \mathbf{T}}{\partial xz} \right)^2 \\ & \left. + 2 \left(\frac{\partial^2 \mathbf{T}}{\partial yz} \right)^2 \right] dx dy dz \end{aligned}$$

The **objective function** is a compromise between similarity of images and smoothness of the transformation

$$\mathcal{C}_{\text{similarity}} (I, \mathbf{T}(I)) + \lambda \mathcal{C}_{\text{smooth}} (\mathbf{T})$$

Elastic deformations

The transformation is defined by a displacement field u over the whole image

$$\phi_u(x) = x + u(x)$$

where x is a point in \mathbb{R}^2 (or \mathbb{R}^3 for a 3D image)

The registration problem is then

$$\hat{u} = \arg \max_{u \in H} S(I, \phi_u(J)) + Reg(u)$$

Problem: no guarantee that the transformation is invertible.
In particular, invertibility would be only obtained for very small displacement fields

LDDMM (Large Deformation Diffeomorphic Metric Mapping)

Diffeomorphisms: invertible, differentiable deformations which inverse is also differentiable

LDDMM: mathematical framework for diffeomorphic registration

- principled approach
- can be used for morphometry through analysis of the computed deformations

LDDMM (Large Deformation Diffeomorphic Metric Mapping)


Intuition: One can consider ϕ as the concatenation of small deformations ϕ_{u_i} .

$$\phi = \Phi_n \text{ where the } \Phi_k \text{ are recursively defined by } \Phi_0 = Id \text{ and } \Phi_{k+1} = \phi_{u_{k+1}} \circ \Phi_k$$

LDDMM: The deformation ϕ is defined as the integration of a time-dependent velocity vector field $v(., t)$:

$$\begin{cases} \frac{\partial \phi_v}{\partial t}(x, t) = v(\phi_v(x, t), t) & \forall t \in [0, 1] \\ \phi_v(x, 0) = x & \forall x \in \mathbb{R}^3 \end{cases}$$

Position of x at
time t



The resulting transformation is $\phi = \phi_v(x, 1)$


One can define a right-invariant distance on the group of diffeomorphisms:

$$D(Id, \phi) = \inf \left\{ \int_0^1 \|v(\cdot, t)\|_V dt; v \in L^2([0, 1], V), \phi_v = \phi \right\}$$


Part 8 – Registration

8.3 (Dis)similarity measures


(Dis)similarity measures




(Dis)similarity measures




(Dis)similarity measures




(Dis)similarity measures



(Dis)similarity measures




(Dis)similarity measures



(Dis)similarity measures



(Dis)similarity measures



(Dis)similarity measures

Objective function

, cost function, energy function

$$C(T) = D(I \circ T, J)$$

transformation
moving image
dissimilarity measure
fixed image

The diagram shows the mathematical expression for a dissimilarity measure, $C(T) = D(I \circ T, J)$. Handwritten labels with colored arrows point to each part of the equation:

- A blue arrow points from the label "transformation" to the term T inside the parentheses.
- A purple arrow points from the label "moving image" to the term $I \circ T$ inside the parentheses.
- A green arrow points from the label "dissimilarity measure" to the entire function $D(\cdot, \cdot)$.
- A red arrow points from the label "fixed image" to the term J inside the parentheses.

(Dis)similarity measures

Optimisation problem

$$\hat{T} = \arg \min_T C(T)$$

return the argument (not the value)

search T with minimum cost value

cost function $C: \mathbb{R}^d \rightarrow \mathbb{R}$

d.o.f./parameters of transform

The diagram shows the optimization equation $\hat{T} = \arg \min_T C(T)$. A purple bracket underlines the $\arg \min_T$ part, with a handwritten note below it stating "return the argument (not the value)". A red circle highlights the T in \min_T , with a handwritten note below it stating "search T with minimum cost value". A blue bracket underlines the $C(T)$ part, with a handwritten note to its right stating "cost function $C: \mathbb{R}^d \rightarrow \mathbb{R}$ ". A green circle highlights the d in \mathbb{R}^d , with a handwritten note below it stating "d.o.f./parameters of transform".

(Dis)similarity measures

Mono-modal registration

- Image intensities are related by a (simple) function

Multi-modal registration

- Image intensities are related by a complex function or statistical relationship

(Dis)similarity measures

Intensity differences

Sum of squared differences (SSD)


$$D_{SSD}(I \circ T, J) = \frac{1}{N} \sum_{i=1}^N (I(T(x_i)) - J(x_i))^2$$

Sum of absolute differences (SAD)

$$D_{SAD}(I \circ T, J) = \frac{1}{N} \sum_{i=1}^N |I(T(x_i)) - J(x_i)|$$

Assumption: **identity** relationship between intensity distributions

Application: mono-modal registration (e.g. CT-CT)




(Dis)similarity measures

Correlation coefficient (CC)

$$D_{CC}(I \circ T, J) = -\frac{\frac{1}{N} \sum_{i=1}^N (I(T(x_i)) - \mu_I)(J(x_i) - \mu_J)}{\sqrt{\frac{1}{N} \sum_{i=1}^N (I(T(x_i)) - \mu_I)^2} \sqrt{\frac{1}{N} \sum_{i=1}^N (J(x_i) - \mu_J)^2}}$$


cov(I, J)

μ_I : mean intensity of image I
 μ_J : mean intensity of image J




Assumption: linear relationship between intensity distributions

Application: (mainly) mono-modal registration (e.g. MR-MR)






(Dis)similarity measures

Statistical relationship





(Dis)similarity measures

2D intensity histograms



(Dis)similarity measures

MR/MR





registered

misregistered by 2mm

misregistered by 5mm

(Dis)similarity measures

CT/MR





registered

misregistered by 2mm

misregistered by 5mm

(Dis)similarity measures

MR/PET



registered

misregistered by 2mm

misregistered by 5mm

(Dis)similarity measures

Intensity distributions

$$p(i, j) = \frac{h(i, j)}{N} \quad \text{— counts in histogram}$$


joint probability of an image point having a value i in image I and value j in image J

$$p(i) = \sum_j p(i, j)$$

marginal probability of an image point having a value i in image I

$$p(j) = \sum_i p(i, j)$$

marginal probability of an image point having a value j in image J



(Dis)similarity measures

Shannon entropy

$$H(I) = - \sum_i p(i) \log p(i)$$

amount of information contained in image I

Joint entropy

$$H(I, J) = - \sum_i \sum_j p(i, j) \log p(i, j)$$

amount of information contained in the combined image I, J

Could be used for
registration...

$$\mathcal{D}_{\mathcal{J}^E}(I \circ \bar{T}, \bar{J}) = H(I \circ \bar{T}, \bar{J})$$

(Dis)similarity measures

Mutual information [Viola et al. 1995]

$$MI(I, J) = H(I) + H(J) - H(I, J)$$

describes how well one image can be explained by another image

This can be rewritten in terms of marginal and joint probabilities

$$MI(I, J) = - \sum_i \sum_j p(i, j) \log \frac{p(i, j)}{p(i) p(j)}$$

The dissimilarity measure is then defined as

$$D_{MI}(I \circ T, J) = -MI(I \circ T, J)$$

(Dis)similarity measures

Normalised mutual information [Studholme et al. 1999]

$$NMI(I, J) = \frac{H(I) + H(J)}{H(I, J)}$$

is independent of the amount of overlap between images

The dissimilarity measure is then defined as



$$D_{NMI}(I \circ T, J) = -NMI(I \circ T, J)$$

Assumption: **statistical** relationship between intensity distributions


Application: (mainly) multi-modal registration (e.g. CT-MR)

(Dis)similarity measures


Translation experiment: mono-modal



D_{SSD}





D_{CC}



D_{NMI}

(Dis)similarity measures

Translation experiment: multi-modal




D_{SSD}

D_{CC}

D_{NMI}


(Dis)similarity measures

(Dis)similarity measures are evaluated in the overlapping region of the two images




(Dis)similarity measures

Capture Range



(Dis)similarity measures


Local Optima



(Dis)similarity measures

Multi-scale, hierarchical Registration

- Successively increase degrees of freedom
- Gaussian image pyramids




Part 8 – Registration

8.4 Other technical aspects


Interpolation

$$D_{SSD}(I \circ T, J) = \frac{1}{N} \sum_{i=1}^N (I(T(x_i)) - J(x_i))^2$$



zoom

compute weighted sum for $I(T(x_i))$
interpolation





Resampling

Forward warping

- Cycle through original image, and transport intensities forward
- Holes can occur!

Backward warping

- Cycle through the new image grid, and do backward look up in original image




Initialisation

Initialisation is critical for intensity-based registration

Two common heuristics to deal with initialisation:

- 1) Ignore image specific origin information, align image centres



Initialisation


Initialisation is critical for intensity-based registration

Two common heuristics to deal with initialisation:

2) Align the centres of intensity masses

$$c_I = \frac{1}{Z} \sum_{i=1}^N (I(x_i) - \min(I)) \cdot T_{ItW} x_i$$


$$\text{with } Z = \sum_{i=1}^N (I(x_i) - \min(I))$$




Part 8 – Registration

8.5 Applications

Multimodal image fusion




Pre and post-op (surgical operation)




Motion

Cardiac Motion




Respiratory Motion



Source: Oktay et al. MICCAI 2016

Contrast and non-contrast images


Contrasted and non-contrasted images [Rueckert et al. 1999]




Atlas construction

Atlas construction

- Builds an “average” of a group of participants
- This avoids choosing an arbitrary patient as a target when registering N ($N > 2$) patients together
- The “average” is called an atlas or template
- Two options when doing inter-subject registration (with $N > 2$)
 - Build an atlas from the group of patients
 - Use a predefined atlas (built from another population)




Segmentation based on registration




Reference MRI



Registration:
compute
transformation
 ϕ




MRI to
segment



Reference
segmentation




Apply
transformation
 ϕ



Obtained
segmentation

Segmentation based on registration



With a multiple references (better handling of anatomical variability)

Segmentation based on registration

- Multi-atlas registration-based segmentation
 - Was the state of the art before deep learning
 - Is still a competitive method, thanks to its precision and robustness


Part 8 – Registration

8.6 Registration using deep learning

Supervised approaches

Nonrigid Image Registration Using Multi-scale 3D CNNs



Trained on synthetic deformations



https://doi.org/10.1007/978-3-319-66182-7_27

Unsupervised approaches



Spatial Transformer Networks



<https://arxiv.org/abs/1506.02025>

Unsupervised approaches

Spatial Transformer Networks




https://pytorch.org/tutorials/intermediate/spatial_transformer_tutorial.html

<https://arxiv.org/abs/1506.02025>

Unsupervised approaches


End-to-End Unsupervised Deformable Image Registration with a CNN



Unsupervised approaches

An Unsupervised Learning Model for Deformable Image Registration


Moving 3D Image (M)



Fixed 3D Image (F)



$$g_{\theta}(F, M)$$




$$\text{Moved } (M(\phi))$$

Spatial Transform

$$\text{Loss Function } (\mathcal{L})$$




$$g_{\theta}(F, M) \text{ for VoxelMorph-1}$$



Registration using deep learning

VoxelMorph: A Learning Framework for Deformable Image Registration



Part 8 – Registration

8.7 Some classical registration softwares

Software

- Often, you may need to register your data prior to doing machine learning
- For instance, it is quite common to perform a linear registration before applying deep learning algorithms
 - This often helps the training
- For this, there are some robust and well-validated freely available software developed by the community

Software

- ANTs - <http://stnava.github.io/ANTs/>
 - Provides different types of deformation models and similarity metrics
 - Linear transformation
 - Non-linear transformation using B-splines
 - Non-linear transformation using diffeomorphisms
- FSL – <https://fsl.fmrib.ox.ac.uk/fsl/fslwiki/FSL>
 - Very commonly used for linear registration
 - FIRST – linear registration tool
 - <https://fsl.fmrib.ox.ac.uk/fsl/fslwiki/FLIRT>
- Deformetrica - <https://www.deformetrica.org/>
 - Diffeomorphic deformations
 - Provides atlas construction and deformation-based analysis
 - Can be used with surface data