Gap-Aware Instance Optimality of the Secretary Problem under Smoothed Perturbation

Ethan Farah
CS 264: Beyond Worst Case Analysis
Department of Mechanical Engineering, Stanford School of Engineering
Department of Computer Science, Stanford School of Engineering
Department of Mathematics, Stanford University
efarah@stanford.edu

Abstract

The classical secretary problem admits at most a $\frac{1}{e} \approx 0.37$ success probability in the worst case, yet practitioners routinely beat this benchmark on real data. Why? I answer this by embedding the problem in a *smoothed perturbation model*: an adversary chooses the value range $[\min, \max]$ and an i.i.d. generating process, but every density is capped by $\frac{1}{\sigma R}$, where $R = \max - \min$ and $\sigma > 0$ is a tunable *concentration parameter*.

Two structural quantities drive the difficulty of an instance: the *gap* $g = \frac{m - m_2}{R}$ between the top two values and the concentration σ that limits how tightly the remaining values can cluster. I design a σ*-aware* algorithm whose threshold adapts automatically to these two signals and prove three results.

First, I establish **near-optimal performance whenever the gap is visible**. If g is large (a condition that holds with high probability when σ is small), the algorithm succeeds with probability $(1 - \frac{1}{e})\big(1 - o(1)\big)$. Second, I prove a **tight upper bound** through an adversarial "two-bump" construction that shows *no* algorithm that knows σ can beat my guarantee by more than a constant factor. Third, I demonstrate **instance-optimality**: uniformly over all input distributions that satisfy the density cap, the new algorithm achieves at least one-third of the success probability of the true optimum, making it $\frac{1}{3}$–instance-optimal.

Together these results explain precisely when, and by how much, the secretary problem becomes easier than its worst case.

1 Introduction

Let us define the secretary problem concretely: An adversary fixes n numeric values $v_1, \ldots, v_n$. These values arrive in a uniformly random order. An algorithm observes each value once and must immediately make a permanent decision on that value, ultimately accepting just one item. The algorithm aims to maximize the probability of selecting the maximum. The best worst-case success probability is famously $\frac{1}{e}$ (roughly 0.37).

In the spirit of the course, worst-case analysis (as done by Borodin and El-Yaniv) is not sufficient to capture how the "distinguishability" of the top value affects algorithm performance. For many real-world multisets of values, the optimal success probability can be significantly higher than $\frac{1}{e}$.

I resolve this gap between theory and practice by introducing a smoothed perturbation model that captures when and why the secretary problem becomes easier than its worst case.

My contributions are threefold. First, I provide a **gap-aware algorithm** through a simple σ-aware threshold strategy. When the gap is visible (precisely, when $m_2(1 + \beta) < m$ with $\beta = 1$) it wins

37th Conference on Neural Information Processing Systems (NeurIPS 2023).

with probability $(1-\frac{1}{e})\big(1-\varepsilon(n,\sigma)\big)$ where $\varepsilon \to 0$ as n grows. Second, I establish a **matching lower bound** where a two-bump adversary shows that any algorithm, no matter how sophisticated, can be forced below this curve by a constant factor $\kappa \leq 3$. Third, I prove $\frac{1}{3}$**–instance optimality** by putting the two bounds together to show

$$\Pr[\text{ALG picks } m] \;\geq\; \tfrac{1}{3}\,\mathrm{OPT}_\sigma,$$

where OPT_σ is the best success probability achievable with full knowledge of σ. A more cautious reading—useful if one mistrusts constants—already yields a $\frac{1}{6}$ guarantee.

These results recover the classical $\frac{1}{e}$ barrier when the gap is genuinely tiny, yet confirm the folklore that "easy" secretary instances are ubiquitous and exploitable.

2 Related Work

The secretary problem has been extensively studied beyond worst-case analysis. Recent work has explored the problem with predictions [1], where algorithms have access to machine-learned advice about future arrivals. My approach differs by focusing on structural properties of the value distribution rather than external predictions.

The concept of instance optimality in online algorithms has been explored in various contexts. For the secretary problem specifically, prior work has considered different arrival models and objective functions [4, 5], but the gap-based parameterization I propose provides a new lens for understanding instance difficulty.

3 Problem Formulation

3.1 Smoothed Perturbation Model

Without any information or constraints on the distributions of values, analysis becomes either *really* hard to get a valuable bound or *really* boring just to get a functionally useless bound on performance. We will allow the adversary to choose a specific range $[\min, \max]$ with $\max - \min = R$. Next, the adversary will choose the maximum value $m \in [\min, \max]$. Finally, the adversary will choose distributions $F_1, \ldots F_{n-1}$ from which the remaining $n-1$ values will be drawn.

We will also apply a density constraint to each distribution: each F_i has density $f_i(x) \leq \frac{1}{\sigma R}$ for all $x \in [\min, \max]$. This will prevent values from clustering near m.

Nature will draw values $v_1, \ldots, v_{n-1}$ from these distributions (with value $v_n = m$), and all of these values will arrive in a uniformly random order to the online algorithm.

3.2 The Gap Parameter

My EXTRA twist on the problem will be to use a so-called "gap" parameter, which I semantically define as the normalized difference between the true highest value in V and the true second-highest value in V.

Definition 1 (Normalized Gap)**.** *Let $V = \{v_1, \ldots, v_n\}$ be a multiset of values with $|V| \geq 2$. Let m and R be defined as above and $m_2 = \max\{V \setminus \{m\}\}$. Then, define the gap g to be*

$$g(V) = \begin{cases} \frac{m-m_2}{R} & \textit{if } R > 0 \\ 1 & \textit{if all values in } V \textit{ are identical.} \end{cases}$$

Essentially, I identify and exploit the fact that when g is really large, the maximum stands out significantly compared to the other values and should be easy/obvious to identify. Small gap instances ($g \to 0$) present similar challenges to the traditional worst-case analysis, where no structural advantage can be exploited.

3.3 Model Assumptions

My work operates within the smoothed random permutation model, where an adversary chooses the value generation process subject to concentration constraints, and nature both draws the values and

presents them in uniformly random order. Unlike the standard analysis, I focus on how the structural properties of the realized multiset V (specifically the gap parameter) affect achievable performance:

- **Adversary's choices:** Range $[\min, \max]$ with $R = \max - \min > 0$ and $\min \geq 0$, maximum value $m \in [\min, \max]$, and distributions $F_1, \ldots, F_{n-1}$ subject to density constraint $f_i(x) \leq \frac{1}{\sigma R}$ for all $x \in [\min, \max]$ and all i.
- **Nature's role:** Draws values $v_1, \ldots, v_{n-1}$ from the chosen distributions, then presents all n values (including m) in uniformly random order.
- **Algorithm's knowledge:** Knows the concentration parameter $\sigma > 0$ and number of items n, but does not know the realized values, true gap $g(V)$, or adversary's specific choices.
- **Technical assumptions:** All values lie in $[\min, \max]$ with probability 1, distributions are continuous (ties have probability 0), $n \geq 3$, values drawn independently, and each F_i is absolutely continuous with respect to Lebesgue measure (no point masses).

I will define OPT_σ to be the maximum success probability achievable by any algorithm that knows the concentration parameter σ.

3.4 Probabilistic Gap Condition Analysis

When σ is small (tight concentration constraints), our analysis will show the gap condition holds with high probability, enabling strong performance guarantees. When σ is large, the condition may fail more often, but this corresponds precisely to instances where no algorithm can significantly outperform the classical $\frac{1}{e}$ bound anyway.

Our performance guarantees in Section 4 require the condition $m_2(1+\beta) < m$ to hold for the realized instance. While the algorithm cannot verify this condition in advance, we now establish the probability with which this gap condition holds under our density constraints.

Theorem 1 (Probabilistic Gap Condition)**.** *Consider the smoothed perturbation model with density constraint $f_i(x) \leq \frac{1}{\sigma R}$ for all $i \in \{1, \ldots, n-1\}$ and $x \in [\min, \max]$, and fix $\beta = 1$. Then for any adversary's choice of range, maximum value, and distributions (subject to the density constraints):*

$$\Pr[m_2(1+\beta) \geq m] \leq \min\left\{1, \frac{n-1}{2\sigma}\right\}$$

where the probability is taken over nature's randomness in drawing the values $v_1, \ldots, v_{n-1}$.

Proof. For the gap condition to fail, we need $m_2 \geq \frac{m}{1+\beta} = \frac{m}{2}$. Define the "bad" region $\mathcal{B} = [\frac{m}{2}, m)$.

For each value v_i drawn from distribution F_i, the probability it falls in the bad region is:

$$\Pr[v_i \in \mathcal{B}] = \int_{\frac{m}{2}}^{m} f_i(x)\, dx \leq \int_{\frac{m}{2}}^{m} \frac{1}{\sigma R}\, dx = \frac{\frac{m}{2}}{\sigma R}$$

Since $m \leq \max \leq \min + R$, we have $\frac{m}{R} \leq 1$, so:

$$\Pr[v_i \in \mathcal{B}] \leq \frac{1}{2\sigma}$$

The gap condition fails if and only if at least one of the $n-1$ values falls in $\mathcal{B}$. Because draws are independent, $\Pr[\exists i : v_i \in \mathcal{B}] \leq \sum_i \Pr[v_i \in \mathcal{B}]$; we do not need the stronger Chernoff bound here. Therefore:

$$\begin{aligned}\Pr[m_2 \geq m/2] &= \Pr[\exists i : v_i \in \mathcal{B}] \\ &\leq (n-1) \cdot \frac{1}{2\sigma} = \frac{n-1}{2\sigma}\end{aligned}$$

Since probabilities cannot exceed 1, we have:

$$\Pr[m_2(1+\beta) \geq m] \leq \min\left\{1, \frac{n-1}{2\sigma}\right\}$$

□

Remark 1. *This theorem shows that the gap condition failure probability scales as $\frac{n-1}{\sigma}$. When $\sigma \ll n$, the gap condition fails with high probability, but this occurs precisely in the regime where the density constraint is so loose that no algorithm can significantly outperform the classical $\frac{1}{e}$ bound. Conversely, when $\sigma \gg n$, the gap condition holds with high probability, enabling the strong performance guarantees of our subsequent theorems.*

3.5 σ-Optimality Framework

My original goal is to first design an algorithm or algorithm family that, for every adversary's choice of range, maximum value, and distributions, achieves the optimal success probability up to a constant-factor slack c, and second to prove matching lower bounds, thus yielding true instance optimality.

Definition 2 (σ-Optimal Secretary Algorithm)**.** *An algorithm ALG is c-instance optimal for a concentration parameter σ if for every adversary's choice (subject to the density constraints),*

$$\Pr[\textit{ALG selects } m] \geq c \cdot \textit{OPT}_\sigma$$

where the expectation is over nature's randomness in both drawing the values and presenting them in random order, and $\textit{OPT}_\sigma$ is the maximum expected success probability achievable by any algorithm that knows σ.

4 Algorithm Design and Bounding Performance

4.1 Defining the Algorithm

Our approach will center on designing an algorithm that adapts its aggressiveness based on the concentration parameter σ. When σ is small, the density constraint severely limits how values can cluster, allowing the algorithm to be more selective. When σ is large, values can concentrate more freely, so the algorithm must be more conservative. This adaptation is achieved through a threshold scaling function $f(\sigma)$ that decreases as concentration constraints tighten.

Algorithm 1 σ-Aware Secretary Algorithm

Require: Concentration parameter $\sigma > 0$, number of items $n \geq 3$
Ensure: Constants $\beta > 0$ and $c > 0$ where:
  β (threshold cap): prevents overly aggressive thresholds
  c (scaling parameter): controls responsiveness to concentration level σ
 Phase 1 (Sampling): Observe first $t = \lfloor \frac{n}{e} \rfloor$ items
  Let $s = \max_{i \in \{1,\ldots,t\}} v_i$
 Phase 2 (Gap Exploitation): For items $t+1$ to $n-1$:
  Let $\tau = s(1 + f(\sigma))$ where $f(\sigma) = \min\left\{\beta, \frac{c}{\sigma}\right\}$
  Accept first item v_i such that $v_i > \tau$
 Phase 3 (Fallback): If no item accepted yet:
  Accept item n if it exceeds all previous items

4.2 Performance Analysis for Large Gap Instances

We begin our analysis by establishing performance guarantees when the gap between the maximum and second maximum is sufficiently large. The key insight is that when this gap exceeds our algorithm's threshold scaling factor, we can guarantee success whenever certain favorable events occur during the sampling phase.

Note that while our analysis characterizes performance in terms of the realized second maximum m_2, the algorithm itself never needs to know m_2—we are simply analyzing how the algorithm performs on instances with specific structural properties.

Lemma 1 (Large Gap Performance)**.** *Consider the σ-aware secretary algorithm with $f(\sigma) = \min\{\beta, \frac{c}{\sigma}\}$ and $t = \lfloor \frac{n}{e} \rfloor$. Let V be a realized instance with normalized gap $g(V) = \frac{m-m_2}{R}$ Assume $m_2(1+\beta) < m$ and $n \geq 3$. Let event S represent algorithm success. Define the "happy set"*

$\mathcal{H} = \{v \in V \setminus \{m\} \mid v > \frac{m_2}{1+f(\sigma)}\}$. *Then:*

$$\Pr[S] \geq \left(1 - \frac{1}{e}\right)\left(1 - \frac{(n-1-|\mathcal{H}|)!(n-1-t)!}{(n-1-|\mathcal{H}|-t)!(n-1)!}\right)$$

Remark 2. *The condition $m_2(1+\beta) < m$ is satisfied when the gap between the maximum and second maximum is sufficiently large relative to the algorithm's threshold scaling factor β. This connects to our gap parameter: larger values of $g(V) = \frac{m-m_2}{R}$ make this condition more likely to hold.*

Proof. Recall that Phase 1 observes the first $t = \lfloor \frac{n}{e} \rfloor$ items and rejects them all. We begin by defining event $E = \{m \text{ appears after position } t\}$. If E does not happen, then we cannot ever pick m because we will have skipped over it in Phase 1. We will proceed conditioning on E.

Because m appears after the first t items, we know that s is upper bounded by m_2. Thus, we may rewrite τ

$$\begin{aligned}\tau &= s(1+f(\sigma)) \\ &\leq m_2(1+f(\sigma))\end{aligned}$$

Since $f(\sigma) = \min\left\{\beta, \frac{c}{\sigma}\right\}$, we always have $f(\sigma) \leq \beta$, so

$$\begin{aligned}\tau &\leq m_2(1+\beta) \\ &< m \quad \text{(by assumption)}\end{aligned}$$

Now, we note that we will only succeed if the threshold $\tau > m_2$. If at least one happy item is found during Phase 1, then $s \in \mathcal{H}$ and $\tau > m_2$. Define event $H := \{\text{at least one } h \in \mathcal{H} \text{ during Phase 1}\}$. By symmetry of the random permutation, conditioning on E means the first t positions contain a uniformly random subset of the $n-1$ non-maximum values. We will now compute $\Pr[H \mid E]$

$$\begin{aligned}\Pr[H \mid E] &= 1 - \Pr[H^c \mid E] \quad \text{(a.k.a. } \textit{no} \text{ items from } \mathcal{H} \text{ appear during Phase 1)} \\ &= 1 - \frac{\binom{(n-1)-|\mathcal{H}|}{t}}{\binom{n-1}{t}} \quad \text{(by modeling } H^c \sim \text{Hypergeometric}(n-1, |\mathcal{H}|, t)) \\ &= 1 - \frac{(n-1-|\mathcal{H}|)!(n-1-t)!}{(n-1-|\mathcal{H}|-t)!(n-1)!}\end{aligned}$$

We will now show that if E and H both happen, we are guaranteed success. Given H, we must have that $\tau = s(1+f(\sigma)) > \frac{m_2}{1+f(\sigma)}(1+f(\sigma)) = m_2$. Under E, when m appears (after position t), it satisfies $m > \tau$. Since all values $v \neq m$ satisfy $v \leq m_2 < \tau$, no non-maximum value that appears after position t can exceed τ. Therefore, m is the first value after position t to exceed τ, so the algorithm accepts it. Together, $\Pr[S \mid E \cap H] = 1$.

Combining these results, we see

$$\begin{aligned}\Pr[S] \geq \Pr[S \cap E \cap H] &= \Pr[S \mid E \cap H] \cdot \Pr[E \cap H] \\ &= 1 \cdot \Pr[E] \cdot \Pr[H \mid E] \\ &\geq \left(1 - \frac{1}{e}\right)\left(1 - \frac{(n-1-|\mathcal{H}|)!(n-1-t)!}{(n-1-|\mathcal{H}|-t)!(n-1)!}\right)\end{aligned}$$

where we used $\Pr[E] = \frac{n-t}{n} \geq 1 - \frac{1}{e}$ since $t = \lfloor \frac{n}{e} \rfloor$. □

4.3 Bounding Happy Set Size via Density Constraints

To convert our conditional performance bounds into concrete guarantees, we must characterize the size of the happy set $\mathcal{H}$. The density constraint provides exactly the tool we need: by limiting how much probability mass can concentrate near any threshold value, we can lower bound the expected number of values that exceed our happiness threshold.

Lemma 2 (Happy Set Size via Density Constraint)**.** *Consider the σ-aware secretary algorithm with threshold function $f(\sigma) = \min\{\beta, \frac{c}{\sigma}\}$. Let V be a realized instance with second maximum m_2. Let $\ell = \frac{m_2}{1+f(\sigma)}$ Define the happy set $\mathcal{H} = \{v \in V \setminus \{m\} \mid v > \ell\}$. We analyze the expected size of $\mathcal{H}$ by conditioning on the value of m_2. Assume $\ell \geq \min$. Then*

$$\mathbb{E}[|\mathcal{H}| \mid m_2] \geq (n-1)\left(1 - \frac{\ell - \min}{\sigma R}\right)$$

Proof. Let ℓ denote the happy threshold as defined in the lemma. Then values $v \notin \mathcal{H}$ are those satisfying $v \leq \ell$, which lie in the interval $[\min, \ell]$.

For each value v_i drawn from distribution F_i, conditional on m_2, the probability it falls in this interval is

$$\begin{aligned}\Pr[v_i \leq \ell] &= \int_{\min}^{\ell} f_i(x)\,dx \\ &\leq \int_{\min}^{\ell} \frac{1}{\sigma R}\,dx \\ &= \frac{\ell - \min}{\sigma R}\end{aligned}$$

Therefore, the expected number of values not in $\mathcal{H}$ is

$$\begin{aligned}\mathbb{E}[n-1-|\mathcal{H}|] &= \sum_{i=1}^{n-1} \Pr[v_i \leq \ell] \\ &\leq (n-1) \cdot \frac{\ell - \min}{\sigma R}\end{aligned}$$

Rearranging yields

$$\begin{aligned}\mathbb{E}[|\mathcal{H}|] &= (n-1) - \mathbb{E}[n-1-|\mathcal{H}|] \\ &\geq (n-1)\left(1 - \frac{\ell - \min}{\sigma R}\right)\end{aligned}$$

□

Remark 3. *Since our bounds hold for any realization of m_2, they also hold in expectation over m_2. That is, $\mathbb{E}[|\mathcal{H}|] = \mathbb{E}[\mathbb{E}[|\mathcal{H}| \mid m_2]] \geq \mathbb{E}[(n-1)\left(1 - \frac{\ell - \min}{\sigma R}\right)]$.*

Remark 4. *This bound is vacuous if $\ell - \min \geq \sigma R$; in that case the lemma gives $\mathbb{E}[|\mathcal{H}|] \geq 0$, which remains true but uninformative.*

4.4 Concentration of Happy Set Size

While the previous lemma provides an expectation bound on the size of the happy set, we need high-probability guarantees to convert our conditional performance analysis into concrete algorithmic bounds. Since the happy set size is a sum of independent random variables, concentration inequalities allow us to show that $|\mathcal{H}|$ is close to its expectation with high probability.

Lemma 3 (Concentration of Happy Set Size)**.** *Let $\ell = \frac{m_2}{1+f(\sigma)}$ as in Lemma 2. For any $\delta > 0$, with probability at least $1 - \delta$:*

$$|\mathcal{H}| \geq (n-1)\left(1 - \frac{\ell - \min}{\sigma R}\right) - \sqrt{2(n-1)\ln\frac{1}{\delta}}$$

Proof. For each $i \in \{1, \ldots, n-1\}$, define the indicator random variable

$$X_i = \begin{cases} 1 & \text{if } v_i \in \mathcal{H} \\ 0 & \text{otherwise} \end{cases}$$

Then $|\mathcal{H}| = \sum_{i=1}^{n-1} X_i$.

From the proof of Lemma 2, we know that for each i,

$$\mathbb{E}[X_i] = \Pr[v_i \in \mathcal{H}] = \Pr[v_i > \ell] \geq 1 - \frac{\ell - \min}{\sigma R}$$

Therefore,

$$\begin{aligned}\mathbb{E}[|\mathcal{H}|] &= \sum_{i=1}^{n-1} \mathbb{E}[X_i] \\ &\geq (n-1)\left(1 - \frac{\ell - \min}{\sigma R}\right)\end{aligned}$$

Since the values $v_1, \ldots, v_{n-1}$ are drawn independently from their respective distributions, the random variables $X_1, \ldots, X_{n-1}$ are independent. Moreover, each X_i is bounded: $0 \leq X_i \leq 1$.

By Hoeffding's inequality[1], for any $t > 0$,

$$\Pr\left[|\mathcal{H}| \leq \mathbb{E}[|\mathcal{H}|] - t\right] \leq \exp\left(\frac{-2t^2}{n-1}\right)$$

Setting $\exp\left(\frac{-2t^2}{n-1}\right) = \delta$ and solving for t,

$$t = \sqrt{2(n-1)\ln\frac{1}{\delta}}$$

Therefore, with probability at least $1 - \delta$,

$$\begin{aligned}|\mathcal{H}| &\geq \mathbb{E}[|\mathcal{H}|] - \sqrt{2(n-1)\ln\frac{1}{\delta}} \\ &\geq (n-1)\left(1 - \frac{\ell - \min}{\sigma R}\right) - \sqrt{2(n-1)\ln\frac{1}{\delta}}\end{aligned}$$

□

4.5 Main Performance Guarantee

We now combine our conditional performance analysis with the concentration results to establish our primary theorem. This result shows that when the structural conditions favor good performance—namely, when the gap is sufficiently large and the concentration parameter allows for meaningful probabilistic guarantees—our algorithm achieves substantially better than the classical $\frac{1}{e}$ bound with high probability.

Theorem 2 (High-Probability Performance Guarantee)**.** *Consider the σ-aware secretary algorithm with $f(\sigma) = \min\{\beta, \frac{c}{\sigma}\}$ and $t = \lfloor \frac{n}{e} \rfloor$. Let V be a realized instance with second maximum m_2 and $\ell = \frac{m_2}{1+f(\sigma)}$. Assume:*

1. $m_2(1+\beta) < m$ *(sufficient gap condition)*
2. $\ell \geq \min$ *(valid threshold condition)*
3. $(n-1)\left(1 - \frac{\ell - \min}{\sigma R}\right) \geq \sqrt{2(n-1)\ln\frac{1}{\delta}}$ *(concentration condition)*

Then with probability at least $1 - \delta$, the algorithm achieves:

$$\Pr[S] \geq \left(1 - \frac{1}{e}\right)\left(1 - \left(\frac{A(\delta)}{n-1}\right)^t\right)$$

where $A(\delta) = \frac{\ell - \min}{\sigma R} \cdot (n-1) + \sqrt{2(n-1)\ln\frac{1}{\delta}}$.

[1] Hoeffding's Inequality: Let $X_1, \ldots, X_k$ be independent random variables with $X_i \in [a_i, b_i]$ for all i. Let $S = \sum_{i=1}^{k} X_i$. Then for any $t > 0$, $\Pr[S \leq \mathbb{E}[S] - t] \leq \exp\left(\frac{-2t^2}{\sum_{i=1}^{k}(b_i - a_i)^2}\right)$.

This theorem reveals the fundamental relationship between concentration constraints and algorithmic performance in the secretary problem. When the concentration parameter σ is small, the density constraint forces most values to spread out across the range, making the second maximum m_2 likely to be far from the true maximum m. This creates a large gap, which in turn makes the happy threshold $\ell = \frac{m_2}{1+f(\sigma)}$ small relative to the range σR, leading to a small value of $A(\delta)$ and excellent performance. Conversely, when σ is large, values can cluster more freely, potentially creating smaller gaps and degrading performance—but in such cases, no algorithm can significantly outperform the classical $\frac{1}{e}$ bound anyway. The concentration term $\sqrt{2(n-1)\ln\frac{1}{\delta}}$ becomes negligible for large n, so the primary driver of performance is the ratio $\frac{\ell-\min}{\sigma R}$, which directly captures how the density constraint interacts with the realized gap structure. This suggests that our algorithm naturally adapts to instance difficulty: it performs well precisely when the structural properties of the instance (controlled by σ) make good performance possible.

Proof. Let Ω be the event that the concentration bound from Lemma 3 holds

$$\Omega = \left\{ |\mathcal{H}| \geq (n-1)\left(1 - \frac{\ell - \min}{\sigma R}\right) - \sqrt{2(n-1)\ln\frac{1}{\delta}} \right\}$$

By Lemma 3, $\Pr[\Omega] \geq 1 - \delta$.

We will show that conditioning on Ω, the algorithm achieves the desired performance bound. Since the conditions of Lemma 1 are satisfied (by assumptions 1 and 2), we have

$$\Pr[S \mid \Omega] \geq \left(1 - \frac{1}{e}\right)\left(1 - \frac{(n-1-|\mathcal{H}|)!(n-1-t)!}{(n-1-|\mathcal{H}|-t)!(n-1)!}\right)$$

Now we bound the factorial term. Under event Ω, we have

$$|\mathcal{H}| \geq (n-1)\left(1 - \frac{\ell - \min}{\sigma R}\right) - \sqrt{2(n-1)\ln\frac{1}{\delta}}$$

Rearranging to find an upper bound on $n - 1 - |\mathcal{H}|$

$$\begin{aligned}
n - 1 - |\mathcal{H}| &\leq n - 1 - \left[(n-1)\left(1 - \frac{\ell - \min}{\sigma R}\right) - \sqrt{2(n-1)\ln\frac{1}{\delta}}\right] \\
&= n - 1 - (n-1)\left(1 - \frac{\ell - \min}{\sigma R}\right) + \sqrt{2(n-1)\ln\frac{1}{\delta}} \\
&= (n-1)\cdot\frac{\ell - \min}{\sigma R} + \sqrt{2(n-1)\ln\frac{1}{\delta}} \\
&= A(\delta)
\end{aligned}$$

Therefore, under event Ω, we have $n - 1 - |\mathcal{H}| \leq A(\delta)$. We can now bound the factorial expression. If $A(\delta) \geq t$, then

$$\begin{aligned}
\frac{(n-1-|\mathcal{H}|)!(n-1-t)!}{(n-1-|\mathcal{H}|-t)!(n-1)!} &\leq \frac{A(\delta)!(n-1-t)!}{(A(\delta)-t)!(n-1)!} \\
&= \prod_{j=0}^{t-1} \frac{A(\delta)-j}{n-1-j} \leq \left(\frac{A(\delta)}{n-1}\right)^t
\end{aligned}$$

If $A(\delta) < t$, then $|\mathcal{H}|$ is so large that essentially all non-maximum values are happy, and the hypergeometric probability approaches 0, giving near-optimal performance.

Substituting this bound back into our performance inequality

$$\Pr[S \mid \Omega] \geq \left(1 - \frac{1}{e}\right)\left(1 - \left(\frac{A(\delta)}{n-1}\right)^t\right)$$

Since this bound holds whenever Ω occurs, and $\Pr[\Omega] \geq 1 - \delta$, we conclude that with probability at least $1 - \delta$, the algorithm achieves

$$\Pr[S] \geq \left(1 - \frac{1}{e}\right)\left(1 - \left(\frac{A(\delta)}{n-1}\right)^t\right).$$

□

4.6 Tightened Analysis via Multiplicative Concentration

The preceding theorem provides a strong performance guarantee, but we can achieve even tighter bounds by leveraging multiplicative concentration inequalities. The key observation is that Hoeffding's inequality provides additive concentration around the expectation, with deviation scaling as $\sqrt{n-1}$. However, when the expected size of the happy set $\mu = \mathbb{E}[|\mathcal{H}|]$ is large—which occurs precisely when the concentration parameter σ is small and our algorithm should perform well—we can apply Chernoff bounds to achieve multiplicative concentration with deviation scaling as $\sqrt{\mu}$. Since $\mu \leq n-1$ always, and $\mu \ll n-1$ when σ is large, this substitution never worsens our bound and can provide substantial improvements in the regime where good performance is achievable. The following lemma formalizes this multiplicative concentration result.

Lemma 4 (Concentration of Happy Set Size — Multiplicative)**.** *Let $\ell = \frac{m_2}{1+f(\sigma)}$ as in Lemma 2. Define $\mu = (n-1)\left(1 - \frac{\ell - \min}{\sigma R}\right)$ and assume $\mu \geq 1$. For any $\varepsilon \in (0,1)$ and $\delta > 0$ such that $\delta = \exp\left(-\frac{\varepsilon^2 \mu}{3}\right)$, with probability at least $1-\delta$:*

$$|\mathcal{H}| \geq (1-\varepsilon)\mu$$

Equivalently, setting $\varepsilon = \sqrt{\frac{3 \ln \frac{1}{\delta}}{\mu}}$, with probability at least $1-\delta$:

$$|\mathcal{H}| \geq \mu - \sqrt{3\mu \ln \frac{1}{\delta}}$$

Proof. For each $i \in \{1, \ldots, n-1\}$, define the indicator random variable

$$X_i = \begin{cases} 1 & \text{if } v_i \in \mathcal{H} \\ 0 & \text{otherwise} \end{cases}$$

Then $|\mathcal{H}| = \sum_{i=1}^{n-1} X_i$. From the proof of Lemma 2, we know that for each i

$$\mathbb{E}[X_i] = \Pr[v_i \in \mathcal{H}] = \Pr[v_i > \ell] \geq 1 - \frac{\ell - \min}{\sigma R}$$

Therefore

$$\mathbb{E}[|\mathcal{H}|] = \sum_{i=1}^{n-1} \mathbb{E}[X_i] \geq (n-1)\left(1 - \frac{\ell - \min}{\sigma R}\right) = \mu$$

Since the values $v_1, \ldots, v_{n-1}$ are drawn independently from their respective distributions, the random variables $X_1, \ldots, X_{n-1}$ are independent. Moreover, each X_i is bounded: $0 \leq X_i \leq 1$.

By the Chernoff bound[2], for any $\varepsilon \in (0,1)$

$$\Pr\left[|\mathcal{H}| \leq (1-\varepsilon)\mathbb{E}[|\mathcal{H}|]\right] \leq \exp\left(-\frac{\varepsilon^2 \mathbb{E}[|\mathcal{H}|]}{3}\right)$$

Since $\mathbb{E}[|\mathcal{H}|] \geq \mu$, we have

$$\Pr\left[|\mathcal{H}| \leq (1-\varepsilon)\mu\right] \leq \exp\left(-\frac{\varepsilon^2 \mu}{3}\right)$$

[2]Chernoff Bound (Lower Tail, 3-denominator variant): Let $X_1, \ldots, X_k$ be independent random variables with $X_i \in [0,1]$ and $S = \sum_{i=1}^k X_i$. Then for any $\varepsilon \in (0,1)$, $\Pr[S \leq (1-\varepsilon)\mathbb{E}[S]] \leq \exp\left(-\frac{\varepsilon^2 \mathbb{E}[S]}{3}\right)$.

Setting $\exp\left(-\frac{\varepsilon^2\mu}{3}\right) = \delta$ and solving for ε

$$\varepsilon = \sqrt{\frac{3\ln\frac{1}{\delta}}{\mu}}$$

Therefore, with probability at least $1-\delta$

$$\begin{aligned}|\mathcal{H}| &\geq (1-\varepsilon)\mu \\ &= \left(1-\sqrt{\frac{3\ln\frac{1}{\delta}}{\mu}}\right)\mu \\ &= \mu - \sqrt{3\mu\ln\frac{1}{\delta}}\end{aligned}$$

□

Building on this multiplicative concentration result, we can now state a refined version of our main theorem that provides tighter bounds, particularly in the regime where σ is small and our algorithm is expected to perform well.

Theorem 3 (Tightened Performance Guarantee via Chernoff Bound)**.** *Consider the σ-aware secretary algorithm with $f(\sigma) = \min\{\beta, \frac{c}{\sigma}\}$ and $t = \lfloor \frac{n}{e} \rfloor$. Let V be a realized instance with second maximum m_2, $\ell = \frac{m_2}{1+f(\sigma)}$, and $\mu = (n-1)\left(1-\frac{\ell-\min}{\sigma R}\right)$. Assume:*

1. $m_2(1+\beta) < m$ *(sufficient gap condition)*
2. $\ell \geq \min$ *(valid threshold condition)*
3. $\mu \geq \max\left\{1, 3\ln\frac{1}{\delta}\right\}$ *(multiplicative concentration condition)*

Then with probability at least $1-\delta$, the algorithm achieves:

$$\Pr[S] \geq \left(1-\frac{1}{e}\right)\left(1-\left(\frac{A_{\textit{tight}}(\delta)}{n-1}\right)^t\right)$$

where $A_{\textit{tight}}(\delta) = (n-1)\cdot\frac{\ell-\min}{\sigma R} + \sqrt{3\mu\ln\frac{1}{\delta}}$.

This tightened result significantly improves upon Theorem 2 when the concentration parameter σ is small. The key insight is that the Chernoff bound's deviation term $\sqrt{3\mu\ln\frac{1}{\delta}}$ scales with the expected size of the happy set μ, rather than the total number of non-maximum items $n-1$. When σ is small, the density constraint forces μ to be close to $n-1$, so both bounds are comparable. However, when σ is moderately sized, we have $\mu < n-1$, making $A_{\text{tight}}(\delta) < A(\delta)$ and yielding substantially better performance guarantees. This captures the intuition that multiplicative concentration inequalities are naturally suited to settings where we expect most random variables to "succeed" (i.e., fall into the happy set).

Proof. Let Ω be the event that the concentration bound from Lemma 4 holds

$$\Omega = \left\{|\mathcal{H}| \geq \mu - \sqrt{3\mu\ln\frac{1}{\delta}}\right\}$$

By Lemma 4, $\Pr[\Omega] \geq 1-\delta$.

We will show that conditioning on Ω, the algorithm achieves the desired performance bound. Since the conditions of Lemma 1 are satisfied (by assumptions 1 and 2), we have

$$\Pr[S \mid \Omega] \geq \left(1-\frac{1}{e}\right)\left(1-\frac{(n-1-|\mathcal{H}|)!(n-1-t)!}{(n-1-|\mathcal{H}|-t)!(n-1)!}\right)$$

We can now bound the factorial expression. If $A(\delta) \geq t$, then

$$\frac{(n-1-|\mathcal{H}|)!(n-1-t)!}{(n-1-|\mathcal{H}|-t)!(n-1)!} \leq \frac{A(\delta)!(n-1-t)!}{(A(\delta)-t)!(n-1)!}$$
$$= \prod_{j=0}^{t-1} \frac{A(\delta)-j}{n-1-j} \leq \left(\frac{A(\delta)}{n-1}\right)^t$$

If $A(\delta) < t$, then $|\mathcal{H}|$ is so large that essentially all non-maximum values are happy, and the hypergeometric probability approaches 0, giving near-optimal performance.

Therefore, under event Ω, we have $n-1-|\mathcal{H}| \leq A_{\text{tight}}(\delta)$. Using the same factorial bound as in Theorem 2

$$\frac{(n-1-|\mathcal{H}|)!(n-1-t)!}{(n-1-|\mathcal{H}|-t)!(n-1)!} \leq \left(\frac{A_{\text{tight}}(\delta)}{n-t}\right)^t \leq \left(\frac{A_{\text{tight}}(\delta)}{n-1}\right)^t$$

Substituting this bound back into our performance inequality

$$\Pr[S \mid \Omega] \geq \left(1-\frac{1}{e}\right)\left(1-\left(\frac{A_{\text{tight}}(\delta)}{n-1}\right)^t\right)$$

Since this bound holds whenever Ω occurs, and $\Pr[\Omega] \geq 1-\delta$, we conclude that with probability at least $1-\delta$, the algorithm achieves the stated bound. □

Remark 5 (Gap Condition Trade-off)**.** *The condition $m_2(1+\beta) < m$ creates a trade-off in parameter selection: larger β allows the algorithm to succeed on instances with smaller gaps but risks overly aggressive thresholds, while smaller β provides safer thresholds but requires larger gaps for the theoretical guarantee to apply.*

Remark 6 (Fallback Phase Contribution)**.** *Our analysis focuses on Phases 1 and 2, but Phase 3 provides an additional $\frac{1}{n}$ success probability when neither phase succeeds. Since this term is always positive and independent of our bounds, it only improves performance without affecting our theoretical guarantees.*

Lemma 5 (Performance When Gap Condition Fails)**.** *If $m_2(1+\beta) \geq m$ with $\beta = 1$, then any secretary algorithm (including ours) achieves success probability at most $\frac{1}{e}$.*

Proof. When $m_2 \geq \frac{m}{2}$, the maximum and second maximum are indistinguishable to any algorithm that cannot see future values. In this case, even an algorithm with perfect knowledge of all distributions faces the fundamental limitation of the classical secretary problem: any threshold-based strategy either accepts a non-maximum value or risks missing the maximum entirely. The classical $\frac{1}{e}$ bound applies regardless of the algorithm's sophistication. □

5 Instance Optimality Analysis

Our main theorems establish absolute performance guarantees for the σ-aware secretary algorithm. To complete the instance optimality picture, we must show these bounds are competitive with the best possible performance achievable by any algorithm that knows σ. Specifically, we aim to prove that our algorithm is c-instance optimal for some universal constant $c > 0$.

The key challenge is upper bounding OPT_σ—the maximum success probability achievable by any σ-aware algorithm—across all possible adversarial choices of distributions. We approach this by constructing a particularly challenging family of instances that force any algorithm to make difficult trade-offs between being too conservative (missing opportunities when gaps are large) and too aggressive (failing when gaps are small).

Our approach centers on constructing a "worst-case" family of instances that forces any σ-aware algorithm into an impossible trade-off. We use a two-bump construction where the adversary concentrates probability mass at two carefully chosen locations: one near the minimum value and another just below the anticipated second maximum. This construction saturates the density constraint while creating a scenario where any algorithm must choose between being too aggressive (accepting low-value items) or too conservative (missing the true maximum). The following lemma formalizes this construction and proves a matching upper bound.

Lemma 6 (Upper Bound on OPT_σ)**.** *Fix $\beta = 1$, so $f(\sigma) = \min\{1, \frac{1}{\sigma}\}$. For every $n \geq 3$ and $\sigma > 0$, there exists an adversarial choice of distributions satisfying the density constraint such that*

$$OPT_\sigma \leq \left(1 - \frac{1}{e}\right) \min\{1, \kappa A\},$$

where $\kappa = 3$ is a universal constant and $A = \frac{n-1}{2\sigma}$.

Remark 7. *For every σ we normalize the bound to the worst-case value $A = \frac{n-1}{2\sigma}$, which represents the maximum expected number of values that could fall in the critical region under our density constraints.*

Proof. By Yao's minimax principle[3], it suffices to construct a probability distribution over instances and show that every deterministic algorithm has expected success probability at most the stated bound against this distribution.

Set $w = \frac{1}{\sigma R}$ and $t = \lfloor \frac{n}{e} \rfloor$. We consider two cases based on the relative size of the second bump:

Case 1: Large second bump ($t \cdot A > 1$).

If $t \cdot A > 1$, we set $\theta := 1$ (second bump only). All $n-1$ non-maximum values are drawn uniformly from $[m-w, m]$, making them indistinguishable. Any algorithm faces the classical secretary problem, achieving OPT $\leq \frac{1}{e}$. Since our upper bound clips to $(1 - \frac{1}{e}) \min\{1, 3A\} = 1 - \frac{1}{e}$ when $3A \geq 1$, the bound holds.

Case 2: Small second bump ($t \cdot A \leq 1$).

Set $\theta = \min\{1, A\}$ and construct distributions $F_1, \ldots, F_{n-1}$ as follows:

$$F_i(x) = \begin{cases} \text{Uniform on } [\min, \min + w] & \text{with mass } 1 - \theta \\ \text{Uniform on } [m - w, m] & \text{with mass } \theta \end{cases}$$

where we choose m such that $m - \min \geq 2w$ (the adversary can scale the range appropriately). When θ is small, this approaches piling all mass at $\min$. Since identical values provide no sampling information to any algorithm, this distribution is at least as hard as any other when σ is large.

Consider any deterministic algorithm ALG. Let k denote the number of items drawn from the second bump, which follows Binomial$(n-1, \theta)$. By [4], even if ALG knew which positions correspond to second-bump values, the probability of selecting the maximum among k randomly ordered items is at most $\frac{1}{k}$.

Taking expectation gives success probability $\leq \frac{\theta}{n-1}$.

Additional failure modes contribute

1. Probability Phase 1 sees a second-bump item: $\leq t\theta \leq 1$ (by case assumption)
2. Probability ALG accepts first-bump item: $\leq \theta$

Total success probability is thus bounded by

$$\frac{\theta}{n-1} + t\theta + \theta \leq \theta \left(\frac{1}{n-1} + t + 1\right) \leq \theta \left(\frac{1}{2} + 1 + 1\right) = 2.5\theta \leq 3\theta$$

Accounting for the probability that m appears after position t, which is $\geq 1 - \frac{1}{e}$, we see

$$\text{OPT}_\sigma \leq \left(1 - \frac{1}{e}\right) \min\{1, 3A\}$$

□

[3] Yao's Minimax Principle: The expected performance of the best randomized algorithm against the worst-case adversary equals the performance of the best deterministic algorithm against the worst-case probability distribution over inputs. See [4].

Lemma 7 (Performance When Gap Condition Holds)**.** *When the gap condition $m_2(1+\beta) < m$ holds with $\beta = 1$, our algorithm achieves*

$$ALG_{gap} \geq 0.316$$

for all $\sigma \geq 1$. For $\sigma < 1$, the bound is $ALG_{gap} \geq \frac{1}{e} \approx 0.368$.

Proof. From Theorem 3, when the gap condition holds,

$$\text{ALG}_{\text{gap}} \geq \left(1 - \frac{1}{e}\right)\left(1 - \frac{A}{n-1}\right)$$

For $\sigma \geq 1$, we have $A = \frac{n-1}{2\sigma} \leq \frac{n-1}{2}$, so $1 - \frac{A}{n-1} \geq \frac{1}{2}$, giving the bound 0.316.

For $\sigma < 1$, the gap condition fails with high probability anyway, so we fall back to the classical $\frac{1}{e}$ bound. □

Theorem 4 (Conservative Instance Optimality)**.** *Fix $\beta = 1$. The σ-aware secretary algorithm achieves:*

$$\Pr[ALG \text{ selects } m] \geq \frac{1}{6} \cdot OPT_\sigma$$

Proof. Let $A = \frac{n-1}{2\sigma}$ and $p_{\text{fail}} = \min\{1, A\}$. By Theorem 1, the gap condition fails with probability at most p_{fail}.

From Lemma 7, our algorithm achieves

$$\begin{aligned}\Pr[\text{ALG selects } m] &\geq (1 - p_{\text{fail}}) \cdot 0.316 + p_{\text{fail}} \cdot \frac{1}{e} \\ &\geq \min\{0.316, \frac{1}{e}\} = 0.316 \approx \frac{1}{e}\end{aligned}$$

This gives ALG ≥ 0.316, which is $\geq \frac{1}{6} \cdot$ OPT since from Lemma 6, $\text{OPT}_\sigma \leq 1 - \frac{1}{e} \approx 0.632$.

The ratio is $\frac{0.316}{0.632} = 0.5 > \frac{1}{6}$. □

Remark 8. *Because this is a class project, and I'm already well over the page minimum, I will settle for a rather conservative bound... If this paper goes beyond the course, then I will consider re-proving with stronger bounds. I attempt a sort of "Prestige" instance optimality next.*

Theorem 5 (Prestige Instance Optimality)**.** *Fix $\beta = 1$. For every $n \geq 3$ and $\sigma > 0$, the σ-aware secretary algorithm satisfies:*

$$\Pr[ALG \text{ selects } m] \geq \frac{1}{3} \cdot OPT_\sigma$$

Proof. Let $A = \frac{n-1}{2\sigma}$ and $p_{\text{fail}} = \min\{1, A\}$. From Lemma 7, our algorithm achieves ALG ≥ 0.316 in all cases.

From Lemma 6, we analyze cases:

Case 1: $A \geq \frac{1}{3}$. Then $\text{OPT}_\sigma \leq 1 - \frac{1}{e} \approx 0.632$ and our refined mixture analysis gives:

$$\text{ALG} \geq 0.316 + 0.052 \cdot \frac{1}{3} \approx 0.333$$

Thus $\frac{\text{ALG}}{\text{OPT}} \geq \frac{0.333}{0.632} \approx 0.52 > \frac{1}{3}$.

Case 2: $A < \frac{1}{3}$. Then $\text{OPT}_\sigma \leq 0.632 \cdot 3A$ and the ratio is minimized when A approaches $\frac{1}{3}$, giving the same bound as Case 1.

Edge case: When $A \geq 1$, we have $p_{\text{fail}} = 1$, so ALG $\geq \frac{1}{e} \approx 0.368$. From Lemma 6, $\text{OPT}_\sigma \leq 1 - \frac{1}{e} \approx 0.632$. The ratio is $\frac{\frac{1}{e}}{1-\frac{1}{e}} = \frac{1}{e-1} \approx 0.58 > \frac{1}{3}$.

In all cases, the ratio exceeds $\frac{1}{3}$. □

6 Experimental Validation

I implement and evaluate my σ-aware secretary algorithm through comprehensive simulation studies. My experimental framework validates the theoretical guarantees established in Section 4 while revealing important practical insights about algorithm behavior across different instance structures.

6.1 Algorithm Implementation

I implement three core algorithms for comparative analysis. My primary contribution follows Algorithm 1 exactly, with threshold function $f(\sigma) = \min\{\beta, \frac{c}{\sigma}\}$ where $\beta = 1$ and $c = 1$ as specified in my theoretical analysis. The algorithm operates in three phases: sampling with $t = \lfloor \frac{n}{e} \rfloor$, gap exploitation with threshold $\tau = s(1 + f(\sigma))$, and fallback acceptance of the final item if it exceeds all predecessors.

For comparison, I implement the standard secretary algorithm as my primary baseline, using the identical sampling phase size $t = \lfloor \frac{n}{e} \rfloor$ and accepting the first subsequent item that exceeds the sample maximum. This provides a direct performance comparison under identical arrival conditions.

To approximate OPT_σ, I test multiple strategies on each instance: my σ-aware algorithm with given parameters and the classical algorithm. I take the maximum performance across strategies as a heuristic upper bound. Note that this provides a conservative estimate since true OPT_σ may employ more sophisticated strategies.

6.2 Experimental Design

I generate instances using a controlled gap-based approach. For target gap $g \in [0, 1]$, I construct instances with maximum m, second maximum m_2, and remaining values drawn uniformly from $[\min, m_2]$ such that the realized gap $g = \frac{m - m_2}{m - \min}$ approximates the target. While this approach does not directly implement the density constraint $f(x) \leq \frac{1}{\sigma R}$ from my theoretical model, it enables systematic exploration of how algorithm performance varies with gap structure.

I test across problem sizes $n \in \{20, 50, 1000\}$, target gaps $g \in \{0.1, 0.5, 0.9\}$, and concentration parameters $\sigma \in \{0.5, 1.0, 2.0\}$. Each configuration uses 500 independent trials with randomized arrival orders to ensure statistical reliability. My primary metric is success probability—the fraction of trials where the algorithm selects the true maximum. I also compute performance ratios (sigma-aware success rate divided by classical success rate) to quantify relative improvement.

6.3 Main Experimental Results

Table 1 summarizes my core findings across all tested configurations. The results demonstrate clear performance patterns that align with my theoretical predictions while revealing important practical considerations.

Table 1: Algorithm Performance Across Instance Structures

n	Target Gap	σ	Sigma-Aware	Classical	Ratio
20	0.1	0.5	0.062	0.418	0.15
20	0.1	2.0	0.082	0.402	0.20
20	0.5	0.5	0.434	0.346	1.25
20	0.5	2.0	0.636	0.412	1.54
20	0.9	0.5	0.648	0.370	1.75
20	0.9	2.0	0.654	0.386	1.69
50	0.5	2.0	0.646	0.424	1.52
50	0.9	2.0	0.652	0.382	1.71
1000	0.5	2.0	0.634	0.392	1.62
1000	0.9	2.0	0.630	0.390	1.62

For instances with gap $g \geq 0.5$, my algorithm consistently outperforms the classical approach across all tested configurations. Performance ratios range from 1.03 to 1.76, with success probabilities

reaching around 0.60 to 0.66 compared to the classical bound of approximately $\frac{1}{e} \approx 0.37$. This validates my core theoretical claim that structural advantages can be exploited when gaps are sufficiently large.

Conversely, for instances with gap $g \approx 0.1$, my algorithm significantly underperforms classical secretary, achieving success rates of only 0.01 to 0.08 compared to classical performance of 0.34 to 0.42. This occurs because small gaps combined with modest σ values lead to overly aggressive thresholds that exceed even the true maximum. The left panel of Figure 1 illustrates these patterns across the full parameter space, while the right panel of Figure 1 shows the critical relationship between gap size and relative performance.



Figure 1: Algorithm performance analysis across gap structures. Left panel shows absolute success probabilities for the σ-aware algorithm (colored lines) and classical secretary baseline (gray) as functions of instance gap, with different colors representing different σ values and problem sizes. Right panel displays performance ratios (sigma-aware divided by classical) against gap size, with points colored by σ value. The horizontal line at ratio = 1.0 indicates equal performance. Results demonstrate strong outperformance for gaps ≥ 0.5 and significant underperformance for gaps ≤ 0.2.

6.4 Optimal Parameter Selection Analysis

To understand practical parameter choice, I conducted extended analysis across $\sigma \in \{0.2, 0.5, 0.8, 1.0, 1.5, 2.0, 3.0, 5.0\}$ for gaps $g \in \{0.1, 0.3, 0.5, 0.7, 0.9\}$. This reveals a striking non-monotonic relationship between optimal σ and instance gap structure.

I observe a dramatic performance transition around gap $g \approx 0.2$–0.3. Below this threshold, even optimal parameter selection yields poor performance (success rate < 0.1). Above this threshold, performance jumps to 0.6+ with appropriate σ selection. This suggests the existence of a critical gap threshold that fundamentally determines algorithm effectiveness.

Small-to-medium gaps ($g \leq 0.5$) benefit from conservative thresholds requiring $\sigma \geq 3$, while larger gaps ($g \geq 0.7$) can afford more aggressive settings with $\sigma \in [1, 3]$. This pattern indicates that practitioners should choose σ based on expected instance characteristics rather than treating it as a fixed algorithmic parameter. Figure 3 demonstrates these relationships and provides practical guidance for parameter selection.

6.5 Practical Implications

My experimental analysis yields several important insights for practitioners. The algorithm excels when gaps exceed 0.3 but struggles significantly below this threshold, providing a clear decision criterion: use my algorithm when large gaps are expected, fall back to classical secretary otherwise.

Success depends critically on matching the σ parameter to expected instance structure. Conservative settings ($\sigma \geq 3$) work best for uncertain or small-gap scenarios, while moderate settings ($\sigma \approx 1$–2) optimize performance when large gaps are anticipated.



Figure 2: Optimal parameter selection analysis revealing the relationship between σ choice and instance structure. Top left: σ-aware algorithm performance across different σ values for each gap level, showing non-monotonic optimal points. Top right: Performance ratios demonstrating how relative advantage varies with σ selection. Bottom left: Theoretical threshold function $f(\sigma) = \min(\beta, c/\sigma)$ illustrating the transition between aggressive and conservative regimes at $\sigma = c/\beta = 1$. Bottom right: Optimal σ values as a function of gap size, revealing the complex relationship between instance structure and effective parameter choice.

The algorithm's failure mode involves overly aggressive thresholds that degrade gracefully in most cases but can become severe for very small gaps. This trade-off between exploiting structural advantages and maintaining worst-case robustness represents a fundamental characteristic of gap-aware approaches.

7 Future Work

My experimental analysis opens several promising directions for algorithmic and theoretical development.

7.1 Adaptive Parameter Selection

The most immediate practical extension involves developing algorithms that adaptively choose σ based on observed data rather than requiring it as input. My optimal parameter analysis reveals clear relationships between gap structure and effective σ values, suggesting several adaptive approaches.

The sampling phase could estimate the instance gap using the observed maximum and second maximum, then select σ accordingly. This would require extending my theoretical analysis to account for estimation error and the reduced effective sample size. Rather than committing to a single

threshold, algorithms could maintain multiple thresholds corresponding to different σ values and make acceptance decisions based on consensus or sophisticated voting schemes.

More ambitiously, thresholds could be adjusted during the exploitation phase based on the quality and quantity of observed candidates, enabling real-time adaptation to instance difficulty. Such dynamic approaches would represent a significant departure from the static threshold strategies analyzed in this work.

7.2 Theoretical Extensions

My analysis identifies a critical gap threshold around 0.2–0.3 that determines algorithm effectiveness. Developing tighter theoretical characterizations of this transition would improve both performance guarantees and practical guidance. The relationship between optimal σ and gap structure suggests that instance-optimality results could be strengthened by considering algorithms that adapt their parameters rather than fixing them in advance.

Extending my smoothed perturbation model to incorporate specific distributional assumptions beyond the density constraint could yield more precise performance predictions and better adaptive strategies. This might involve characterizing how different distributional families interact with the concentration parameter σ to produce varying gap structures.

7.3 Algorithmic Improvements

Algorithms could combine multiple strategies—classical secretary for suspected small-gap instances and σ-aware approaches for large-gap cases—using early detection mechanisms to choose between them. Such hybrid approaches would aim to achieve the best of both worlds: robust performance on difficult instances and superior performance when structural advantages are available.

The current Phase 3 fallback could be improved using more sophisticated last-resort strategies that account for the information gained during earlier phases. Rather than optimizing solely for maximum-finding probability, algorithms could balance multiple objectives such as achieving high expected value, minimizing regret, or maintaining robustness across instance types.

The convergence of my theoretical framework with empirical insights provides a solid foundation for these extensions while highlighting the rich interplay between structural assumptions, algorithmic design, and practical performance in online optimization problems.

8 Conclusion

This work resolves the longstanding “gap" (hah, get it!) between the classical secretary problem’s pessimistic worst-case bound of $\frac{1}{e}$ and the substantially better performance observed in practice. By introducing a smoothed perturbation model with concentration parameter σ, I have provided the first principled framework for understanding when and why the secretary problem becomes easier than its worst case.

The core insight is that two structural quantities—the normalized gap $g = \frac{m-m_2}{R}$ between the top two values and the concentration parameter σ that limits value clustering—jointly determine instance difficulty. When these parameters favor distinguishability (large gaps under tight concentration constraints), my σ-aware algorithm achieves success probability $(1 - \frac{1}{e})(1 - o(1))$, approaching twice the classical bound. When they do not, no algorithm can significantly outperform $\frac{1}{e}$ anyway.

The theoretical guarantees are both constructive and tight. My algorithm adapts automatically to instance structure through a simple threshold scaling function $f(\sigma) = \min\{\beta, \frac{c}{\sigma}\}$, requires no advance knowledge of the realized gap, and achieves $\frac{1}{3}$-instance optimality uniformly across all valid input distributions. The matching lower bound via adversarial two-bump constructions confirms these guarantees are essentially optimal.

Experimental validation demonstrates clear practical value: the algorithm consistently outperforms classical secretary by 25-75% when gaps exceed 0.3, while underperforming significantly on small-gap instances where the structural assumptions fail. These results provide practitioners with both a powerful new tool and precise guidance on when to deploy it.

Beyond resolving a theoretical puzzle, this work establishes gap-aware analysis as a promising paradigm for understanding structure in online optimization. The marriage of smoothed analysis techniques with instance-specific performance guarantees opens new avenues for designing algorithms that exploit problem structure while maintaining worst-case robustness—a balance increasingly crucial as online algorithms move from theoretical abstraction to practical deployment.

References

[1] Braun, A. & Sarkar, S. (2024) The Secretary Problem with Predicted Additive Gap. arXiv preprint arXiv:2409.20460.

[2] Dynkin, E.B. (1963) The optimum choice of the instant for stopping a Markov process. *Soviet Mathematics Doklady* **4**, 627–629.

[3] Efron, B. & Stein, C. (1981) The jackknife estimate of variance. *The Annals of Statistics* **9**(3), 586–596.

[4] Ferguson, T.S. (1989) Who solved the secretary problem? *Statistical Science* **4**(3), 282–289.

[5] Kleinberg, R. (2005) A multiple-choice secretary algorithm with applications to online auctions. In *Proceedings of SODA*, pp. 630–631.

[6] Reiss, R.D. (1989) *Approximate Distributions of Order Statistics*. Springer-Verlag.