

Time and Ordering of Events

Dominic Duggan
Stevens Institute of Technology
Partly based on material by
Sape Mullender and Ken Birman

1

What time is it?

- Agree that update A occurred before update B
- Offer a “lease” on a resource that expires at time 10:10.0150
- Guarantee that a time critical event will reach all interested parties within 100ms

2

What does time “mean”?

- Time on a global clock?
 - E.g. with GPS receiver
- Machine’s local clock
 - But was it set accurately?
 - And could it drift, e.g. run fast or slow?
 - What about faults, like stuck bits?
- Or try to agree on time

3

LOGICAL TIME


4

Lamport: Logical Time

- Time lets a system ask “Which came first: event A or event B?”
- Time is a means of labeling events so that...
 - If A happened before B, $\text{TIME}(A) < \text{TIME}(B)$
 - If $\text{TIME}(A) < \text{TIME}(B)$, A happened before B


5

Drawing time-line pictures:



6


Drawing time-line pictures:



- A, B, C and D are “events”.
 - So are `snd(m)` and `rcv(m)` and `deliv(m)`
- What ordering claims are meaningful?

7


Drawing time-line pictures:



- A happens before B, and C before D
 - *Local ordering* at a single process
 - Write $A \rightarrow^p B$ and $C \rightarrow^q D$

8


Drawing time-line pictures:



- `snd(m)` also happens before `rcv(m)`
 - *Distributed ordering* introduced by a message
 - Write `snd(m) → rcv(m)`

9


Drawing time-line pictures:



- A happens before D
 - *Transitivity*: A happens before `snd(m)`, which happens before `rcv(m)`, which happens before D

10

Drawing time-line pictures:



- B and D are concurrent
 - Looks like B happens first, but D has no way to know. No information flowed...

11

“Happens before” relation

- We'll say that “*A happens before B*”, written $A \rightarrow B$, if
 - $A \rightarrow^p B$ according to the local ordering, or
 - A is $\text{snd}(m)$ and B is $\text{rcv}(m)$ and $A \rightarrow B$, or
 - A and B are related under the transitive closure of rules (1) and (2)

12

LOGICAL CLOCKS

13

Logical clocks

- First version: uses just a single integer
 - Designed for big (64-bit or more) counters
 - Each process p maintains LT_p , a local counter
 - A message m will carry timestamp $TS(m)$


14

Rules for managing logical clocks

- When an event happens at a process p it increments LT_p
 - Any event that matters to p
 - Normally, also snd and rcv events (since we want receive to occur “after” the matching send)
- When p sends m , set
 - $TS(m) = LT_p$
- When q receives m , set
 - $LT_q = \max(LT_q, TS(m)) + 1$



15



Time-line with LT annotations







- $LT(A) = 1$, $LT(snd(m)) = 2$, $TS(m) = 2$
- $LT(rcv(m)) = \max(1, 2) + 1 = 3$, etc...

16















DISTRIBUTED MUTUAL EXCLUSION

29

Distributed Mutual Exclusion

- Idea: purely distributed protocol for mutually exclusive access to a resource
 - No central coordinator

30

Distributed Mutual Exclusion

- Idea: purely distributed protocol for mutually exclusive access to a resource
 - No central coordinator
- Requests are ordered using logical time
 - Use (ts, pid) with pid to break ties
 - $(m, p) < (n, q)$ if $m < n$ or $(m = n \text{ and } p < q)$

31

Distributed Mutual Exclusion

- Idea: purely distributed protocol for mutually exclusive access to a resource
 - No central coordinator
- Requests are ordered using logical time
 - Use (ts, pid) with pid to break ties
 - $(m, p) < (n, q)$ if $m < n$ or $(m = n \text{ and } p < q)$
- Data structures
 - Logical time LT_p
 - Request queue, ordered by request timestamp
 - $LT[i]$, timestamp of last message received from process p_i

32

Request a Resource

- Process p_i
 - Increments its logical clock
 - Adds request m ($TS(m)=LT_i$) to its request queue
 - Broadcasts request to every other process

33

Request a Resource

- Process p_i
 - Increments its logical clock
 - Adds request m ($TS(m)=LT_i$) to its request queue
 - Broadcasts request to every other process
- Process p_j ($j \neq i$)
 - Acknowledges receipt of request ($TS(ack)=LT_j$)

34



Request a Resource

- Process p_i
 - Increments its logical clock
 - Adds request m ($TS(m)=LT_i$) to its request queue
 - Broadcasts request to every other process
- Process p_j ($j \neq i$)
 - Acknowledges receipt of request ($TS(ack)=LT_j$)
- Process p_i has access when:
 - Its request is in the front of its request queue
 - $LT[i] \geq TS(m)$ for all $i=1,\dots,n$

35



36




CONSISTENT CUTS

39

Temporal distortions

- What does “now” mean?




40

- What does “now” mean?




- Timelines can “stretch”...



Temporal distortions

- Timelines can “shrink”




- E.g. something lets a machine speed up

43

Temporal distortions

- Cuts represent instants of time.



- But not every “cut” makes sense

44


Consistent cuts and snapshots

- Identify system states that “might” have occurred in real-life
 - Avoid capturing “inconsistent” states
 - Receive without a send
 - This is the problem with the gray cuts

45

Temporal distortions


- Red messages cross gray cuts “backwards”



46

Temporal distortions

- Red messages cross gray cuts “backwards”



- In a nutshell: the cut includes a message that “was never sent”

47


DISTRIBUTED LOGGING

48

Distributed Logging


- We have n processes p_1, \dots, p_n
- We want to use a monitor process p_0 to build a trace of the system for debugging purposes
- Protocol: every time an event e happens at a process p_i , it sends a notification of that event to p_0

49




50

Inconsistent Cut



51

Delay Delivery for Consistency



52

Clock Condition

- **Clock Condition:**
 - $e \rightarrow e'$ implies $LT(e) < LT(e')$
- **Delivery Rule 1 (DR1):**
 - At time t , deliver all received messages with timestamps up to t , in increasing timestamp order
- Clock condition ensures consistent observations


53

Gap Detection

- We cannot deliver a message m with $TS(m) = t$ unless we are certain that no message m' with $TS(m') < t$ can be received
- **Gap Detection:**
 - Given two events e and e'
 - Given $LT(e) < LT(e')$
 - Determine whether an event e'' exists such that $LT(e) < LT(e'') < LT(e')$

54

Safe to Deliver?




55

Stable Messages

- Message m received at p is **stable** if no future messages with smaller timestamps will be received at p
- **Delivery Rule 2 (DR2):** Deliver all stable messages at p_0 in increasing time-stamp order
- With *FIFO* channels, stability is assured once messages with greater timestamps are received from every other process

56



57

Problem

- Delivery Rule 2 is too conservative
 - We have to see later messages from every other process before delivering a message from p

58

VECTOR TIME

59

Ordering Relations

- Ordered set (A, \leq)
- **Total order:** order is
 - *Total:* for all x, y , either $x \leq y$ or $y \leq x$
 - *Symmetric:* $x \leq y$ and $y \leq x$ implies $x = y$
 - *Transitive:* $x \leq y$ and $y \leq z$ implies $x \leq z$
- **Partial order:** weaken totality to *reflexivity*: $x \leq x$ for all x
- **Preorder:** ordering relation is transitive, not refl
 - $x < y$ and $y < z$ implies $x < z$

60


Potential Causality

- If A happens before B, $A \rightarrow B$, then $LT(A) < LT(B)$
- But converse might not be true:
 - If $LT(A) < LT(B)$ can't be sure that $A \rightarrow B$
 - Total order placed on what is a partial order

61

Vector Clocks


- Here we treat timestamps as a list
 - One counter for each process
 - Vector of n counters represents a “cut” of the executions of n processes



62

Operational Interpretation

- $VT(e_i)[i]$ = number of events p_i has executed up to and including e_i
- $VT(e_i)[j]$ = number of events of p_j that causally precede event e_i of p_i ($j \neq i$)







63



Vector Clocks



- Rules for managing vector clock
 - When event happens at p , increment $VT_p[index_p]$
 - Normally, also increment for snd and rcv events
 - When sending a message, set $TS(m) = VT_p$
 - When receiving, set $VT_q = \max(VT_q, TS(m))$

64









Rules for comparison of VTs

- We'll say that $VT_A \leq VT_B$ if
 - $VT_A[i] \leq VT_B[i]$ for all i
- And we'll say that $VT_A < VT_B$ if
 - $VT_A \leq VT_B$ but $VT_A \neq VT_B$
 - That is, for some i , $VT_A[i] < VT_B[i]$
- Examples?
 - $[2,4] \leq [2,4]$
 - $[1,3] < [7,3]$
 - $[1,3]$ is “incomparable” to $[3,1]$

73


Vector time and happens before

- If $A \rightarrow B$, then $VT_A < VT_B$
 - Write a chain of events from A to B
 - Step by step the vector clocks get larger
- If $VT_A < VT_B$ then $A \rightarrow B$
 - Two cases: if A and B both happen at same process p , trivial
 - If A happens at p and B at q , can trace the path back by which q “learned” $VT_A[p]$
- Otherwise A and B happened concurrently

74

DISTRIBUTED LOGGING AND VECTOR TIME

75



76

Clock Condition


- Delivery Rule 2 too conservative
- Clock Condition:
 - $e \rightarrow e'$ implies $LT(e) < LT(e')$
 - Possible: $LT(e) < LT(e')$, but not $(e \rightarrow e')$
- Logical clocks give potential causality
 - Hence the need to wait for stability

77

Strong Clock Condition

- **Delivery Rule 3 (DR3):**
 - Deliver messages all of whose causal predecessors have been delivered
- Relies on: **Strong Clock Condition**
 - $e \rightarrow e'$ if and only if $VT(e) < VT(e')$

78



Causal Delivery

- We have used causal delivery at monitor process to construct consistent observations
- Causal delivery may also be used in general message delivery
- Deadlock problems with point-to-point (requires matrix clock)
- Vector clock used with causal broadcast

ORDERED MESSAGE DELIVERY

81

FIFO Order


- FIFO Delivery Rule:
 - $\text{send}(m) \text{ on } i \rightarrow \text{send}(m') \text{ on } i$
implies that
 $\text{deliver}(m) \text{ on } k \rightarrow \text{deliver}(m') \text{ on } k$

82


Causal Order

- Causal Delivery Rule:
 - $\text{send}(m) \text{ on } i \rightarrow \text{send}(m') \text{ on } j$
implies that
 $\text{deliver}(m) \text{ on } k \rightarrow \text{deliver}(m') \text{ on } k$
- FIFO Order not sufficient to ensure Causal Order


83



84




85




86

Causal Point-to-Point May Deadlock




87

Causal Point-to-Point May Deadlock




88

Causal Multicast avoids Deadlock




89

FIFO With One Sender




90

Causal with One Thread



91

Causal but not Total



92

Total Ordered Multicast

