

Certified Analytical Bounds for Multi-Phase Hypersonic Reachable Sets

Ethan Knox

Independent Researcher, Champaign, IL, USA

2026

Abstract

Keywords: reachable sets; occupation measures; Liouville equation; concentration-compactness; profile decomposition; comparison principle; barrier certificates; hybrid systems; hypersonic entry; entry corridor; boost-glide

MSC 2020: 34A38

Contents

1	Introduction	5
1.1	Grid-based Hamilton-Jacobi-Isaacs evaluations	5
1.2	Fixed-grid pseudospectral methods	5
1.3	Thesis statement	5
1.4	Outline of contributions	5
2	The Model Problem	6
2.1	Abstract formulation of the multi-phase optimal control problem	6
2.2	The mode alphabet	6
2.3	Trajectory families as admissible words	6
2.4	The entry corridor: hypersonic path constraints	6
2.5	Certified envelopes for constitutive and coupling effects	6
2.6	Phase boundaries: physical, constitutive, and numerical	6
2.7	Asymptotic regimes and the dimensionless groups	6
2.8	Quantity of interest and uncertainty	6
3	Infinite-Dimensional Embedding and Measure Theory	7
3.1	Sobolev space formulation	7
3.2	Occupation measures and the weak Liouville identity	7
3.3	Per-mode measures, guard measures, and linkage	7
3.4	The embedding as a linear problem on a Banach space	7
4	Concentration-Compactness and Profile Decomposition	8
4.1	Prokhorov tightness as a preliminary	8
4.2	The singular limit and the scaling group	8
4.3	Tightness of the rescaled family	8
4.4	The dichotomy	8
4.5	The skeleton: concentration on the equilibrium glide manifold	8
4.6	The bubbles: boundary-layer profiles at each skip	8
4.7	The compact residual	8
4.8	Consequence: dimension reduction for the certificate	8
5	Bounding Limits and Certificates	9
5.1	Relaxation and the direction of inclusion	9
5.2	The comparison principle	9
5.3	Constructing the certificate from the decomposition	9
5.4	Verification over the corridor	9
5.5	Exact arithmetic and machine-checkable certification	9
5.6	Inner point cloud and the bounding gap	9
5.7	Limits of the analytical construction	9
6	Verification and Results	10
6.1	Validating the degenerate limit	10
6.2	Tightness against the extremal cloud	10
6.3	Independent numerical cross-check	10
6.4	The corridor constraints as hypotheses	10
6.5	Multi-mode words	10

6.6	Numerical evidence for the profile decomposition	10
6.7	Computational cost	10
6.8	Reproducibility environment	10
7	Discussion	11
7.1	Limitations	11
7.2	Scope: the boost-glide and aeroassisted class	11
7.3	Extensions	11
A	Six-Degree-of-Freedom Equations of Motion	13
A.1	State vector and frames	13
A.2	Translational equations	14
A.3	Rotational equations	14
A.4	Aerodynamic forces and moments	16
A.5	Atmosphere	16
A.6	Per-mode forms	16
A.7	Boundary discipline	16
B	Corridor Constraints and Certified Envelopes	16
B.1	The corridor constraints in polynomial form	16
B.2	Compactness of the corridor	16
B.3	Aerodynamic coefficient envelopes	16
B.4	Ablation and aerothermoelastic envelopes	16
B.5	How the envelopes enter the certificate	16
C	Polynomial Embedding of the Entry Dynamics	16
C.1	Augmentation	16
C.2	The augmented state and its constraint set	16
C.3	Dimension arithmetic	16
C.4	Effect on conditioning	16
D	Exact Verification of the Certificate	16
D.1	What must be discharged	16
D.2	Rational constants and exact algebra	16
D.3	The verification script	16
D.4	What exact verification does and does not establish	16
E	The Extremal Control Law	16
F	The Moment-LP Dual and its Semidefinite Tightening	16
F.1	From the measure problem to its dual	16
F.2	Putinar's Positivstellensatz and the multipliers	16
F.3	Semidefinite assembly	16
F.4	Multi-phase assembly	16
F.5	Solver interface and verification of the certificate	16

G	Fixed-Grid Spectral Machinery	16
G.1	Chebyshev operators by direct recurrence	16
G.2	Ultraspherical banded operators	16
G.3	Conditioning	16
G.4	Boundary immobilization on a fixed grid	16
H	Sum-of-Squares in a Chebyshev Basis	16
H.1	Nondimensionalization and per-band scaling	16
H.2	Gram matrices in a non-monomial basis	16
H.3	Assembly and operator reuse	16
H.4	Conditioning claim	16

1 Introduction

1.1 Grid-based Hamilton-Jacobi-Isaacs evaluations

1.2 Fixed-grid pseudospectral methods

1.3 Thesis statement

1.4 Outline of contributions

2 The Model Problem

2.1 Abstract formulation of the multi-phase optimal control problem

The vehicle is a rigid body, not a point mass (Appendix A). Its state

$$x = (r, \theta, \phi, u, v, w, q_0, q_1, q_2, q_3, \omega_1, \omega_2, \omega_3) \in \mathcal{X} \subseteq \mathbb{R}^{13}, \quad (2.1)$$

augmented by mass, recession depth s and modal state $(\eta, \dot{\eta})$ where the corresponding mode or coupling is active, carries geocentric position, body-frame velocity, attitude quaternion and body rates as components. The attitude coordinates are redundant: every admissible state satisfies

$$q_0^2 + q_1^2 + q_2^2 + q_3^2 = 1, \quad (2.2)$$

so the thirteen coordinates carry twelve degrees of freedom. The control

$$c = (\vec{\delta}, \vec{\tau}_{\text{rcs}}, \varsigma) \in U, \quad (2.3)$$

collects flap deflections $\vec{\delta}$, reaction-control moments $\vec{\tau}_{\text{rcs}}$ and, in a propulsive mode, throttle ς ; $U \subset \mathbb{R}^{n_c}$ is compact.

Crucially the incidence angles (α, β) are *outputs* of the attitude solution (??), not commanded quantities: trim is not assumed solvable, and attitudes the vehicle cannot hold are excluded automatically rather than by fiat. The reachable set cannot contain a state reached only by an unattainable incidence.

list deflection, RCS, and throttle limits (one citation each). compactness follows.

elaborate

2.2 The mode alphabet

2.3 Trajectory families as admissible words

2.4 The entry corridor: hypersonic path constraints

2.5 Certified envelopes for constitutive and coupling effects

2.6 Phase boundaries: physical, constitutive, and numerical

2.7 Asymptotic regimes and the dimensionless groups

2.8 Quantity of interest and uncertainty

3 Infinite-Dimensional Embedding and Measure Theory

3.1 Sobolev space formulation

3.2 Occupation measures and the weak Liouville identity

3.3 Per-mode measures, guard measures, and linkage

3.4 The embedding as a linear problem on a Banach space

4 Concentration-Compactness and Profile Decomposition

- 4.1 Prokhorov tightness as a preliminary
- 4.2 The singular limit and the scaling group
- 4.3 Tightness of the rescaled family
- 4.4 The dichotomy
- 4.5 The skeleton: concentration on the equilibrium glide manifold
- 4.6 The bubbles: boundary-layer profiles at each skip
- 4.7 The compact residual
- 4.8 Consequence: dimension reduction for the certificate

5 Bounding Limits and Certificates

5.1 Relaxation and the direction of inclusion

5.2 The comparison principle

5.3 Constructing the certificate from the decomposition

5.4 Verification over the corridor

5.5 Exact arithmetic and machine-checkable certification

5.6 Inner point cloud and the bounding gap

5.7 Limits of the analytical construction

6 Verification and Results

- 6.1 Validating the degenerate limit
- 6.2 Tightness against the extremal cloud
- 6.3 Independent numerical cross-check
- 6.4 The corridor constraints as hypotheses
- 6.5 Multi-mode words
- 6.6 Numerical evidence for the profile decomposition
- 6.7 Computational cost
- 6.8 Reproducibility environment

7 Discussion

7.1 Limitations

7.2 Scope: the boost-glide and aeroassisted class

7.3 Extensions

References

A Six-Degree-of-Freedom Equations of Motion

This appendix records the rigid-body dynamics the body of the paper treats as given. Nothing here is a contribution; the derivation is standard entry mechanics [assembled once with a fixed set of frames and a fixed parametrization](#). Frame errors are the classic 6-DOF defect and are invisible in the assembled algebra, so the transformations are stated explicitly and used without exception.

[cite sources](#)

A.1 State vector and frames

Frames. Four frames are used throughout.

- $\mathcal{I}$: Earth-centred inertial (ECI), non-rotating.
- $\mathcal{E}$: Earth-centred Earth-fixed (ECEF), rotating with the constant planetary rate $\vec{\omega}_E = \omega_E \hat{z}_{\mathcal{I}}$.
- $\mathcal{L}$: local geocentric frame at the vehicle, with unit vectors $(\hat{e}_r, \hat{e}_\theta, \hat{e}_\phi)$ pointing radially outward, east, and north.
- $\mathcal{B}$: body frame, fixed at the instantaneous centre of mass, axes along the vehicle's principal design directions.

The attitude quaternion $\vec{q}$ carries $\mathcal{I} \rightarrow \mathcal{B}$; the geocentric angles (θ, ϕ) carry $\mathcal{I} \rightarrow \mathcal{L}$.

The direction-cosine matrix built from $\vec{q}$,

$$\mathbf{R}_{B/I}(\vec{q}) = \begin{pmatrix} q_0^2 + q_1^2 - q_2^2 - q_3^2 & 2(q_1q_2 + q_0q_3) & 2(q_1q_3 - q_0q_2) \\ 2(q_1q_2 - q_0q_3) & q_0^2 - q_1^2 + q_2^2 - q_3^2 & 2(q_2q_3 + q_0q_1) \\ 2(q_1q_3 + q_0q_2) & 2(q_2q_3 - q_0q_1) & q_0^2 - q_1^2 - q_2^2 + q_3^2 \end{pmatrix}, \quad (\text{A.1})$$

is polynomial of degree two in $\vec{q}$, which is the property [Appendix C](#) exploits. The geocentric map is

$$\mathbf{R}_{L/I}(\theta, \phi) = \begin{pmatrix} \cos \phi \cos \theta & \cos \phi \sin \theta & \sin \phi \\ -\sin \theta & \cos \theta & 0 \\ -\sin \phi \cos \theta & -\sin \phi \sin \theta & \cos \phi \end{pmatrix}. \quad (\text{A.2})$$

State vector. Before augmentation the state carries thirteen components,

$$x = \left(\underbrace{r, \theta, \phi}_{\text{position}}, \underbrace{u, v, w}_{\text{body velocity}}, \underbrace{q_0, q_1, q_2, q_3}_{\text{attitude}}, \underbrace{p, q, r_b}_{\text{body rates}} \right) \in \mathbb{R}^{13}, \quad (\text{A.3})$$

augmented by mass m when a propulsive mode is present ([Appendix A.6](#)), and by the recession depth s and modal state $(\eta, \dot{\eta})$ once the aerothermoelastic loop is closed ([Appendix A.3](#) and [Section 2.5](#)). Here (r, θ, ϕ) are geocentric radius, longitude and latitude; (u, v, w) are the body-axis components of the *planet-relative* velocity

$$\vec{V} = \vec{V}_{\mathcal{I}} - \vec{\omega}_E \times \vec{r} - \vec{w}_{\text{wind}}, \quad (\text{A.4})$$

with $\vec{V}_{\mathcal{I}}$ the inertial velocity and $\vec{w}_{\text{wind}}$ the local wind ([Appendix A.5](#)); and (p, q, r_b) are the body components of the inertial angular velocity $\vec{\omega} \equiv \vec{\omega}_{B/I}$.

A.2 Translational equations

Newton's law holds in $\mathcal{I}$: $m \dot{\vec{V}}_{\mathcal{I}}|_{\mathcal{I}} = \vec{F}$, with $\vec{F} = \vec{F}_g + \vec{F}_a + \vec{F}_t$ (gravity, aerodynamic, thrust). We want the rate of the *relative* velocity resolved in $\mathcal{B}$. Writing $\vec{V}_{\mathcal{I}} = \vec{V} + \vec{\omega}_E \times \vec{r}$ and differentiating in $\mathcal{I}$,

$$\dot{\vec{V}}_{\mathcal{I}}|_{\mathcal{I}} = \dot{\vec{V}}|_{\mathcal{I}} + \vec{\omega}_E \times \vec{V}_{\mathcal{I}} = \underbrace{\dot{\vec{V}}|_{\mathcal{B}} + \vec{\omega} \times \vec{V}}_{\text{transport of } \vec{V}} + \vec{\omega}_E \times \vec{V} + \vec{\omega}_E \times (\vec{\omega}_E \times \vec{r}), \quad (\text{A.5})$$

where the transport theorem $\frac{d}{dt}|_{\mathcal{I}} = \frac{d}{dt}|_{\mathcal{B}} + \vec{\omega} \times$ was applied to $\vec{V}$. Solving for the body-frame rate,

$$\dot{\vec{V}}|_{\mathcal{B}} = \frac{1}{m} (\vec{F}_a + \vec{F}_t) + \vec{g} - (\vec{\omega} + \vec{\omega}_E) \times \vec{V} - \vec{\omega}_E \times (\vec{\omega}_E \times \vec{r}) \quad (\text{A.6})$$

with $\vec{F}_g = m\vec{g}$. The term $(\vec{\omega} + \vec{\omega}_E) \times \vec{V}$ collects body-rotation transport and Coriolis; expanding $\vec{\omega} = \vec{\omega}_{B/E} + \vec{\omega}_E$ recovers the familiar $\vec{\omega}_{B/E} \times \vec{V} + 2\vec{\omega}_E \times \vec{V}$ split, the second being the Coriolis acceleration proper.

A.3 Rotational equations

Angular momentum about the center of mass is $\vec{h} = \mathbf{I}\vec{\omega}$, and $\dot{\vec{h}}|_{\mathcal{I}} = \vec{M}$; transporting to $\mathcal{B}$,

$$\mathbf{I} \dot{\vec{\omega}} = \vec{M} - \vec{\omega} \times (\mathbf{I}\vec{\omega}) - \dot{\mathbf{I}}\vec{\omega} \quad (\text{A.7})$$

with $\vec{M} = \vec{M}_a + \vec{M}_{\text{rcs}}$. The gyroscopic term is quadratic in $\vec{\omega}$, hence polynomial once $\mathbf{I}$ is; the inversion $\dot{\vec{\omega}} = \mathbf{I}^{-1}(\cdots)$ is carried as the linear solve $\mathbf{I}\dot{\vec{\omega}} = (\cdots)$ so that no rational function of the state enters the embedding.

Remark A.1 (The inertia tensor is not constant). Ablation removes mass from the nose and structural deformation redistributes it, so $\mathbf{I} = \mathbf{I}(s, \eta)$ through the recession depth s and modal amplitudes η (Section 2.5), and Euler's equations acquire the $\dot{\mathbf{I}}\vec{\omega}$ term in Eq. (A.7). We carry it rather than drop it: the whole point of going to 6-DOF is to keep the deformation→incidence→moment→attitude loop closed, and that loop runs through $\mathbf{I}(s, \eta)$. Its magnitude is bounded by the recession and modal-amplitude envelopes, so carrying it costs one Jacobian block, not a new uncertainty.

A.4 Aerodynamic forces and moments

A.5 Atmosphere

A.6 Per-mode forms

A.7 Boundary discipline

B Corridor Constraints and Certified Envelopes

B.1 The corridor constraints in polynomial form

B.2 Compactness of the corridor

B.3 Aerodynamic coefficient envelopes

B.4 Ablation and aerothermoelastic envelopes

B.5 How the envelopes enter the certificate

C Polynomial Embedding of the Entry Dynamics

C.1 Augmentation

C.2 The augmented state and its constraint set

C.3 Dimension arithmetic

C.4 Effect on conditioning

D Exact Verification of the Certificate

D.1 What must be discharged

D.2 Rational constants and exact algebra

D.3 The verification script

D.4 What exact verification does and does not establish

E The Extremal Control Law

F The Moment-LP Dual and its Semidefinite Tightening

F.1 From the measure problem to its dual

F.2 Putinar's Positivstellensatz and the multipliers

F.3 Semidefinite assembly

F.4 Multi-phase assembly

F.5 Solver interface and verification of the certificate

G Fixed-Grid Spectral Machinery

G.1 Chebyshev operators by direct recurrence

G.2 Ultraspherical banded operators

G.3 Conditioning

G.4 Boundary immobilization on a fixed grid