

Backtracking


Jie He

From GeeksforGeeks.org

- Backtracking is an algorithmic-technique for solving problems **recursively** by trying to build a solution **incrementally**, one piece at a time, **removing those solutions that fail to satisfy the constraints** of the problem at any point of time
 - Recursion/Iteration of N-step problem
 - DFS of solution tree graph
 - Trim by constraints

Basic Steps

- (Preprocessing)
- Start at Step 0
- At Step N
 - Output the constructed solution
- At Step $i < N$:
 - Iterate through each available choice
 - Add the choice to the solution under construction
 - (Label the choice as used/visited)
 - **Go to Step $i+1$**
 - Remove the added choice
 - (Label the choice as available)

- 
- Check/Trim/Skip by
 - Order
 - Repetition
 - Constraints

784. Letter Case Permutation

Easy 767 91 Favorite Share

Given a string *S*, we can transform every letter individually to be lowercase or uppercase to create another string. Return a list of all possible strings we could create.

Examples:

Input: *S* = "a1b2"

Output: ["a1b2", "a1B2", "A1b2", "A1B2"]

Input: *S* = "3z4"

Output: ["3z4", "3Z4"]

Input: *S* = "12345"

Output: ["12345"]

Note:

- *S* will be a string with length between 1 and 12.
- *S* will consist only of letters or digits.

- Explicit iteration of choices
- No labels

Can you solve it iteratively?

```
class Solution {
public:
    vector<string> letterCasePermutation(string S) {
        // Preprocessing: transform to lowercase
        transform(S.begin(), S.end(), S.begin(), ::tolower);

        string str;
        vector<string> ans;
        // Step 0
        lCP(S, str, ans);
        return ans;
    }

    void lCP(const string& S, string& str, vector<string>& ans) {
        // Step N
        if (str.size() == S.size()) {
            ans.push_back(str);
            return;

            //Step i < N
            str.push_back(S[str.size()]);
            lCP(S, str, ans);


            if (islower(str.back())) {
                str.back() = toupper(str.back());
                lCP(S, str, ans);
            }

            str.pop_back();
            return;
        }
    };
};
```

51. N-Queens

Hard 1182 52 Favorite Share

The n -queens puzzle is the problem of placing n queens on an $n \times n$ chessboard such that no two queens attack each other.



One solution to the eight queens puzzle

- No preprocessing
- Label by "qcol"

Given an integer n , return all distinct solutions to the n -queens puzzle.

Each solution contains a distinct board configuration of the n -queens' placement, where 'Q' and '.' both indicate a queen and an empty space respectively.

```
class Solution {
public:
    vector<vector<string>> solveNQueens(int n) {
        // qcols[i] = col number of the queen on i-th row
        vector<int> qcols(n, 0);
        vector<vector<string>> ans;
        // Step 0
        solveCurrRow(qcols, 0, ans);
        return ans;
    }

    void solveCurrRow(vector<int>& qcols, int row,
                     vector<vector<string>>& ans) {
        // Step N
        if (row == qcols.size()) {
            ans.push_back(newSolution(qcols));
            return;
        }
        // Step i < N
        for (int j = 0; j != qcols.size(); ++j) {
            if (!validcol(qcols, row, j)) continue;
            qcols[row] = j;
            solveCurrRow(qcols, row + 1, ans);
        }

        return;
    }
}
```

HW: Can you solve 52. N-Queens II?

LC51. N-Queens: Code for checking validity & construct new Solution

```
bool validcol(const vector<int>& qcols, int row, int col) {  
    for (auto i = 0; i != row; ++i) {  
        // check if same col or diagonal  
        if (col == qcols[i] ||  
            col - row == qcols[i] - i ||  
            col - qcols[i] == i - row ) return false;  
    }  
  
    return true;  
}  
  
vector<string> newSolution(const vector<int>& qcols) {  
    vector<string> solution;  
  
    for (auto& col : qcols) {  
        string onerow(qcols.size(), '.');  
        onerow[col] = 'Q';  
        solution.push_back(move(onerow));  
    }  
  
    return solution;  
}
```

78. Subsets

Medium

👍 2372

💬 58

❤ Favorite

🔗 Share

Given a set of **distinct** integers, *nums*, return all possible subsets (the power set).

Note: The solution set must not contain duplicate subsets.

Example:

Input: *nums* = [1,2,3]

Output:

```
[
  [3],
  [1],
  [2],
  [1,2,3],
  [1,3],
  [2,3],
  [1,2],
  []
]
```

- No preprocessing/labels
- Trimming by “next”
- Output at every step/choice

```
class Solution {
public:
    vector<vector<int>> subsets(vector<int>& nums) {
        vector<int> subset;
        vector<vector<int>> ans;

        // Step 0
        supersets(nums, subset, 0, ans);
        return ans;
    }

    void supersets(const vector<int>& nums,
                  vector<int>& subset,
                  size_t next,
                  vector<vector<int>>& ans) {
        // Output the current subset
        ans.push_back(subset);

        // Step i <= N
        for (size_t j = next; j != nums.size(); ++j) {
            subset.push_back(nums[j]);
            supersets(nums, subset, j + 1, ans);
            subset.pop_back();
        }

        return;
    }
};
```

Can you solve it iteratively?

90. Subsets II

Medium

1083

53

Favorite

Share

Given a collection of integers that might contain duplicates, *nums*, return all possible subsets (the power set).

Note: The solution set must not contain duplicate subsets.

Example:

Input: [1,2,2]

Output:

```
[
  [2],
  [1],
  [1,2,2],
  [2,2],
  [1,2],
  []
]
```

- Preprocess by sorting
- Trim by "next"
- Skip repetitions

```
class Solution {
public:
    vector<vector<int>> subsetsWithDup(vector<int>& nums) {
        // Preprocessing
        sort(nums.begin(), nums.end());

        vector<int> subset;
        vector<vector<int>> ans;

        // Step 0
        sWD(nums, subset, 0, ans);

        return ans;
    }

    void sWD(const vector<int>& nums,
             vector<int>& subset,
             size_t next,
             vector<vector<int>>& ans) {
        // Output current subset
        ans.push_back(subset);

        // Step i <= N
        for (auto j = next; j != nums.size(); ){
            subset.push_back(nums[j]);
            sWD(nums, subset, j + 1, ans);
            subset.pop_back();

            // skip repetitions
            for (auto k = j++;
                j != nums.size() && nums[j] == nums[k]; ++j);
        }
        return;
    }
};
```


79. Word Search

Medium

👍 2231

💬 113

❤ Favorite

🔗 Share

Given a 2D board and a word, find if the word exists in the grid.

The word can be constructed from letters of sequentially adjacent cell, where "adjacent" cells are those horizontally or vertically neighboring. The same letter cell may not be used more than once.

Example:

```
board =  
[  
  ['A','B','C','E'],  
  ['S','F','C','S'],  
  ['A','D','E','E']  
]
```

Given word = "ABCCED", return true.

Given word = "SEE", return true.

Given word = "ABCB", return false.

```
class Solution {  
public:  
    bool exist(vector<vector<char>>& board, string word) {  
        // Corner case  
        if(word.empty()) return true;  
  
        auto nrow = board.size();  
        auto ncol = board[0].size();  
  
        // Labels  
        vector<vector<bool>> visited(nrow,  
                                    vector<bool>(ncol, false));  
  
        // Step 0  
        for (size_t i = 0; i != nrow; ++i)  
            for (size_t j = 0; j != ncol; ++j)  
                if (xst(board, word, visited, i, j, 0)) return true;  
  
        return false;  
    }  
}
```

- Check corner case
- See next page for xst()

- Check corner case to avoid out of bound error
- Explicit iterations
- Stop at Step N - 1 or the test case below will fail

```
bool xst(const vector<vector<char>>& board,
        const string& word,
        vector<vector<bool>>& visited,
        size_t i, size_t j, size_t k) {
```

```
// Trim by constraints
if (visited[i][j] || board[i][j] != word[k]) return false;
```

```
// Step N - 1
if (++k == word.size()) return true;
```

```
// Step i < N - 1
// a. Label the cell visited
visited[i][j] = true;
```

```
// b. Go to next step
if (i > 0 && xst(board, word, visited, i - 1, j, k)) return true;
if (j > 0 && xst(board, word, visited, i, j - 1, k)) return true;
if (i < board.size() - 1 && xst(board, word, visited, i + 1, j, k)) return true;
if (j < board[0].size() - 1 && xst(board, word, visited, i, j + 1, k)) return true;
```

```
// c. Label the cell available
visited[i][j] = false;
```

```
return false;
```

```
}
```

Wrong Answer Details >

Input

```
[["a"]]
"a"
```