

# Learning with Errors and GSW's Homomorphic Encryption

July 4, 2019

# Intuition of LWE

$$14s_1 + 15s_2 + 5s_3 + 2s_4 \approx 8 \pmod{17}$$

$$13s_1 + 14s_2 + 14s_3 + 6s_4 \approx 16 \pmod{17}$$

$$6s_1 + 10s_2 + 13s_3 + s_4 \approx 3 \pmod{17}$$

$$10s_1 + 4s_2 + 12s_3 + 16s_4 \approx 12 \pmod{17}$$

$$9s_1 + 5s_2 + 9s_3 + 6s_4 \approx 9 \pmod{17}$$

$$3s_1 + 6s_2 + 4s_3 + 5s_4 \approx 16 \pmod{17}$$

$\vdots$

$$6s_1 + 7s_2 + 16s_3 + 2s_4 \approx 3 \pmod{17}$$

# Definition (LWE Problem)

- Pick uniformly random  $\vec{s} \in \mathbb{Z}_q^n$

# Definition (LWE Problem)

- Pick uniformly random  $\vec{s} \in \mathbb{Z}_q^n$
- Take  $\chi$  to be a discrete Gaussian distribution with some variance to be specified

# Definition (LWE Problem)

- Pick uniformly random  $\vec{s} \in \mathbb{Z}_q^n$
- Take  $\chi$  to be a discrete Gaussian distribution with some variance to be specified
- Input:  $\text{poly}(n)$  equations sampled as below:

# Definition (LWE Problem)

- Pick uniformly random  $\vec{s} \in \mathbb{Z}_q^n$
- Take  $\chi$  to be a discrete Gaussian distribution with some variance to be specified
- Input:  $\text{poly}(n)$  equations sampled as below:
  - pick coefficients  $\vec{a} \in \mathbb{Z}_q^n$  at random

# Definition (LWE Problem)

- Pick uniformly random  $\vec{s} \in \mathbb{Z}_q^n$
- Take  $\chi$  to be a discrete Gaussian distribution with some variance to be specified
- Input:  $\text{poly}(n)$  equations sampled as below:
  - pick coefficients  $\vec{a} \in \mathbb{Z}_q^n$  at random
  - Sample error  $e \leftarrow \chi$

# Definition (LWE Problem)

- Pick uniformly random  $\vec{s} \in \mathbb{Z}_q^n$
- Take  $\chi$  to be a discrete Gaussian distribution with some variance to be specified
- Input:  $\text{poly}(n)$  equations sampled as below:
  - pick coefficients  $\vec{a} \in \mathbb{Z}_q^n$  at random
  - Sample error  $e \leftarrow \chi$
  - Output  $(\vec{a} \cdot \vec{s} + e, \vec{a}) \in \mathbb{Z}_q^{1+n}$



# Definition (LWE Problem)

- Pick uniformly random  $\vec{s} \in \mathbb{Z}_q^n$
- Take  $\chi$  to be a discrete Gaussian distribution with some variance to be specified
- Input:  $\text{poly}(n)$  equations sampled as below:
  - pick coefficients  $\vec{a} \in \mathbb{Z}_q^n$  at random
  - Sample error  $e \leftarrow \chi$
  - Output  $(\vec{a} \cdot \vec{s} + e, \vec{a}) \in \mathbb{Z}_q^{1+n}$
- Output:  $\vec{s}$

# Definition (LWE Problem)

- Pick uniformly random  $\vec{s} \in \mathbb{Z}_q^n$
- Take  $\chi$  to be a discrete Gaussian distribution with some variance to be specified
- Input:  $\text{poly}(n)$  equations sampled as below:
  - pick coefficients  $\vec{a} \in \mathbb{Z}_q^n$  at random
  - Sample error  $e \leftarrow \chi$
  - Output  $(\vec{a} \cdot \vec{s} + e, \vec{a}) \in \mathbb{Z}_q^{1+n}$
- Output:  $\vec{s}$
- Note that  $(\vec{a} \cdot \vec{s} + e, \vec{a}) \cdot (1, -\vec{s}) = e$

# Homomorphic encryption

Allows secure communication by using the tools below:

# Homomorphic encryption

Allows secure communication by using the tools below:

- $pk$ : “public key”, used for encryption

# Homomorphic encryption

Allows secure communication by using the tools below:

- $pk$ : “public key”, used for encryption
- $\text{Enc}_{pk} : \Sigma^* \times \mathcal{R} \rightarrow U$

# Homomorphic encryption

Allows secure communication by using the tools below:

- $pk$ : “public key”, used for encryption
- $\text{Enc}_{pk} : \Sigma^* \times \mathcal{R} \rightarrow U$
- $sk$ : “secret key”, used for decryption

# Homomorphic encryption

Allows secure communication by using the tools below:

- $pk$ : “public key”, used for encryption
- $\text{Enc}_{pk} : \Sigma^* \times \mathcal{R} \rightarrow U$
- $sk$ : “secret key”, used for decryption
- $\text{Dec}_{sk} : U \rightarrow \Sigma^*$ .

# Homomorphic encryption

Allows secure communication by using the tools below:

- $pk$ : “public key”, used for encryption
- $\text{Enc}_{pk} : \Sigma^* \times \mathcal{R} \rightarrow U$
- $sk$ : “secret key”, used for decryption
- $\text{Dec}_{sk} : U \rightarrow \Sigma^*$ .
- $evk$ : “evaluation key”



# Idea of GSW's homomorphic encryption

Intuitive idea as follows:

- private key  $\vec{v}$  is a vector

# Idea of GSW's homomorphic encryption

Intuitive idea as follows:

- private key  $\vec{v}$  is a vector
- ciphertexts are matrices with  $\vec{v}$  approximately as an eigenvector

# Idea of GSW's homomorphic encryption

Intuitive idea as follows:

- private key  $\vec{v}$  is a vector
- ciphertexts are matrices with  $\vec{v}$  approximately as an eigenvector
- plaintexts are corresponding approximate eigenvalues

# Idea of GSW's homomorphic encryption

Intuitive idea as follows:

- private key  $\vec{v}$  is a vector
- ciphertexts are matrices with  $\vec{v}$  approximately as an eigenvector
- plaintexts are corresponding approximate eigenvalues
- $(C_1 + C_2)\vec{v} \approx (\lambda_1 + \lambda_2)\vec{v}$

# Idea of GSW's homomorphic encryption

Intuitive idea as follows:

- private key  $\vec{v}$  is a vector
- ciphertexts are matrices with  $\vec{v}$  approximately as an eigenvector
- plaintexts are corresponding approximate eigenvalues
- $(C_1 + C_2)\vec{v} \approx (\lambda_1 + \lambda_2)\vec{v}$
- $(C_1 C_2)\vec{v} \approx (\lambda_1 \lambda_2)\vec{v}$

# Idea of GSW's homomorphic encryption

Intuitive idea as follows:

- private key  $\vec{v}$  is a vector
- ciphertexts are matrices with  $\vec{v}$  approximately as an eigenvector
- plaintexts are corresponding approximate eigenvalues
- $(C_1 + C_2)\vec{v} \approx (\lambda_1 + \lambda_2)\vec{v}$
- $(C_1 C_2)\vec{v} \approx (\lambda_1 \lambda_2)\vec{v}$
- When plaintexts are booleans,  $I_N - C_1 C_2$  encodes NAND.

# Idea of GSW's homomorphic encryption cont.

- Take  $pk$  to be a matrix where each row is a tuple

# Idea of GSW's homomorphic encryption cont.

- Take  $pk$  to be a matrix where each row is a tuple
- Take  $sk = (1, -\vec{s})$



# Idea of GSW's homomorphic encryption cont.

- Take  $pk$  to be a matrix where each row is a tuple
- Take  $sk = (1, -\vec{s})$
- Take  $C = \mu I_n +$

# GSW's tools - terminology

- For the sake of illustration, fix  $q = 2^l = 2^4$ .

# GSW's tools - terminology

- For the sake of illustration, fix  $q = 2^l = 2^4$ .
- Let  $a = \underline{a_3 a_2 a_1 a_0} = \sum 2^i a_i$  represent the base-2 digits of  $a$

- For the sake of illustration, fix  $q = 2^l = 2^4$ .
- Let  $a = \underline{a_3 a_2 a_1 a_0} = \sum 2^i a_i$  represent the base-2 digits of  $a$
- Similarly, denote base-2 numbers like  $\underline{1011} = 8 + 2 + 1 = 11$

- $\text{Powersof2}(a) = (2^3a, 2^2a, 2a, a)$

- $\text{Powersof2}(a) = (2^3a, 2^2a, 2a, a)$

- $= \begin{pmatrix} 2^3a \\ 2^2a \\ 2a \\ a \end{pmatrix}$

- $\text{Powersof2}(a) = (2^3a, 2^2a, 2a, a)$
- $= \begin{pmatrix} 2^3a \\ 2^2a \\ 2a \\ a \end{pmatrix}$
- $\text{Powersof2}(\underline{11}) = (\underline{1000}, \underline{1100}, \underline{110}, \underline{11})$

- $\text{Powersof2}(a) = (2^3a, 2^2a, 2a, a)$
- $= \begin{pmatrix} 2^3a \\ 2^2a \\ 2a \\ a \end{pmatrix}$
- $\text{Powersof2}(\underline{11}) = (\underline{1000}, \underline{1100}, \underline{110}, \underline{11})$
- $\text{Powersof2}(a, b) = (2^3a, 2^2a, 2a, a, 2^3b, 2^2b, 2b, b)$



- $\text{BitDecomp}(\underline{a_3 a_2 a_1 a_0}) = (a_3 \ a_2 \ a_1 \ a_0)$

- $\text{BitDecomp}(\underline{a_3 a_2 a_1 a_0}) = (a_3 \ a_2 \ a_1 \ a_0)$
- $\text{BitDecomp}\left(\frac{a_3 a_2 a_1 a_0}{c_3 c_2 c_1 c_0} \ \frac{b_3 b_2 b_1 b_0}{d_3 d_2 d_1 d_0}\right) =$   
$$\begin{pmatrix} a_3 & a_2 & a_1 & a_0 & b_3 & b_2 & b_1 & b_0 \\ c_3 & c_2 & c_1 & c_0 & d_3 & d_2 & d_1 & d_0 \end{pmatrix}$$

- $\text{BitDecomp}(\underline{a_3 a_2 a_1 a_0}) = (a_3 \ a_2 \ a_1 \ a_0)$
- $\text{BitDecomp} \left( \begin{array}{cc} \underline{a_3 a_2 a_1 a_0} & \underline{b_3 b_2 b_1 b_0} \\ \underline{c_3 c_2 c_1 c_0} & \underline{d_3 d_2 d_1 d_0} \end{array} \right) =$   
 $\begin{pmatrix} a_3 & a_2 & a_1 & a_0 & b_3 & b_2 & b_1 & b_0 \\ c_3 & c_2 & c_1 & c_0 & d_3 & d_2 & d_1 & d_0 \end{pmatrix}$
- $\text{BitDecomp}(A) \text{Powersof2}(\vec{b}) = A\vec{b}$

- $\text{BitDecomp}^{-1} (1 \ 0 \ 0 \ 1) = \underline{1001}$

# GSW's tools - $\text{BitDecomp}^{-1}$

- $\text{BitDecomp}^{-1} (1 \ 0 \ 0 \ 1) = \underline{1001}$
- $\text{BitDecomp}^{-1} (0 \ 0 \ \underline{10} \ 0) = \underline{0100}$

- $\text{BitDecomp}^{-1} \begin{pmatrix} 1 & 0 & 0 & 1 \end{pmatrix} = \underline{1001}$
- $\text{BitDecomp}^{-1} \begin{pmatrix} 0 & 0 & \underline{10} & 0 \end{pmatrix} = \underline{0100}$
- $A\text{Powersof2}(\vec{b}) = \text{BitDecomp}^{-1}(A)\vec{b}$

# GSW's tools (Flatten)

- $\text{Flatten} = \text{BitDecomp} \circ \text{BitDecomp}^{-1}$

# GSW's tools (Flatten)

- $\text{Flatten} = \text{BitDecomp} \circ \text{BitDecomp}^{-1}$
- $\text{Flatten}(\underline{110} \quad \underline{101} \quad 1 \quad \underline{11})$



# GSW's tools (Flatten)

- $\text{Flatten} = \text{BitDecomp} \circ \text{BitDecomp}^{-1}$
- $\text{Flatten}(\underline{110} \quad \underline{101} \quad 1 \quad \underline{11})$
- $= \text{BitDecomp} \circ \text{BitDecomp}^{-1}(\underline{110} \quad \underline{101} \quad 1 \quad \underline{11})$

# GSW's tools (Flatten)

- $\text{Flatten} = \text{BitDecomp} \circ \text{BitDecomp}^{-1}$
- $\text{Flatten}(\underline{110} \quad \underline{101} \quad 1 \quad \underline{11})$
- $= \text{BitDecomp} \circ \text{BitDecomp}^{-1}(\underline{110} \quad \underline{101} \quad 1 \quad \underline{11})$
- $= (1 \quad 0 \quad 0 \quad 1)$

# GSW's tools (Flatten)

- $\text{Flatten} = \text{BitDecomp} \circ \text{BitDecomp}^{-1}$
- $\text{Flatten}(\underline{110} \quad \underline{101} \quad 1 \quad \underline{11})$
- $= \text{BitDecomp} \circ \text{BitDecomp}^{-1}(\underline{110} \quad \underline{101} \quad 1 \quad \underline{11})$
- $= (1 \quad 0 \quad 0 \quad 1)$
- $\text{Flatten}(A)$  has only 0, 1 entries

# GSW's tools (Flatten)

- $\text{Flatten} = \text{BitDecomp} \circ \text{BitDecomp}^{-1}$
- $\text{Flatten}(\underline{110} \quad \underline{101} \quad 1 \quad \underline{11})$
- $= \text{BitDecomp} \circ \text{BitDecomp}^{-1}(\underline{110} \quad \underline{101} \quad 1 \quad \underline{11})$
- $= (1 \quad 0 \quad 0 \quad 1)$
- $\text{Flatten}(A)$  has only 0, 1 entries
- $\text{Flatten}(A)\text{Powersof2}(\vec{b}) = A\text{Powersof2}(\vec{b})$

# GSW's Construction - Setup

Choose the following parameters:

- Modulus  $q = 2^l$  (to simplify some proofs)

# GSW's Construction - Setup

Choose the following parameters:

- Modulus  $q = 2^l$  (to simplify some proofs)
- Lattice dimension  $n$

# GSW's Construction - Setup

Choose the following parameters:

- Modulus  $q = 2^l$  (to simplify some proofs)
- Lattice dimension  $n$
- Error distribution  $\chi(\lambda, L)$

# GSW's Construction - Setup

Choose the following parameters:

- Modulus  $q = 2^l$  (to simplify some proofs)
- Lattice dimension  $n$
- Error distribution  $\chi(\lambda, L)$
- $m \in O(n \log q)$



# GSW's Construction - Secret Keygen

- 1 Sample  $\vec{s} \leftarrow \mathbb{Z}_q^n$  uniformly. This represents the solution of the LWE system of equations.

# GSW's Construction - Secret Keygen

- 1 Sample  $\vec{s} \leftarrow \mathbb{Z}_q^n$  uniformly. This represents the solution of the LWE system of equations.
- 2 Output  $sk$  as 1 on the first coordinate, followed by  $-\vec{s}$ .

# GSW's Construction - Public Keygen

- 1 Generate  $B \leftarrow \mathbb{Z}_q^{m \times n}$  uniformly

# GSW's Construction - Public Keygen

- 1 Generate  $B \leftarrow \mathbb{Z}_q^{m \times n}$  uniformly
- 2 Sample  $\vec{e} \leftarrow \chi^m$

# GSW's Construction - Public Keygen

- 1 Generate  $B \leftarrow \mathbb{Z}_q^{m \times n}$  uniformly
- 2 Sample  $\vec{e} \leftarrow \chi^m$
- 3 Set  $pk$  as  $B\vec{s} + \vec{e}$  on the first column, followed by the columns of  $B$ .

# GSW's Construction - Public Keygen

- 1 Generate  $B \leftarrow \mathbb{Z}_q^{m \times n}$  uniformly
- 2 Sample  $\vec{e} \leftarrow \chi^m$
- 3 Set  $pk$  as  $B\vec{s} + \vec{e}$  on the first column, followed by the columns of  $B$ .
- 4 Observe that  $pk \cdot sk = \vec{e}$

# GSW's Construction - Encryption

Input:  $\mu$

- 1 Sample  $R \in \{0, 1\}^{N \times m}$

# GSW's Construction - Encryption

Input:  $\mu$

- 1 Sample  $R \in \{0, 1\}^{N \times m}$
- 2 Output  $\text{Flatten}(\mu \cdot I + \text{BitDecomp}(R \cdot pk))$



# GSW's Construction - Decryption

$$\text{Flatten}(\mu \cdot I + \text{BitDecomp}(R \cdot pk)) \cdot \text{Powersof2}(sk)$$

# GSW's Construction - Decryption

$$\begin{aligned} & \text{Flatten}(\mu \cdot I + \text{BitDecomp}(R \cdot pk)) \cdot \text{Powersof2}(sk) \\ &= (\mu \cdot I + \text{BitDecomp}(R \cdot pk)) \cdot \text{Powersof2}(sk) \end{aligned}$$

# GSW's Construction - Decryption

$$\begin{aligned} & \text{Flatten}(\mu \cdot I + \text{BitDecomp}(R \cdot pk)) \cdot \text{Powersof2}(sk) \\ &= (\mu \cdot I + \text{BitDecomp}(R \cdot pk)) \cdot \text{Powersof2}(sk) \\ &= \mu \text{Powersof2}(sk) + R \cdot pk \cdot sk \end{aligned}$$

# GSW's Construction - Decryption cont.

$$\mu \text{Powersof2}(sk) + R \cdot pk \cdot sk$$

- The second term is small.

# GSW's Construction - Decryption cont.

$$\mu \text{Powersof2}(sk) + R \cdot pk \cdot sk$$

- The second term is small.
- The first coordinate of  $sk$  is 1.

# GSW's Construction - Decryption cont.

$$\mu \text{Powersof2}(sk) + R \cdot pk \cdot sk$$

- The second term is small.
- The first coordinate of  $sk$  is 1.
- $\Rightarrow$  The first coordinates of the first term are  $2^{l-1}\mu, 2^{l-2}\mu, \dots, \mu$

# GSW's Construction - Decryption cont.

$$\mu \text{Powersof2}(sk) + R \cdot pk \cdot sk$$

- The second term is small.
- The first coordinate of  $sk$  is 1.
- $\Rightarrow$  The first coordinates of the first term are  $2^{l-1}\mu, 2^{l-2}\mu, \dots, \mu$
- Recover  $\mu$ 's least significant bit by  $LSB(\mu) = 2^{l-1}\mu$

# GSW's Construction - Decryption cont.

$$\mu \text{Powersof2}(sk) + R \cdot pk \cdot sk$$

- The second term is small.
- The first coordinate of  $sk$  is 1.
- $\Rightarrow$  The first coordinates of the first term are  $2^{l-1}\mu, 2^{l-2}\mu, \dots, \mu$
- Recover  $\mu$ 's least significant bit by  $LSB(\mu) = 2^{l-1}\mu$
- Recover  $\mu$ 's next bit by  $2^{l-2}(\mu - LSB(\mu))$



# GSW's Construction - Decryption cont.

$$\mu \text{Powersof2}(sk) + R \cdot pk \cdot sk$$

- The second term is small.
- The first coordinate of  $sk$  is 1.
- $\Rightarrow$  The first coordinates of the first term are  $2^{l-1}\mu, 2^{l-2}\mu, \dots, \mu$
- Recover  $\mu$ 's least significant bit by  $LSB(\mu) = 2^{l-1}\mu$
- Recover  $\mu$ 's next bit by  $2^{l-2}(\mu - LSB(\mu))$
- Similar for all other bits of  $\mu$ .

# GSW's Construction - Decryption cont.

$$\mu \text{ Powers of } 2(sk) + R \cdot pk \cdot sk$$

- The second term is small.
- The first coordinate of  $sk$  is 1.
- $\Rightarrow$  The first coordinates of the first term are  $2^{l-1}\mu, 2^{l-2}\mu, \dots, \mu$
- Recover  $\mu$ 's least significant bit by  $LSB(\mu) = 2^{l-1}\mu$
- Recover  $\mu$ 's next bit by  $2^{l-2}(\mu - LSB(\mu))$
- Similar for all other bits of  $\mu$ .
- Decryption breaks down when the error reaches  $q/4$ .

# GSW's Construction - Security

- $\text{BitDecomp}^{-1}(C) = \mu \cdot \text{BitDecomp}^{-1}(I) + R \cdot A$

# GSW's Construction - Security

- $\text{BitDecomp}^{-1}(C) = \mu \cdot \text{BitDecomp}^{-1}(I) + R \cdot A$
- Fact: The joint distribution  $(A, R \cdot A)$  is indistinguishable from uniform, if  $m > 2nl$

# GSW's Construction - Security

- $\text{BitDecomp}^{-1}(C) = \mu \cdot \text{BitDecomp}^{-1}(I) + R \cdot A$
- Fact: The joint distribution  $(A, R \cdot A)$  is indistinguishable from uniform, if  $m > 2nl$
- $\Rightarrow \text{BitDecomp}^{-1}(C)$  hides  $\mu$

# GSW's Construction - Security

- $\text{BitDecomp}^{-1}(C) = \mu \cdot \text{BitDecomp}^{-1}(I) + R \cdot A$
- Fact: The joint distribution  $(A, R \cdot A)$  is indistinguishable from uniform, if  $m > 2nl$
- $\Rightarrow \text{BitDecomp}^{-1}(C)$  hides  $\mu$
- $C = \text{Flatten}(C) = \text{BitDecomp} \circ \text{BitDecomp}^{-1}(C)$  hides  $\mu$

- What does it mean for an encryption scheme to be secure?

- What does it mean for an encryption scheme to be secure?
- Chosen plaintext attack (CPA): The "intuitive" definition. An (efficient) adversary who's able to encrypt anything shouldn't be able to decrypt anything.



- What does it mean for an encryption scheme to be secure?
- Chosen plaintext attack (CPA): The "intuitive" definition. An (efficient) adversary who's able to encrypt anything shouldn't be able to decrypt anything.
- Ciphertext indistinguishability

# GSW's Construction - NAND

- $(I - C_1 \cdot C_2)\vec{v} = (1 - \mu_1\mu_2)\vec{v} - \mu_2\vec{e}_1 - C_1\vec{e}_2$

# GSW's Construction - NAND

- $(I - C_1 \cdot C_2)\vec{v} = (1 - \mu_1\mu_2)\vec{v} - \mu_2\vec{e}_1 - C_1\vec{e}_2$
- Error increased by a factor of  $N + 1$ .

# GSW's Construction - NAND

- $(I - C_1 \cdot C_2)\vec{v} = (1 - \mu_1\mu_2)\vec{v} - \mu_2\vec{e}_1 - C_1\vec{e}_2$
- Error increased by a factor of  $N + 1$ .
- Final error increase by a factor of  $(N + 1)^L$

# GSW's Construction - Multiplying by constant

Input:  $C, \alpha$

- Set  $M_\alpha = \text{Flatten}(\alpha I)$

# GSW's Construction - Multiplying by constant

Input:  $C, \alpha$

- Set  $M_\alpha = \text{Flatten}(\alpha I)$
- Output  $\text{Flatten}(M_\alpha \cdot C)$

# GSW's Construction - Multiplying by constant

Input:  $C, \alpha$

- Set  $M_\alpha = \text{Flatten}(\alpha I)$
- Output  $\text{Flatten}(M_\alpha \cdot C)$
- Observe  $M_\alpha \cdot C\vec{v} = M_\alpha \cdot (\mu\vec{v} + \vec{e}) = \alpha\mu\vec{v} + M_\alpha \cdot \vec{e}$

# GSW's Construction - Multiplying by constant

Input:  $C, \alpha$

- Set  $M_\alpha = \text{Flatten}(\alpha I)$
- Output  $\text{Flatten}(M_\alpha \cdot C)$
- Observe  $M_\alpha \cdot C\vec{v} = M_\alpha \cdot (\mu\vec{v} + \vec{e}) = \alpha\mu\vec{v} + M_\alpha \cdot \vec{e}$
- Error increases by a factor of  $N$



# GSW's Construction - Addition

- Output Flatten( $C_1 + C_2$ )

# GSW's Construction - Addition

- Output Flatten( $C_1 + C_2$ )
- Error increases by a factor of 2

# GSW's Construction - Multiplication

- Output Flatten( $C_1 C_2$ )

# GSW's Construction - Multiplication

- Output Flatten( $C_1 C_2$ )
- $C_1 \cdot C_2 \vec{v} = C_1(\mu_2 \vec{v} + \vec{e}_2) = \mu_1 \mu_2 \vec{v} + \mu_2 \vec{e}_1 + C_1 \vec{e}_2$

# GSW's Construction - Multiplication

- Output Flatten( $C_1 C_2$ )
- $C_1 \cdot C_2 \vec{v} = C_1(\mu_2 \vec{v} + \vec{e}_2) = \mu_1 \mu_2 \vec{v} + \mu_2 \vec{e}_1 + C_1 \vec{e}_2$
- Error increase depends on what's encrypted

# GSW's Construction - Multiplication

- Output Flatten( $C_1 C_2$ )
- $C_1 \cdot C_2 \vec{v} = C_1(\mu_2 \vec{v} + \vec{e}_2) = \mu_1 \mu_2 \vec{v} + \mu_2 \vec{e}_1 + C_1 \vec{e}_2$
- Error increase depends on what's encrypted
- May need to assume bounds on the values being computed

# Choosing parameters

- $\frac{q}{B} > 4(N + 1)^L$  for NANDs

# Choosing parameters

- $\frac{q}{B} > 4(N + 1)^L$  for NANDs
- $\frac{q}{B} > 4(N + T)^L$  for arithmetic circuit, where  $T$  is the upper bound on plaintexts



# Choosing parameters

- $\frac{q}{B} > 4(N + 1)^L$  for NANDs
- $\frac{q}{B} > 4(N + T)^L$  for arithmetic circuit, where  $T$  is the upper bound on plaintexts
- $N$  increases linearly with  $\log \frac{q}{B}$  for LWE's security

# Choosing parameters

- $\frac{q}{B} > 4(N + 1)^L$  for NANDs
- $\frac{q}{B} > 4(N + T)^L$  for arithmetic circuit, where  $T$  is the upper bound on plaintexts
- $N$  increases linearly with  $\log \frac{q}{B}$  for LWE's security
- Pick  $(q, B, N)$  accordingly

- O. Regev. The Learning with Errors Problem.
- C. Gentry, A. Sahai, B. Waters. Homomorphic Encryption from Learning with Errors: Conceptually-Simpler, Asymptotically-Faster, Attribute-Based.