Q-StaR: A Quasi-Static Routing Scheme for NoCs

This report condenses the paper into a more readable conference-style summary with structured analysis, key metrics, and design critique.

Paper Information

Title	Q-StaR: A Quasi-Static Routing Scheme for NoCs
Authors	Yang Zhang, Yiren Zhao, Xu Wang, Fengyuan Ren
Source	arXiv:2603.10637, version analyzed: v1
Date	March 11, 2026
Core Idea	Use offline load-trend inference to guide low-cost runtime routing.

NoC Routing · 2D Mesh · Load Balancing · Quasi-Static Design

At a Glance

THROUGHPUT
+42.9%
vs. XY routing under uniform traffic.

AVG. LATENCY
-86.4%
149.6 to 20.4 cycles on the realistic workload.

MAX LATENCY
-95.3%
572 to 27 cycles on the realistic workload.

1. Executive Summary

Q-StaR addresses the gap between static and adaptive routing in networks-on-chip. The paper argues that while static routing is implementation-friendly, it ignores load imbalance; adaptive routing balances traffic better, but at the cost of hardware complexity and runtime overhead. The authors propose a middle-ground approach in which long-term load tendencies are computed offline and then used to drive deterministic routing choices online.

> **Key contribution:** The paper combines `N-Rank` and `BiDOR` so that predicted load hotspots influence route selection without requiring fully dynamic congestion sensing.

> **Method:** The system derives node weights from topology and traffic distribution, then chooses between XY and YX minimal paths using those weights. Runtime control is reduced to a bitmap lookup.

> **Main result:** The reported gains are substantial, especially against standard XY routing, suggesting that quasi-static workload knowledge can be operationally valuable in NoC design.

2. Introduction

> **Background:** 2D mesh NoCs and dimension-order routing remain popular because they are simple, analyzable, and easy to verify for deadlock freedom. These properties matter in SoCs where cost, timing closure, and predictability are design constraints.

> **Problem statement:** Deterministic routing does not account for actual traffic distribution, so certain routers or channels may become persistent hotspots. This leads to poor load balance, reduced throughput, and inflated latency.

> **Motivation:** The authors observe that traffic is often structured rather than arbitrary. Since topology and communication patterns can often be profiled or inferred, they propose using this slower-changing information to guide routing decisions more intelligently than plain XY routing.

3. Key Methods

N-Rank

> **Purpose:** Estimate which nodes are likely to experience high long-term load.

> **Mechanism:** An evolutionary model injects, transfers, and drains traffic over the topology using a traffic matrix and no-detour assumptions. The cumulative exposure of each node becomes its `w_NR`.

> **Why it works:** It captures structural load trends rather than noisy instantaneous congestion, which is exactly the information a quasi-static scheme needs.

In more concrete terms, N-Rank tries to answer a predictive question:

BiDOR

> **Purpose:** Convert node-level load estimates into concrete routing decisions.

> **Mechanism:** For each source-destination pair, BiDOR computes the total `w_NR` along the XY path and the YX path, then selects the cheaper one offline.

> **Why it works:** The online path choice becomes a constant-time bitmap lookup, so the router retains deterministic behavior while avoiding structurally congested regions.

BiDOR is the execution layer of Q-StaR. Once N-Rank assigns a relative cost to each node, BiDOR evaluates the two dimension-order