

COSC 3340
Examination 3
Wednesday, April 9, 2008, 1 – 2:30 pm
Open Book and Notes

1. Prove that the following language L is not contextfree:

$$L = \{ 0^k 1^j 2^i \mid i > j > k \geq 0 \}.$$

2. Construct a pda P for the following language:

$$L = \{ 0^i 1^{3i} \mid i \geq 0 \} \text{ where } L = L_f(P) \text{ (acceptance by final state).}$$

State on which side you write the top of the stack, left: ☐ or right: ☐.
 Hint: Put three markers on the stack for every 0.

3. Construct a pda P that accepts the following language by empty stack:

$$L = L(G) \text{ where } G = (T, N, P, S) \text{ with } T = \{ \langle S \rangle, [] \},$$

$$N = \{ S, A \}, \text{ and } P = \{ S \rightarrow \langle S \rangle A \mid [A]A, A \rightarrow [A]S \mid \langle S \rangle S \mid \varepsilon \}.$$

State on which side you write the top of the stack, left: ☐ or right: ☐.
 Note: You must use the construction "cfg \rightarrow pda" given in class. Get G into GNF first!

4. Construct a grammar for $L(G)$ for the language $N(2)$:

$P = (\{ p, q \}, \{ a, b \}, \{ Z, X \}, \delta, p, Z, \emptyset)$ where the move function δ is given by:

$$\delta(p, a, Z) = \{ (p, XZ) \} \quad \delta(p, \varepsilon, Z) = \{ (p, \varepsilon) \} \quad \delta(p, a, X) = \{ (p, XX) \}$$

$$\delta(q, a, Z) = \{ (q, \varepsilon) \} \quad \delta(p, b, X) = \{ (q, X) \} \quad \delta(q, b, Z) = \{ (p, Z) \}.$$

Here, the top of the stack is on the left.

5. Construct a Turing machine for the language in Question 1.

$$L = \{ 0^k 1^j 2^i \mid i > j > k \geq 0 \}.$$

Describe first in words what you are doing, then formulate the formal Turing machine.

Points: 1: 20 2: 12 3: 18 4: 30 5: 20

$$L = \{0^k 1^i 2^j \mid i > j > k \geq 0\}$$

1) assume L is cfl

\Rightarrow then $\exists G(N, T, P, S)$ in CNF s.t. $L = L(G)$

assume $t = \text{no. of vars}$, assume a word $z = 0^{2^t} 1^{2^{t+1}} 2^{2^{t+2}}$ $|z| > 2^t$

1	20
2	12
3	18
4	30
5	20
<hr/>	
	100

by pumping Lemma $z = uv^iwx^iy$ where $|vx| \geq 1$
 $\& uv^iwx^iy \in L(G)$
 For all $i \geq 0$

case 1. $V \& X$ are all 0's \Rightarrow for $i=2$ no. of zero can be equal
 no. of 1. $\notin L(G), \notin L$

case 2. $V \& X$ are all 1's \Rightarrow for $i=2$ $\notin L(G)$, $\notin L$

case 3. $V \& X$ are all 2's \Rightarrow for $i=0$ $\notin L(G)$, $\notin L$

case 4. No 2's in $vwx \Rightarrow$ for $i=2 \in L(G)$, $\notin L$
 because No. of 1's can be equal to no. of 2's

case 5. No 1's in $vwx \Rightarrow$ for $i=2 \in L(G)$, $\notin L$

case 6. No 0's in $vwx \Rightarrow$ for $i=0 \in L(G)$, $\notin L$
 because No. of 1's decrease to be equal No. of zeros

case 7. at least one 0, one 1, one 2 in vwx

for $i > 1$ the pattern will change

i.e. zeros can follow 2's which is not acceptable by L

\therefore there is contradiction in each case

\therefore the language L is not Context free

20

④

		a	b	ε
p	z	{(p,x,z)}	/	{(p,ε)}
	x	{(p,x,x)}	{(q,x)}	/
q	z	{(q,ε)}	{(p,z)}	/
	x	/	/	/

30

$$S \rightarrow [p, z, p] \mid [p, z, q] \rightarrow \textcircled{1}$$

$$(p, xz) \in \delta(p, a, z)$$

$$[p, z, p] \rightarrow a[p, x, p][p, z, p]$$

$$\textcircled{2} \leftarrow [p, z, p] \rightarrow a[p, x, p][p, z, p] \mid a[p, x, q][q, z, p]$$

$$\textcircled{3} \leftarrow \text{and } [p, z, q] \rightarrow a[p, x, p][p, z, q] \mid a[p, x, q][q, z, q]$$

$$(p, xx) \in \delta(p, a, x)$$

$$[p, x, p] \rightarrow a[p, x, p][p, x, p]$$

$$\textcircled{4} \leftarrow [p, x, p] \rightarrow a[p, x, p][p, x, p] \mid a[p, x, q][q, x, p]$$

$$\textcircled{5} \leftarrow [p, x, q] \rightarrow a[p, x, p][p, x, q] \mid a[p, x, q][q, x, q]$$

$$* (p, \epsilon) \in \delta(p, \epsilon, z)$$

$$[p, z, p] \rightarrow \epsilon \quad \checkmark \rightarrow \textcircled{6}$$

$$* (q, x) \in \delta(p, b, x)$$

$$[p, x, p] \rightarrow b [q, x, p]$$

$$[p, x, p] \rightarrow b [q, x, p] \quad \checkmark \rightarrow \textcircled{7}$$

$$[p, x, q] \rightarrow b [q, x, q] \quad \checkmark \rightarrow \textcircled{8}$$

$$* (q, \epsilon) \in \delta(q, a, z)$$

$$[q, z, q] \rightarrow a \quad \checkmark \rightarrow \textcircled{9}$$

$$* (p, z) \in \delta(q, b, z)$$

$$[q, z, p] \rightarrow b [p, z, p]$$

$$\Rightarrow [q, z, p] \rightarrow b [p, z, p] \quad \checkmark \rightarrow \textcircled{10}$$

$$[q, z, q] \rightarrow b [p, z, q] \quad \checkmark \rightarrow \textcircled{11}$$

The $L(G)$ is defined with ~~productions~~ ^{productions} 1. 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11

⑥

② First I'll construct a pda that accepts by empty stack then change it to one that accepts by final state

$$P_1 = (\{0,1\}, \{q_0, q_1\}, \{z_0, z\}, \delta, q_0, \emptyset, z_0)$$

δ_1 (The top of the stack is on the left)

	0	1	ϵ
z_0	$\{(q_0, zzzz_0)\}$	/	$\{(q_1, \epsilon)\}$
q_0	$z \{(q_0, zzzz_0)\}$	$\{(q_1, \epsilon)\}$	/
	z_0	/	$\{(q_1, \epsilon)\}$
q_1	z	$\{(q_0, \epsilon)\}$	/

~~P_1~~ $P_2 = (\{0,1\}, \{q'_0, q_0, q_1, q_f\}, \{z'_0, z_0, z\}, \delta', q'_0, q_f, z'_0)$

δ'

	0	1	ϵ
z'_0	/	/	$\{(q'_0, zzzz_0)\}$
q'_0	z_0	/	/
	z	/	/
	z'_0	/	$\{(q_1, \epsilon)\}$
q_0	z_0	$\{(q_0, zzzz_0)\}$	$\{(q_1, \epsilon)\}$
	z	$\{(q_0, zzzz_0)\}$	$\{(q_1, \epsilon)\}$
	z'_0	/	$\{(q_1, \epsilon)\}$
q_1	z_0	/	$\{(q_1, \epsilon)\}$
	z	$\{(q_1, \epsilon)\}$	/
	z'_0	/	/
q_f	z_0	/	/
	z	/	/

Final state

⑤

$$③ \quad S \rightarrow \langle S \rangle A \mid [A] A$$

$$A \rightarrow [A] S \mid \langle S \rangle S \mid \epsilon$$

$$S \rightarrow \langle S \rangle A \mid \langle S \rangle \mid [A] A \mid [A] \mid [\epsilon] A \mid [\epsilon]$$

eliminate ϵ

$$A \rightarrow [A] S \mid [] S \mid \langle S \rangle S$$

$$S \rightarrow \langle S X_1 \rangle A \mid \langle S X_1 \rangle \mid [A X_1] A \mid [A X_1] \mid [\epsilon X_1] A \mid [X_1]$$

To GNF

$$A \rightarrow [A X_1] S \mid [X_1] S \mid \langle S X_1 \rangle S$$

$$X_1 \rightarrow \langle \rangle$$

$$X_2 \rightarrow []$$

$$18 \quad P_n = (\{ \langle, \rangle, [] \}, \{ q_0 \}, \{ S, A, X_1, X_2 \}, \delta, q_0, \emptyset, S)$$

		<	>	[]	ϵ
q ₀	S	{(q ₀ , S, A), (q ₀ , S, <)} /	/	{(q ₀ , A, X ₁), (q ₀ , A, X ₂)} /	{(q ₀ , X ₁ , A), (q ₀ , X ₂ , A)} /	/
	A	{(q ₀ , S, X ₁ S)} /	/	{(q ₀ , A, X ₁ S), (q ₀ , X ₁ S)} /	{(q ₀ , X ₂ S)} /	/
	X ₁	/	{(q ₀ , ϵ)}	/	/	/
	X ₂	/	/	{(q ₀ , ϵ)}	/	/

The top of stack on the left


⑤ $\{0^k 1^j 2^i \mid i > j > k \geq 0\}$
 ex. of accepted words 122, 011222
 001112222



first we ~~mark~~ start reading from the left, if a zero is found then we mark it and skip all zeros till we find a 1 then we mark it and skip 1's till we find a two then we mark it then we start move back to the left skipping everything till we find a 0 then we turn to move right and repeat the whole process till all zeros are marked.

then we repeat the same process for only the 1's and 2's till all 1's are marked then we make sure that there is at least a 2 left (or more) then we mark all 2's till we reach ϵ

if at the start no zeros are found we proceed as if all zeros were marked and this is the case when $k=0$



This state is reached when there are no 0's in the word i.e. $k=0$

q_0
 q_1
 q_2
 q_3
 q_4
 reaching 15 means we marked all 0's
 q_5
 q_6
 q_7
 q_8
 we marked all 1's
 q_9
 q_{10}
 q_f

	0	1	2	0'	1'	2'	ϵ
q_0	$(q_1, 0', R)$	$(q_1, 1', R)$	/	/	/	/	/
q_1	$(q_1, 0', R)$	$(q_2, 1', R)$	/	/	$(q_{11}, 1', R)$	/	/
q_2	/	$(q_2, 1', R)$	$(q_3, 2', L)$	/	/	$(q_{12}, 2', R)$	/
q_3	$(q_3, 0', L)$	$(q_3, 1', L)$	/	$(q_{11}, 0', R)$	$(q_{13}, 1', L)$	$(q_{13}, 2', L)$	/
q_4	$(q_4, 0', R)$	/	/	/	$(q_{15}, 1', R)$	/	/
q_5	/	$(q_6, 1', R)$	/	/	$(q_{15}, 1', R)$	/	/
q_6	/	$(q_6, 1', R)$	$(q_7, 2', L)$	/	/	$(q_{16}, 2', R)$	/
q_7	/	$(q_7, 1', L)$	/	/	$(q_{18}, 1', R)$	$(q_{17}, 2', L)$	/
q_8	/	$(q_6, 1', R)$	/	/	/	$(q_{17}, 2', R)$	/
q_9	/	/	$(q_{10}, 2', R)$	/	/	$(q_{14}, 2', R)$	/
q_{10}	/	/	$(q_{10}, 2', R)$	/	/	/	$(q_{14}, 1', R)$
q_f	accepting state						

The Turing Machine for the language $L = \{0^k 1^j 2^l \mid j \geq k, l \geq k\}$