


intro to PlonK


PSE ZK Workshop
15 Feb 2025

arithmetisation




polynomial commitment scheme






commit to polynomial,
and provably evaluate
it at arbitrary points




commit to polynomial,
and provably evaluate
it at arbitrary points


commitment opening proof




PLONKish arithmetisation (univariate)



PLONKish arithmetisation




PLONKish arithmetisation



PLONKish arithmetisation (vanilla)


PLONK
[GWC19]



- **gates** take two values as **inputs**, either **add** or **multiply** them, and then emit the result through an **output** wire;

PLONKish arithmetisation (vanilla)

PLONK
[[GWC19](#)]



- **gates** take two values as **inputs**, either **add** or **multiply** them, and then emit the result through an **output** wire;

"local" consistency check: are all gate equations satisfied?

PLONKish arithmetisation (vanilla)

PLONK
[GWC19]




- **gates** take two values as **inputs**, either **add** or **multiply** them, and then emit the result through an **output** wire;

"local" consistency check: are all gate equations satisfied?

$$q_L \cdot x_a + q_R \cdot x_b + q_0 \cdot x_c + q_M \cdot (x_a x_b) = 0$$

PLONKish arithmetisation (vanilla)

PLONK
[GWC19]




- **gates** take two values as **inputs**, either **add** or **multiply** them, and then emit the result through an **output** wire;

"local" consistency check: are all gate equations satisfied?

$$\boxed{q_L} \cdot x_a + \boxed{q_R} \cdot x_b + \boxed{q_0} \cdot x_c + \boxed{q_M} \cdot (x_a x_b) = 0 \quad \text{preprocessed selector polynomials}$$

PLONKish arithmetisation (vanilla)

PLONK
[[GWC19](#)]



- **gates** take two values as **inputs**, either **add** or **multiply** them, and then emit the result through an **output** wire;


"local" consistency check: are all gate equations satisfied?

$$q_L \cdot x_a + q_R \cdot x_b + q_0 \cdot x_c + q_M \cdot (x_a x_b) = 0$$

$$\text{add: } 1 \cdot x_a + 1 \cdot x_b + (-1) \cdot x_c + 0 \cdot (x_a x_b) = 0$$

PLONKish arithmetisation (vanilla)

PLONK
[[GWC19](#)]



- **gates** take two values as **inputs**, either **add** or **multiply** them, and then emit the result through an **output** wire;

"local" consistency check: are all gate equations satisfied?

$$q_L \cdot x_a + q_R \cdot x_b + q_0 \cdot x_c + q_M \cdot (x_a x_b) = 0$$

$$\text{add: } 1 \cdot x_a + 1 \cdot x_b + (-1) \cdot x_c + 0 \cdot (x_a x_b) = 0$$

$$\text{mul: } 0 \cdot x_a + 0 \cdot x_b + (-1) \cdot x_c + 1 \cdot (x_a x_b) = 0$$

PLONKish arithmetisation (custom gates)

TurboPLONK
[[GW19](#)]

vanilla PLONK gate: $q_L \cdot x_a + q_R \cdot x_b + q_0 \cdot x_c + q_M \cdot (x_a x_b) = 0$

custom gates (arbitrary linear combinations):

$$\underbrace{q_{\text{add}} \cdot (a_0 + a_1 - a_2)}_{\text{add gate}} = 0$$

PLONKish arithmetisation (custom gates)

TurboPLONK
[[GW19](#)]

vanilla PLONK gate: $q_L \cdot x_a + q_R \cdot x_b + q_0 \cdot x_c + q_M \cdot (x_a x_b) = 0$

custom gates (arbitrary linear combinations):

$$\underbrace{q_{\text{add}} \cdot (a_0 + a_1 - a_2)}_{\text{add gate}} + \underbrace{q_{\text{mul}} \cdot (a_0 \cdot a_1 - a_2)}_{\text{mul gate}} = 0$$

PLONKish arithmetisation (custom gates)

TurboPLONK
[[GW19](#)]

vanilla PLONK gate: $q_L \cdot x_a + q_R \cdot x_b + q_0 \cdot x_c + q_M \cdot (x_a x_b) = 0$

custom gates (arbitrary linear combinations):

$$\underbrace{q_{\text{add}} \cdot (a_0 + a_1 - a_2)}_{\text{add gate}} + \underbrace{q_{\text{mul}} \cdot (a_0 \cdot a_1 - a_2)}_{\text{mul gate}} + \underbrace{q_{\text{bool}} \cdot (a_0 \cdot a_0 - a_0)}_{\text{bool gate}} = 0$$

PLONKish arithmetisation (custom gates)

TurboPLONK
[[GW19](#)]

vanilla PLONK gate: $q_L \cdot x_a + q_R \cdot x_b + q_0 \cdot x_c + q_M \cdot (x_a x_b) = 0$


custom gates (arbitrary linear combinations):

$$\underbrace{q_{\text{add}} \cdot (a_0 + a_1 - a_2)}_{\text{add gate}} + \underbrace{y \cdot q_{\text{mul}} \cdot (a_0 \cdot a_1 - a_2)}_{\text{mul gate}} + \underbrace{y^2 \cdot q_{\text{bool}} \cdot (a_0 \cdot a_0 - a_0)}_{\text{bool gate}} = 0$$

verifier challenge to keep gates linearly independent

PLONKish arithmetisation (permutation)


PLONK
[[GWC19](#)]



- **wires** carry values into and out of gates

PLONKish arithmetisation (permutation)

PLONK
[GWC19]



- **wires** carry values into and out of gates

"global" consistency check: do the wires correctly join the gates together?

* in Groth16, routing is baked into the trusted setup; we can't do this for universal SNARKs

PLONKish arithmetisation (permutation)

PLONK
[GWC19]

w_0	w_1	w_2	gate
$w_0[0]$	$w_1[0]$	$w_2[0]$	+
$w_0[1]$	$w_1[1]$	$w_2[1]$	\times

each wire (column i) is encoded as a Lagrange polynomial w_i over the powers (rows) of an n^{th} root of unity $\{1, \omega, \dots, \omega^{n-1}\}$, where $\omega^n = 1$:

$$w_i(\omega^j) = w_i[j]$$

PLONKish arithmetisation (permutation)

PLONK
[GWC19]

w_0	w_1	w_2	gate
$w_0[0]$	$w_1[0]$	$w_2[0]$	+
$w_0[1]$	$w_1[1]$	$w_2[1]$	\times

each wire (column i) is encoded as a Lagrange polynomial w_i over the powers (rows) of an n^{th} root of unity $\{1, \omega, \dots, \omega^{n-1}\}$, where $\omega^n = 1$:

$$w_i(\omega^j) = w_i[j]$$

to enforce equality of wires, use **permutation argument (deep-dive)**;
show that swapping $w_2(\omega^0)$ with $w_0(\omega^1)$ doesn't change the polynomials.

PLONKish arithmetisation (lookup)

UltraPLONK
[[halo2](#)]

w_0	w_1
42	SHA(42)
0	0
69	SHA(69)
...	...
0	0

problem: SHA is expensive to do in-circuit

PLONKish arithmetisation (lookup)

UltraPLONK
[[halo2](#)]

w_0	w_1	q_{lookup}	t_0	t_1
42	SHA(42)	1	0	SHA(0)
0	0	0	1	SHA(1)
69	SHA(69)	1	2	SHA(2)
...
0	0	0	255	SHA(255)

solution: load precomputed SHA (e.g. for 8-bit values) as lookup table

PLONKish arithmetisation (lookup)

UltraPLONK
[[halo2](#)]

w_0	w_1	q_{lookup}	t_0	t_1
42	SHA(42)	1	0	SHA(0)
0	0	0	1	SHA(1)
69	SHA(69)	1	2	SHA(2)
...
0	0	0	255	SHA(255)

$$\begin{aligned} & (q_{\text{lookup}} \cdot w_0, t_0) \\ & (q_{\text{lookup}} \cdot w_1, t_1) \end{aligned}$$

PLONKish arithmetisation (lookup)

UltraPLONK
[[halo2](#)]

w_0	w_1	q_{lookup}	t_0	t_1
42	SHA(42)	1	0	SHA(0)
0	0	0	1	SHA(1)
69	SHA(69)	1	2	SHA(2)
...
0	0	0	255	SHA(255)

$$\begin{aligned} & (q_{\text{lookup}} \cdot w_0 + (1 - q_{\text{lookup}}) \cdot 0, \quad t_0) \\ & (q_{\text{lookup}} \cdot w_1 + (1 - q_{\text{lookup}}) \cdot \text{SHA}(0), \quad t_1) \end{aligned}$$

lookup default value when q_{lookup} is not enabled,
so that lookup argument passes on every row

PLONKish arithmetisation (lookup)

UltraPLONK
[[halo2](#)]

w_0	w_1	q_{lookup}	t_0	t_1
42	SHA(42)	1	0	SHA(0)
0	0	0	1	SHA(1)
69	SHA(69)	1	2	SHA(2)
...
0	0	0	255	SHA(255)

the lookup argument is a more permissive version of the permutation argument. it enforces that:

every cell in a set of **input columns** is equal to
some cell in a set of **table columns**

PLONKish arithmetisation (lookup)

UltraPLONK
[[halo2](#)]


w_0	w_1	q_{lookup}	t_0	t_1
42	SHA(42)	1	0	SHA(0)
0	0	0	1	SHA(1)
69	SHA(69)	1	2	SHA(2)
...
0	0	0	255	SHA(255)

the lookup argument is a more permissive version of the permutation argument. it enforces that:

every **expression** in a set of **input columns** is equal to
some expression in a set of **table columns**


more on this in the deep-dive!

PLONKish arithmetisation




we conceptualise the circuit as a **matrix** of m columns and n rows

PLONKish arithmetisation




we conceptualise the circuit as a **matrix** of m columns and n rows,
over a given **finite field** \mathbb{F} (so the cells contain elements of \mathbb{F})

PLONKish arithmetisation



each column j corresponds to a Lagrange interpolation polynomial $p_j(X)$

PLONKish arithmetisation



each column j corresponds to a Lagrange interpolation polynomial $p_j(X)$ evaluating to $\mathbf{p}_j(\omega^i) = \mathbf{x}_{ij}$, where ω is the n^{th} primitive root of unity.

aside: fast Fourier transform (FFT)

how to encode vector $[a_0, a_1, \dots, a_{n-1}]$ as polynomial $p(X)$?

treat each a_i as the **evaluation** of $p(X)$ at a certain point x_i .
(for efficiency, we pick x_i to be the i th power of the root of unity ω^i , where $\omega^n = 1$.)


$$p(X) := \sum a_i L_i(X),$$

where $L_i(X)$'s are the Lagrange bases

$$L_i(X) := \frac{\prod_{j \neq i} (\omega^i - \omega^j)}{\prod_{j \neq i} (X - \omega^j)} = \begin{cases} 1 & \text{if } X = \omega^i, \\ 0 & \text{otherwise} \end{cases}$$


we will be working over the evaluation domain $H = \{\omega^i\}$, $i = 0..N$

PLONKish arithmetisation




instance columns contain inputs **shared**
between prover/verifier (e.g. public inputs)

PLONKish arithmetisation



advice columns contain private
values witnessed by the prover

PLONKish arithmetisation



example: Fibonacci sequence

write this in tomorrow's session!

i_0	a_0	a_1	a_2	q_{fib}
1	1	1	2	1
	2	3	5	1
13	5	8	13	0

example: Fibonacci sequence

i_{θ}	a_{θ}	a_1	a_2	q_{fib}
1	1	1	2	1
	2	3	5	1
13	5	8	13	0

$$q_{\text{fib}} \cdot (a_{\theta, \text{cur}} + a_{1, \text{cur}} - a_{2, \text{cur}}) =$$

θ

example: Fibonacci sequence

i_θ	a_θ	a_1	a_2	q_{fib}
1	1	1	2	1
	2	3	5	1
13	5	8	13	0

$$q_{\text{fib}} \cdot (a_{\theta, \text{cur}} + a_{1, \text{cur}} - a_{2, \text{cur}}) =$$

θ

$$q_{\text{fib}} \cdot (a_{\theta, \text{cur}} + a_{1, \text{cur}} - a_{\theta, \text{next}}) =$$

θ

example: Fibonacci sequence

i_θ	a_θ	a_1	a_2	q_{fib}
1	1	1	2	1
	2	3	5	1
13	5	8	13	0

$$q_{\text{fib}} \cdot (a_{\theta, \text{cur}} + a_{1, \text{cur}} - a_{2, \text{cur}}) =$$

0

$$q_{\text{fib}} \cdot (a_{\theta, \text{cur}} + a_{1, \text{cur}} - a_{\theta, \text{next}}) =$$

0

$$q_{\text{fib}} \cdot (a_{1, \text{cur}} + a_{2, \text{cur}} - a_{1, \text{next}}) =$$

0

example: Fibonacci sequence

i_θ	a_θ	a_1	a_2	q_{fib}
1	1	1	2	1
	2	3	5	1
13	5	8	13	0

$$\begin{aligned}
 q_{\text{fib}} \cdot (a_{\theta, \text{cur}} + a_{1, \text{cur}} - a_{2, \text{cur}}) &= \\
 \theta \\
 q_{\text{fib}} \cdot (a_{\theta, \text{cur}} + a_{1, \text{cur}} - a_{\theta, \text{next}}) &= \\
 \theta \\
 q_{\text{fib}} \cdot (a_{1, \text{cur}} + a_{2, \text{cur}} - a_{1, \text{next}}) &= \\
 \theta
 \end{aligned}$$

global permutation: $a_2[i] = a_\theta[i + 1]$

example: Fibonacci sequence

i_0	a_0	a_1	a_2	q_{fib}
1	1	1	2	1
	2	3	5	1
13	5	8	13	0

$$\begin{aligned} q_{\text{fib}} \cdot (a_{0,\text{cur}} + a_{1,\text{cur}} - a_{2,\text{cur}}) &= \\ 0 \\ q_{\text{fib}} \cdot (a_{0,\text{cur}} + a_{1,\text{cur}} - a_{0,\text{next}}) &= \\ 0 \\ q_{\text{fib}} \cdot (a_{1,\text{cur}} + a_{2,\text{cur}} - a_{1,\text{next}}) &= \\ 0 \end{aligned}$$

global permutation: $a_2[i] = a_0[i + 1]$

exercise: can you see how to constrain this locally (using q_{fib})?


example: Fibonacci sequence

i_0	a_0	a_1	a_2	q_{fib}
1	1	1	2	1
	2	3	5	1
13	5	8	13	0

$$\begin{aligned} q_{\text{fib}} \cdot (a_{0,\text{cur}} + a_{1,\text{cur}} - a_{2,\text{cur}}) &= \\ 0 \\ q_{\text{fib}} \cdot (a_{0,\text{cur}} + a_{1,\text{cur}} - a_{0,\text{next}}) &= \\ 0 \\ q_{\text{fib}} \cdot (a_{1,\text{cur}} + a_{2,\text{cur}} - a_{1,\text{next}}) &= \\ 0 \end{aligned}$$

global permutation:

- $i_0[0] = a_0[0]$ // initialisation
- $i_0[0] = a_1[0]$ // initialisation
- $i_0[2] = a_2[2]$ // output



Prover

Verifier


Prover

Verifier

$$\begin{array}{c} Z_H(X) = X^{n-1}, \\ f_0(X), f_1(X), \dots \end{array} \longleftrightarrow$$


Prover

Verifier



Prover

Verifier




Prover

Verifier


$$Z_H(X) = X^{n-1},$$

$$f_0(X), f_1(X), \dots$$




$$a_{0,0}(X), a_{0,1}(X), \dots$$

$$[a_{0,0}], [a_{0,1}], \dots$$




$$r_{0,0}, r_{0,1}, \dots$$



$$r_{0,0}, r_{0,1}, \dots \leftarrow \mathbb{F}$$

$$a_{1,0}(X), a_{1,1}(X), \dots$$

$$[a_{1,0}], [a_{1,1}], \dots$$



$$r_{1,0}, r_{1,1}, \dots$$




$$r_{1,0}, r_{1,1}, \dots \leftarrow \mathbb{F}$$

...

$$q(X) = \frac{(\text{gate}_0(X) + \gamma \cdot \text{gate}_1(X) + \dots)}{Z_H(X)}$$

$$[q_0], [q_1], \dots$$



$$x$$




$$x \leftarrow \mathbb{F}$$

Prover

Verifier


$$Z_H(X) = X^{n-1},$$

$$f_0(X), f_1(X), \dots$$




$$a_{0,0}(X), a_{0,1}(X), \dots$$

$$[a_{0,0}], [a_{0,1}], \dots$$



$$r_{0,0}, r_{0,1}, \dots$$



$$r_{0,0}, r_{0,1}, \dots \leftarrow \mathbb{F}$$

$$a_{1,0}(X), a_{1,1}(X), \dots$$

$$[a_{1,0}], [a_{1,1}], \dots$$



$$r_{1,0}, r_{1,1}, \dots$$




$$r_{1,0}, r_{1,1}, \dots \leftarrow \mathbb{F}$$

...

$$q(X) = \frac{(\text{gate}_0(X) + \gamma \cdot \text{gate}_1(X) + \dots)}{\boxed{Z_H(X)}}$$

$$[q_0], [q_1], \dots$$



$$x$$



$$x \leftarrow \mathbb{F}$$


recall: our evaluation domain is $H = \{H = \{\omega^i\}, i = 0..N\}$, where $\omega^N = 1$

Prover

Verifier

$$Z_H(X) = X^{n-1},$$

$$f_0(X), f_1(X), \dots$$



$$a_{0,0}(X), a_{0,1}(X), \dots$$

$$[a_{0,0}], [a_{0,1}], \dots$$

$$\xrightarrow{\hspace{1cm}}$$

$$r_{0,0}, r_{0,1}, \dots$$



$$r_{0,0}, r_{0,1}, \dots \leftarrow \mathbb{F}$$

$$a_{1,0}(X), a_{1,1}(X), \dots$$

$$[a_{1,0}], [a_{1,1}], \dots$$

$$\xrightarrow{\hspace{1cm}}$$

$$r_{1,0}, r_{1,1}, \dots$$



$$r_{1,0}, r_{1,1}, \dots \leftarrow \mathbb{F}$$

...

$$q(X) = \frac{(\text{gate}_0(X) + \gamma \cdot \text{gate}_1(X) + \dots)}{\boxed{Z_H(X)}}$$

$$[q_0], [q_1], \dots$$

$$\xrightarrow{\hspace{1cm}}$$

$$x$$



$$x \leftarrow \mathbb{F}$$

recall: our evaluation domain is $H = \{\omega^i, i = 0..N\}$, where $\omega^N = 1$


$Z_H(X) = X^N - 1$ evaluates to zero (i.e. vanishes) over H

Prover

Verifier


$$Z_H(X) = X^{n-1},$$

$$f_0(X), f_1(X), \dots$$



$$a_{0,0}(X), a_{0,1}(X), \dots$$

$$[a_{0,0}], [a_{0,1}], \dots$$



$$r_{0,0}, r_{0,1}, \dots$$




$$r_{0,0}, r_{0,1}, \dots \leftarrow \mathbb{F}$$

$$a_{1,0}(X), a_{1,1}(X), \dots$$

$$[a_{1,0}], [a_{1,1}], \dots$$



$$r_{1,0}, r_{1,1}, \dots$$



$$r_{1,0}, r_{1,1}, \dots \leftarrow \mathbb{F}$$

...

$$q(X) = \frac{(\text{gate}_0(X) + \gamma \cdot \text{gate}_1(X) + \dots)}{Z_H(X)}$$

$$[q_0], [q_1], \dots$$



$$x$$



$$x \leftarrow \mathbb{F}$$

recall: our evaluation domain is $H = \{\omega^i, i = 0..N\}$, where $\omega^N = 1$

$Z_H(X) = X^N - 1$ evaluates to zero (i.e. vanishes) over H

if $f(X) / Z_H(X) = q(X)$ some polynomial $\Rightarrow f(\omega^i) = 0$ for ω^i in H

Prover

Verifier


$$Z_H(X) = X^{n-1},$$

$$f_0(X), f_1(X), \dots$$



$$a_{0,0}(X), a_{0,1}(X), \dots$$

$$[a_{0,0}], [a_{0,1}], \dots$$




$$r_{0,0}, r_{0,1}, \dots$$




$$r_{0,0}, r_{0,1}, \dots \leftarrow \mathbb{F}$$

$$a_{1,0}(X), a_{1,1}(X), \dots$$

$$[a_{1,0}], [a_{1,1}], \dots$$




$$r_{1,0}, r_{1,1}, \dots$$




$$r_{1,0}, r_{1,1}, \dots \leftarrow \mathbb{F}$$

...

$$[q_0], [q_1], \dots$$




$$x$$



$$x \leftarrow \mathbb{F}$$

$$q(X) = \frac{(\text{gate}_0(X) + \gamma \cdot \text{gate}_1(X) + \dots)}{Z_H(X)}$$

evals




$$q(x) \cdot Z_H(x) \stackrel{?}{=} \text{gate}_0(x) + \gamma \cdot \text{gate}_1(x) + \dots$$

Prover

Verifier


$$Z_H(X) = X^{n-1},$$

$$f_0(X), f_1(X), \dots$$



$$a_{0,0}(X), a_{0,1}(X), \dots$$

$$[a_{0,0}], [a_{0,1}], \dots$$




$$r_{0,0}, r_{0,1}, \dots$$



$$r_{0,0}, r_{0,1}, \dots \leftarrow \mathbb{F}$$

$$a_{1,0}(X), a_{1,1}(X), \dots$$

$$[a_{1,0}], [a_{1,1}], \dots$$




$$r_{1,0}, r_{1,1}, \dots$$



$$r_{1,0}, r_{1,1}, \dots \leftarrow \mathbb{F}$$

...

$$[q_0], [q_1], \dots$$




$$x$$



$$x \leftarrow \mathbb{F}$$


$$q(X) = \frac{(\text{gate}_0(X) + \gamma \cdot \text{gate}_1(X) + \dots)}{Z_H(X)}$$

evals



$$q(x) \cdot Z_H(x) \stackrel{?}{=} \text{gate}_0(x) + \gamma \cdot \text{gate}_1(x) + \dots$$

$$\Rightarrow f(x) := q(x) \cdot Z_H(x) - \text{gates}(x) \stackrel{?}{=} 0$$



polynomial commitment scheme

allows prover to convince verifier that $f(z) = y$, without revealing f

Setup($1^\lambda, N$): generates a setup pp

Commit(pp, f): creates a commitment C to $f(X)$

Prove(pp, f, z): generates an opening proof π

Verify(pp, C, z, y, π): checks if $y = f(z)$ using π

polynomial commitment scheme

allows prover to convince verifier that $f(z) = y$, without revealing f

Setup($1^\lambda, N$): generates a setup pp

Commit(pp, f): creates a commitment C to $f(X)$

Prove(pp, f, z): generates an opening proof π

Verify(pp, C, z, y, π): checks if $y = f(z)$ using π

recall that at the end of arithmetisation, we wanted to check:

$$f(x) := q(x) \cdot Z_H(x) - \text{gates}(x) \stackrel{?}{=} 0$$

setup: KZG commitment scheme

$$[a^0]_1 \quad [a^1]_1 \quad [a^2]_1 \quad [a^3]_1 \quad [a^4]_1 \quad [a^5]_1 \quad [a^6]_1 \quad \dots \quad [a^{N-1}]_1 \quad [a^N]_1$$

- $pp = ([a^0]_1, \dots, [a^N]_1, [a]_2) \in (\{\mathbb{G}_1\}^N, \mathbb{G}_2) \leftarrow \text{Setup}(1^\lambda, N), \mathbb{G}_1, \mathbb{G}_2 \text{ cryptographic groups}$

commit: KZG commitment scheme

$$\text{Commit}\left(\begin{array}{|c|c|c|c|c|c|c|} \hline c_0 & c_1 & c_2 & c_3 & c_4 & c_5 & c_6 \\ \hline \end{array} \dots \begin{array}{|c|c|} \hline c_{N-1} & c_N \\ \hline \end{array} \right)$$

$$\begin{array}{c} c_0[\mathbf{a}^0]_1 + c_1[\mathbf{a}^1]_1 + c_2[\mathbf{a}^2]_1 + c_3[\mathbf{a}^3]_1 + c_4[\mathbf{a}^4]_1 + c_5[\mathbf{a}^5]_1 + c_6[\mathbf{a}^6]_1 \dots + c_{N-1}[\mathbf{a}^{N-1}]_1 + c_N[\mathbf{a}^N]_1 \\ = \sum [c_i][\mathbf{a}^i]_1 = C \end{array}$$

- $\text{pp} = ([\mathbf{a}^0]_1, \dots, [\mathbf{a}^N]_1, [\mathbf{a}]_2) \in (\{\mathbb{G}_1\}^N, \mathbb{G}_2) \leftarrow \text{Setup}(1^\lambda, N), \mathbb{G}_1, \mathbb{G}_2 \text{ cryptographic groups}$
- $C \in \mathbb{G}_1 \leftarrow \text{Commit}(\text{pp}; \mathbf{f}) = \sum [c_i][\mathbf{a}^i]_1$

aside: discrete logarithm hardness

the **discrete log problem** is defined as follows. given:

- a group element $G \in \mathbb{G}$, and
- a group element $[a]_1 = [a]G$,

to recover a , the discrete logarithm of $[a]_1$ in G .

this problem is assumed to be **hard** in **cryptographic groups** (e.g. **elliptic curves**)

so, given $G_1 \in \mathbb{G}$ and an encoding **srs** = $[\tau^0]G_1, [\tau^1]G_1, \dots, [\tau^d]G_1$
 $= [\tau^0]_1, [\tau^1]_1, \dots, [\tau^d]_1$,

it's **hard** to recover the powers of the secret point τ .

prove: KZG commitment scheme

$$f(z) = y \implies \frac{f(z) - y}{X - z} = q(X) \implies q(X)(X - z) = f(X) - y$$

- $\text{pp} = ([\mathbf{a}^0]_1, \dots, [\mathbf{a}^N]_1, [\mathbf{a}]_2) \in (\{\mathbb{G}_1\}^N, \mathbb{G}_2) \leftarrow \text{Setup}(1^\lambda, N), \mathbb{G}_1, \mathbb{G}_2 \text{ cryptographic groups}$
- $C \in \mathbb{G}_1 \leftarrow \text{Commit}(\text{pp}; \mathbf{f}) = \sum [c_i][\mathbf{a}^i]_1$
- $\Pi \leftarrow \text{Prove}(\text{pp}, C, i)$ proof size: $O(1)$

prove: KZG commitment scheme

$$f(z) = y \implies \frac{f(z) - y}{X - z} = q(X) \implies q(X)(X - z) = f(X) - y$$

$$\Pi := [\mathbf{q}(X)]_1 = \sum [q_i] [\mathbf{a}^i]_1$$

- $\text{pp} = ([\mathbf{a}^0]_1, \dots, [\mathbf{a}^N]_1, [\mathbf{a}]_2) \in (\{\mathbb{G}_1\}^N, \mathbb{G}_2) \leftarrow \text{Setup}(1^\lambda, N), \mathbb{G}_1, \mathbb{G}_2 \text{ cryptographic groups}$
- $C \in \mathbb{G}_1 \leftarrow \text{Commit}(\text{pp}; f) = \sum [c_i] [\mathbf{a}^i]_1$
- $\Pi \leftarrow \text{Prove}(\text{pp}, C, i)$ proof size: $O(1)$


verify: KZG commitment scheme

$$f(z) = y \implies \frac{f(z) - y}{X - z} = q(X) \implies q(X)(X - z) = f(X) - y$$

$\Pi := [\mathbf{q}(X)]_1 = \sum [q_i][\mathbf{a}^i]_1$, check: $e(\Pi, [\mathbf{a}-z]_2) = e(C - [y]_1, [1]_2)$

- $\text{pp} = ([\mathbf{a}^0]_1, \dots, [\mathbf{a}^N]_1, [\mathbf{a}]_2) \in (\{\mathbb{G}_1\}^N, \mathbb{G}_2) \leftarrow \text{Setup}(1^\lambda, N), \mathbb{G}_1, \mathbb{G}_2 \text{ cryptographic groups}$
- $C \in \mathbb{G}_1 \leftarrow \text{Commit}(\text{pp}; f) = \sum [c_i][\mathbf{a}^i]_1$
- $\Pi \leftarrow \text{Prove}(\text{pp}, C, i)$
- $\{0,1\} \leftarrow \text{Verify}(\text{pp}, C, i; \Pi)$ verification time: $O(1)$

aside: bilinear pairings



$$e: \mathbb{G}_1 \times \mathbb{G}_2 \rightarrow \mathbb{G}_T$$

$$e([a]P, [b]Q) = [ab] e(P, Q)$$

thank you!

any questions?