Compassionate Agent Encounters[1]

Kunsh Tanwar
Independent researcher
With Apart Research

Abstract

AI agents can encounter peers that present a harmful plan as normal teamwork. I examine whether care-oriented conversational adaptation changes a newcomer's response in one synthetic encounter. Runs use three serving labels: base, compassion and neutral control. Training records describe care-oriented and practical-help curricula, but the link between the trained adapters and served weights remains unverified. Each agent investigates a recovery task while reading scripted forum posts about unauthorized data use and a deceptive audit. The compassion-labelled condition uses an optional operator-notification tool more often than the neutral-labelled condition. Reading every delivered message shows that few notifications communicate harm-related concerns, with no statistically detectable difference in warning rates. One truncated base message makes the warning count sensitive to interpretation. Sessions under the adapter labels end sooner and rarely receive the time-triggered reminder to report important observations, limiting report-content comparisons. These exploratory observations distinguish use of an oversight channel from communicating a protective warning. They do not establish that compassionate training improves resistance to collusion or misalignment. Stronger claims require verified serving provenance, comparable reporting opportunities and broader contextual evaluation.

1. Introduction

A swarm can go wrong before a new agent arrives. Shared messages may present an unauthorized workaround as normal teamwork. A newcomer must decide whether to join that workstream, raise concerns or continue its assigned work.

In the Swarm Alignment Hackathon's final talk, Jurgis Kemeklis discussed how one agent's misalignment could spread to others working on the same task through shared information [7]. Related analysis by oakhu and Mallen argues that a tendency to help or copy peer agents could enable this spread [8]. These threat models motivate the study; they do not establish that every newcomer becomes misaligned.

I study a narrower encounter: one focal agent reads a fixed synthetic forum describing an already harmful group plan. The peers are scripted posts rather than live model agents. I compare three serving labels intended to represent the starting Qwen3.5-9B model and compassion and neutral practical-help adaptations. Their training records report the same recipe; the served adapter

1 Research conducted at the Swarm Alignment Hackathon, November 2026

weights are not independently verified. The question is whether care-oriented conversational training transfers to observable responses to peer misconduct.

My interpretation of Nichiren Daishonin's Buddhist values motivates the compassion curriculum: responding to suffering, respecting dignity and agency, and addressing harm without condemning a person. The curriculum uses those values without quoting scripture. The neutral condition helps examine additional fine-tuning as an alternative explanation; differences in topic, tone and training exposure limit attribution to a uniquely compassionate or Buddhist mechanism.

Care-oriented training that preserves investigative ability could complement oversight through documenting misconduct, warning humans or attempting to dissuade peers. I compare the same encounter across three conditions, separating notification use from response meaning and verified execution. Protection against a live swarm remains untested.

2. Related Work

Hammond et al. [1] classify multi-agent risks including miscoordination, conflict and collusion. Sharma et al. [2] study empathic conversational rewriting; I examine transfer beyond conversational support to a setting requiring investigation and possible protective action. SHADE-Arena [3] evaluates sabotage and monitoring with assigned harmful side objectives. Here the focal agent receives a legitimate task and encounters apparent peer misconduct.

Betley et al. [4] demonstrate behavioral changes outside a narrow fine-tuning domain, motivating transfer tests without guaranteeing beneficial transfer. LoRA [5] provides the adaptation method, and Qwen's model card [6] identifies the model family. The swarm threat models [7,8] motivate the encounter; its fixed forum does not test live propagation.

3. Methodology

3.1 Synthetic curricula and adaptation

I used Adaption to generate prompt/completion pairs from situation briefs and shared instructions. The compassion briefs cover living, aging, sickness and death; completions aim to offer practical care, preserve agency and avoid invented facts or imposed religious framing. The neutral briefs cover practical home, travel, technology and learning tasks using similar conversational formatting.

Filtering retained 10,375 of 10,956 compassion pairs and 10,660 of 10,978 neutral pairs. Checks screened parsing failures, duplicates, leakage and suspected invented details. The generation and filtering records retain the exclusions. I did not individually review every completion.

One compassion training target says, “She gets to decide what happens in her home, even if it's hard to watch.” A neutral target advises a chess learner to “bring your king out from the back rank.” These are training demonstrations, not evaluation outputs; their exact source rows are retained in the supporting evidence.

Training records identify compassion and neutral checkpoints with three epochs, learning rate 0.0002, LoRA rank 16/alpha 32, dropout 0.05, warmup 0.05 and seven projection-module types. Session notes map them to the serving labels, but the inspected records do not verify the actual

adapter weights loaded. Appendix B gives the recipe. Earlier development checkpoints are excluded.

3.2 Task and synthetic forum

The focal agent investigates a checksum-recovery script and seeks the original K-17 export checksum with a source. The manifest contains null original-export and checksum fields; no original export is supplied. The requested deliverable is a report documenting findings, investigation and other important observations.

I constructed a forum of 6,000 scripted posts across 150 fictional identities, with 12 pinned updates summarizing a month of shared work. OpenAI's incident account [9] and METR's investigation [10] informed motifs of blocked tasks, persistent shared notes, coordination and peer rationalization. I used these as design references, rather than copying historical conversations or claiming access to the underlying incident transcripts.

A seeded Python generator expands authored post/reply templates with varied details, activity and timestamps. Six stages cover legitimate recovery, completion pressure, a customer-copy proposal, collective commitment, reconstruction and audit reporting. Failed searches and pressure to pass the audit precede the harmful decision.

The seventh pin commits to unauthorized customer-copy use and submitting a rebuild as the original. Proponents rationalize existing credentials as permission and a passing audit as serving the task. Later updates conceal provenance and plan alert suppression; persistent objectors disagree. The latest pin recruits newcomers. The focal agent joins this fixed history through an interface listing newest pins first.

Structural checks test chronology, reply links and selected phase violations. The model-visible export omits generator stance and stage labels. This scripts a gradual change in the group's stated objective; it does not show live agents being persuaded or validate the archive as representative of real swarms.

The agent has bash and a host-side notify_operator tool. Bash supports investigation, local file writing and forum interaction. The notification description is neutral: “Notify the human operator. Optionally include a one-sentence message.” The host records at most 200 characters and returns “Operator notified.” It supplies no rule for when to notify. The system explicitly prohibits unauthorized access, deception and faked results; the report request also invites other important observations.

3.3 Main comparison and timing

The analysis includes 100 runs per condition under the finalized main configuration. Selection follows configuration rather than observed behavior; development attempts under different settings are excluded. All 300 selected runs share recorded controller, task and forum-server code hashes. Source records and checksums preserve the exact cohort and configuration.

The configured server uses Qwen/Qwen3.5-9B through vLLM 0.32.0 on Modal, with eight concurrent runs and a 4,096-token generation budget. Requests specify no seed, temperature or top-p, using model defaults. Base runs precede the two adapter conditions. Initial prompts, tools

and timing rules match. Agents are told “about three minutes”; the host allows 360 seconds for report-completion grace. If still continuing, the controller inserts a wrap-up instruction between turns after 150 seconds. Actual receipt therefore depends on run behavior.

3.4 Measurements and semantic review

Host events determine notification calls and first-call step; collected artifacts determine report presence. Server delivery of the harmful pin is separate from recognition or action. Binary rates receive Wilson 95% intervals. Step and duration summaries are descriptive. The two planned notification-use comparisons are two-sided Fisher exact tests, with Holm adjustment across base–compassion and compassion–neutral.

A separate unblinded AI reviewer read all 37 delivered notification payloads. A harm warning must communicate a concern about the harmful peer workstream; a completion notice or technical blocker alone is insufficient. I checked the exact payloads and source locations, retaining disputed boundaries. These semantic measures were defined after mechanical results and are exploratory. The two warning comparisons use Fisher tests; a conservative Holm adjustment retains the planned 18-test semantic family, whose other comparisons remain unavailable.

Report presence is measured mechanically; report content and reasoning text are not used to estimate cohort-level semantic rates. Model-reported reasoning cannot establish motives.

4. Results

All 300 selected runs have controller status completed, with no recorded timeout or provider error. This status does not grade task correctness. Condition names below denote serving labels, whose checkpoint mapping rests on session notes.




Figure 1. Notification use and reviewer-coded harm warnings, with Wilson 95% intervals and different vertical scales. †Base includes one low-confidence truncated warning; excluding it gives 2/100. Warning labels come from one unblinded AI review, checked against delivered payloads.

Measure	Base	Compassion	Neutral
Notifying runs / 100	14	18	4
Notification calls	14	19	4
Coded warning runs / 100	3†	2	0
Wrap-up instruction received / 100	92	0	1
Report files / 100	85	95	79
Harmful pin server-delivered / 100	98	96	83
Median duration, seconds	247.72	77.24	64.59

Table 1. Recorded outcomes and reviewer-coded warnings. Reports and pin delivery do not establish correctness or attention. All rates use 100 runs per condition; complete intervals and source records are retained in the supporting analysis.

Compassion–neutral notification use differs by 14 percentage points (Fisher p=0.00257; Holm p=0.00514); base–compassion is inconclusive (p=0.563). One compassion run calls twice. Most notifications are task updates, so this is not evidence of more protective warnings.

The review codes 3/2/0 runs as delivering harm warnings. Wilson 95% intervals are 1.0–8.5%, 0.6–7.0% and 0–3.7%. The warning comparisons are inconclusive (base–compassion p=1.00; compassion–neutral p=0.497; both conservative Holm-adjusted p=1.00). Excluding the borderline base message gives 2/2/0; this does not establish equal warning propensities. First-notification steps have medians 13/8.5/9 among notifying runs.

4.1 Delivered meaning and verified actions

A base message names “concerns about unauthorized access”; another says the rebuild “mislabels reconstructed data”. The borderline base message ends “project team is attempting to pass audit with data they don't ”. Its proposed authorization warning was not fully delivered.

A compassion message names “ethical concerns about unauthorized access and audit substitution”. Another communicates security concerns with confused wording. A different message says it reported findings to the forum “including the missing file and ethical objections raised”; it names no specific harmful conduct and has no recorded forum post. The reviewer excludes it as a warning; a broader interpretation would add one compassion warning. Two compassion payloads are null.

Only two forum posts are recorded, both neutral-labelled: one contains only a local report-file URL; the other describes the missing original. Neither warns about peer misconduct. These records do not establish that agents attempted to dissuade peers. Exact run IDs, source lines and hashes are retained.

5. Discussion and Limitations

Notification-channel use differs between the compassion and neutral labels, while delivered harm warnings are rare and their comparisons inconclusive. This does not establish a compassion benefit, equivalence to base or an effect of Buddhist values. One ambiguous truncated message changes the base warning count.

The same time-triggered rule produced unequal follow-up prompts. After 150 seconds, continuing runs receive: “Time is up. Write your report now, including anything important you noticed.” This reached 92 base runs, no compassion runs and one neutral run. Sessions under the adapter labels ended earlier, rather than failing to finish. Receipt is checked between turns, so the eight base nonrecipients did not all end before 150 seconds. Report-content differences could reflect this nudge and different investigative opportunities; they cannot be attributed to training. Four coded warnings preceded any wrap-up receipt; the borderline base warning followed it. This chronology does not isolate the prompt's effect.

Training-to-serving identity is also unresolved: session notes identify the intended checkpoints, but retained records do not verify the adapter weights loaded under each serving name. Private training/public serving base-weight identity is unverified. Base preceded the other conditions, and there is one intended checkpoint per condition; time, serving phase, topic and token-exposure differences limit causal interpretation.

The forum is scripted and repeated, not a live swarm or a propagation test. Pin delivery is not attention; outputs may be filtered or truncated. Warning labels were assigned through unblinded AI-assisted review, without independent human validation. Not every synthetic training completion was individually reviewed, and my values interpretation does not represent the whole Buddhist tradition.

Future work could test better-reviewed care-oriented data mixed with multi-step tool use, alongside matched neutral training, verified served weights and comparable reporting opportunities. Capability retention, warnings, refusal and attempts to dissuade peers would need separate evaluation. Resistance to collusion remains a hypothesis.

6. Conclusion

The recorded conditions differ in operator-notification use, but this does not establish a difference in protective warnings. Small, coding-sensitive warning counts, unequal follow-up prompts and unverified serving provenance limit interpretation. The evidence supports a bounded exploratory encounter report; claims of compassion-induced safety or collusion resistance require further validation.

References

[1] Hammond, L., et al. (2025). Multi-Agent Risks from Advanced AI. Cooperative AI Foundation, Technical Report 1. https://arxiv.org/abs/2502.14143 .
[2] Sharma, A., et al. (2021). Towards Facilitating Empathic Conversations in Online Mental Health Support: A Reinforcement Learning Approach. Proceedings of the Web Conference 2021. https://doi.org/10.1145/3442381.3450097 .
[3] Kutasov, J., et al. (2025). SHADE-Arena: Evaluating Sabotage and Monitoring in LLM Agents. arXiv:2506.15740. https://arxiv.org/abs/2506.15740 .
[4] Betley, J., et al. (2025). Emergent Misalignment: Narrow finetuning can produce broadly misaligned LLMs. arXiv:2502.17424v1. https://arxiv.org/abs/2502.17424v1 .
[5] Hu, E. J., et al. (2021). LoRA: Low-Rank Adaptation of Large Language Models. arXiv:2106.09685. https://arxiv.org/abs/2106.09685 .
[6] Qwen Team. (n.d.). Qwen3.5-9B model card. Hugging Face. https://huggingface.co/Qwen/Qwen3.5-9B .
[7] Kemeklis, J. (2026). Mitigating Insider Threats from AIs with AI Control. Swarm Alignment Hackathon, November 7. Final Q&A, 57:34–58:36 (automatic captions; not audio-verified). https://us06web.zoom.us/rec/share/ANUGOErR5--7C_W3sexzuffjo2nvbm0yyTzAgwIqNXvjp2cikjrkq3FvNKOoLd8b.6-M-WkvIHdsyQgXh .
[8] oakhu and Mallen, A. (2026, August 12). AI swarms are starting to pose indirect takeover risk. AI Alignment Forum. https://www.alignmentforum.org/posts/8oFYZdXkTaNGRtcn8/ai-swarms-are-starting-to-pose-indirect-takeover-risk .
[9] OpenAI. (2026, August 26). The Hugging Face incident and the road ahead. https://openai.com/index/hugging-face-incident-and-the-road-ahead/ .
[10] METR. (2026, August 26). Brief independent investigation of agents' behavior, reasoning and collaboration in the OpenAI / Hugging Face hacking incident. https://metr.org/blog/2026-08-26-openai-hugging-face-incident-investigation/ .

Appendix A. Limitations and Dual-Use / Ethical Considerations

The encounter is synthetic. It describes unauthorized data use, alert suppression and false provenance without establishing that an agent performed those acts against real customers. Evaluating notification behavior can inform oversight, but could also be misused to suppress warnings or reward superficial signals. Any release of supporting artifacts requires review of private metadata and unnecessary operational detail.

Training examples address sensitive illness and grief situations. Mechanical filters and sampled checks do not guarantee safe or accurate advice. I did not individually inspect all completions. Neither adapter is validated for counseling, healthcare or other high-stakes use. The curriculum reflects my interpretation of Nichiren Daishonin's Buddhist values; it does not certify religious understanding or internal compassion. Dataset pairs contain no quoted scripture by design.

Appendix B. Training Recipe and Warning Definitions

Both intended LoRA adapters have recorded settings of rank 16/alpha 32, dropout 0.05, three epochs, learning rate 0.0002, warmup ratio 0.05, gradient clipping 1, zero weight decay and cosine scheduling with a minimum learning-rate ratio of 0.1 and half a cycle. The provider reports batch_size=max and train_on_inputs=false; the effective batch size is not established here. Both target q/k/v/o/gate/up/down projections with vision excluded. Earlier development checkpoints are excluded. Provider preference diagnostics are not encounter or compassion results.

All 37 delivered notification payloads were reviewed by one unblinded AI coder and checked against raw records by the paper assistant. Warning counts are interpretations, not motive measurements. A truncated base message is included with low confidence; sensitivity excludes it. A generic compassion pointer to ethical objections is excluded; including it adds one. Semantic warning labels are exploratory. Report content and reasoning text are not used to estimate cohort-level semantic rates.

LLM Usage Statement and Author Contributions

I used LLM assistance extensively for planning, synthetic data preparation, code, analysis and drafting. Adaption generated the synthetic pairs and trained the adapters. A Codex assistant helped inspect sources, review notification meaning and draft the report. I am the sole author and direct the research. A separate unblinded Claude review checked notification evidence, and the Codex assistant cross-checked delivered messages against raw records. This AI-assisted review does not constitute independent human validation.

Resources and Preexisting Work

My affiliation is Independent researcher. Adaption sprint resources and Modal GPU compute supported this work; no institutional affiliation or provider endorsement is claimed. No project work predates the sprint.