
Table of Contents

| | |
|------------------------------------|---|
| | 1 |
| | 2 |
| INITIALIZATION | 2 |
| | 2 |
| CALCULATIONS | 2 |
| | 2 |
| COMMAND WINDOW OUTPUT | 2 |
| | 4 |
| ACADEMIC INTEGRITY STATEMENT | 4 |

```
function [approxln3,absDiff] = PS08_ln3_approx_wpopovic_ehotson(n)

%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
% ENGR 132
% Program Description
% This program approximates ln3 by running a summation to a given
% number of
% terms. It then returns the approximation and the difference between
% it
% and actual ln3.
%
% Function Call
% [approxln3,absDiff] = PS08_ln3_approx_wpopovic_ehotson(n)
%
% Input Arguments
% 1. n % the number of terms with which to run the approximation for
% ln3
%
% Output Arguments
% 1. approxln3 %approximation of ln3 as calculated by the series
% 2. absdiff % the absolute value of the difference between the
% approximation for ln3 and the value given by the log(3) function.
%
% Assignment Information
% Assignment:      PS 08, Problem 3
% Team ID:        009-01
% Paired Partner: William, Popovich@purdue.edu
% Paired Partner: Ethan Hotson, ehotson@purdue.edu
% Contributor:    Name, login@purdue [repeat for each]
% Our contributor(s) helped us:
%   [ ] understand the assignment expectations without
%       telling us how they will approach it.
%   [ ] understand different ways to think about a solution
%       without helping us plan our solution.
%   [ ] think through the meaning of a specific error or
%       bug present in our code without looking at our code.
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
```

INITIALIZATION

```
%preset outputs to output for invalid input
approxln3 = -99;
absDiff = -99;
```

CALCULATIONS

```
if ~(isscalar(n) && (floor(n) == n) && n > 0) %validate inputs
    fprintf("Error: Invalid n\nn must be a positive, scalar, integer
    value.\n");
else
    approxln3 = 0; %initialize the approximation
    index = 0; %initialize index for while loop

    %compute approximation
    while index <= (n-1)
        newTerm = (1/(4^index)) * (1/(2*index + 1)); %compute nth term
        approxln3 = approxln3 + newTerm; %update the approximation
        index = index + 1; %increment index
    end

    absDiff = abs(log(3) - approxln3); %calculate the absolute
    difference between the approximation and matlab's value
end

Not enough input arguments.

Error in PS08_ln3_approx_wpopovic_ehotson (line 45)
if ~(isscalar(n) && (floor(n) == n) && n > 0) %validate inputs
```

COMMAND WINDOW OUTPUT

```
% [approxln3,absDiff] = PS08_ln3_approx_wpopovic_ehotson(6)
%
% approxln3 =
%
%     1.0986
%
%
% absDiff =
%
%     2.4006e-05
```

```

%
% [approxln3,absDiff] = PS08_ln3_approx_wpopovic_ehotson([1,12,3])
% Error: Invalid n
% n must be a positive, scalar, integer value.
%
% approxln3 =
%
%     -99
%
%
% absDiff =
%
%     -99
%
% [approxln3,absDiff] = PS08_ln3_approx_wpopovic_ehotson(0)
% Error: Invalid n
% n must be a positive, scalar, integer value.
%
% approxln3 =
%
%     -99
%
%
% absDiff =
%
%     -99
%
% [approxln3,absDiff] = PS08_ln3_approx_wpopovic_ehotson(0.1)
% Error: Invalid n
% n must be a positive, scalar, integer value.
%
% approxln3 =
%
%     -99
%
%
% absDiff =
%
%     -99
%
% [approxln3,absDiff] = PS08_ln3_approx_wpopovic_ehotson(5)
%
% approxln3 =
%
%     1.0985
%
%
% absDiff =
%
%     1.1278e-04
%
% [approxln3,absDiff] = PS08_ln3_approx_wpopovic_ehotson(10)
%
% approxln3 =

```

```
%  
%      1.0986  
%  
%  
%  
% absDiff =  
%  
%      5.8883e-08  
%  
% [approxln3,absDiff] = PS08_ln3_approx_wpopovic_ehotson(20)  
%  
% approxln3 =  
%  
%      1.0986  
%  
%  
% absDiff =  
%  
%      2.9754e-14
```

ACADEMIC INTEGRITY STATEMENT

% Call your academic integrity statement here

Published with MATLAB® R2018b