


MANIPULATION OF UNCOOPERATIVE OBJECTS IN
ZERO-GRAVITY WITH MODULAR
SELF-RECONFIGURABLE ROBOT

by

Thibault L.



Submitted for the degree of
Doctor of Philosophy

DEPARTMENT OF COMPUTER SCIENCE
SCHOOL OF MATHEMATICAL AND COMPUTER SCIENCES
HERIOT-WATT UNIVERSITY

May 2020

The copyright in this thesis is owned by the author. Any quotation from the report or use of any of the information contained in it must acknowledge this report as the source of the quotation or information.

Abstract

PhD theme definition: mass distribution change as a control mechanism using a robot that changes its shape i.e. a self-reconfigurable robot in the specific context of attitude and rotational motion maintenance.

Acknowledgements

write ...

Contents

1	Introduction	1
1.1	Section	1
1.1.1	Subsection	1
1.1.1.1	Subsubsection	1
2	Background	2
2.1	Section	2
2.1.1	Subsection	3
2.1.1.1	Subsubsection	3
3	Stability study	4
3.1	System modelling	4
3.2	Hamiltonian Lagrange formulation	4
3.2.1	Subsection	4
3.2.1.1	Subsubsection	4
4	Design	6
4.1	Section	6
4.1.1	Subsection	7
4.1.1.1	Subsubsection	7
5	Conclusion and Future Work	8
A	Foo	9
	Bibliography	10

List of Tables

2.1	Table Caption	3
3.1	Table Caption	5
4.1	Table Caption	7

List of Figures

2.1	Figure Caption.	2
3.1	Figure Caption.	5
4.1	Figure Caption.	6

Chapter 1

Introduction

Write..

1.1 Section

[2]

1.1.1 Subsection

1.1.1.1 Subsubsection

Chapter 2

Background

Write.. Glasgow Haskell Compiler (GHC).

Write..GHC.

2.1 Section

Write.. Processing Element (PE).

Write.. PEs.




Figure 2.1: Figure Caption.

2.1.1 Subsection

Case	Method#1	Method#2	Method#3
1	50	837	970
2	47	877	230
3	31	25	415
4	35	144	2356
5	45	300	556

Table 2.1: Table Caption

2.1.1.1 Subsubsection

Chapter 3

Stability study

define the stability of the rotational motion of the object???

System definition and model: The system is composed of an undeformable rotating object and a modular robot made out of identical spherical modules. The robot moves and deploys itself at the surface of the object by maintaining contact at all time. As the rotational motion is the only focus of this study, the system is considered to be isolated. The best way to model is to use

Write..GHC.

3.1 System modelling

Write.. PE.

Write.. PEs.

3.2 Hamiltonian Lagrange formulation

Write.. PE.

Write.. PEs.

[3, 1]

3.2.1 Subsection

3.2.1.1 Subsubsection




Figure 3.1: Figure Caption.

Case	Method#1	Method#2	Method#3
1	50	837	970
2	47	877	230
3	31	25	415
4	35	144	2356
5	45	300	556

Table 3.1: Table Caption

Chapter 4

Design

Write..

4.1 Section

According to [2] ...




Figure 4.1: Figure Caption.

4.1.1 Subsection

Audio Name	Sum of Extracted Bits						
Police	5	-1	5	5	-7	-5	3
Midnight	7	-3	5	3	-1	-3	5
News	9	-3	7	9	-5	-1	9

Table 4.1: Table Caption

4.1.1.1 Subsubsection

Chapter 5

Conclusion and Future Work

Appendix A

Foo

Bibliography

- [1] T. Harris, S. Marlow, and S. P. Jones. Haskell on a Shared-Memory Multiprocessor. In *Proceedings of the 2005 ACM SIGPLAN workshop on Haskell*, Haskell '05, pages 49–61, New York, NY, USA, 2005. ACM.
- [2] J. D. Jones, S. Marlow, and S. Singh. Parallel performance tuning for Haskell. In *Proceedings of the 2nd ACM SIGPLAN symposium on Haskell*, Haskell '09, pages 81–92, New York, NY, USA, 2009. ACM.
- [3] P. W. Trinder, K. Hammond, J. S. Mattson Jr., A. S. Partridge, and S. L. Peyton Jones. GUM: a Portable Parallel Implementation of Haskell. In *PLDI '96, Philadelphia, USA*, pages 78–88. ACM Press, 1996.