Tishidi Seshoka (Student No: 2805000306)

Exercise 2

1. Select Count (id) AS Total_employees
From employees;

Total_employees
10

2. Select department,
SUM (salary) AS Total_salary
From employees
Where department = 'IT'
Group by department;

department	Total_salary
IT	220 000

3. Select department,
AVG (salary) AS HR_salary_avg
From employees
Where department = 'HR'
Group by department;

department	HR_salary_avg
HR	49 500

4. Select MIN (salary) AS Lowest_salary,
MAX (salary) AS Highest_salary
From employees;

Lowest_salary	Highest_salary
48 000	62 000

5. Select department,
SUM (salary) AS Total_salary_per_department
From employees
Group by department;

department	Total_salary_per_department
IT	220 000
HR	99 000
Finance	119 000
Marketing	105 000

6. Select city,
Count (id) AS Total_employees_per_city
From ~~'employees'~~ employees
Group by city;

city	Total_employees_per_city
New York	2
Chicago	3
Los Angels	2
San Franscisco	2
Houston	1

7. Select department,
AVG (salary) AS Avg_salary_per_department
From 'employees'
Group by department
~~Order by DESC; Order by salary DE~~
Order by Avg_salary_per_department DESC;

department	Avg_salary_per_department
Finance	59 500
IT	55 000
Marketing	52 500
HR	49 500

8. Select department,
   Sum(salary) AS Total_salary
   From employees
   Group by department
   Having Total_salary > 100 000;

department	Total_salary
IT	220 000
Finance	119 000
Marketing	105 000

9. Select city
   ~~Con~~ Count(id) AS Total_employees
   From employees
   Group by city
   Having Total_employees > 1
   Order by Total_employees DESC;

city	Total employees
Chicago	3
New york	2
Los Angels	2
San Franscisco	2

10. Select department,
AVG (salary) AS Highest_average_salary
From employees
Group by department
Order by Highest_average_salary DESC Limit 1;

department	Highest_average_salary
Finance	59 500