McBidAsk recalc-on-load and daily tick chunking: implementation spec

Repo: ettiennehugo/MultiCharts.Net. **Base:** `origin/main` 33a51bf (merge of PR #76). All line numbers refer to that commit. **Scope:** two fixes in one new PR, kept apart from every other branch (see the coder brief). PriceAction is not touched. **Author:** Grok Bot (spec only, no code). **Status:** draft for Ettienne. Nine API points (P-RC1..P-RC9) need the probe in §8 before the defaults are final.

---

1. Evidence (log 01M6C29N9KQHKWP9Z2V017GD3Q.csv, runs 180c9976 and f625f122, @ES 1-min, chart 2026-08-31 → 2026-09-18)

Observation	Log line(s)	Cause
`OF McBidAsk diag request ... chartType(Regular) from(2026-08-30 17:02) to(2026-11-02 12:19)`	97	The request `To` is `DateTime.Now+1d`, which is 6 weeks past the chart's last bar. `chartType` prints `Regular` even though `CreateFootPrint` was used (§7.1).
`OF T9 session(..) bars(13xx) mcCover(0.0)` and `OF tier McBidAsk->Unavailable reason(missing)` for every session	100–126	The McBidAsk history arrives only after the backtest has passed all bars (see the next row).
B: `RUN-END ... 16:00` comes first, then `history done batches(1) data2Bars(61837) levels(479517)`	85–92	The loader finishes after the last bar, so the levels are never used. Nothing triggers a second pass.
B: 3× `OF tick loader callback exception(System.ApplicationException) message(Array dimensions exceeded supported range.)`	86–88	Each of the Trade/Bid/Ask 1-tick requests covers 2026-08-30 → 2026-11-02 (~45 Globex days of ES ticks), which is more than one .NET array can hold. All tick history is lost.
C (f625f122): **no** callback, exception, `history done` or `stop` lines after RUN-END (the last lines are 128–130)	–	The queued callback lines drain only in `CalcBar`/`StopCalc` (`_VolumeProfileFuturesBase.Strategy.CS` 138–145, 627–639). A finished historical chart gets no new bar, so the lines sit in the queue until the study is removed. The log cannot show whether run C's callbacks have fired.
`OF MaxBars cap 5000 hit at bar 5051`	107	See §7.4.

2. MC .NET API facts used (with sources)

Fact	Source
`IStudy.ExecControl` is `ICalculationControl` and "allows the user to interrupt the calculation, recalculate the study, or force the study to calculate over a given period of time".	PLStudiesProxy metadata (`specs/mc-portfolio-api.txt` l.176); PG v1.0 §4.1.2 (l.690)
`ExecControl.Recalculate()` restarts the study from `StartCalc` and then runs `CalcBar` over all bars. Statements after it in the same method do not run, so it unwinds the stack. Calling it unconditionally loops forever, so it needs a persistent guard.	PG VolumeProfile section, txt l.3616/3700 (`this.ExecControl.Recalculate()` from the `EChanged` handler); MC wiki *RecalcLastBarAfter / Recalculate*; forum (recalc guard via persistent vars)
`StartCalc` "can be called repeatedly during the object's life cycle". `Create` runs once. The object instance is reused, so **plain C# fields survive a Recalculate** unless `StartCalc`/`StopCalc` reset them.	PG §4.1.2; MC wiki *How Indicators and Signals are Calculated*
MC uses internal exceptions for its own control flow (MaxBarsBack restart). Foreign exceptions must not be caught.	MC wiki (same page)
`ExecControl.RecalcLastBarAfter(TimeSpan)` makes MC call `protected override void OnRecalcLastBarAfterEvent()` after the timeout, **even when no ticks arrive**. It does not recalculate by itself.	MC wiki; forum t=43339 (confirmed on indicators; untested on signals, so see P-RC2). The repo already calls it from a signal: `_CustomSignal.Strategy.CS` 2068.
DataLoader callbacks run on a separate thread. `Bars`, `Output`, `trace()` and `engineSink` belong to the calc thread only.	PG §4.7.4; repo comment 712–713
	PG §4.7.4 (l.2979–3045, 3083–3131)

Fact	Source
`InstrumentDataRequest`: `Resolution`, `QuoteField`, `From`/`To` (the PG calls these "outdated, better to use Range"), `DataRequest Range`, `RequestTimeZone TimeZone` (Local/Exchange/GMT), `Subscribe`2RT. `Bars.Request` returns a copy of the chart's request (same feed, session and time zone).	
`DataRequest.CreateFromTo(DateTime, DateTime)` is typed and static.	Already used in `_CheckData.Strategy.CS` 184
`Bars.FullSymbolData` indexes "from the current bar, leftwards with positive indices, and rightwards with negative ones", and `.Count` is the total bar count. The last chart bar is therefore `Time[Current - Count]`.	PG §4.1.2 (l.931–945)
Footprint levels need `Resolution.CreateFootPrint(EResolution, size, CumulativeDeltaChartType, FootPrintChartType, bool)`. Without it, `Data2` stays null.	Forum t=52737 (in code since #74); Data2 delivered 61837 bars in run B

Anything not in this table is unverified and is listed in §8.

3. Code map (origin/main 33a51bf)

`_VolumeProfileFuturesBase.Strategy.CS` - 127–136 `StartCalc`: calls `startOrderFlow()` (no trace possible here, per comment 135). - 138–145 `CalcBar`: `drainFlowQueue()` first, then `updateOrderFlow()`. - 589–609 config and fields: `FlowCfg` (protected `_OrderFlow.FlowConfig`), `McBidAskChartType` (606), `m_mc*` state. - 614–625 `startOrderFlow`: **ends all loads and resets every McBidAsk field, including `m_mcHistoryDone`. It also replaces `m_flow`, which is where the levels live.** A recalc therefore loses everything today. - 627–639 `StopCalc` and 641–648 `stopOrderFlowLoads` (`EndLoadData` on everything). - 650–673 `startFlowLoader`: the three whole-range 1-tick requests (662–664). **This is Fix 2's target.** - 677–698 `startMcLevelLoader`: the CreateFootPrint request; `To = Now+1d` at 689; the request diag line at 696. - 700–739: diag counters, `mcDiag`, the queue (`enqueueFlowMsg`, `queueSink`, `drainFlowQueue`). - 743–794 `onMcLevels`; 796–813 `mcSet` (writes only into `m_flow`); 816–841 `mcJournal`. - 844–865 `onFlowData` (the exception at 864 is the source of the three "Array dimensions" lines); 869–875 `flowTick`. - 877–921 `updateOrderFlow`: starts the loader on the first call (888). The all-or-nothing tick gate is at 910.

`_OrderFlow.Function.CS` (MC-free; the `// <order-flow>` block 30–519 is extracted by `tests/OrderFlowTests`) - 71–90 `FlowConfig` (`MaxBars = 5000` at 80). - 175–187 `Ev` and `Queue` (each stream must be pushed in time order). - 193–361 `FlowEngine`: `AddMcLevels` 226; `takeMc`/`applyMc` 234–270; **`CloseBar` 294–361 pops every queued trade with `Time <= CloseTime` into the current bar (301–319)**. See the backlog bug in §7.3.

`_CmeSessionClock.Function.CS`: `ToEastern` 142–154, `GlobexDate` 164, `GlobexTradingDayEt` 235, `IsGlobexClosedDay` 368, `DefaultHaltStart` 17:00 ET (58). `_CustomSignal.Strategy.CS`: logger `WriteTrace` (one `File.AppendAllText` per line under a lock) 110–125; `trace` ~360; `engineSink` 1831; RUN-END 2131–2139; `RecalcLastBarAfter` for account loading 2068. `tools/sem/stubs/McStubs.cs`: `IExecControl` has only `RecalcLastBarAfter` (57); `DataRequest` has no `CreateFromTo` (36); `InstrumentDataRequest` has no `TimeZone` (37).

4. Fix 1: cache the McBidAsk history and recalculate once on load

4.1 Pure parts (in the `<order-flow>` block, unit-tested)

- **`McLevelCache`** (sealed class):
- `SortedDictionary<DateTime, double[][]>` holding the same `{price, ask, bid}` triple as `AddMcLevels`.
- `string Signature`, `bool HistoryDone`, `DateTime First, Last`, `int Sets`, `long Levels`.
- `Add(DateTime, double[], double[], double[])`, `ReplayInto(FlowEngine)`, `Clear()`.
- `bool Covers(DateTime from, DateTime to)` (HistoryDone && First ≤ from+1 bar && Last ≥ to−1 bar).
- **`McRecalcGate`** (sealed class, no MC types). Fields: `int RecalcCount`, `string RecalcSignature`, `int MissedBeforeDone`, `DateTime MissedFirst/MissedLast`, `int Pass`.
- `NoteMissed(DateTime)`.
- `Decide(bool historyDone, bool cacheCoversMissed, bool autoTrading, bool enabled, int max, string sig)` returns a typed `enum RecalcDecision { Wait, Recalc, SkipNoMissed, SkipGuard, SkipAutoTrading, SkipDisabled }`.
- The guard: `RecalcCount < max` **for this signature**. If a pass 2 request ever re-fired its history, `SkipGuard` stops a second recalc.

4.2 Field lifetime (the core of the fix)

- Add `private readonly McLevelCache m_mcCache = new McLevelCache();` and `private readonly McRecalcGate m_mcGate = new McRecalcGate();` to `_VolumeProfileFuturesBase`, next to 607–609.
- **`startOrderFlow` (614–625) must not clear either of them.**
- `StopCalc` (627–639) does not clear them either. It still ends the loads.
- They are cleared only when the signature no longer matches (§4.3), so a user-driven reload with a different symbol, resolution or chart start starts clean.
- P-RC1 (§8) confirms that the instance survives `Recalculate`.
- If the probe shows MC re-creates the object instead, the fallback is a `static Dictionary<string, McLevelCache>` keyed by signature and process-local. It holds the last 2 signatures at most.

4.3 Flow

1. **First CalcBar, at the point where `startFlowLoader` runs today (888).** Build the signature on the calc thread: `Bars.Info.Name | Bars.Info.DataFeed | res.Type | res.Size | McBidAskChartType | FlowCfg.McBidAsk | firstBarTime`. Compute `lastBarTime = Bars.FullSymbolData.Time[Current - Count]`. - **Hit** when `Signature == sig && m_mcCache.Covers(firstBarTime, lastBarTime)`:
   - Call `m_mcCache.ReplayInto(m_flow)` under `m_flowLock`.
   - Set `m_mcHistoryDone = true`, `m_mcLoaded = Sets`, `m_mcFirst/Last`.
   - **Do not call `startMcLevelLoader`**, except on a live chart (`Environment.IsRealTimeCalc` or `lastBarTime` ≥ Now−1 day), which gets a tail request instead: `Range = DataRequest.CreateFromTo(m_mcCache.Last, Now+1d)`, `Subscribe2RT = true`. It covers RT and the bars since the cache was filled and is logged as `request(tail)`.
   - Log `cache hit` and `recalc pass using cache`.
   - **Miss** (any other case): log `cache miss reason(..)`, then `m_mcCache.Clear(); m_mcCache.Signature = sig`, then issue the normal request (with the `To` clamp of §4.5).
2. **Callback (`onMcLevels` 743–794, `mcSet` 796–813).** `mcSet` writes each set into `m_mcCache` **and** into `m_flow` (under `m_flowLock`, which is already held). When History is completed: `m_mcCache.HistoryDone = true` (next to 790). Only state is set; **no MC call from this thread**.
3. **`mcJournal` (816–841).** When `fp.McMiss == "missing" && !m_mcHistoryDone`, call `m_mcGate.NoteMissed(fp.CloseTime)` to count the pass-1 bars that would have used McBidAsk.
4. **Trigger. This runs on the calc thread only and is factored into `private void mcRecalcCheck(string from)`.** It is called at the end of `CalcBar` (after `updateOrderFlow`) and from `OnRecalcLastBarAfterEvent`. - When `m_mcHistoryDone && m_mcGate.Decide(...) == Recalc`:
   - Log `recalc triggered`, then `drainFlowQueue()`.
   - Set `m_mcGate.RecalcCount++; m_mcGate.RecalcSignature = sig`.
   - **Then `ExecControl.Recalculate();` as the last statement, not inside any `try/catch`** (it unwinds; see §2).
   - `cacheCoversMissed` = `m_mcCache.First ≤ MissedLast && m_mcCache.Last ≥ MissedFirst`.
   - `SkipNoMissed` means the history arrived before any bar needed it, so no recalc is needed.
   - `SkipAutoTrading`: never auto-recalc while `Environment.IsAutoTradingMode`, because orders would be re-evaluated. Log the skip once.
5. **Idle poll.** This is what makes the trigger, and the log drain, work with no new bar. - In `CalcBar`, when `Bars.LastBarOnChart && Bars.Status == EBarState.Close` and either (a) `m_mcStarted && !m_mcHistoryDone`, or (b) the flow queue is non-empty, or (c) a tick chunk is pending (Fix 2):
   - call `ExecControl.RecalcLastBarAfter(TimeSpan.FromMilliseconds(FlowCfg.McIdlePollMs))` once;
   - set `m_idleArmed = true`;
   - log `idle poll armed` once.
   - New override in `_VolumeProfileFuturesBase`:
```
protected override void OnRecalcLastBarAfterEvent()
 {
     base.OnRecalcLastBarAfterEvent();   // keep whatever the base does (_CustomSignal arms it for account loading, 2068)
     drainFlowQueue();
     pumpTickChunks();                   // Fix 2
     if (mcRecalcDecision() == RecalcDecision.Recalc) { mcRecalcNow("idle"); return; }   // mcRecalcNow ends with ExecControl.Recalculate()
     if (!idleWorkPending()) return;
```

```
    if ((DateTime.Now - m_idleSince).TotalSeconds < FlowCfg.McIdleTimeoutSec)
        ExecControl.RecalcLastBarAfter(TimeSpan.FromMilliseconds(FlowCfg.McIdlePollMs));
    else logOnce("OF McBidAsk idle poll timeout ...");
}
```

- `drainFlowQueue` stamps lines through `trace()` with `Bars.Time[0]`. This is legal only if the event runs in calc context (P-RC3).

6. **Fallback if P-RC2/P-RC3 fail** (the event does not fire on a historical signal, or `Bars` is not accessible in it). Add `FlowCfg.McRecalcFromCallback = false`. When it is `true`, the history-completed branch of `onMcLevels` calls `ExecControl.Recalculate()` directly once, guarded by the gate. The precedent is the PG VolumeProfile `EChanged` handler (txt l.3616) and the repo's `_VolumeProfileStatistics.Indicator.CS` 357. - The queued lines then get a direct-write path: snapshot `Bars.Time[0]`, the zone label and `RunId` in each `CalcBar` into volatile fields, and add a protected `_CustomSignal.traceAt(ETraceLevel, DateTime stamp, string msg)` (the logger is private, at 62) that callbacks call with the snapshot. That is still one `File.AppendAllText` per line. Mark these lines with `async(1)`. - Ship this path disabled. The probe decides the default.

4.4 Diag lines (Journal; prefix `OF McBidAsk`, so the `_VolumeProfileBaseLog` parsers keep working)

```
OF McBidAsk cache miss reason(empty|signature|incomplete|coverage) sig(<sig>)
OF McBidAsk cache stored sets(N) levels(L) first(yyyy-MM-dd HH:mm) last(..) sig(<sig>)          (calc
thread, once after historyDone)
OF McBidAsk cache hit sets(N) levels(L) first(..) last(..) pass(P) request(none|tail from(..))
OF McBidAsk recalc triggered from(bar|idle|callback) pass(P) missedBars(M) missedFirst(..)
missedLast(..) recalcCount(1/1)
OF McBidAsk recalc pass using cache pass(P) recalcCount(1)
OF McBidAsk recalc skipped reason(noMissedBars|guard|autoTrading|disabled)                      (once
per pass)
OF McBidAsk idle poll armed ms(1000)   /   OF McBidAsk idle poll timeout sec(900) historyDone(False)
chunksPending(n)
```

`Pass` counts the `StartCalc` calls in the object's lifetime (a field that is never reset). The existing `RUN id(..)` line gets a new id per pass (CS-3, 2014), which is expected.

4.5 Request window clamp (applies to Fix 1 and Fix 2)

- Replace `To = DateTime.Now.AddDays(1)` (663, 689) with `lastBarTime.AddDays(1)`, where `lastBarTime` is as in §4.3.
- Set the range through `req.Range = DataRequest.CreateFromTo(from, to)` (typed, as in `_CheckData` 184), and also set `From`/`To` to the same values until P-RC5 says which field wins.
- On run B this cuts the McBidAsk load from 61837 to about 20k bars (14 Globex days × ~1380).

5. Fix 2: daily, session-aware tick chunks

5.1 Plan (pure, unit-tested; `<order-flow>` block)

- `static List<DayChunk> PlanGlobexDays(DateTime firstGx, DateTime lastGx, Func<DateTime, bool> closedDay, TimeSpan boundaryEt)` returns one `DayChunk { DateTime GlobexDate, FromEt, ToEt }` per Globex date that is not closed.
- Each window is `[GlobexDate−1 day + boundaryEt, GlobexDate + boundaryEt)`, with `boundaryEt = 17:00` (CME daily halt start, `_CmeSessionClock.DefaultHaltStart`), so no tick straddles two chunks. Monday's chunk starts Sunday 17:00 ET.
- `firstGx`/`lastGx` come from `clock().GlobexDate(firstBarTime / lastBarTime)`, and `closedDay` from `clock().IsGlobexClosedDay`.
- **Time zone.** The windows are built in ET and converted to the request zone with a new `public DateTime FromEastern(DateTime et)` on `_CmeSessionClock` (the inverse of `ToEastern` at 142; DST-aware; ambiguous → standard). The request keeps `Bars.Request`'s `TimeZone` (Exchange on 9a: CME, Central), so tick times and bar times share one zone. Confirm `TimeZone` is copied in P-RC6.
- **`TickChunkScheduler`** (pure). Its state per (day, stream): `Pending → InFlight → Done | Failed | Skipped`.
- `Next(DateTime calcPosition)` yields up to `MaxInFlightDays` days (all streams of a day together).
- `Complete(day, stream, ok, count)` records the outcome.

- `ReleasableInOrder()` frees completed days strictly in day order per stream, because `FlowEngine.Queue` needs each stream in time order (177, 190). With `MaxInFlightDays = 1` (the default) the order is guaranteed and the release buffer is a no-op.

5.2 Requests (replace 650–667)

- For each chunk and stream (Trade, plus Bid/Ask when `QuotesExpected`):
- `req = Bars.Request; req.Resolution = new Resolution(EResolution.Tick, 1); req.QuoteField = field; req.Range = DataRequest.CreateFromTo(from, to)` (plus the same `From`/`To`).
- `req.Subscribe2RT = isLastChunk`.
- `state = chunkIndex * 3 + stream`, boxed `int` as today (848).
- **Issued only from the calc thread** by `pumpTickChunks()`, which is called in `updateOrderFlow` (replacing 888) and from `OnRecalcLastBarAfterEvent`. BeginLoadData is never called from a callback; that is unverified, so it is not used.
- **Late days.** Under `FlowCfg.TickChunkLate == Skip` (the default), a day whose window ends before the last closed bar at issue time is marked `Skipped reason(late)` and not requested, because its ticks could no longer be used. The last chunk, which carries RT, is always requested.
- **Bounded wait mode** (`FlowCfg.TickChunkWaitMs > 0`; default 0 = off). This mode makes the tick tier usable in historical backtests. At the first bar of each Globex day, `CalcBar` waits up to `TickChunkWaitMs` for that day's chunks with `Thread.Sleep(50)` polling of a volatile flag. Late days are then not skipped. P-RC7 confirms that callbacks arrive while the calc thread sleeps. Log `OF tick chunk wait day(..) ms(..) ready(True|False)`.

5.3 Callback (`onFlowData` 844–865)

- Look up the chunk from `State`.
- Copy `result.Data` once into a local array inside its own `try`. Iterate under `m_flowLock` as today, but only after the chunk is releasable.
- On `IsCompleted`, set the chunk to Done and record the count.
- **Errors are per chunk.** The `catch` marks only that (day, stream) Failed and queues `OF tick chunk failed ...`. If `TickChunkSplitOnFail > 0` and this was the first attempt, the scheduler re-plans that day as N equal sub-windows (default 4 × 6 h), issued by the pump. Otherwise the day stays Failed and the next day continues.
- **The tick gate (910) becomes per bar.** A bar uses `TickStream` iff the chunks covering its close time are Done for Trade (and Bid/Ask when quotes are on). Otherwise it uses `BarsOnly`, so a failed day falls back to the bar tiers. Replace `m_flowHistoryDone[0]` with `m_chunks.ReadyAt(CloseTime)`. `onFlowData` keeps setting `m_flowHistoryDone[stream]` for the last chunk only, which keeps the RT semantics.
- **Memory guard.** When `TickChunkLate == Skip`, the callback drops the ticks of a chunk whose window ends at or before the last closed bar (volatile snapshot) instead of queuing them. They are counted as `late`.

5.4 Diag lines (Info per chunk; Journal for the plan, failures and the summary)

```
Journal  OF tick chunk plan days(D) streams(Trade,Bid,Ask) first(yyyy-MM-dd) last(..) zone(Exchange)
boundaryEt(17:00) maxInFlightDays(1) waitMs(0) late(Skip)
Info     OF tick chunk start day(yyyy-MM-dd) stream(Bid) from(yyyy-MM-dd HH:mm) to(..) rt(False)
attempt(1)
Info     OF tick chunk done day(..) stream(..) ticks(n) ms(t)
Info     OF tick chunk skipped day(..) reason(late|closedDay)
Journal  OF tick chunk failed day(..) stream(..) attempt(a) exception(<FullName>) message(..)
action(split4|giveUp)
Journal  OF tick chunk summary done(x) failed(y) skipped(z) ticks(n) lateDropped(m)      (once, when
nothing is pending, or in StopCalc)
```

5.5 Config (all on the protected `FlowCfg`; no `[Input]`; set by the derived strategy as today)

Field	Default	Meaning
`McRecalcOnLoad`	`true`	Fix 1 trigger on/off
`McRecalcMax`	`1`	recalcs per cache signature (loop guard)
`McIdlePollMs`	`1000`	`RecalcLastBarAfter` interval while idle work is pending
		stop polling after this

Field	Default	Meaning
`McIdleTimeoutSec`	`900`	
`McRecalcFromCallback`	`false`	fallback §4.3 step 6 (the probe decides)
`TickChunkByDay`	`true`	`false` = legacy single request (for A/B only)
`TickChunkMaxInFlightDays`	`1`	1..4
`TickChunkSplitOnFail`	`4`	sub-windows for a failed day; 0 = no retry
`TickChunkLate`	`Skip`	typed enum `ETickChunkLate { Skip, Load }`
`TickChunkWaitMs`	`0`	bounded per-day wait in CalcBar; 0 = off
`TickChunkBoundaryEt`	`17:00`	chunk boundary (ET)

6. Threading rules (all from §2)

1. MC calls (`ExecControl.*`, `DataLoader.BeginLoadData/EndLoadData`, `Bars`, `trace`, `engineSink`) run only in `CalcBar`, `StartCalc` (no trace there), `StopCalc` and `OnRecalcLastBarAfterEvent` (P-RC3). The only exceptions are `McRecalcFromCallback` and the existing `EndLoadData` paths.
2. Callbacks touch only `m_flow`, `m_mcCache` and scheduler state under `m_flowLock`, plus the queue under `m_flowQueueLock`.
3. `Recalculate()` is the last statement on its path and is never wrapped in a catch-all.
4. Don't catch exceptions around `base.*` calls (MC's MaxBarsBack restart).

7. Code issues found (flag to Ettienne; fix in this PR unless noted)

7.1 `chartType(Regular)` on the "FootPrint" request (696)

- When `McBidAskChartType == FootPrint`, line 684 builds `Resolution.CreateFootPrint(...)` and logs `res.ChartType`, which reads **Regular**.
- The request does work: run B returned `data2Bars(61837) levels(479517)`. So `CreateFootPrint` carries the footprint mode in other `Resolution` members (the stubs hint at a delta-type member), and `ChartType` stays `Regular`.
- The line is misleading, and so is `chartType(FootPrint)` in the `loaded` line (822), because that one prints the config value rather than the request.
- **Fix:** log `builder(CreateFootPrint delta(ASK_TRADE_BID_TRADE) footprint(BID_ASK_VOL) pct(False)) resChartType(Regular)` from the typed enum values passed in. Once the dump (§8) names the footprint members, log them typed as well.
- No behaviour change. Also confirm the `res.Size` type that is passed through (P-BA open item from the PR #74 review).

7.2 `To = Now+1d` (663, 689)

This loads 6 weeks of data past the chart end, and it is a direct contributor to the array overflow. Fixed by §4.5.

7.3 Backlog bug in `FlowEngine.CloseBar` (301–319). This must be fixed in commit 2, because chunking makes late arrival normal.

- `CloseBar` pops **every** queued trade with `Time <= CloseTime`. When history arrives after bars have already closed as `BarsOnly`, the first `TickStream` bar absorbs all the earlier ticks into one giant footprint. With `McBidAsk = Prefer`, that bar's MC set then fails the volume check (`volMismatch`, 251), and the garbage footprint stays tagged Quote/High.
- The first bar also absorbs the extra day of ticks from `from = first − 1 day` (654).
- **Fix (MC-free):** the engine remembers `m_lastClose`, the previous `CloseBar`'s CloseTime. Trades with `Time <= m_lastClose` are popped and **not added**; count them in a new `fp.BacklogDropped` / `BacklogTrades` counter. The first bar uses `CloseTime − bar duration`, passed as a new `BarInput.OpenTime`.
- The quote queues already only advance state (287–291), so nothing changes there.

7.4 MaxBars 5000 (80, 353–359)

- The 19072-bar run drops the oldest footprints from bar 5051.

- CumDelta is **not** actually truncated with `ResetMode.Session` on 1-min ES (a reset period is ≤ ~1380 bars, which is less than 5000). Only ladder/footprint lookups more than 5000 bars back return null, and the warning text overstates this.
- **Out of scope.** Proposal for later: `MaxBars = 0` means auto = `max(5000, 2 × bars per reset period)`. Do not scale with the loaded range, because footprint memory is roughly 2–5 KB per bar.
- Trivial wording fix allowed in this PR: "...; CumDelta is Truncated only if a reset period exceeds the cap".

7.5 Smaller items

- **Separate PR, not this one.** `_CustomSignal.Strategy.CS` 1292–1310 (`M-TICK enqueueTick/tickBarMember`) reads `Bar` members **by reflection with member-name strings** ("Time", "Close", "TotalVolume"). That breaks the hard rule. Use the typed `b.Time`, `b.Close`, `(double)b.TotalVolume`, as `flowTick` 869–875 already does.
- **FYI.** `_VolumeProfileStatistics.Indicator.CS` 357 wraps `Recalculate()` in `catch { }`, which may swallow MC's unwind (§2).
- `startOrderFlow` (618) resets `m_mcResult`/counters while a callback of the previous pass may still be running. This is harmless once the cache is the source of truth, but keep the callback's `m_flow == null` check (763).
- The stubs (`McStubs.cs` 36–37, 57) need `ICalculationControl.Recalculate()`, `DataRequest.CreateFromTo`, `InstrumentDataRequest.TimeZone` and `IFullSymbolData.Count` for `tools/sem` compile checks.

8. Open API points: the user runs two one-off files

The files are saved as `/workspace/specs/_McRecalcProbe.Strategy.CS` (signal) and `/workspace/specs/_McApiDump2.Indicator.CS` (indicator). Import both into the PowerLanguage .NET Editor and compile. - Put `_McApiDump2` on any @ES chart and copy the Output window. - Put `_McRecalcProbe` alone on a historical @ES 1-min chart (the 9a setup), wait about 30 s, remove it, and send `%TEMP%\McRecalcProbe.csv`.

ID	Question	Answered by
P-RC1	Same object instance (`obj`) and instance fields kept across `Recalculate`?	probe: `obj(..)` and `instRecalcs` on pass 2
P-RC2	Does `OnRecalcLastBarAfterEvent` fire on a **signal** on a non-real-time chart after the last bar?	probe: the `OnRecalcLastBarAfterEvent` line
P-RC3	Its thread vs CalcBar (`tid`), and are `Bars` readable in it?	probe: `tid(..)`, `Bars.Time[0]` line
P-RC4	May `Recalculate()` be called from that event, and how does it unwind (exception type)?	probe: `Recalculate threw ...` / `returned`
P-RC5	`DataRequest` members (`CreateFromTo`, `To`, `ToAlwaysIsNow`, `Count`); which wins, `Range` or `From/To`?	dump + probe's `callback ... first(..)` (should be ≈ last−2 days)
P-RC6	`InstrumentDataRequest.TimeZone` exists and is copied by `Bars.Request`; `FullSymbolData.Time[Current−Count]` = last bar	probe first-bar line; dump
P-RC7	Do callbacks arrive while CalcBar sleeps (bounded wait)?	probe: `wait in CalcBar ended` `loadDone(True)`
P-RC8	`Resolution` members after `CreateFootPrint` (why `ChartType` = Regular) and the `Size` type	dump: `Resolution.<prop>: chart=..` `createFootPrint=..`
P-RC9	`ICalculationControl` members and the virtual hooks on the SignalObject base chain	dump

Decision table: if P-RC2 or P-RC3 fails, set `McRecalcFromCallback = true` as the default and enable the direct-write log path. If P-RC7 fails, remove `TickChunkWaitMs`. If P-RC5 shows that `From`/`To` win, keep setting both (harmless).

Probe source (the dump is in the file):

```
// (abridged; full file /workspace/specs/_McRecalcProbe.Strategy.CS)
protected override void StartCalc() { m_pass++; m_bars = 0; m_armed = false; log("StartCalc"); }
protected override void CalcBar() {
  m_bars++;
  if (m_bars == 1) { /* log Current, Count, Time[Current-Count], Bars.Request.TimeZone; pass 1:
BeginLoadData with
                       Range = DataRequest.CreateFromTo(last-2d, last), then Sleep(50)-wait up to 20 s
for the callback */ }
```

```
  if (Bars.LastBarOnChart && Bars.Status == EBarState.Close && !m_armed) { m_armed = true;
ExecControl.RecalcLastBarAfter(TimeSpan.FromSeconds(1)); }
}
protected override void OnRecalcLastBarAfterEvent() {
  log("OnRecalcLastBarAfterEvent");                    // every log line carries tid, obj, pass,
instRecalcs, staticRecalcs
  try { log("Bars.Time[0](" + Bars.Time[0] + ")"); } catch (Exception ex) { log("Bars exception " +
ex.GetType().FullName); }
  if (m_pass == 1 && s_recalcs == 0 && m_recalcs == 0) { s_recalcs++; m_recalcs++;
    try { ExecControl.Recalculate(); } catch (Exception ex) { log("Recalculate threw " +
ex.GetType().FullName); throw; }
    log("returned from Recalculate"); }
}
```

9. Tests

Off-MC unit tests (`tests/OrderFlowTests/Program.cs`, C# 7.3, run with `run.sh`): - `McLevelCache`: Add/Covers/ReplayInto produce the same `CloseBar` result as direct `AddMcLevels`. - `Clear` on a signature change. - `McRecalcGate`: - `Wait` before historyDone. - `SkipNoMissed` when no misses; `Recalc` once; `SkipGuard` on the second call with the same signature. - `SkipAutoTrading`; `SkipDisabled`. - `PlanGlobexDays`: Sep 1–18 2026 gives 14 Globex days (Sep 7 Labor Day trades with an early halt; the log has `session(2026-09-07) bars(1139)`). Monday starts Sunday 17:00 ET. Windows are contiguous and non-overlapping. - `TickChunkScheduler`: - in-order release with MaxInFlight 1 and 3 (out-of-order completion); - Failed → split into 4 → Done; - Skip-late; last chunk RT; - `ReadyAt`. - Backlog fix: ticks pushed after 3 BarsOnly bars are not added to bar 4; the counter equals their count; bar 4 contains only its own ticks.

`tests/SessionClockTests`: `FromEastern(ToEastern(t)) == t` across both DST changes for Exchange/Central and Local zones.

Live acceptance (Ettienne runs, Analyst checks the log): - **A1, Fix 1 (9a rerun, @ES 1-min, Aug 31 → Sep 18, McBidAsk = Prefer)**: - exactly one `OF McBidAsk diag request` line in pass 1; - one `cache stored`; - exactly one `recalc triggered`; - a second `RUN id(..)` followed by `cache hit ... request(none)` and `recalc pass using cache`; - **no** further `diag request` line and no second `recalc triggered`; - `OF T9 session(..) mcCover(> 0)` for every session inside the loaded window, expected ≈ 100% except `volMismatch` bars; - the `diag stop` / chunk summary lines appear **without** removing the study (idle drain). - **A2, Fix 2 (same chart, Sep 1–18)**: - no `Array dimensions exceeded` anywhere; - one `tick chunk plan`; - per-chunk `start`/`done` (or `skipped reason(late)`) lines; - a `summary` with `failed(0)`. - **A3, Fix 2 wait mode (`TickChunkWaitMs = 120000`, McBidAsk = Off)**: - every day `done`; - Quote/TickRule bars present in sessions (the quality line shows source Quote); - no bar with a backlog footprint (`BacklogDropped` journaled only if > 0). - **A4, regression**: with `McBidAsk = Off`, `TickChunkByDay = false`, the run behaves like 33a51bf, except for the clamp and the backlog fix. - **A5, loop guard**: in a `McRecalcMax = 1` run, press Recalculate manually after A1. The result must be `cache hit`, no request, and no recalc.